

# Rajalakshmi Engineering College

Name: naveenraj s  
Email: 240701350@rajalakshmi.edu.in  
Roll no: 240701350  
Phone: 6379711376  
Branch: REC  
Department: CSE - Section 3  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 10\_PAH

Attempt : 1  
Total Mark : 30  
Marks Obtained : 30

#### Section 1 : Coding

##### 1. Problem Statement

Sarah is working on a spam detection system that analyzes incoming messages for unique patterns. Spammers often use repetitive character sequences, making it important to identify the first non-repeating character in a message.

Given a string, Sarah needs to determine the first character that appears only once. If all characters repeat, the system should return -1.

She decides to use a HashMap to efficiently track character frequencies and find the solution.

##### ***Input Format***

The first line contains an integer N representing , the length of the string.

The second line contains a string of N lowercase English letters (a-z).

### **Output Format**

The output prints a character representing the first non-repeating character. If none exist, print -1.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10  
abacabadac

Output: d

### **Answer**

```
// You are using Java
import java.util.*;
```

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        String s = sc.next();

        HashMap<Character, Integer> map = new HashMap<>();

        // Count frequency of each character
        for (char c : s.toCharArray()) {
            map.put(c, map.getOrDefault(c, 0) + 1);
        }

        // Find first non-repeating character
        for (char c : s.toCharArray()) {
            if (map.get(c) == 1) {
                System.out.println(c);
                return;
            }
        }
    }
}
```

```
// If all characters repeat
System.out.println(-1);
}
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Riya is building a calendar event scheduler where each event is stored in chronological order using a TreeMap. The key represents the event time in 24-hour format (HH:MM), and the value is the event description.

She wants the system to:

Automatically sort events by time. Avoid duplicate time entries — if a duplicate time is entered, ignore the new entry. Print all scheduled events in order.

Implement this logic using a class named EventManager.

### **Input Format**

The first line of the input contains an integer  $n$ , representing the number of events.

The next  $n$  lines each contain a string in the format: "HH:MM Description"  
(Example: 09:00 TeamMeeting).

### **Output Format**

The first line of the output prints "Scheduled Events:"

The next  $k$  lines print each event in the format: "HH:MM - Description"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

09:00 TeamMeeting

13:30 LunchBreak

11:00 ProjectUpdate

09:00 Standup

15:00 ClientCall

Output: Scheduled Events:

09:00 - TeamMeeting

11:00 - ProjectUpdate

13:30 - LunchBreak

15:00 - ClientCall

### **Answer**

// You are using Java

import java.util.\*;

class EventManager {

    TreeMap<String, String> events = new TreeMap<>();

    public void addEvent(String time, String description) {

        // Add only if time not already present

        if (!events.containsKey(time)) {

            events.put(time, description);

        }

    }

    public void displayEvents() {

        System.out.println("Scheduled Events:");

        for (Map.Entry<String, String> entry : events.entrySet()) {

            System.out.println(entry.getKey() + " - " + entry.getValue());

        }

    }

}

public class Main {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();

        EventManager manager = new EventManager();

        for (int i = 0; i < n; i++) {

```

        String time = sc.next();
        String desc = sc.next();
        manager.addEvent(time, desc);
    }

    manager.displayEvents();
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

A university maintains a list of student records and wants to store them in a sorted manner based on their GPA. If two students have the same GPA, they should be further sorted by their name in lexicographical order. Implement a program that uses a TreeSet to store student records and ensures unique student IDs.

#### ***Input Format***

The first line contains an integer N - the number of students.

The next N lines contain details of each student in the format: "StudentID Name GPA"

- StudentID (Integer) - A unique identifier.
- Name (String) - The student's name (can contain spaces).
- GPA (Double) - The Grade Point Average.

#### ***Output Format***

The output prints the list of students in ascending order of GPA.

If two students have the same GPA, sort them by name.

Print details in the format: "StudentID Name GPA" in the output, GPA is rounded to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

101 John 8.5

102 Alice 9.1

103 Bob 8.5

104 Zoe 7.3

105 Charlie 9.1

Output: 104 Zoe 7.30

103 Bob 8.50

101 John 8.50

102 Alice 9.10

105 Charlie 9.10

### **Answer**

```
import java.util.*;
```

```
class Student implements Comparable<Student> {
```

```
    int id;
```

```
    String name;
```

```
    double gpa;
```

```
    Student(int id, String name, double gpa) {
```

```
        this.id = id;
```

```
        this.name = name;
```

```
        this.gpa = gpa;
```

```
    }
```

```
    public int compareTo(Student s) {
```

```
        if (this.gpa != s.gpa)
```

```
            return Double.compare(this.gpa, s.gpa); // sort by GPA
```

```
        return this.name.compareTo(s.name); // if GPA same, sort by name
```

```
    }
```

```
}
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        Scanner sc = new Scanner(System.in);
```

```
        int n = sc.nextInt();
```

```
        TreeSet<Student> set = new TreeSet<>();
```

```
HashSet<Integer> ids = new HashSet<>();

for (int i = 0; i < n; i++) {
    int id = sc.nextInt();
    String name = sc.next();
    double gpa = sc.nextDouble();

    if (!ids.contains(id)) { // ensure unique ID
        ids.add(id);
        set.add(new Student(id, name, gpa));
    }
}

for (Student s : set) {
    System.out.printf("%d %s %.2f\n", s.id, s.name, s.gpa);
}
}
```

**Status :** Correct

**Marks :** 10/10