RAJALAKSHMI ENGINEERING COLLEGE

Naveen Raj V 251001158-2025-IT

N2

Started on	Thursday, 6 August 2026, 11:21 AM
State	Finished
Completed on	Tuesday, 25 August 2026, 5:38 PM
Time taken	19 days 6 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int majority(int a[], int low, int high) {
    if (low == high)
        return a[low];

    int mid = (low + high) / 2;

    int left = majority(a, low, mid);
    int right = majority(a, mid + 1, high);

    if (left == right)
        return left;

    int leftCount = 0, rightCount = 0;

    for (int i = low; i <= high; i++) {
        if (a[i] == left)
            leftCount++;

        if (a[i] == right)
            rightCount++;
    }

    if (leftCount > rightCount)
        return left;
```

```
    else
        return right;
}

int main() {
    int n;
    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &a[i]);
    }

    printf("%d", majority(a, 0, n - 1));

    return 0;
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course