

Exercise 4: Creating and Configuring a Maven Project

pom.xml

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">
```

```
<modelVersion>4.0.0</modelVersion>
```

```
<groupId>com.library</groupId>
```

```
<artifactId>LibraryManagement</artifactId>
```

```
<version>1.0</version>
```

```
<properties>
```

```
<maven.compiler.source>1.8</maven.compiler.source>
```

```
<maven.compiler.target>1.8</maven.compiler.target>
```

```
</properties>
```

```
<dependencies>
```

```
<dependency>
```

```
<groupId>org.springframework</groupId>
```

```
<artifactId>spring-context</artifactId>
```

```
<version>5.3.30</version>
```

```
</dependency>
```

```
<dependency>
```

```
<groupId>org.springframework</groupId>
```

```
<artifactId>spring-aop</artifactId>
```

```
<version>5.3.30</version>
```

</dependency>

<dependency>

<groupId>org.springframework</groupId>

<artifactId>spring-webmvc</artifactId>

<version>5.3.30</version>

</dependency>

</dependencies>

<build>

<plugins>

<plugin>

<groupId>org.apache.maven.plugins</groupId>

<artifactId>maven-compiler-plugin</artifactId>

<version>3.11.0</version>

<configuration>

<source>1.8</source>

<target>1.8</target>

</configuration>

</plugin>

</plugins>

</build>

</project>

applicationContext.xml

<?xml version="1.0" encoding="UTF-8"?>

<beans xmlns="http://www.springframework.org/schema/beans"

```
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="
http://www.springframework.org/schema/beans
https://www.springframework.org/schema/beans/spring-beans.xsd">
```

```
<bean id="bookRepository" class="com.library.repository.BookRepository"/>
```

```
<bean id="bookService" class="com.library.service.BookService">
  <property name="bookRepository" ref="bookRepository"/>
</bean>
```

```
</beans>
```

BookRepository.java

```
package com.library.repository;
```

```
public class BookRepository {
```

```
    public void display() {
        System.out.println("Book Repository is working");
    }
```

```
}
```

BookService.java

```
package com.library.service;
```

```
import com.library.repository.BookRepository;
```

```
public class BookService {

    private BookRepository bookRepository;

    public void setBookRepository(BookRepository bookRepository) {
        this.bookRepository = bookRepository;
    }

    public void showService() {
        System.out.println("Book Service is working");
        bookRepository.display();
    }

}
```

LibraryManagementApplication.java

```
package com.library;

import com.library.service.BookService;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

public class LibraryManagementApplication {

    public static void main(String[] args) {

        ApplicationContext context = new ClassPathXmlApplicationContext("applicationContext.xml");

        BookService service = context.getBean("bookService", BookService.class);
```

```
        service.showService();
    }
}
```

