

Spring Core – Load Country from Spring Configuration XML

SpringLearnApplication.java

```
package com.cognizant.spring_learn;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

@SpringBootApplication
public class SpringLearnApplication {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(SpringLearnApplication.class);

    public static void main(String[] args) {

        LOGGER.info("START");

        SpringApplication.run(SpringLearnApplication.class, args);

        displayCountry();

        LOGGER.info("END");
    }

    public static void displayCountry() {

        ApplicationContext context =
            new ClassPathXmlApplicationContext("country.xml");

        Country country =
            context.getBean("country", Country.class);

        LOGGER.debug("Country : {}", country);
    }
}
```

```
        ((ClassPathXmlApplicationContext) context).close();
    }
}
```

Country.java

```
package com.cognizant.spring_learn;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class Country {

    private static final Logger LOGGER =
        LoggerFactory.getLogger(Country.class);

    private String code;
    private String name;

    public Country() {
        LOGGER.debug("Inside Country Constructor.");
    }

    public String getCode() {
        LOGGER.debug("Inside getCode()");
        return code;
    }

    public void setCode(String code) {
        LOGGER.debug("Inside setCode()");
        this.code = code;
    }

    public String getName() {
        LOGGER.debug("Inside getName()");
        return name;
    }

    public void setName(String name) {
        LOGGER.debug("Inside setName()");
        this.name = name;
    }
}
```

```

    }

    @Override
    public String toString() {
        return "Country{" +
            "code='" + code + '\'' +
            ", name='" + name + '\'' +
            '}';
    }
}

```

country.xml

```

<?xml version="1.0" encoding="UTF-8"?>

<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="
        http://www.springframework.org/schema/beans
        https://www.springframework.org/schema/beans/spring-beans.xsd">

    <bean id="country"
        class="com.cognizant.spring_learn.Country">

        <property name="code" value="IN"/>
        <property name="name" value="India"/>

    </bean>

</beans>

```

pom.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
        https://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>
    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>4.1.0</version>
        <relativePath/> <!-- lookup parent from repository -->
    </parent>

```

```
</parent>
<groupId>com.cognizant</groupId>
<artifactId>spring-learn</artifactId>
<version>0.0.1-SNAPSHOT</version>
<name/>
<description/>
<url/>
<licenses>
  <license/>
</licenses>
<developers>
  <developer/>
</developers>
<scm>
  <connection/>
  <developerConnection/>
  <tag/>
  <url/>
</scm>
<properties>
  <java.version>17</java.version>
</properties>
<dependencies>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-webmvc</artifactId>
  </dependency>

  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-devtools</artifactId>
    <scope>runtime</scope>
    <optional>true</optional>
  </dependency>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-webmvc-test</artifactId>
    <scope>test</scope>
  </dependency>
  <dependency>
    <groupId>org.springframework</groupId>
```

```

    <artifactId>spring-context</artifactId>
</dependency>
</dependencies>

<build>
    <plugins>
        <plugin>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-maven-plugin</artifactId>
        </plugin>
    </plugins>
</build>

</project>

```

The screenshot shows an IDE interface with a project named 'SpringLearnApplication'. The project structure includes a 'main' directory with a 'java' subdirectory. The 'SpringLearnApplication.java' file is open, showing a public class with a main method. The run console output shows the application starting successfully, with various log messages indicating the initialization of Spring Boot, Tomcat, and the application itself.

```

2026-07-05T13:08:46.033+05:30 INFO 18928 --- [spring-learn] [ restartedMain] c.c.spring_learn.SpringLearnApplication : Starting SpringLearnApplication using Java 26.0.1 with
2026-07-05T13:08:46.035+05:30 DEBUG 18928 --- [spring-learn] [ restartedMain] c.c.spring_learn.SpringLearnApplication : Running with Spring Boot v4.1.0, Spring v7.0.8
2026-07-05T13:08:46.036+05:30 INFO 18928 --- [spring-learn] [ restartedMain] c.c.spring_learn.SpringLearnApplication : No active profile set, falling back to 1 default prof:
2026-07-05T13:08:46.087+05:30 INFO 18928 --- [spring-learn] [ restartedMain] e.DevToolsPropertyDefaultsPostProcessor : Devtools property defaults active! Set 'spring.devtool
2026-07-05T13:08:46.087+05:30 INFO 18928 --- [spring-learn] [ restartedMain] e.DevToolsPropertyDefaultsPostProcessor : For additional web related logging consider setting ti
2026-07-05T13:08:46.893+05:30 INFO 18928 --- [spring-learn] [ restartedMain] o.s.boot.tomcat.TomcatWebServer : Tomcat initialized with port 8080 (http)
2026-07-05T13:08:46.908+05:30 INFO 18928 --- [spring-learn] [ restartedMain] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2026-07-05T13:08:46.909+05:30 INFO 18928 --- [spring-learn] [ restartedMain] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/11.0.22]
2026-07-05T13:08:47.947+05:30 INFO 18928 --- [spring-learn] [ restartedMain] o.w.c.s.WebApplicationContextInitializer : Root WebApplicationContext: initialization completed
2026-07-05T13:08:47.290+05:30 INFO 18928 --- [spring-learn] [ restartedMain] o.s.boot.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path
2026-07-05T13:08:47.295+05:30 INFO 18928 --- [spring-learn] [ restartedMain] c.c.spring_learn.SpringLearnApplication : Started SpringLearnApplication in 1.669 seconds (proc
2026-07-05T13:08:47.366+05:30 DEBUG 18928 --- [spring-learn] [ restartedMain] com.cognizant.spring_learn.Country : Inside Country Constructor.
2026-07-05T13:08:47.367+05:30 DEBUG 18928 --- [spring-learn] [ restartedMain] com.cognizant.spring_learn.Country : Inside setCode()
2026-07-05T13:08:47.367+05:30 DEBUG 18928 --- [spring-learn] [ restartedMain] com.cognizant.spring_learn.Country : Inside setName()
2026-07-05T13:08:47.368+05:30 DEBUG 18928 --- [spring-learn] [ restartedMain] c.c.spring_learn.SpringLearnApplication : Country : Country[code='IN', name='India']
2026-07-05T13:08:47.370+05:30 INFO 18928 --- [spring-learn] [ restartedMain] c.c.spring_learn.SpringLearnApplication : END

```