

# KREISEL BATTERY SYSTEM

Datasheet
**KBP63**

KREISEL

# KBP63
## KREISEL BATTERY SYSTEM

KREISEL

The KBP63 is a standardized KREISEL high voltage battery system that is living up to the highest standards of lifetime, safety, and performance, backed by superior craftsmanship. KREISEL Battery Systems deliver unsurpassed lifetime, downtime and derating prevention regardless of the given ambient temperature. Additionally, the battery system is available in an 800V configuration, allows freedom of placement, and is designed to meet the high frequency and distance requirements of your transportation tasks.

**63 KWH ENERGY**

**44 KW CHARGING**

**250 KW DISCHARGING**

**393 KG (866 LBS)**




### ELECTRICAL DATA

| | |
|---|---|
| **Capacity** | 173 Ah (nominal) |
| **Energy** | 63 kWh (nominal) |
| **Technology** | Li-Ion 21700 |
| **Nominal voltage** | 364 V |
| **Operating voltage max.** | 407 V |
| **Operating voltage min.** | 297 V |
| **Discharge max. (10 sec.)** | 690 A / 250 kW / 3,97 C |
| **Discharge continuous** | 330 A / 120 kW / 1,90 C |
| **Charging continuous** | 121 A / 44 kW / 0,69 C |
| **Expected service life** | ~ 3000 cycles (>70% SOH) |
| **Gravimetric density** | 163 Wh/kg |
| **Thermal system** | Patented immersion cooling technology with highest propagation safety |

### CERTIFICATIONS

| | |
|---|---|
| **Degree of protection** | IP67 (IP6K9K possible) |
| **Automotive / commercial vehicles** | ECE R100.02, ECE R10 |
| **Transportation** | UN38.3 compliant |
| **Marine** | DNV Ru-Ship Pt.6 Ch. 2 |
| **Salt Misting** | IEC 60068-2-52 Method 1 |

### TECHNICAL DATA

| | |
|---|---|
| **Applications** | Marine, Industrial, Off-Highway |
| **Ambient temperature range** | - 40 to 70 °C |
| **Weight** | 393 kg (866 lbs) |
| **Dimensions (L x W x H)** | 1111 x 795 x 351 mm (43“ x 31“ x 14“) |

KREISEL Electric GmbH | info@kreiselelectric.com | KBP63 Datasheet - 2023_10