**HV DC INPUT, CONTACTORS & PRE-CHARGE**

+
-

**CABLE ASSEMBLY 184/22145**

HV DC IN – 2 x 4mm Sq Shielded 4m length
TE 2-WAY HVA280 CONNECTOR (KEY B)



**CONTROL POWER INPUTS & CONTACTOR CONTROL**

- 12-24V SUPPLY IN (KL30)
- 12-24V SUPPLY IN (KL15)
- CONTROL 0V
- KEYSWITCH IN (KL15)
- DIGITAL HIGH SIDE OUT 3
- DIGITAL HIGH SIDE OUT 4
- CONTROL 0V
- CONTROL 0V

**ANALOG/DIGITAL INPUTS**

- ANALOG 1 POWER SUPPLY (+)
- POT 1A WIPER IN
- POT 1B WIPER IN
- ANALOG INPUT 3
- DIGITAL INPUT 1
- DIGITAL INPUT 2

**CAN CONNECTION FOR CONFIGURATION AND SERVICE**

- CAN HIGH (7)
- CAN LOW (2)
- CAN GND (3)
- CAN TERMINATION

**HIGH VOLTAGE INTERLOCK**

- ACTIVE HVIL SOURCE
- ACTIVE HVIL IN 1
- ACTIVE HVIL IN 2
- ACTIVE HVIL SINK

**CAN CONNECTION TO OTHER CAN DEVICES**

- CAN HIGH
- CAN LOW
- CAN GND



**INDUCTION ENCODER INPUTS FROM MOTOR**

- ENCODER_VCC
- ENCODER 0V
- ENCA
- ENCB
- ENCA (-) *optional*
- ENCB (-) *optional*

**CABLE ASSEMBLY 184/22149**

Induction Option – 4m length
MOLEX 48 WAY RECEPTICLE



**RESOLVER ENCODER INPUTS FROM MOTOR**

- RESOLVER COS IN
- RESOLVER COS LO IN
- RESOLVER SIN IN
- RESOLVER SIN LO IN
- RESOLVER EXCITATION (+)
- RESOLVER EXCITATION (-)
- ENCODER GND

**CABLE ASSEMBLY 184/22147**

Resolver Option – 4m length
MOLEX 48 WAY RECEPTICLE



**SIN/COS ENCODER INPUTS FROM MOTOR**

- ENCODER POWER SUPPLY (+)
- ENCODER GND
- SIN INPUT
- COS INPUT

**CABLE ASSEMBLY 184/22148**

Sin/Cos– 4m length
MOLEX 48 WAY RECEPTICLE



Induction Cable Option
Resolver Cable Option
Sin/Cos Cable Option

Encoder Cable



U
V
W

**CABLE ASSEMBLY 184/22155**

HV AC Out– 3 x 2.5mm Sq Shielded 4m length
TE 3-WAY HVA280 CONNECTOR (KEY A)

