Revisions

Rev.	Date	Author	Description
A	21/01/2018	Florent de Labarre	1028
B	21/01/2018	Florent de Labarre	1025
C	10/04/2018	Florent de Labarre	
D	19/02/2019	Maxime Bouyssou	add annotation
E	08/01/2020	Thomas Bouche	arrangement pour lecture
F	03/11/2020	P.L.P	Chgmt Supply Hall captor 5V->12V
G	07/01/2021	P.L.P	Ajout résistance pull-up Hall captor
H	24/02/2021	Pierre Edeline	Suppression : Contact_HT_BMW
I	26/11/2021	P.E	Maj Faisceau complet
J	14-Mar-23	P.E	Ajout controle cavité 65 (+12V) et 66 (0V)
K	13/03/2024	R.F	Refonte complete du plan + changement couleur electrovanne + changement nom canbus
L	11/07/2024	P.E	Modifs Splice 46 et Splice 47

Couper les Cables non utilisés à 30 cm de la prise.
Isoler avec gaines thermo chaque cable non utilisés.
Faire une chaussette avec gaine thermo de l'ensemble des cables non utilisés.

WARNING

Oil Level doit être 1m plus long que les prises se connectant au distributeur

Main_MC42

Cavity	To	Conductor	Color	Gauge	Length
1	CanBus_Main_to_MC4_10.B	W22.White		0,75 mm²	≥ 1,5 m
2	Canbus_keybox.B	W23.White		0,75 mm²	≥ 1,5 m
3	Can_Battery_HV.B	W57.White		0,75 mm²	≥ 1,5 m
4	ID_tag_F.A	W50.White		0,75 mm²	≥ 0,2 m
7	Vref_Plus	W59.White		0,75 mm²	
8	R8.POS	W16.White		0,75 mm²	
9	Pressure_block.2	W17.White		0,75 mm²	≥ 3,5 m
10	Pressure_tracks.2	W19.White		0,75 mm²	≥ 3,5 m
11	Output_A	W55.White		0,75 mm²	
12	Output_B	W61.White		0,75 mm²	
14	PWM_tension_tracks.1	W12.White		0,75 mm²	≥ 3,5 m
17	CanBus_Main_to_MC4_10.A	W21.White		0,75 mm²	≥ 1,5 m
18	Canbus_keybox.A	W24.White		0,75 mm²	≥ 1,5 m
19	Can_Battery_HV.A	W56.White		0,75 mm²	≥ 1,5 m
20	ID_tag_F.B	W49.White		0,75 mm²	≥ 0,2 m
23	Vref_Minus	W60.White		0,75 mm²	
24	R10.POS	W18.White		0,75 mm²	
25	R11.POS	W73.White		1 mm²	
26	Accelerometre.D	W46.White		0,75 mm²	≥ 0,8 m
28	Remote_Power_Box.A	W25.White		0,75 mm²	≥ 0,8 m
29	Remote_Power_Box.B	W45.White		0,75 mm²	≥ 0,8 m
36	Accelerometre.E	W47.White		0,75 mm²	≥ 0,8 m
39	PWM_tension_tracks.2	W13.White		0,75 mm²	≥ 3,5 m
41	ByPass.2	W1.White		0,75 mm²	≥ 3,5 m
42	Landing_DOWN.2	W3.White		0,75 mm²	≥ 3,5 m
43	Landing_Unblock.2	W5.White		0,75 mm²	≥ 3,5 m
44	Electric_Drive_FuseBox_B1.A	W53.White		0,75 mm²	≥ 0,8 m
45	Seat_Control.B	W52.White		0,75 mm²	≥ 0,8 m
46	Splice_C1_46	W14.White		0,75 mm²	
47	Splice_C1_47	W15.White		0,75 mm²	
48	Seat_Control.A	W51.White		0,75 mm²	≥ 0,8 m
52	Accelerometre.F	W48.White		0,75 mm²	≥ 0,8 m
57	Landing_UP.2	W2.White		0,75 mm²	≥ 3,5 m
58	Track_Tension.2	W4.White		0,75 mm²	≥ 3,5 m
59	Landing_Block.2	W6.White		0,75 mm²	≥ 3,5 m
60	Electric_Drive_FuseBox_B1.C	W54.White		0,75 mm²	≥ 0,8 m
62	Splice_C1_46	W66.White		0,75 mm²	
63	Splice_C1_47	W67.White		0,75 mm²	
65	12V	W43.Red		2,5 mm²	
66	Supply.B	W44.Black		2,5 mm²	≥ 1 m

Main_MC42 [5] — [18] MC42

R2

From	To	Conductor	Color	Gauge
R2.NEG	Output_B	W11.White		0,75 mm²
R2.POS	12V	W92.Red		1 mm²

12V

From	To	Conductor	Color	Gauge
12V	Accelerometre.A	W42.Red		1 mm²
12V	Ladder_hal_captor.A	W65.Red		1 mm²
12V	Main_MC42.65	W43.Red		2,5 mm²
12V	R1.POS	W93.Red		1 mm²
12V	R2.POS	W92.Red		1 mm²
12V	Supply.A	W58.Red		2,5 mm²

R1

From	To	Conductor	Color	Gauge
R1.NEG	Output_A	W9.White		0,75 mm²
R1.POS	12V	W93.Red		1 mm²

IDTAG_2

Cavity	To	Conductor	Color	Gauge
1	ID_tag_M.A	W64.Black		1 mm²
2	ID_tag_M.B	W78.Black		1 mm²

IDTAG_2 [1] — ID_tag_M [6, 13, 19, 37]

ID_tag_M

Cavity	To	Conductor	Color	Gauge
A	IDTAG_2.1	W64.Black		1 mm²
B	IDTAG_2.2	W78.Black		1 mm²

ID_tag_F

Cavity	To	Conductor	Color	Gauge
A	Main_MC42.4	W50.White		0,75 mm²
B	Main_MC42.20	W49.White		0,75 mm²

ID_tag_F [12, 16, 19, 34] — [18] IDTAG (MC_21) — 0,2 m

Splice_C1_47


From	To	Conductor	Color	Gauge
Splice_C1_47	Electric_Drive_FuseBox_B1.B	W84.Orange		1 mm²
Splice_C1_47	Electric_Drive_FuseBox_B1.D	W86.Orange		1 mm²
Splice_C1_47	Landing_Block.1	W77.Red		1 mm²
Splice_C1_47	Landing_Unblock.1	W94.Red		1 mm²
Splice_C1_47	Main_MC42.47	W15.White		0,75 mm²
Splice_C1_47	Main_MC42.63	W67.White		0,75 mm²


Vref_Minus


From	To	Conductor	Color	Gauge
Vref_Minus	Accelerometre.B	W30.Black		1 mm²
Vref_Minus	Bilge_Captor.B	W31.Black		1 mm²
Vref_Minus	Ladder_hal_captor.B	W69.Black		1 mm²
Vref_Minus	Main_MC42.23	W60.White		0,75 mm²
Vref_Minus	Oil_Level.B	W28.Black		1 mm²
Vref_Minus	Pressure_block.1	W26.Black		1 mm²
Vref_Minus	Pressure_tracks.1	W27.Black		1 mm²
Vref_Minus	Water_Level.B	W29.Black		1 mm²


Vref_Plus

From	To	Conductor	Color	Gauge
Vref_Plus	Main_MC42.7	W59.White		0,75 mm²
Vref_Plus	Pressure_block.3	W32.Red		1 mm²
Vref_Plus	Pressure_tracks.3	W33.Red		1 mm²
Vref_Plus	R7.NEG	W34.Red		1 mm²
Vref_Plus	R9.NEG	W39.Red		1 mm²
Vref_Plus	R12.NEG	W76.Red		1 mm²










Wiring diagram



Vérifier que la cavité 65 correspond bien au fil rouge
Vérifier que la cavité 66 correspond bien au fil bleu

Supply

Cavity	To	Conductor	Color	Gauge
A	12V	W58.Red		2,5 mm²
B	Main_MC42.66	W44.Black		2,5 mm²

[18] Supply (MC_10)(FBC_21) — 1 m — Supply [7, 15, 21, 36]

Output_B

From	To	Conductor	Color	Gauge
Output_B	Ladder_hal_captor.D	W10.White		0,75 mm²
Output_B	Main_MC42.12	W61.White		0,75 mm²
Output_B	R2.NEG	W11.White		0,75 mm²

R2 [25] — Output_B [26]

Ladder_hal_captor

Cavity	To	Conductor	Color	Gauge
A	12V	W65.Red		1 mm²
B	Vref_Minus	W69.Black		1 mm²
C	Output_A	W20.White		0,75 mm²
D	Output_B	W10.White		0,75 mm²

12V [26] — [18] Captor (MC_11)(LD_04) — 0,8 m — Ladder_hal_captor [9, 16, 22, 34, 37]

R1 [25] — Output_A [26]

Output_A

From	To	Conductor	Color	Gauge
Output_A	Ladder_hal_captor.C	W20.White		0,75 mm²
Output_A	Main_MC42.11	W55.White		0,75 mm²
Output_A	R1.NEG	W9.White		0,75 mm²

Remote_Power_Box

Cavity	To	Conductor	Color	Gauge
A	Main_MC42.28	W25.White		0,75 mm²
B	Main_MC42.29	W45.White		0,75 mm²

Remo (MC_12)(FB_C06) — 0,8 m — [18] Remote_Power_Box [6, 13, 19, 37]

Electric_Drive_FuseBox_B1

Cavity	To	Conductor	Color	Gauge
A	Main_MC42.44	W53.White		0,75 mm²
B	Splice_C1_47	W84.Orange		1 mm²
C	Main_MC42.60	W54.White		0,75 mm²
D	Splice_C1_47	W86.Orange		1 mm²

[18] FB ED (MC_13)(FBA_01) — 0,8 m — Electric_Drive_FuseBox_B1 [9, 16, 22, 34, 37]

Seat_Control

Cavity	To	Conductor	Color	Gauge
A	Main_MC42.48	W51.White		0,75 mm²
B	Main_MC42.45	W52.White		0,75 mm²

[18] Seat (MC_14)(NT_06) — 0,8 m — Seat_Control [6, 13, 19, 37]

R12

From	To	Conductor	Color	Gauge
R12.NEG	Vref_Plus	W76.Red		1 mm²
R12.POS	Splice_Bilge_Level	W75.Red		1 mm²

R11

From	To	Conductor	Color	Gauge
R11.NEG	Splice_Bilge_Level	W68.Red		1 mm²
R11.POS	Main_MC42.25	W73.White		1 mm²

Splice_Bilge_Level

From	To	Conductor	Color	Gauge
Splice_Bilge_Level	Bilge_Captor.A	W74.Red		1 mm²
Splice_Bilge_Level	R11.NEG	W68.Red		1 mm²
Splice_Bilge_Level	R12.POS	W75.Red		1 mm²

R12 [24] — Splice_Bilge_Level [26] — 0,8 m — Bilge Cap (MC_22) — Bilge_Captor [8, 14, 20, 35]

R11 [24]

Bilge_Captor

Cavity	To	Conductor	Color	Gauge
A	Splice_Bilge_Level	W74.Red		1 mm²
B	Vref_Minus	W31.Black		1 mm²

R9

From	To	Conductor	Color	Gauge
R9.NEG	Vref_Plus	W39.Red		1 mm²
R9.POS	Splice_Water_level1	W41.Red		1 mm²

Splice_Water_level1

From	To	Conductor	Color	Gauge
Splice_Water_level1	R9.POS	W41.Red		1 mm²
Splice_Water_level1	R10.NEG	W40.Red		1 mm²
Splice_Water_level1	Water_Level.A	W38.Red		1 mm²

R9 [24] — Splice_Water_level1 [26] — [18] Water (MC_17) — 0,8 m — Water_Level [8, 14, 20, 35]

R10 [24]

Water_Level

Cavity	To	Conductor	Color	Gauge
A	Splice_Water_level1	W38.Red		1 mm²
B	Vref_Minus	W29.Black		1 mm²

R10

From	To	Conductor	Color	Gauge
R10.NEG	Splice_Water_level1	W40.Red		1 mm²
R10.POS	Main_MC42.24	W18.White		0,75 mm²

[18] Main (MC_18)(NT_05) — 1,5 m — CanBus_Main_to_MC4_10 [6, 13, 19, 34]

CanBus_Main_to_MC4_10

Cavity	To	Conductor	Color	Gauge
A	Main_MC42.17	W21.White		0,75 mm²
B	Main_MC42.1	W22.White		0,75 mm²

[18] Canbus keybox (MC_19)(NT08) — 1,5 m — Canbus_keybox [6, 13, 19, 34]

Canbus_keybox

Cavity	To	Conductor	Color	Gauge
A	Main_MC42.18	W24.White		0,75 mm²
B	Main_MC42.2	W23.White		0,75 mm²

[18] CanDrive (MC_20)(FBA03) — 1,5 m — Can_Battery_HV [6, 13, 19, 34]

Can_Battery_HV

Cavity	To	Conductor	Color	Gauge
A	Main_MC42.19	W56.White		0,75 mm²
B	Main_MC42.3	W57.White		0,75 mm²

Vref_Minus [26]
Vref_Plus [26]
Splice_C1_47 [26]

Accelerometre

Cavity	To	Conductor	Color	Gauge
A	12V	W42.Red		1 mm²
B	Vref_Minus	W30.Black		1 mm²
D	Main_MC42.26	W46.White		0,75 mm²
E	Main_MC42.36	W47.White		0,75 mm²
F	Main_MC42.52	W48.White		0,75 mm²

[18] Acc (MC_15) — 0,8 m — Accelerometre [2, 16, 23, 34, 37, 38]

Bouchon_1 [11, 23, 38]

Splice_C1_46 [26]

PWM_tension_tracks

Cavity	To	Conductor	Color	Gauge
1	Main_MC42.14	W12.White		0,75 mm²
2	Main_MC42.39	W13.White		0,75 mm²

[18] PWM (MC01) — 3,5 m — PWM_tension_tracks [4]

Landing_UP

Cavity	To	Conductor	Color	Gauge
1	Splice_C1_46	W8.Red		1 mm²
2	Main_MC42.57	W2.White		0,75 mm²

[18] UP (MC03) — 3,5 m — Landing_UP [3]

Landing_DOWN

Cavity	To	Conductor	Color	Gauge
1	Splice_C1_46	W7.Red		1 mm²
2	Main_MC42.42	W3.White		0,75 mm²

[18] DOWN (MC04) — 3,5 m — Landing_DOWN [3]

Splice_C1_46

From	To	Conductor	Color	Gauge
Splice_C1_46	ByPass.1	W63.Red		1 mm²
Splice_C1_46	Landing_DOWN.1	W7.Red		1 mm²
Splice_C1_46	Landing_UP.1	W8.Red		1 mm²
Splice_C1_46	Main_MC42.46	W14.White		0,75 mm²
Splice_C1_46	Main_MC42.62	W66.White		0,75 mm²
Splice_C1_46	Track_Tension.1	W62.Red		1 mm²

ByPass

Cavity	To	Conductor	Color	Gauge
1	Splice_C1_46	W63.Red		1 mm²
2	Main_MC42.41	W1.White		0,75 mm²

[18] By Pass (MC02) — 3,5 m — ByPass [3]

Track_Tension

Cavity	To	Conductor	Color	Gauge
1	Splice_C1_46	W62.Red		1 mm²
2	Main_MC42.58	W4.White		0,75 mm²

[18] Track (MC05) — 3,5 m — Track_Tension [3]

Landing_Block

Cavity	To	Conductor	Color	Gauge
1	Splice_C1_47	W77.Red		1 mm²
2	Main_MC42.59	W6.White		0,75 mm²

[18] Block (MC06) — 3,5 m — Landing_Block [3]

Landing_Unblock

Cavity	To	Conductor	Color	Gauge
1	Splice_C1_47	W94.Red		1 mm²
2	Main_MC42.43	W5.White		0,75 mm²

[18] Unblock (MC07) — 3,5 m — Landing_Unblock [3]

Pressure_block

Cavity	To	Conductor	Color	Gauge
1	Vref_Minus	W26.Black		1 mm²
2	Main_MC42.9	W17.White		0,75 mm²
3	Vref_Plus	W32.Red		1 mm²

[18] P Block (MC08) — 3,5 m — Pressure_block [10, 17, 34]

Pressure_tracks

Cavity	To	Conductor	Color	Gauge
1	Vref_Minus	W27.Black		1 mm²
2	Main_MC42.10	W19.White		0,75 mm²
3	Vref_Plus	W33.Red		1 mm²

[18] P Track (MC09) — 3,5 m — Pressure_tracks [10, 17, 34]

R7

From	To	Conductor	Color	Gauge
R7.NEG	Vref_Plus	W34.Red		1 mm²
R7.POS	Splice_Oil_level	W35.Red		1 mm²

R7 [24]

R8

From	To	Conductor	Color	Gauge
R8.NEG	Splice_Oil_level	W37.Red		1 mm²
R8.POS	Main_MC42.8	W16.White		0,75 mm²

R8 [24]

Oil_Level

Cavity	To	Conductor	Color	Gauge
A	Splice_Oil_level	W36.Red		1 mm²
B	Vref_Minus	W28.Black		1 mm²

Splice_Oil_level [26] — 4,3 m — [18] Oil (MC_16) — Oil_Level [8, 14, 20, 35]

Splice_Oil_level

From	To	Conductor	Color	Gauge
Splice_Oil_level	Oil_Level.A	W36.Red		1 mm²
Splice_Oil_level	R7.POS	W35.Red		1 mm²
Splice_Oil_level	R8.NEG	W37.Red		1 mm²

Title	#24207 - MC42_CAB (MC) - Ind L		
Description		Revision	G

	Name	Date
Drawn By	----	----
Eng Approved	----	----
Mfg Approved	----	----
QA	----	----

This document contains confidential and proprietary information that cannot be reproduced or divulged, in whole or in part, without written authorization.

Title:	#24207 - MC42_CAB (MC) - Ind L
Description:	

Id	Type	Part Number	Quantity	Description	Manufacturer
1	Connector	#21436 - Parker_IDTAG_1	1	5030061	
2	Connector	#15960 - Delphi_150_6_way_female	1	Delphi 12052848	Delphi
3	Connector	#20694 - Phoenix_valve_2_way	6	651-1410723	
4	Connector	#23554 - Phoenix_3_way_female	1	651-1402983	
5	Connector	#24679 - Parker_C1_66_way	1		
6	Connector	#15215 - Delphi_150_2_way_male	6	Delphi 12162000	Delphi
7	Connector	#17183 - Delphi_480_2_way_male	1	Delphi 12065863	Delphi
8	Connector	#17351 - Delphi_280_2_way_female	3	Delphi 15300027	Delphi
9	Connector	#28050 - Delphi_150_4_way_female	2	Delphi 12160482-B	Delphi
10	Connector	#12189 - Te_Timer_3_way_female	2	571-2821911	TE
11	Connector	#14017 - Delphi_150_6_way_male	1	Delphi 12124107	Delphi
12	Connector	#14869 - Delphi_150_2_way_female	1	Delphi 12052641	Delphi
13	Contact	#10019 Delphi_150_contact_male 0.5-1.0mm² 1.69-2.78mm	12	Delphi 12045773	Delphi
14	Contact	#37579 Delphi_280_contact_female 1.0-2.0mm² 2.48-3.05mm	6	Delphi 12077412-L	Delphi
15	Contact	#17237 Delphi_480_contact_male 5mm² 3.49-5.24mm	2	Delphi 12052172	Delphi
16	Contact	#13657 Delphi_150_contact_female 0.5-1.0mm² 2.03-2.80mm	15	Delphi 12048074	Delphi
17	Contact	#15166 - Junior TIMER RECPT Contact - JPT	6		TE Connectivity
18	Label	Generic White Label	23	Generic Label	
19	Lock	#19468 - Delphi_150_2_way_lock	7	Delphi 12052634	Delphi
20	Lock	#18797 - Delphi_280_2_way_lock	3	Delphi 15300014-B	Delphi
21	Lock	#10273 - Delphi_480_2_way_lock	1	Delphi 12059897	Delphi
22	Lock	#22024 - Delphi_150_4_way_female_lock	2	Delphi 12160480	Delphi
23	Lock	#14848 - Delphi_150_6_way_lock	2	Delphi 12052850	Delphi
24	Resistor	#21463 - 240 Ohm resistor	6		
25	Resistor	10 kOhm	2		
26	Splice	Generic Splice	10	Generic Splice	
27	Wire	1mm² Black	≥ 14,5 m		
28	Wire	1mm² Red	≥ 35,5 m		
29	Wire	2.5mm² - Black	≥ 1 m		
30	Wire	2.5mm² - Red	≥ 1 m		
31	Wire	C1_Wire	≥ 53,2 m		
32	Wire	1mm² - White			
33	Wire	1 mm² Orange	≥ 1,6 m	Generic Wire	
34	Wire Seal	#17898 - Delphi 150 Cable seal – White – 1.60-2.15	20	Delphi 12089442	Delphi
35	Wire Seal	#13381 - Delphi 280 Cable seal – Green– 2.03-2.85	6	Delphi 12015284	Delphi
36	Wire Seal	#15414 - Delphi 480 Cable seal – Red – 2.81-3.76	2	Delphi 12052452	Delphi
37	Wire Seal	#14820 - Delphi 150 Cable seal – Blue – 1.29-1.70	13	Delphi 12052925	Delphi
38	Wire Seal	#19593 - Delphi 150 Cavity plug	7	Delphi 12059168	Delphi
39	Wire	0.75² White			