Revisions			
Rev.	Date	Author	Description
A	05/06/2025	V.M	Création pour premier bateau Kubota #112
B	02/07/2025	R.F	Refonte pour facilité de lecture + nouvelle adaptation aux faisceaux

Splice_port_tension

From	To	Conductor	Color	Size
Splice_port_tension	12V_inboard.A	W7.Red		1,5 mm²
Splice_port_tension	12V_inboard.B	W10.Red		1,5 mm²
Splice_port_tension	Port_tension.A	W6.Red		1,5 mm²
Splice_port_tension	Supply_inboard_solenoid	W15.Red		4 mm²
Splice_port_tension	port_tension_sensor.A	W16.Red		1 mm²

Supply_inboard_solenoid

From	To	Conductor	Color	Size
Supply_inboard_solenoid	Splice_port_tension	W15.Red		4 mm²

Supply_inboard_solenoid [20]

2,5 m

1 Splice_port_tension [21]

[15]

0,8 m

port_tension_sensor IN01 MC24

port_tension_sensor [2, 8, 16, 34, 35]

port_tension_sensor

Cavity	To	Conductor	Color	Size
A	Splice_port_tension	W16.Red		1 mm²

[15]

0,8 m

Port_tension starter inboard IN02 IM10

Port_tension [4, 9, 17, 32, 33]

Port_tension

Cavity	To	Conductor	Color	Size
A	Splice_port_tension	W6.Red		1,5 mm²

12V_inboard

Cavity	To	Conductor	Color	Size
A	Splice_port_tension	W7.Red		1,5 mm²
B	Splice_port_tension	W10.Red		1,5 mm²

12V_inboard [3, 12, 17, 32]

[14]

Cmd supply inboard

1,7 m

2,5 m

Starter_inboard_cmd IN03 IM09

[14]

Starter_inboard_cmd [3, 10, 17, 36]

Starter_inboard_cmd

Cavity	To	Conductor	Color	Size
A	Connecteur_16Voies_Kubota.A	W9.Violet		1,5 mm²

Connecteur_16Voies_Kubota

Cavity	To	Conductor	Color	Size
A	Starter_inboard_cmd.A	W9.Violet		1,5 mm²
C	Fuel_pump.B	W12.Black		1,5 mm²
D	Fuel_pump.A	W11.Red		1,5 mm²
F	Starter.A	W3.Orange		1,5 mm²

Connecteur_16Voies_Kubota [6, 11, 18, 37]



2,5 m

Starter IN04 KE05

[14]

Starter [7, 13, 16, 34, 35]

Starter

Cavity	To	Conductor	Color	Size
A	Connecteur_16Voies_Kubota.F	W3.Orange		1,5 mm²

Fuel_pump

Cavity	To	Conductor	Color	Size
A	Connecteur_16Voies_Kubota.D	W11.Red		1,5 mm²
B	Connecteur_16Voies_Kubota.C	W12.Black		1,5 mm²

Fuel pump

Fuel_pump [4, 9, 17, 32] [14]

0,8 m

Exhaust_pump

Cavity	To	Conductor	Color	Size
A	exhaust_pump_ke.A	W8.Blue		1,5 mm²
B	Minus_splice	W19.Black		1,5 mm²

Minus_splice [22]

Exhaust pump

1

Exhaust_pump [4, 9, 17, 32] [14]

2,5 m

Exhaust pump IN05 KE09

[14]

exhaust_pump_ke [3, 12, 17, 32]

exhaust_pump_ke

Cavity	To	Conductor	Color	Size
A	Exhaust_pump.A	W8.Blue		1,5 mm²
B	Minus_splice	W14.Black		1,5 mm²

Minus_splice

From	To	Conductor	Color	Size
Minus_splice	Can_Engine.C	W17.Black		1 mm²
Minus_splice	Exhaust_pump.B	W19.Black		1,5 mm²
Minus_splice	exhaust_pump_ke.B	W14.Black		1,5 mm²

Can_Engine

Cavity	To	Conductor	Color	Size
A	CanBus_MC42.A	CBL1.White		0,75 mm²
B	CanBus_MC42.B	CBL1.Black		0,75 mm²
C	Minus_splice	W17.Black		1 mm²

Canbus engine

Can_Engine [5, 13, 19, 31, 38]

3,3 m

Can Bus Engine IN03 MC20

[14]

CanBus_MC42 [2, 8, 16, 31]

CanBus_MC42

Cavity	To	Conductor	Color	Size
A	Can_Engine.A	CBL1.White		0,75 mm²
B	Can_Engine.B	CBL1.Black		0,75 mm²

	Name	Date
Drawn By	----	----
Eng Approved	----	----
Mfg Approved	----	----
QA	----	----

Title #39209-Engine Kubota (IN)

Description Création pour premier Kubota #112

Revision ----

This document contains confidential and proprietary information that cannot be reproduced or divulged, in whole or in part, without written authorization.

Title:	#39209-Engine Kubota (IN)
Description:	Création pour premier Kubota #112

Id	Type	Part Number	Quantity	Description	Manufacturer
1	Cable	#33491 Belden shielded twisted pair 0.75mm²	≥ 3,3 m	Belden 8760 060250	Belden
2	Connector	#14869 - Delphi_150_2_way_female	2	Delphi 12052641	Delphi
3	Connector	#16777 - Delphi_280_2_way_male	3	Delphi 15300002	Delphi
4	Connector	#17351 - Delphi_280_2_way_female	3	Delphi 15300027	Delphi
5	Connector	#15412 - Delphi_150_3_way_male	1	829-12129615	Delphi
6	Connector	#34355 - Delphi 15326868 - 16 Way Black GT 150 Sealed Male Connector Assembly	1	Delphi 15326868	Delphi
7	Connector	#15215 - Delphi_150_2_way_male	1	Delphi 12162000	Delphi
8	Contact	#13657 Delphi_150_contact_female 0.5-1.0mm² 2.03-2.80mm	3	Delphi 12048074	Delphi
9	Contact	#37579 Delphi_280_contact_female 1.0-2.0mm² 2.48-3.05mm	5	Delphi 12077412-L	Delphi
10	Contact	#16370 Delphi_280_contact_male 2.0-3.0mm² 2.45-3.8mm	1	Delphi 12129497	Delphi
11	Contact	#35371 - Pin Delphi 15326269-L	4	Delphi 15326269-L	Delphi
12	Contact	#13581 Delphi_280_contact_male 0.5-0.8mm² 1.69-2.78mm	4	Delphi 12048159	Delphi
13	Contact	#10019 Delphi_150_contact_male 0.5-1.0mm² 1.69-2.78mm	4	Delphi 12045773	Delphi
14	Label	Generic White Label	8	Generic Label	
15	Label		2		
16	Lock	#19468 - Delphi_150_2_way_lock	3	Delphi 12052634	Delphi
17	Lock	#18797 - Delphi_280_2_way_lock	6	Delphi 15300014-B	Delphi
18	Lock	#36267 - Delphi 15358785 - 2 row 16 way Secondary Lock GT150	1	Delphi 15358785	Delphi
19	Lock	#17233 - Delphi 150 3Way lock	1		
20	Ring Terminal	#23963 - Cosse à sertir Jaune - 8 mm	1		
21	Splice	#10214 Heatshrinkable crimp splice - Yellow - 3-6mm²	1	TE Duraseal DS-10-12	TE Connectivity
22	Splice	#16489 Heatshrinkable crimp splice - Blue - 1.5-2.5mm²	1	TE Duraseal DS-14-16	TE Connectivity
23	Wire	1.5mm² - Red	≥ 5 m		
24	Wire	1.5 mm² - Orange	≥ 2,5 m		
25	Wire	1.5mm² - Purple	≥ 2,5 m		
26	Wire	1.5mm² - Blue	2,5 m		
27	Wire	1.5mm² - Black	≥ 0,8 m		
28	Wire	4 mm² - Red	2,5 m		
29	Wire	1mm² Red	≥ 0,8 m		
30	Wire	1mm² Black			
31	Wire Seal	#17898 - Delphi 150 Cable seal – White – 1.60-2.15	3	Delphi 12089442	Delphi
32	Wire Seal	#13381 - Delphi 280 Cable seal – Green– 2.03-2.85	9	Delphi 12015284	Delphi
33	Wire Seal	#19508 - Delphi 280 Cavity plug	1	Delphi 12010300	Delphi
34	Wire Seal	#19593 - Delphi 150 Cavity plug	2	Delphi 12059168	Delphi
35	Wire Seal	#18901 - Delphi 150 Cable seal – Dark-red – 2.03-2.85	2	Delphi 12052924	Delphi
36	Wire Seal	#19901 - Delphi 280 Cable seal – Dark Red– 1.29-1.70	1	Delphi 12034365	Delphi
37	Wire Seal	#31056 - Seal Delphi 15366060	4	Delphi 15366060	Delphi
38	Wire Seal	#14820 - Delphi 150 Cable seal – Blue – 1.29-1.70	2	Delphi 12052925	Delphi