



Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

Programming in Modern C++

Module M35: Multiple Inheritance

Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

All url's in this module have been accessed in September, 2021 and found to be functional



Module Recap

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime

Diamond Problem

Exercise

Design Choice

Module Summary

- Understood casting at run-time
- Studied `dynamic_cast` with examples
- Understood RTTI and `typeid` operator



Module Objectives

Module M35

Partha Pratim
Das

Objectives & Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

- Understand Multiple Inheritance in C++

NPTEL



Module Outline

Module M35

Partha Pratim
Das

Objectives & Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

- 1 Multiple Inheritance in C++
 - Semantics
 - Data Members and Object Layout
 - Member Functions – Overrides and Overloads
 - Access Members of Base: protected Access
 - Constructor & Destructor
 - Object Lifetime
- 2 Diamond Problem
 - Exercise
- 3 Design Choice
- 4 Module Summary



Multiple Inheritance in C++

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

Multiple Inheritance in C++

Source:

- [Is inheritance bad practice in OOP?](#), quora, 2019



Multiple Inheritance in C++: Hierarchy

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime


Diamond Problem

Exercise

Design Choice

Module Summary

- TA ISA Student; TA ISA Faculty



```
class Student;                                // Base Class = Student
class Faculty;                                // Base Class = Faculty
class TA: public Student, public Faculty;      // Derived Class = TA
```

- TA inherits properties and operations of both Student as well as Faculty



Multiple Inheritance in C++: Hierarchy

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime


Diamond Problem

Exercise

Design Choice

Module Summary

- **Manager ISA Employee, Director ISA Employee, ManagingDirector ISA Manager, ManagingDirector ISA Director**



```
class Employee;                                     // Base Class = Employee -- Root
class Manager: public Employee;                       // Derived Class = Manager
class Director: public Employee;                     // Derived Class = Director
class ManagingDirector: public Manager, public Director; // Derived Class = ManagingDirector
```

- **Manager** inherits properties and operations of **Employee**
- **Director** inherits properties and operations of **Employee**
- **ManagingDirector** inherits properties and operations of both **Manager** as well as **Director**
- **ManagingDirector**, by transitivity, inherits properties and operations of **Employee**
- **Multiple inheritance hierarchy usually has a common base class**
- This is known as the **Diamond Hierarchy**



Multiple Inheritance in C++: Semantics

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime


Diamond Problem

Exercise

Design Choice

Module Summary

- Derived ISA Base1, Derived ISA Base2



```
class Base1; // Base Class = Base1
class Base2; // Base Class = Base2
class Derived: public Base1, public Base2; // Derived Class = Derived
```

- Use keyword **public** after class name to denote inheritance
- Name of the Base class follow the keyword
- There may be more than two base classes
- public** and **private** inheritance may be mixed



Multiple Inheritance in C++: Semantics

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime

Diamond Problem

Exercise

Design Choice

Module Summary

- Data Members
 - **Derived** class *inherits all* data members of *all Base* classes
 - **Derived** class may *add* data members of its own
- Member Functions
 - **Derived** class *inherits all* member functions of *all Base* classes
 - **Derived** class may *override* a member function of *any Base* class by *redefining* it with the *same signature*
 - **Derived** class may *overload* a member function of *any Base* class by *redefining* it with the *same name*; but *different signature*
- Access Specification
 - **Derived** class *cannot access private* members of *any Base* class
 - **Derived** class *can access protected* members of *any Base* class
- Construction-Destruction
 - A *constructor* of the **Derived** class *must first* call *all constructor*s of the **Base** classes to construct the **Base** class instances of the **Derived** class – **Base** class *constructor*s are called in *listing order*
 - The *destructor* of the **Derived** class *must* call the *destructor*s of the **Base** classes to destruct the **Base** class instances of the **Derived** class



Multiple Inheritance in C++: Data Members and Object Layout

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime

Diamond Problem

Exercise

Design Choice

Module Summary

- Data Members
 - **Derived** class *inherits all* data members of *all Base* classes
 - **Derived** class may *add* data members of its own
- Object Layout
 - **Derived** class *layout* contains instances of *each Base* class
 - Further, **Derived** class *layout* will have data members of its own
 - C++ does not guarantee the *relative position* of the **Base** class instances and **Derived** class members



Multiple Inheritance in C++: Data Members and Object Layout

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime

Diamond Problem

Exercise

Design Choice

Module Summary

```
class Base1 { protected:
    int i_, data_;
public: // ...
};
class Base2 { protected:
    int j_, data_;
public: // ...
};
class Derived: public Base1, public Base2 { // Multiple inheritance
    int k_;
public: // ...
};
```

Object Layout


Object Base1



Object Base2



Object Derived



- Object Derived has two **data_** members!
- Ambiguity to be resolved with base class name: **Base1::data_** & **Base2::data_**



Multiple Inheritance in C++: Member Functions – Overrides and Overloads

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

- **Derived ISA Base1, Base2**
- **Member Functions**
 - **Derived** class *inherits all* member functions of *all Base* classes
 - **Derived** class may *override* a member function of *any Base* class by *redefining* it with the *same signature*
 - **Derived** class may *overload* a member function of *any Base* class by *redefining* it with the *same name*; but *different signature*
- **Static Member Functions**
 - **Derived** class *does not inherit* the static member functions of *any Base* class
- **Friend Functions**
 - **Derived** class *does not inherit* the friend functions of *any Base* class



Multiple Inheritance in C++:

Member Functions – Overrides and Overloads

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

```
class Base1 { protected: int i_, data_;  
public: Base1(int a, int b): i_(a), data_(b) { }  
    void f(int) { cout << "Base1::f(int) \n"; }  
    void g() { cout << "Base1::g() \n"; }  
};  
class Base2 { protected: int j_, data_;  
public: Base2(int a, int b): j_(a), data_(b) { }  
    void h(int) { cout << "Base2::h(int) \n"; }  
};  
class Derived: public Base1, public Base2 { int k_;  
public: Derived(int x, int y, int u, int v, int z): Base1(x, y), Base2(u, v), k_(z) { }  
    void f(int) { cout << "Derived::f(int) \n"; }           // -- Overridden Base1::f(int)  
    // -- Inherited Base1::g()  
    void h(string) { cout << "Derived::h(string) \n"; } // -- Overloaded Base2:: h(int)  
    void e(char) { cout << "Derived::e(char) \n"; }       // -- Added Derived::e(char)  
};
```

```
Derived c(1, 2, 3, 4, 5);
```

```
c.f(5);           // Derived::f(int)    -- Overridden Base1::f(int)  
c.g();           // Base1::g()         -- Inherited Base1::g()  
c.h("ppd");      // Derived::h(string) -- Overloaded Base2:: h(int)  
c.e('a');        // Derived::e(char)   -- Added Derived::e(char)
```



Inheritance in C++:

Member Functions – using for Name Resolution

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime

Diamond Problem

Exercise

Design Choice

Module Summary

Ambiguous Calls

```
class Base1 { public:
    Base1(int a, int b);
    void f(int) { cout << "Base1::f(int) "; }
    void g() { cout << "Base1::g() "; }
};

class Base2 { public:
    Base2(int a, int b);
    void f(int) { cout << "Base2::f(int) "; }
    void g(int) { cout << "Base2::g(int) "; }
};

class Derived: public Base1, public Base2 {
public: Derived(int x, int y, int u, int v, int z);
};

Derived c(1, 2, 3, 4, 5);
```

```
c.f(5); // Base1::f(int) or Base2::f(int)?
c.g(5); // Base1::g() or Base2::g(int)?
c.f(3); // Base1::f(int) or Base2::f(int)?
c.g();  // Base1::g() or Base2::g(int)?
```

Unambiguous Calls

```
class Base1 { public:
    Base1(int a, int b);
    void f(int) { cout << "Base1::f(int) "; }
    void g() { cout << "Base1::g() "; }
};

class Base2 { public:
    Base2(int a, int b);
    void f(int) { cout << "Base2::f(int) "; }
    void g(int) { cout << "Base2::g(int) "; }
};

class Derived: public Base1, public Base2 {
public: Derived(int x, int y, int u, int v, int z);
    using Base1::f; // Hides Base2::f
    using Base2::g; // Hides Base1::g
};

Derived c(1, 2, 3, 4, 5);
```

```
c.f(5); // Base1::f(int)
c.g(5); // Base2::g(int)
c.Base2::f(3); // Base2::f(int)
c.Base1::g(); // Base1::g()
```

- **Overload resolution does not work between `Base1::g()` and `Base2::g(int)`**
- **`using` hides other candidates; Explicit use of base class name can resolve (weak solution)**



Multiple Inheritance in C++:

Access Members of Base: protected Access

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

- Access Specification

- **Derived** class *cannot access private* members of *any* **Base** class
- **Derived** class *can access protected* members of *any* **Base** class



Multiple Inheritance in C++: Constructor & Destructor

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

- Constructor-Destructor
 - Derived class *inherits all* Constructors and Destructor of Base classes (*but in a different semantics*)
 - Derived class *cannot overload* a Constructor or *cannot override* the Destructor of *any* Base class
- Construction-Destruction
 - A *constructor* of the Derived class *must first* call *all constructors* of the Base classes to construct the Base class instances of the Derived class
 - Base class *constructors* are called in *listing order*
 - The *destructor* of the Derived class *must* call the *destructors* of the Base classes to destruct the Base class instances of the Derived class



Multiple Inheritance in C++: Constructor & Destructor

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

```
class Base1 { protected: int i_; int data_;
public: Base1(int a, int b): i_(a), data_(b) { cout << "Base1::Base1() "; }
    ~Base1() { cout << "Base1::~Base1() "; }
};

class Base2 { protected: int j_; int data_;
public: Base2(int a = 0, int b = 0): j_(a), data_(b) { cout << "Base2::Base2() "; }
    ~Base2() { cout << "Base2::~Base2() "; }
};

class Derived: public Base1, public Base2 { int k_;
public: Derived(int x, int y, int z):
    Base1(x, y), k_(z) { cout << "Derived::Derived() "; }
    // Base1::Base1 explicit, Base2::Base2 default
    ~Derived() { cout << "Derived::~Derived() "; }
};

Base1 b1(2, 3);
Base2 b2(3, 7);
Derived d(5, 3, 2);
```

Object Layout

Object b1

Object b2

Object d

2
3

3
7

5
3
0
0
2



Multiple Inheritance in C++: Object Lifetime

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime

Diamond Problem

Exercise

Design Choice

Module Summary

```

class Base1 { protected: int i_; int data_;
public: Base1(int a, int b): i_(a), data_(b)
    { cout << "Base1::Base1() " << i_ << ' ' << data_ << endl; }
    ~Base1() { cout << "Base1::~Base1() " << i_ << ' ' << data_ << endl; }
};

class Base2 { protected: int j_; int data_;
public: Base2(int a = 0, int b = 0): j_(a), data_(b)
    { cout << "Base2::Base2() " << j_ << ' ' << data_ << endl; }
    ~Base2() { cout << "Base2::~Base2() " << j_ << ' ' << data_ << endl; }
};

class Derived: public Base1, public Base2 { int k_; public:
    Derived(int x, int y, int z): Base1(x, y), k_(z)
    { cout << "Derived::Derived() " << k_ << endl; }
    // Base1::Base1 explicit, Base2::Base2 default
    ~Derived() { cout << "Derived::~Derived() " << k_ << endl; }
};

```

Derived d(5, 3, 2);

Construction O/P

```

Base1::Base1(): 5, 3 // Obj. d.Base1
Base2::Base2(): 0, 0 // Obj. d.Base2
Derived::Derived(): 2 // Obj. d

```

Destruction O/P

```

Derived::~Derived(): 2 // Obj. d
Base2::~Base2(): 0, 0 // Obj. d.Base2
Base1::~Base1(): 5, 3 // Obj. d.Base1

```

- First construct base class objects, then derived class object
- First destruct derived class object, then base class objects



Diamond Problem

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

Diamond Problem



Multiple Inheritance in C++: Diamond Problem

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime


Diamond Problem

Exercise

Design Choice

Module Summary

- **Student ISA Person**
- **Faculty ISA Person**
- **TA ISA Student; TA ISA Faculty**



```
class Person; // Base Class = Person -- Root
class Student: public Person; // Base / Derived Class = Student
class Faculty: public Person; // Base / Derived Class = Faculty
class TA: public Student, public Faculty; // Derived Class = TA
```

- **Student** inherits properties and operations of **Person**
- **Faculty** inherits properties and operations of **Person**
- **TA** inherits properties and operations of both **Student** as well as **Faculty**
- **TA**, by transitivity, inherits properties and operations of **Person**



Multiple Inheritance in C++: Diamond Problem

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

```
#include<iostream>
using namespace std;

class Person { // data members of person
    public: Person(int x) { cout << "Person::Person(int)" << endl; }
};
class Faculty: public Person { // data members of Faculty
    public: Faculty(int x): Person(x) { cout << "Faculty::Faculty(int)" << endl; }
};
class Student: public Person { // data members of Student
    public: Student(int x): Person(x) { cout << "Student::Student(int)" << endl; }
};
class TA: public Faculty, public Student {
    public: TA(int x): Student(x), Faculty(x) { cout << "TA::TA(int)" << endl; }
};
int main() { TA ta(30);
}
```

```
Person::Person(int)
Faculty::Faculty(int)
Person::Person(int)
Student::Student(int)
TA::TA(int)
```

- Two instances of base class object (Person) in a TA object!



Multiple Inheritance in C++:

virtual Inheritance – virtual Base Class

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

```
#include<iostream>
using namespace std;
class Person { // data members of person
    public: Person(int x) { cout << "Person::Person(int)" << endl; }
    Person() { cout << "Person::Person()" << endl; } // Default ctor for virtual inheritance
};
class Faculty: virtual public Person { // data members of Faculty
    public: Faculty(int x): Person(x) { cout << "Faculty::Faculty(int)" << endl; }
};
class Student: virtual public Person { // data members of Student
    public: Student(int x): Person(x) { cout << "Student::Student(int)" << endl; }
};
class TA: public Faculty, public Student {
    public: TA(int x): Student(x), Faculty(x) { cout << "TA::TA(int)" << endl; }
};
int main() { TA ta(30); }
```

Person::Person()

Faculty::Faculty(int)

Student::Student(int)

TA::TA(int)

- Introduce a default constructor for root base class **Person**
- Prefix every inheritance of **Person** with **virtual**
- **Only one instance of base class object (Person) in a TA object!**



Multiple Inheritance in C++: virtual Inheritance with Parameterized Ctor

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

```
#include<iostream>
using namespace std;

class Person {
    public: Person(int x) { cout << "Person::Person(int)" << endl; }
    Person() { cout << "Person::Person()" << endl; }
};

class Faculty: virtual public Person {
    public: Faculty(int x): Person(x) { cout << "Faculty::Faculty(int)" << endl; }
};

class Student: virtual public Person {
    public: Student(int x): Person(x) { cout << "Student::Student(int)" << endl; }
};

class TA: public Faculty, public Student {
    public: TA(int x): Student(x), Faculty(x), Person(x) { cout << "TA::TA(int)" << endl; }
};

int main() { TA ta(30); }

Person::Person(int)
Faculty::Faculty(int)
Student::Student(int)
TA::TA(int )
```

- Call parameterized constructor of root base class **Person** from constructor of **TA** class



Multiple Inheritance in C++: Ambiguity

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime

Diamond Problem

Exercise

Design Choice

Module Summary

```
#include<iostream>
using namespace std;

class Person {
    public: Person(int x) { cout << "Person::Person(int)" << endl; }
    Person() { cout << "Person::Person()" << endl; }
    virtual ~Person();
    virtual void teach() = 0;
};

class Faculty: virtual public Person {
    public: Faculty(int x): Person(x) { cout << "Faculty::Faculty(int)" << endl; }
    virtual void teach();
};

class Student: virtual public Person {
    public: Student(int x): Person(x) { cout << "Student::Student(int)" << endl; }
    virtual void teach();
};

class TA: public Faculty, public Student {
    public: TA(int x): Student(x), Faculty(x) { cout << "TA::TA(int)" << endl; }
    virtual void teach();
};
```

• In the absence of `TA::teach()`, which of `Student::teach()` or `Faculty::teach()` should be inherited?



Multiple Inheritance in C++: Exercise

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

```
class A {  
public:  
    virtual ~A() { cout << "A::~~A()" << endl; }  
    virtual void foo() { cout << "A::foo()" << endl; }  
};  
class B: public virtual A {  
public:  
    virtual ~B() { cout << "B::~~B()" << endl; }  
    virtual void foo() { cout << "B::foo()" << endl; }  
};  
class C: public virtual A {  
public:  
    virtual ~C() { cout << "C::~~C()" << endl; }  
    virtual void foobar() { cout << "C::foobar()" << endl; }  
};  
class D: public B, public C {  
public:  
    virtual ~D() { cout << "D::~~D()" << endl; }  
    virtual void foo() { cout << "D::foo()" << endl; }  
    virtual void foobar() { cout << "D::foobar()" << endl; }  
};
```

- Consider the effect of calling `foo` and `foobar` for various objects and various pointers



Design Choice

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

NPTEL

Design Choice



Design Choice: Inheritance or Composition

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime


Diamond Problem

Exercise

Design Choice

Module Summary

- Vehicle Hierarchy



- Wheeled Hierarchy and Engine Hierarchy interact
- Large number of cross links!
- Multiplicative options make modeling difficult



Design Choice: Inheritance or Composition

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime


Diamond Problem

Exercise

Design Choice

Module Summary

- Vehicle Hierarchy



- Wheeled Hierarchy use Engine as Component
- Linear options to simplify models
- Is this dominant?



Design Choice: Inheritance or Composition

Module M35

Partha Pratim Das

Objectives & Outlines

Multiple Inheritance in C++

Semantics

Data Members

Overrides and Overloads

protected Access

Constructor & Destructor

Object Lifetime


Diamond Problem

Exercise

Design Choice

Module Summary

- Vehicle Hierarchy



- Engine Hierarchy use **Wheeled** as Component
- Linear options to simplify models
- Is this dominant?



Module Summary

Module M35

Partha Pratim
Das

Objectives &
Outlines

Multiple
Inheritance in
C++

Semantics

Data Members

Overrides and
Overloads

protected Access

Constructor &
Destructor

Object Lifetime

Diamond
Problem

Exercise

Design Choice

Module Summary

- Introduced the Semantics of Multiple Inheritance in C++
- Discussed the Diamond Problem and solution approaches
- Illustrated the design choice between inheritance and composition