BIRLANU · PRODUCT MAPPING EVAL

RUN_DATE

Mapping, *measured.*

SKU-based, brand-based, normal product title, MRP-based — each mapping logic run on its own set of product titles.



ACC_SKU

SKU-BASED

ACC_BRAND

BRAND-BASED

ACC_TITLE

NORMAL TITLE

ACC_MRP

MRP-BASED

One dataset per mapping logic, each built to *exercise that logic*.

Each logic was run on its own set of `TITLES` product titles, so the four results are comparable lane by lane.

SKU-based	Titles that carry an embedded product code — the code path, tested on its own.
Brand-based	Titles carrying the brand token and no code — the brand path, tested on its own.
Normal product title	Plain titles: no code and no brand token — matching on the words alone.
MRP-based	Titles matched with price in the picture — the price-led path, tested on its own.

One run per logic, every title scored against its *recorded result*.

01	The sets	Four datasets, one per mapping logic, each holding its own product titles as the agent receives them — no codes or hints added.
02	The runs	One run per logic, same revision and the same conditions throughout; nothing adjusted afterwards.
03	The scoring	Each title carries its expected result, fixed in the set before the run; every title is scored against it the same way.

How each mapping logic *performed*.

SKU-based	ACC_SKU
Brand-based	ACC_BRAND
Normal title	ACC_TITLE
MRP-based	ACC_MRP

Each logic scored against the expected result recorded in its own set; results as reported by the run.