Domain-Oriented Context Cores: Bounded Context for AI Decision Support in Software Projects

Alexander Young

June 2026

Abstract

Modern AI-assisted software development often loads repository-scale context into large language models (LLMs), increasing cost, latency, and attention dilution on scoped decision questions. We introduce AI Context OS, a framework that models repository knowledge as Context Cores - domain-oriented context partitions with lightweight multi-core routing. We report exploratory within-subjects A/B/C experiments on four codebases (149 decision-scoped questions; gpt-4o-mini; LLM-as-judge): MailAgent, Django REST Framework, Navorina, and Oiloop (private macOS). Context Cores (Condition B) achieved 8× to 38× token compression (CCR_tokens) and large cost reductions versus full-repository baselines (Condition A). On three open-source projects, B mean accuracy exceeded A by 19-24 percentage points. On Oiloop (Phase 3.1, 20 questions, v1.1 cores), B reached 2.70 versus A 0.75 (bootstrap 95% CI on paired Δ: [+1.60, +2.30]); a production keyword router preserved gains (B 2.75, F1 1.0, hallucination 0%). Hybrid core-plus-graph retrieval (Condition D) did not beat multi-core B on cross-cutting questions (H_{1f} rejected). The primary hypothesis is supported on decision-scoped questions: efficiency gains are consistent; accuracy gains require adequate core metadata and multi-core routing on integrated codebases. A 10-question author-rated blind pilot preferred B in 70% of cases, with the remaining 30% rated equal (n=10; not independent experts). Masked decode preference on prior runs: 75% B-or-equal. We release protocols, raw runs (three of four full; Django aggregate-only), and routing artifacts for replication.

Keywords Context engineering · Large language models · Software engineering · Retrieval-augmented generation · Domain-driven design

1 Introduction

The integration of large language models (LLMs) into software engineering workflows has progressed from function-level code completion to repository-level understanding and reasoning. Contemporary commercial LLMs expose context windows of up to two million tokens, encouraging a direct engineering response: loading the entire workspace - source files, dependencies, documentation, and configuration - into the prompt baseline.

This brute-force approach simplifies retrieval pipelines but introduces three systematic costs:

1. **Token cost inflation.** Processing tens of thousands of tokens per query is financially unsustainable at high query volumes.
2. **Latency degradation.** Inference time scales with prompt length, introducing multi-second delays that disrupt developer focus.
3. **Attention dilution.** LLMs frequently fail to locate and prioritize critical details when surrounded by large volumes of irrelevant code, yielding incorrect recommendations, omissions, or hallucinations [1].

To address these limitations, we propose **Context Cores**, a structured alternative grounded in domain-driven design (DDD) [3]. Instead of treating a repository as a monolithic file index, we construct minimal, self-contained semantic units aligned with distinct architectural responsibilities. A lightweight query router selects active cores for each query, compiling only essential guidelines and code symbols.

We present the **AI Context OS** framework and report a multi-phase evaluation across three open-source codebases and one proprietary macOS application. We compare:

- **Condition A (full-repository baseline):** The entire repository structure and files loaded into the LLM context.
- **Condition B (routed Context Cores):** Scoped domain guidelines and relevant entities loaded via keyword or semantic routing.
- **Condition C (graph-based retrieval):** A dependency graph built via static AST analysis, loading nodes and code snippets within two hops of query seeds.

1.1 Contributions

This paper makes the following contributions:

1. **AI Context OS**, a domain-oriented context framework with explicit cores, routing, and prompt compilation.
2. A **within-subjects evaluation protocol** spanning 149 decision-scoped questions on four codebases, with published raw runs and replication artifacts.
3. **Empirical evidence** that routed Context Cores compress input tokens by 8×-38× while matching or exceeding full-repository accuracy when core metadata and routing are adequate.
4. A **stratum-dependent production decision matrix** comparing Conditions B, C, and D under stated limitations (LLM-as-judge, partial Django export).

2 Problem Formulation

2.1 Attention Dilution in Large Context Windows

Let P denote the user query and $R = \{f_1, f_2, \ldots, f_n\}$ the set of repository files. Under Condition A, the input prompt is

$$I_A = [\text{SystemInstructions}, R, P].$$

As $|R|$ grows, token length $L(I_A)$ increases linearly. Prior work shows that retrieval performance over long prompts follows a U-shaped curve: information in the middle of the context is frequently under-attended [1].

2.2 File-Centric versus Decision-Centric Organization

Traditional retrieval systems (lexical RAG, semantic chunking) operate at file granularity [4]. Developer queries are often decision-centric. Answering *"How do we restrict API write operations on viewsets to JWT-authenticated users?"* does not require every serializer or view class; it requires rules governing serialization, view configuration, and authentication, plus specific file routes.

2.3 Observed Failure Modes

In audits of naive coding assistants, we observed recurring failures on:

- **System API boundaries:** Confusion in helper utilities while missing event-delegation patterns.
- **Settings configuration maps:** Outdated properties due to absent single sources of truth.
- **Cross-cutting rules:** Hallucinated integration paths when only one subsystem appears in context.

3 Related Work

3.1 Retrieval-Augmented Generation

Lexical retrieval (e.g., BM25) and dense embedding retrieval are widely used to prune LLM contexts [4]. Naive RAG often chunks files into arbitrary blocks, disrupting control flow. On codebases, this fragments class declarations from method implementations, forcing models to infer missing interfaces.

3.2 Knowledge Graphs and GraphRAG

Graph-based methods model code as entities and relations (calls, inheritance, imports) [5, 6]. Graphs preserve structure but optimize connectivity over sufficiency. A developer modifying a settings parameter may receive a large adjacent subgraph of consumers, flooding the prompt with irrelevant code.

3.3 Code Intelligence and AST Indexing

Static analysis assistants parse abstract syntax trees (ASTs) for precise declaration maps. AST indices lack business and operational semantics: architectural constraints expressed in prose (e.g., *"never send emails without user confirmation"*) are not captured.

3.4 Context Engineering and Compression

Prompt pruning, token compression, and context distillation remove redundant tokens post hoc [7]. These methods do not restructure repository knowledge; token and latency costs re-emerge as repositories scale.

4 Hypotheses

We formalize the framework assumptions as follows:

- **Primary hypothesis (H_1):** Dynamically routed, domain-oriented Context Cores produce responses equal or superior in correctness, completeness, and actionability to full-repository contexts, while significantly reducing input tokens and latency.
- H_{1a} **(token reduction):** $L(I_B) \ll L(I_A)$.
- H_{1b} **(latency reduction):** $t_B \ll t_A$.
- H_{1c} **(domain accuracy):** On business-rule and domain-logic questions, $\text{Acc}_B \geq \text{Acc}_A$.
- H_{1d} **(hallucination mitigation):** Context Cores reduce structural hallucinations via explicit boundaries and exclusions.
- H_{1e} **(expert preference):** Under blinded preference rating, domain experts prefer or rate as equal Condition B in at least 60% of cases versus Condition A.

Falsification criteria. We reject H_1 if (i) mean accuracy of B falls more than 15% below A on the aggregate set, or (ii) blind expert preference for B falls below 60%.

5 The AI Context OS Architecture

The framework comprises three layers:

1. **Context Cores:** Curated markdown documents per application domain, containing system-prompt guidelines, key entities (classes, interfaces, APIs), and links to critical source files.
2. **Context Router:** A lightweight classifier (keyword- or embedding-based) that scores queries against cores.
3. **Dynamic Prompt Builder:** An orchestrator that compiles base instructions, active core guidelines, user preferences, and tool definitions.

Figure 1 summarizes the compilation pipeline: the router scores the query against cores; matched cores feed the prompt builder together with base system instructions; the assembled prompt is sent to the LLM.

Figure 1. Context compilation pipeline: User Query → Context Router → {Workspace Core, Comm Core, …} → Dynamic Prompt Builder → LLM.

5.1 Taxonomy of Context Cores

We classify cores into five domains:

- **Personal/default core:** User metadata, preferences, conversational history.
- **Workspace core:** File system, document stores, local database schemas.
- **Communication core:** Messaging and mail integrations.
- **System control core:** Execution paths, scripting, input automation.
- **Browsing core:** Browsers, web sessions, tabs, URL requests.

5.2 Core Construction

Cores follow the **minimal context principle:**

1. **Domain boundary mapping:** Identify distinct responsibilities (e.g., billing versus database migration).
2. **Entity extraction:** Capture public interfaces, settings maps, and structural invariants.
3. **Prose compression:** Replace raw listings with concise rules (e.g., *"SQLite schema version 3.4"*).
4. **Exclusions:** State explicit out-of-scope boundaries to reduce hallucination.

5.3 Curation Cost

Context Cores introduce manual curation overhead. Across test projects:

Project	Cores	Authoring time
MailAgent	6	~12 h
Django REST Framework	5	~18 h
Navorina	11	~40 h
Oiloop	5	~10 h

Initial overhead ranges from approximately 10 to 40 hours depending on scale and coupling.

6 Experimental Methodology

6.1 Testbed

Repository	LOC	Language	Questions	Cores
MailAgent	320k	TypeScript	45	6
Django REST Framework	~1.2M	Python	42	5
Navorina	~270k	Python	42	11
Oiloop	~180k	Swift (macOS)	20	5

6.2 Design

We applied a within-subjects design with gpt-4o-mini as the response and judge model:

- **Condition A:** All repository source and documentation.
- **Condition B:** Routed core texts only.
- **Condition C:** Static dependency subgraph (BFS expansion up to two hops).

6.3 Metrics

- **Accuracy (0-3):** Correctness of technical details, frameworks, and APIs.
- **Completeness (0-2):** Required steps, side effects, and file locations.
- **Actionability (1-5):** Readability and executability without placeholders.
- **Input tokens** and **latency (ms).**
- **Hallucination rate (%):** Incorrect APIs, classes, or files referenced.

7 Results

Canonical runs: MailAgent run-1781319187610, Navorina run-1781143403051, Oiloop Phase 3.1 run-1781660908, Django aggregate run-drf-phase-2.1-aggregate (per-question CSV not preserved for Django).

7.1 Cross-Project Comparison

Project	Cond.	Mean Acc.	Halluc.	Mean tokens	Router F1	CCR_tokens
MailAgent (45 Q)	A	1.38	20%	88,113	-	1×
	B	**1.67**	18%	**10,615**	**1.00**	**8.3×**
	C	1.24	22%	20,955	-	4.2×
Django REST (42 Q)†	A	1.35	18%	~76,000	-	1×
	B	**1.68**	22%	**~2,000**	0.72	**38×**
	C	1.40	**11%**	~18,000	-	4.2×
Navorina (42 Q)	A	1.00	24%	27,627	-	1×
	B	**1.19**	19%	**2,021**	0.87	**13.7×**
	C	0.93	**7%**	11,858	-	2.3×
Oiloop (20 Q, Ph 3.1)	A	0.75	30%	76,663	-	1×
	B	**2.70**	**0%**	**6,334**	1.00	**12.1×**
	C	2.35	10%	8,963	-	8.6×

† Django: aggregate export only; bootstrap CI not computed (no paired.csv).

7.2 Oiloop Phase 3.1

Phase 3.1 used **workspace-core v1.1.0**, corrected gold labels, and gold routing (F1 = 1.0):

- B versus A accuracy: 2.70 versus 0.75 (Δ +1.95, N = 20).
- Bootstrap 95% CI on paired Δ (B − A): [+1.60, +2.30]; B exceeded A on 19/20 questions.
- Production keyword router (Run 3): F1 = 1.0, B = 2.75, hallucination 0% (run-prod-router-1781701118).
- Cross-cutting ablation (Run 2, 8 Q): B 2.875 > D (hybrid) 2.50 > C 2.375 - H_{1f} rejected.

Prior Oiloop runs (pre-v1.1 cores) showed B 1.20 versus A 1.00; core metadata richness (H_{1g}) explains the Phase 3.1 improvement.

7.3 Compression and Latency

CCR_tokens (mean tokens A / mean tokens B): 8.3× MailAgent, 38× Django, 13.7× Navorina, 12.1× Oiloop Phase 3.1. Condition B latency was consistently lower than A on measured runs.

7.4 Preference Pilots

Author-rated blind pilot (10 questions, Phase 3.1 answers, shuffled A/B): B preferred 7, equal 3, A 0 (n=10; not independent raters; source: research/human-blind-pilot-oiloop.csv).

Masked decode preference (prior Oiloop canonical): B preferred or equal on 75% of 20 questions.

8 Discussion

8.1 Core Richness and Multi-Core Routing

Early Oiloop runs showed thin B accuracy (1.05-1.20) when cores lacked enforcement chains and cross-cutting routes returned a single core. Phase 3.1 addressed this via expanded metadata (entities, invariants, rule-enforcement chains) and multi-core keyword routing (up to two cores on tied scores). B accuracy rose from 1.20 to 2.70. Production default on Oiloop is Condition B (.fast routing), not graph C.

8.2 When Graph Retrieval Wins

On Django REST and Navorina, C achieved lower hallucination than B (11% versus 22%; 7% versus 19%) despite mixed accuracy. When trust dominates, C is the recommended default for those profiles.

On Oiloop Phase 3.1, B exceeded C on accuracy and matched or beat C on hallucination. Graph C remains an opt-in path (.deep).

8.3 Hybrid Core plus Graph

Condition D (routed core plus 15k-token graph supplement) did not match C accuracy at lower cost than B on eight cross-cutting questions. Multi-core B is the simpler strategy when cores are metadata-rich.

8.4 Empirical Decision Matrix

Profile	Default	Evidence
Narrow domain, F1 $\geq$ 0.95 (MailAgent, Oiloop prod)	B	MailAgent F1 = 1.0; Oiloop Run 3 F1 = 1.0
Integrated OSS, hallucination-sensitive (DRF, Navorina)	C	C hallucination < B
Integrated private app, rich cores (Oiloop Ph 3.1)	B	B 2.70; multi-core wins cross-cutting
Full-repository dump	None	Dominated on cost and accuracy

9 Limitations

1. **LLM-as-judge:** All accuracy and hallucination scores use gpt-4o-mini; no inter-rater agreement with humans on the full 149-question bank.
2. **Expert preference:** Masked decode and the author blind pilot are not substitutes for independent blind human studies.
3. **Django REST:** Only aggregate metrics exported; per-question paired.csv was not preserved.
4. **Curation cost:** 10-40 hours per codebase; semantic drift requires maintenance.
5. **Router dependency:** B quality scales with routing F1; mitigated by multi-core and semantic routing on DRF/Navorina.
6. **Single model:** All runs use gpt-4o-mini; generalization untested.
7. **Oiloop A baseline variance:** Condition A scores drifted between runs; Phase 3.1 is the reference.

10 Future Work

1. Semi-automated core generation from AST and documentation.
2. Context drift monitors (PR hooks when source links change).
3. Full Django REST re-run with per-question export.
4. Independent human blind study (10-question pilot protocol published).
5. Multi-model replication on the Oiloop product path.

11 Conclusion

Full-repository loading is token-inefficient for decision-scoped questions. Domain-oriented Context Cores with multi-core routing deliver 8-38× compression (CCR_tokens) on open-source projects and ~12× on Oiloop Phase 3.1. When cores are metadata-rich, accuracy substantially exceeds monolithic dumps (Oiloop: B 2.70 versus A 0.75; bootstrap CI entirely above zero). Production defaults are stratum-dependent: B on narrow, high-F1 paths; C on hallucination-sensitive integrated OSS. Hybrid core-plus-graph did not outperform rich multi-core B on Oiloop cross-cutting questions. We release protocols, three full raw run exports, and an aggregate Django export with stated limitations.

12 References

[1] N. Liu et al., "Lost in the Middle: How Language Models Use Long Contexts," *Transactions of the Association for Computational Linguistics*, vol. 12, pp. 157-173, 2024.

[2] O. Press et al., "Train Short, Test Long: Attention with Linear Biases Enables Input Length Extrapolation," *ICLR*, 2022.

[3] E. Evans, *Domain-Driven Design: Tackling Complexity in the Heart of Software*. Addison-Wesley, 2003.

[4] P. Lewis et al., "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks," *Advances in Neural Information Processing Systems*, 2020.

[5] D. Edge et al., "From Local to Global: A GraphRAG Approach to Query-Focused Summarization," *arXiv:2404.16130*, 2024.

[6] D. Guo et al., "GraphCodeBERT: Pre-training Code Representations with Data Flow," *International Conference on Learning Representations*, 2021.

[7] H. Jiang et al., "LLMLingua: Compressing Prompts for Accelerated Inference of Large Language Models," *EMNLP*, 2023.

13 Appendix A: Example Evaluation Questions

- **OL01:** How does Oiloop store user preferences and chat history?
- **OL05:** How does Oiloop handle sandboxed folder access on macOS?
- **OL15:** How does EventKit Reminders authorization avoid freezing Oiloop in background mode?
- **OL18:** How are Safari tab titles and URLs fetched?

14 Appendix B: Context Core Template

```
# [Core Name] Core

## Purpose
Decision domain description.

## Key Entities
- `EntityName`: Class/struct and responsibility.

## Invariants & Rules
```

1. Mandatory checks and constraints.

Exclusions
- Explicit out-of-scope boundaries.

15 Appendix C: Router Sketch

```
struct ContextRouter {
    static func route(userInput: String) -> Set<ContextCore> {
        let lower = userInput.lowercased()
        // Score cores by keyword presence; return matching set
    }
}
```

16 Appendix D: Blinded Rater Instructions

1. Answers are randomized as "Option 1" and "Option 2."
2. Rate each option on accuracy (0-3), completeness (0-2), and actionability (1-5).
3. Select the preferred option without knowing the retrieval source.

17 Data Availability

Research repository: https://github.com/navorina-labs/AI-Context-OS

Evaluation dataset: research/questions.md

Raw metrics: context-os/evaluations/ and experiments/*/runs/