RETAILIQ

Online Retail Analytics & Intelligence System

Project Title: RetailIQ – Online Retail Analytics & Intelligence System
Project Category: Data Science & Machine Learning Capstone Mini-Project
Domain: E-Commerce Analytics, Unsupervised Customer Segmentation, Time-Series Forecasting
Primary Frameworks: Python 3, Streamlit, Scikit-Learn, Statsmodels, Plotly, ReportLab
Date: November 2026

Chapter 1: Introduction

Modern enterprise e-commerce platforms generate vast volumes of transactional data daily. Extracting actionable intelligence requires moving beyond basic retrospective reporting to automated machine learning disciplines. **RetailIQ** is an end-to-end analytics and intelligence system designed to process multi-million pound transactional datasets, group customers by behavioral lifetime value via RFM-driven unsupervised clustering, and project future revenue demands using statistical time-series forecasting models.

Chapter 2: Problem Statement & Objectives

Retail organizations encounter two pivotal operational challenges:
1. **Customer Heterogeneity:** Treating all buyers uniformly leads to wasted promotional expenditure and increased churn.
2. **Demand Uncertainty:** Inaccurate sales projections cause inventory stockouts or capital lockup in unsold stock.

Key Objectives:
• Engineer an automated data validation and cleaning pipeline handling cancellations, missing identities, and return transactions.
• Implement RFM (Recency, Frequency, Monetary) modeling combined with K-Means clustering to identify high-value customer cohorts.
• Formulate statistical time-series models (ARIMA and Holt-Winters Exponential Smoothing) to forecast 7, 30, and 90-day demand.

Chapter 3: Literature & Technical Background

RFM Segmentation: First proposed in database marketing, RFM measures how recently a customer purchased (R), how frequently they purchase (F), and their total expenditure (M). Because retail spending typically follows a Pareto power-law distribution, logarithmic feature transformations and z-score standardizations are mandatory prior to Euclidean distance calculations in K-Means.
Time-Series Modeling: Autoregressive Integrated Moving Average (ARIMA) models capture non-seasonal and seasonal serial autocorrelation, whereas Holt-Winters Exponential Smoothing models handle additive level, trend, and seasonal periodicities.

Chapter 4: Dataset Description

The application utilizes the UCI Online Retail dataset, comprising 541,909 raw transactional records registered between December 1, 2010 and December 9, 2011 by a UK-based non-store online retailer specializing in giftware.

Attribute	Type	Description & Hygiene Observations
InvoiceNo	String	6-digit transaction identifier. Prefixed with 'C' for 9,288 cancellations.
StockCode	String	Product code identifying 4,070 unique inventory SKUs.
Description	String	Product name; contains 1,454 null entries imputed via StockCode lookup.
Quantity	Integer	Items per transaction; contains 10,624 negative values indicating returns or damages.
InvoiceDate	Datetime	Timestamp of purchase spanning 374 days (2010-12-01 to 2011-12-09).
UnitPrice	Float	Unit price in GBP (£); contains 2,517 non-positive values.
CustomerID	Float/Str	Customer identifier; 135,080 transactions (24.9%) lack identified customer IDs.
Country	String	Geographic destination across 38 countries (dominated by the UK).

Chapter 5: System Design & Methodology

RetailIQ is structured into a strictly modular architecture separating data extraction, transformation, analytical modeling, and user presentation. The system pipeline comprises: (1) Data ingestion with dual Excel/CSV fallback; (2) Data cleaning and transaction view partitioning; (3) RFM feature extraction and K-Means segmentation; (4) Chronological time-series forecasting with ARIMA and Exponential Smoothing; (5) Streamlit interactive UI with cached session state.

Chapter 6: Data Preprocessing & Exploratory Analysis

Data Preprocessing Decisions:
• **Duplicates:** 5,268 exact duplicate rows (0.97%) were pruned to prevent artificial order inflation.
• **Returns vs Sales:** Rather than discarding negative quantities indiscriminately, transactions were separated into: *Valid Sales* (Qty > 0, Price > 0, non-cancelled), *Returns & Cancellations* (InvoiceNo starting with 'C' or Qty < 0), and *Adjustment Entries*.
• **Customer Partitioning:** For aggregate store revenue, all valid transactions (including guest checkouts) are tracked. For customer clustering, only identified customer accounts (4,372 distinct profiles) are evaluated.

Chapter 7: Customer Segmentation (RFM + K-Means)

Customer behavior was summarized along Recency, Frequency, and Monetary dimensions. Due to severe positive skewness, logarithmic transformation $y = ln(1 + x)$ was applied prior to z-score standardization. Cluster evaluation via the Elbow Method and Silhouette Score confirmed an optimal partition of **k = 4 clusters** (Silhouette Score ~ 0.30 - 0.35).

Segment Persona	Customer Count	Customer Share	Total Revenue (£)	Avg Recency	Avg Frequency	Avg Spend (£)
At-Risk Customers	1,617	37.3%	£562,469.24	183 days	1.3 orders	£347.85
Loyal Customers	1,173	27.0%	£2,117,050.02	70 days	4.1 orders	£1,804.82
Potential Loyalists	839	19.3%	£455,624.56	18 days	2.1 orders	£543.06
Champions	709	16.3%	£5,752,065.07	12 days	13.8 orders	£8,112.93

Chapter 8: Time-Series Sales Forecasting

Daily sales revenue was aggregated into a continuous chronological time series. A strict chronological train-test split was enforced (the final 30 calendar days serving as out-of-sample evaluation) to prevent lookahead leakage. Both ARIMA (with weekly seasonality order) and Holt-Winters Exponential Smoothing were benchmarked.

Model Name	MAE (£)	RMSE (£)	MAPE (%)	sMAPE (%)	R^2 Score
ARIMA / SARIMAX	£15,561.66	£26,789.08	34.04%	51.70%	0.3368
Holt-Winters Exp Smoothing	£13,648.68	£28,228.21	24.14%	47.93%	0.2636

Chapter 9: Results & Discussion

Customer Persona Insights:

• *Champions:* Represent top revenue drivers with high frequency and recent activity; targeted with loyalty rewards and VIP early access.

• *Loyal Customers:* Steady recurring spenders who respond strongly to cross-selling and product recommendations.

• *At-Risk Customers:* High historical spenders inactive for over 90–120 days; prime candidates for win-back promotions.

• *Hibernating:* Low spend and prolonged inactivity requiring low-cost re-engagement.

Forecasting Caveats:

Because the historical dataset spans only 12 months (December 2010 – December 2011), true annual seasonality cannot be separated from unique holiday surge effects. Projections beyond 30 days should be treated as indicative trend lines rather than deterministic targets.

Chapter 10: Conclusion, Future Scope & References

Conclusion: RetailIQ fulfills all academic and production engineering goals for an integrated e-commerce intelligence platform. By grounding business logic in validated statistical algorithms, the system demonstrates the practical value of data science in retail operations.
Future Scope: Integration of deep learning forecasting (e.g., Temporal Fusion Transformers, N-BEATS), real-time streaming ingestion via Kafka, and true predictive customer lifetime value (CLV) via BG/NBD models.

Academic References:

1. Chen, D., Sain, S.L., & Guo, K. (2012). Data mining for the online retail industry. *Journal of Database Marketing & Customer Strategy Management*, 19(3), 197-208.
2. Box, G.E.P., Jenkins, G.M., Reinsel, G.C., & Ljung, G.M. (2015). *Time Series Analysis: Forecasting and Control*. 5th Edition, John Wiley & Sons.
3. MacQueen, J. (1967). Some methods for classification and analysis of multivariate observations. *Proc. 5th Berkeley Symp. Math. Statist. Prob.*, 1, 281-297.