

C++ for Scientific Computation

Rajeev Singh

Contents

1	Day 1: Basic input/output	3
1.1	aa_hello_world.c	3
1.2	ab_hello_world.cpp	4
1.3	ac_hello_world.cpp	5
1.4	ad_powers_of_integer.cpp	6
1.5	ae_powers_of_real.cpp	7
2	Day 2: Pointers/References, Arithmetic/Logical	8
2.1	af_pointer.cpp	8
2.2	ag_reference.cpp	9
2.3	ah_arithmetic_operators.cpp	10
2.4	ai_relational_logical.cpp	11
3	Day 3: Scope, Conditional, Loops	12
3.1	aj_blocks_scope.cpp	12
3.2	ak_scope.cpp	13
3.3	al_if_else.cpp	14
3.4	am_for_loop.cpp	15
3.5	an_while_loop.cpp	16
3.6	ao_do_while_loop.cpp	17
3.7	ap_break.cpp	18
3.8	aq_break_nested_loop.cpp	19
3.9	ar_break_all_loops.cpp	20
4	Day 4: Functions, Call by value/reference	21
4.1	as_function_square.cpp	21
4.2	at_function_factorial.cpp	22
4.3	au_function_call_by_value.cpp	23
4.4	av_function_call_by_reference.cpp	24
4.5	aw_function_call_by_reference_using_pointers.cpp	25
4.6	ax_function_multiple_return_values.cpp	26

5	Day 5: Functions- default args, function pointers; Arrays	27
5.1	ay_function_default_arguments.cpp	27
5.2	az_function_inline.cpp	28
5.3	ba_function_pointers.cpp	29
5.4	bb_function_pointers_as_arguments.cpp	30
5.5	bc_static_variables.cpp	31
5.6	bd_array.cpp	32
5.7	be_function_with_array_argument.cpp	33
5.8	bf_multidimensional_arrays.cpp	34
5.9	bg_array_and_pointer.cpp	35
6	Day 6: Dynamic memory, Multidimensional Array, BLAS	36
6.1	bh_dynamic_memory.cpp	36
6.2	bi_dynamic_array_size_input.cpp	37
6.3	bj_multidimensional_array_with_pointer.cpp	38
6.4	bk_multidimensional_dynamic_array.cpp	39
6.5	bl_multidimensional_dynamic_array_size_input.cpp	40
6.6	bm_multidimensional_array_with_mapping.cpp	41
7	Day 7: String, Advanced Datatypes, BLAS, Sparse Matrices	42
7.1	bn_strings.cpp	42
7.2	bo_typedef.cpp	43
7.3	bp_struct.cpp	44
7.4	bq_struct_pointer.cpp	46
7.5	br_struct_array.cpp	48

1 Day 1: Basic input/output

1.1 aa_hello_world.c

```
// C program to print "Hello World".  
//  
// Rajeev Singh  
// 2013-03-27  
  
#include <stdio.h>  
  
int main() {  
    printf("Hello World from C\n");  
    return 0;  
}
```

1.2 ab_hello_world.cpp

```
// C++ program to print "Hello World".
//
// Rajeev Singh
// 2013-03-27

#include <iostream>

int main() {
    std::cout << "Hello World from C++"; // << std::endl;
    return 0;
}
```

1.3 ac_hello_world.cpp

```
// C++ program to print "Hello World".  
//  
// Rajeev Singh  
// 2013-03-27  
  
#include <iostream>  
  
using namespace std;  
  
int main() {  
    cout << "Hello World from C++" << endl;  
    return 0;  
}
```

1.4 ad_powers_of_integer.cpp

```
// Program to calculate powers of given integer.
//
// Rajeev Singh
// 2013-03-27

#include <iostream>
#include <cmath>
using namespace std;

int main() {
    //int given_number;
    long int given_number;
    cout << "Enter an integer: ";
    cin >> given_number;

    cout << "Given number = " << given_number << endl
         << "Square      = " << pow(given_number,2) << endl
         << "Cube        = " << pow(given_number,3) << endl
         << "Forth power  = " << pow(given_number,4) << endl;

    return 0;
}
```

1.5 ae_powers_of_real.cpp

```
// Program to calculate powers of given integer.
//
// Rajeev Singh
// 2013-03-27

#include <iostream>
#include <cmath>
using namespace std;

int main() {
    double given_number;
    //long double given_number;
    cout << "Enter a real number : ";
    cin  >> given_number;

    cout << "Given number = " << given_number << endl
         << "Square      = " << pow(given_number,2) << endl
         << "Square root  = " << pow(given_number,1./2) << endl
         << "Cube        = " << pow(given_number,3) << endl
         << "Forth power  = " << pow(given_number,4) << endl;

    return 0;
}
```

2 Day 2: Pointers/References, Arithmetic/Logical

2.1 af_pointer.cpp

```
// Program to illustrate pointers.
//
// Rajeev Singh
// 2013-03-28

#include <iostream>
using namespace std;

int main() {
    int *np = NULL;
    int n = 10;

    cout << "Initial" << endl
         << "n    = " << n    << endl
         << "np   = " << np   << endl
         << "*np  = " << "since np is NULL, printing *np gives segmentation fault"
    << endl << endl;

    np = &n;
    cout << "After: np = &n" << endl
         << "n    = " << n    << endl
         << "np   = " << np   << endl
         << "*np  = " << *np  << endl << endl;

    *np = 22;
    cout << "After: *np = 22" << endl
         << "n    = " << n    << endl
         << "np   = " << np   << endl
         << "*np  = " << *np  << endl << endl;

    return 0;
}
```


2.2 ag_reference.cpp

```
// Program to illustrate the use of references (special pointers).
//
// Rajeev Singh
// 2013-03-28

#include <iostream>
using namespace std;

int main() {
    int    n = 5;
    int & r = n;
    int    m;

    cout << "Initial" << endl
         << "n = " << n << endl
         << "r = " << r << endl
         << "m = " << m << endl << endl;

    m = r + 3;      // m == n + 3
    cout << "After: m = r + 3" << endl
         << "n = " << n << endl
         << "r = " << r << endl
         << "m = " << m << endl << endl;

    r = m;          // r still points to n and n == m
    cout << "After: r = m" << endl
         << "n = " << n << endl
         << "r = " << r << endl
         << "m = " << m << endl << endl;

    m = 0;          // r and n are unchanged
    cout << "After: m = 0" << endl
         << "n = " << n << endl
         << "r = " << r << endl
         << "m = " << m << endl << endl;

    int & s = m;
    r = s;          // r still points to n and n == m (== 0)
    cout << "After: r = s where s is new reference to m" << endl
         << "n = " << n << endl
         << "r = " << r << endl
         << "m = " << m << endl << endl;

    return 0;
}
```

2.3 ah_arithmetic_operators.cpp

```
// Program to illustrate basic arithmetic operators.
//
// Rajeev Singh
// 2013-03-28

#include <iostream>
using namespace std;

int main() {
    int m = 100,
        n = 200;

    cout << "Initial" << endl
         << "m = " << m << endl
         << "n = " << n << endl
         << "m + n = " << m + n << endl
         << "m - n = " << m - n << endl
         << "m * n = " << m * n << endl
         << "m / n = " << m / n << endl
         << "m % n = " << m % n << endl << endl;

    //m = m + 200;
    m += 200;      // both this commands are same
    cout << "After: m += 200" << endl
         << "m = " << m << endl
         << "n = " << n << endl
         << "m + n = " << m + n << endl
         << "m - n = " << m - n << endl
         << "m * n = " << m * n << endl
         << "m / n = " << m / n << endl
         << "m % n = " << m % n << endl << endl;

    m++;
    cout << "After: m++" << endl
         << "m = " << m << endl
         << "n = " << n << endl
         << "m + n = " << m + n << endl
         << "m - n = " << m - n << endl
         << "m * n = " << m * n << endl
         << "m / n = " << m / n << endl
         << "m % n = " << m % n << endl << endl;

    return 0;
}
```

2.4 ai_relational_logical.cpp

```
// program to illustrate logical and relational operators.
//
// Rajeev Singh
// 2013-03-28

#include <iostream>
using namespace std;

int main() {
    int    x = 2;
    int    y = 4;
    int    z = 4;
    bool    b;

    cout << "x = " << x << endl
         << "y = " << y << endl
         << "z = " << z << endl << endl;

    // z == 4 is not tested
    b = ( x == 2 && y == 3 && z == 4 );
    cout << "b = ( x == 2 && y == 3 && z == 4 )" << endl
         << "b = " << b << endl << endl;

    // only x == 2 is tested
    b = ( x == 2 || y == 3 || z == 4 );
    cout << "b = ( x == 2 || y == 3 || z == 4 )" << endl
         << "b = " << b << endl << endl;

    // correct, since x != 0 in "y/x"
    b = ( x != 0 && y/x > 1 );
    cout << "b = ( x != 0 && y/x > 1 )" << endl
         << "b = " << b << endl << endl;

    return 0;
}
```

3 Day 3: Scope, Conditional, Loops

3.1 aj_blocks_scope.cpp

```
// program to illustrate blocks.
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    { // block 1
        int n1 = 1;
        double f1 = 0.0;
        cout << "Block 1 " << endl;
        cout << "n1 = " << n1 << endl;
        cout << "f1 = " << f1 << endl;
    }

    { // block 2
        int n1 = 2;
        // n1 has value 2 in this block
        cout << "Block 2 " << endl;
        cout << "n1 = " << n1 << endl;

        //int n1 = 5; // ERROR
    }

    return 0;
}
```

3.2 ak_scope.cpp

```
// program to illustrate scope of variables
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    { // block 1
        int m, n1 = 1;
        { // block 1.1
            int n2 = 2;
            { // block 1.1.1
                m = n1 + n2; // evaluates to m = 3
                cout << "Block 1.1.1: m = " << m << endl;
            }
        }

        { // block 1.2
            int n2 = 3;
            m = n1 + n2; // evaluates to m = 4
            cout << "Block 1.2 : m = " << m << endl;
        }
    }

    return 0;
}
```

3.3 al_if_else.cpp

```
// program to illustrate conditional structure
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    int n = 1;

    if ( n > 0 )
    {
        n = n / n;
    }

    if ( n < 0 ) {
        n += 5; // NOTE: trivial block!
        cout << "hello " << n << endl;
    }
    else if ( n %2 == 0 ) {
        n += 1;
        cout << "hello " << n << endl;
    }
    else {
        n -= 6;
        cout << "hello " << n << endl;
    }

    cout << "n = " << n << endl;

    return 0;
}
```

3.4 am_for_loop.cpp

```
// program to illustrate for loop
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    int n = 1;

    for (int i=1; i<10; i++) {
        if (i>5) {
            n *= i;
            cout << "n = " << n << endl;
        }
    }

    return 0;
}
```

3.5 an_while_loop.cpp

```
// program to illustrate while loop
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    int n = 1;
    int i = 1;

    while (i < 10) {
        n *= i;
        i++;
        cout << "n = " << n << endl;
    }

    return 0;
}
```


3.6 ao_do_while_loop.cpp

```
// program to illustrate do-while loop
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    int n = 1;
    int i = 100;

    do {
        n *= i;
        i++;
        cout << "n = " << n << endl;
    } while (i < 10);

    return 0;
}
```

3.7 ap_break.cpp

```
// program to illustrate use of break
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    int n = 1;

    for ( int i = 1; i < 20; i++ ) {
        // avoid overflow
        if ( n > 21474836 )
            break;
        n *= i;
        cout << "n = " << n << endl;
    }

    return 0;
}
```

3.8 aq_break_nested_loop.cpp

```
// program to illustrate behavior of break in nested loops
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    for ( int i = 1; i < 20; i++ ) {
        int n = 1;
        for ( int j = 1; j < i; j++ ) {
            if ( n > 21474836 )
                break;
            n *= j;
        }

        cout << "n = " << n << endl;
    }

    return 0;
}
```

3.9 ar_break_all_loops.cpp

```
// program to illustrate breaking all nested loops
//
// Rajeev Singh
// 2013-03-29

#include <iostream>
using namespace std;

int main() {
    int flag = 0;
    for ( int i = 1; i < 20; i++ ) {
        int n = 1;
        for ( int j = 1; j < i; j++ ) {
            if ( n > 21474836 ) {
                flag = 1;
                break;
            }
            n *= j;
        }
        if (flag == 1)
            break;

        cout << "n = " << n << endl;
    }

    return 0;
}
```

4 Day 4: Functions, Call by value/reference

4.1 as_function_square.cpp

```
// program to illustrate defining function
//
// Rajeev Singh
// 2013-03-31

#include <iostream>
using namespace std;

double
square (const double x) {
    return x*x;
}

int main() {
    double a = 2.5;

    cout << "a    = " << a << endl
          << "a^2 = " << square(a) << endl;

    return 0;
}
```

4.2 at_function_factorial.cpp

```
// program to illustrate defining the factorial function
//
// Rajeev Singh
// 2013-03-31

#include <iostream>
using namespace std;

int
factorial (const int n) {
    int f = 1;
    for (int i = 1; i <= n; i++ )
        f *= i;

    return f;
}

int main() {
    int m = 10;

    cout << "m   = " << m << endl
         << "m! = " << factorial(m) << endl;

    return 0;
}
```

4.3 au_function_call_by_value.cpp

```
// program to illustrate call by value feature
//
// Rajeev Singh
// 2013-03-31

#include <iostream>
using namespace std;

int
f (int n) {
    n = 10;
    return n;
}

int main() {
    int m = 5;

    cout << "m before calling = " << m << endl;
    cout << "function output   = " << f(m) << endl;
    cout << "m after calling   = " << m << endl;

    return 0;
}
```

4.4 av_function_call_by_reference.cpp

```
// program to illustrate call by reference feature
//
// Rajeev Singh
// 2013-03-31

#include <iostream>
using namespace std;

int
f (int & n) {
    n = 10;
    return n;
}

int main() {
    int m = 5;

    cout << "m before calling = " << m << endl;
    cout << "function output   = " << f(m) << endl;
    cout << "m after calling   = " << m << endl;

    return 0;
}
```


4.5 aw_function_call_by_reference_using_pointers.cpp

```
// program to illustrate call by reference feature using general  
// pointers  
//  
// Rajeev Singh  
// 2013-03-31  
  
#include <iostream>  
using namespace std;  
  
int  
f (int * n) {  
    *n = 10;  
    return *n;  
}  
  
int main() {  
    int m = 5;  
  
    cout << "m before calling = " << m << endl;  
    cout << "funtion output    = " << f(&m) << endl;  
    cout << "m after calling   = " << m << endl;  
  
    return 0;  
}
```

4.6 ax_function_multiple_return_values.cpp

```
// program to illustrate funtions with multiple return values using
// call by reference
//
// Rajeev Singh
// 2013-03-31

#include <iostream>
using namespace std;

void
min_max ( const int n1, const int n2,
          int & min, int & max );

int main() {
    int m1, m2, min, max;

    cout << "Enter two integers :";
    cin >> m1 >> m2;

    min_max(m1, m2, min, max);
    cout << "m1          = " << m1 << endl
         << "m2          = " << m2 << endl << endl
         << "min(m1,m2) = " << min << endl
         << "max(m1,m2) = " << max << endl;

    return 0;
}

void
min_max ( const int n1, const int n2,
          int & min, int & max ) {
    if ( n1 < n2 ) {
        min = n1;
        max = n2;
    }
    else {
        min = n2;
        max = n1;
    }
}
```

5 Day 5: Functions- default args, function pointers; Arrays

5.1 ay_function_default_arguments.cpp

```
// program to illustrate function with default arguments
//
// Rajeev Singh
// 2013-04-01

#include <iostream>
using namespace std;

double
square (const double x = 10.0) {
    return x*x;
}

int main() {
    double a = 2.5;

    cout << "a          = " << a << endl;
    cout << "a^2        = " << square(a) << endl;
    cout << "square() = " << square() << endl;

    return 0;
}
```

5.2 az_function_inline.cpp

```
/* program to illustrate inline functions
 *
 * WARNING: do not inline functions with large bodies. it can cause
 *          the final executable to be very large in size and decrease
 *          performance.
 *
 *
 * Rajeev Singh
 * 2013-04-01
 *
 */

#include <iostream>
using namespace std;

inline double
square (const double x = 10.0) {
    return x*x;
}

int main() {
    double a = 2.5;

    cout << "a          = " << a << endl;
    cout << "a^2        = " << square(a) << endl;
    cout << "square() = " << square() << endl;

    return 0;
}
```

5.3 ba_function_pointers.cpp

```
/* program to illustrate function pointers
 *
 * Rajeev Singh
 * 2013-04-01
 *
 */

#include <iostream>
using namespace std;

double
square (const double x) {
    return x*x;
}

int main() {
    double a = 2.5;
    double (* pf) (const double x);
    pf = square;

    cout << "a          = " << a << endl;
    cout << "square(a) = " << square(a) << endl;
    cout << "pf(a)      = " << pf(a) << endl;

    return 0;
}
```

5.4 bb_function_pointers_as_arguments.cpp

```
/* program to illustrate function pointers as arguments
 *
 * Rajeev Singh
 * 2013-04-01
 *
 */

#include <iostream>
using namespace std;

double
square (const double x) {
    return x*x;
}

double
cube (const double x) {
    return x*x*x;
}

double
f ( double ( * func ) ( const double x ),
    const double x ) {
    return func( x );
}

int main() {
    double a = 2.5;

    cout << "a          = " << a << endl;
    cout << "f(square, a) = " << f(square, a) << endl;
    cout << "f(cube,   a) = " << f(cube,   a) << endl;

    return 0;
}
```

5.5 bc_static_variables.cpp

```
/* program to illustrate static variables
 *
 * Rajeev Singh
 * 2013-04-01
 *
 */

#include <iostream>
using namespace std;

double
f ( const double x, long & cnt ) {
    static long counter = 0; // allocated and initialised
                             // once per program

    cnt = ++counter;
    return 2.0*x*x - x;
}

int main() {
    long cnt = 0;

    for ( double x = -10; x <= 10.0; x += 0.1 )
        f( x, cnt );

    cout << "num times f called = " << cnt << endl;

    return 0;
}
```

5.6 bd_array.cpp

```
/* program to illustrate array
*
* Rajeev Singh
* 2013-04-01
*
*/

#include <iostream>
using namespace std;

int main() {
    double f[5];

    for ( int i = 0; i < 5; i++ )
        f[i] = 2*i;

    cout << "f = " << f << endl;
    for ( int i = 0; i < 5; i++ )
        cout << "f[" << i << "] = " << f[i] << endl;

    cout << "f[5] = " << f[5] << endl; // bug but program still compiles
    // if you lucky such bugs will be detected by segmentation fault

    return 0;
}
```


5.7 be_function_with_array_argument.cpp

```
/* program to illustrate arrays as function arguments
 *
 * Rajeev Singh
 * 2013-04-01
 *
 */

#include <iostream>
using namespace std;

void
copy ( const double x[3], double y[3] ) {
    for ( int i = 0; i < 3; i++ )
        y[i] = x[i];
}

void
add ( const double x[3], double y[3] ) {
    for ( int i = 0; i < 3; i++ )
        y[i] += x[i];
}

int main() {
    double a[3],
           b[] = {0, 0, 0}; // b is automaticall of size 3

    for ( int i = 0; i < 3; i++ )
        a[i] = 2*i;

    cout << "Intial a and b:" << endl;
    for ( int i = 0; i < 3; i++ )
        cout << "a[" << i << "] = " << a[i]
              << " b[" << i << "] = " << b[i]<< endl;

    copy( a, b );
    cout << endl << "After calling copy funtion:" << endl;
    for ( int i = 0; i < 3; i++ )
        cout << "a[" << i << "] = " << a[i]
              << " b[" << i << "] = " << b[i]<< endl;

    add( a, b );
    cout << endl << "After calling sum funtion:" << endl;
    for ( int i = 0; i < 3; i++ )
        cout << "a[" << i << "] = " << a[i]
              << " b[" << i << "] = " << b[i]<< endl;

    return 0;
}
```

5.8 bf_multidimensional_arrays.cpp

```
/* program to illustrate multidimensional arrays
 *
 * Rajeev Singh
 * 2013-04-01
 *
 */

#include <iostream>
using namespace std;

void
mulvec ( const double M[3][3],
         const double x[3],
         double y[3] ) {
    for ( int i = 0; i < 3; i++ ) {
        y[i] = 0.0;

        for ( int j = 0; j < 3; j++ )
            y[i] += M[i][j] * x[j];
    }
}

int main() {
    double M[3][3],
           x[3], y[3];

    for ( int i = 0; i < 3; i++ ) {
        x[i] = 2*i;
        for ( int j = 0; j < 3; j++ )
            M[i][j] = 3*i+j;
    }

    mulvec(M, x, y);

    cout << "M:" << endl;
    for ( int i = 0; i < 3; i++ ) {
        for ( int j = 0; j < 3; j++ )
            cout << " " << M[i][j];
        cout << endl;
    }

    cout << "x:" << endl;
    for ( int j = 0; j < 3; j++ )
        cout << " " << x[j] << endl;

    cout << "y = M*x:" << endl;
    for ( int j = 0; j < 3; j++ )
        cout << " " << y[j] << endl;

    return 0;
}
```

5.9 bg_array_and_pointer.cpp

```
/* program to illustrate pointers as arrays
 *
 * in C/C++ there is NO distinction between a pointer and an array.
 *
 * Rajeev Singh
 * 2013-04-01
 *
 */

#include <iostream>
using namespace std;

int main() {
    int    n[5] = { 2, 3, 5, 7, 11 };
    int * p    = n;
    int * q    = &n[1];

    cout << "n:" << endl;
    for ( int j = 0; j < 5; j++ )
        cout << " " << n[j] << endl;

    cout << "p:" << endl;
    for ( int j = 0; j < 5; j++ )
        cout << " " << p[j] << endl;

    cout << "q:" << endl;
    for ( int j = 0; j < 5; j++ )
        cout << " " << q[j] << endl;

    return 0;
}
```

6 Day 6: Dynamic memory, Multidimensional Array, BLAS

6.1 bh_dynamic_memory.cpp

```
/* program to illustrate dynamic memory
 *
 * this example shows the C++ way of doing the job. this will not work
 * for C.
 *
 * Rajeev Singh
 * 2013-04-02
 *
 */

#include <iostream>
using namespace std;

int main() {
    int    n = 10;
    double * v = new double[n];

    for ( int i = 0; i < n; i++ )
        v[i] = double( i*i );

    cout << "n = " << n << endl;
    cout << "v:" << endl;
    for ( int j = 0; j < n; j++ )
        cout << " " << v[j] << endl;

    delete[] v;
    return 0;
}
```

6.2 bi_dynamic_array_size_input.cpp

```
/* program to illustrate dynamic memory
 *
 * Rajeev Singh
 * 2013-04-02
 *
 */

#include <iostream>
using namespace std;

int main() {
    int n;

    cout << "Enter the size of the array: ";
    cin >> n;

    double * v = new double[n];

    for ( int i = 0; i < n; i++ )
        v[i] = double( i*i );

    cout << "n = " << n << endl;
    cout << "v:" << endl;
    for ( int j = 0; j < n; j++ )
        cout << " " << v[j] << endl;

    delete[] v;
    return 0;
}
```

6.3 bj_multidimensional_array_with_pointer.cpp

```
/* program to illustrate dynamic memory
 *
 * Rajeev Singh
 * 2013-04-02
 *
 */

#include <iostream>
using namespace std;

int main() {
    int n1[4], n2[4], n3[4], n4[4];
    int * p1 = n1;           // p1 -> pointer
    int * p2 = n2;
    int * p3 = n3;
    int * p4 = n4;

    int *p[4] = {p1, p2, p3, p4}; // p -> pointer of pointers

    for (int i = 0; i < 4; i++ )
        for (int j = 0; j < 4; j++ )
            p[i][j] = 4*i+j;

    cout << "p:" << endl;
    for (int i = 0; i < 4; i++ ) {
        for (int j = 0; j < 4; j++ )
            cout << " " << p[i][j];
        cout << endl;
    }

    return 0;
}
```

6.4 bk_multidimensional_dynamic_array.cpp

```
/* program to illustrate dynamic memory
 *
 * Rajeev Singh
 * 2013-04-02
 *
 */

#include <iostream>
using namespace std;

int main() {
    int * p1 = new int[4];
    int * p2 = new int[4];
    int * p3 = new int[4];
    int * p4 = new int[4];

    int **p = new int*[4];

    p[0] = p1;
    p[1] = p2;
    p[2] = p3;
    p[3] = p4;

    for (int i = 0; i < 4; i++ )
        for (int j = 0; j < 4; j++ )
            p[i][j] = 4*i+j;

    cout << "p:" << endl;
    for (int i = 0; i < 4; i++ ) {
        for (int j = 0; j < 4; j++ )
            cout << " " << p[i][j];
        cout << endl;
    }

    return 0;
}
```

6.5 bl_multidimensional_dynamic_array_size_input.cpp

```
/* program to illustrate dynamic memory
 *
 * Rajeev Singh
 * 2013-04-02
 *
 */

#include <iostream>
using namespace std;

int main() {
    int m, n;
    cout << "Enter the size of the matrix: ";
    cin >> m >> n;

    int **p = new int*[m];

    for (int i = 0; i < m; i++ )
        p[i] = new int[n];

    for (int i = 0; i < m; i++ )
        for (int j = 0; j < n; j++ )
            p[i][j] = n*i+j;

    cout << "p:" << endl;
    for (int i = 0; i < m; i++ ) {
        for (int j = 0; j < n; j++ )
            cout << " " << p[i][j];
        cout << endl;
    }

    return 0;
}
```


6.6 bm_multidimensional_array_with_mapping.cpp

```
/* program to illustrate dynamic memory
 *
 * NOTE: using pointer of pointers can be slower than using mappings
 * for big arrays for the following reason:
 *
 * pointer of pointers -> two access to RAM to get an element
 * mapping              -> single access to RAM for the same
 *
 * accessing RAM is much more expensive than simple integer
 * multiplication and addition
 *
 * Rajeev Singh
 * 2013-04-02
 */

#include <iostream>
using namespace std;

int main() {
    int m, n;
    cout << "Enter the size of the matrix: ";
    cin >> m >> n;

    int *p = new int[m*n];

    for (int i = 0; i < m; i++ )
        for (int j = 0; j < n; j++ )
            p[n*i+j] = n*i+j;

    cout << "p:" << endl;
    for (int i = 0; i < m; i++ ) {
        for (int j = 0; j < n; j++ )
            cout << " " << p[n*i+j];
        cout << endl;
    }

    return 0;
}
```

GO TO THE TALK TO DISCUSS BLAS

7 Day 7: String, Advanced Datatypes, BLAS, Sparse Matrices

7.1 bn_strings.cpp

```
/* program to illustrate strings as array of characters
 *
 * Rajeev Singh
 * 2013-04-03
 *
 */

#include <iostream>
using namespace std;

int main() {
    char str1[] = { 'S', 't', 'r', 'i', 'n', 'g', '\0' };
    char str2[] = "String"; // '\0' is appended automatically
    char str3[] = "This is a very long \
string";

    cout << str1 << endl;
    cout << str2 << endl;
    cout << str3 << endl;

    return 0;
}
```

7.2 bo_typedef.cpp

```
/* program to illustrate renaming datatypes using typedef
 *
 * Rajeev Singh
 * 2013-04-03
 *
 */

#include <iostream>
using namespace std;

int main() {
    typedef char * string_t;
    string_t str2 = "String"; // '\0' is appended automatically
    string_t str3 = "This is a very long \
string";

    cout << str2 << endl;
    cout << str3 << endl;

    return 0;
}
```

7.3 bp_struct.cpp

```
/* program to illustrate defining new datatypes using struct
*
* Rajeev Singh
* 2013-04-03
*
*/

#include <iostream>
using namespace std;

typedef double real_t;

struct vector_t {
    size_t size;
    real_t * coeffs;
};

void
add_vec ( const vector_t & x,
          const vector_t & y,
          vector_t &      z ) {
    for ( int i = 0; i < x.size; i++ )
        z.coeffs[i] = x.coeffs[i] + y.coeffs[i];
}

int main() {
    int      n = 10;
    vector_t a, b, c;
    a.size = n;
    b.size = n;
    c.size = n;

    a.coeffs = new real_t[n];
    b.coeffs = new real_t[n];
    c.coeffs = new real_t[n];

    for ( int i = 0; i < n; i++ ) {
        a.coeffs[i] = i;
        b.coeffs[i] = 2*i;
    }

    add_vec( a, b, c );

    cout << "a:" << endl;
    cout << "a.size = " << a.size << endl;
    cout << "a.coeffs:" << endl;
    for ( int i = 0; i < n; i++ )
        cout << "      " << a.coeffs[i] << endl;

    cout << "b:" << endl;
    cout << "b.size = " << b.size << endl;
    cout << "b.coeffs:" << endl;
```

```

    for ( int i = 0; i < n; i++ )
        cout << "          " << b.coeffs[i] << endl;

    cout << "c:" << endl;
    cout << "c.size = " << c.size << endl;
    cout << "c.coeffs:" << endl;
    for ( int i = 0; i < n; i++ )
        cout << "          " << c.coeffs[i] << endl;

    delete[] a.coeffs;
    delete[] b.coeffs;
    delete[] c.coeffs;
    return 0;
}

```

7.4 bq_struct_pointer.cpp

```
/* program to illustrate using pointers to struct
 *
 * Rajeev Singh
 * 2013-04-03
 *
 */

#include <iostream>
using namespace std;

typedef double real_t;

struct vector_t {
    size_t size;
    real_t * coeffs;
};

void
add_vec ( const vector_t * x,
          const vector_t * y,
          vector_t *      z ) {
    for ( int i = 0; i < x->size; i++ )
        z->coeffs[i] = x->coeffs[i] + y->coeffs[i];
}

int main() {
    int n = 10;
    vector_t * a = new vector_t,
              * b = new vector_t,
              * c = new vector_t;

    a->size = n;
    b->size = n;
    c->size = n;

    a->coeffs = new real_t[n];
    b->coeffs = new real_t[n];
    c->coeffs = new real_t[n];

    for ( int i = 0; i < n; i++ ) {
        a->coeffs[i] = i;
        b->coeffs[i] = 2*i;
    }

    add_vec( a, b, c );

    cout << "a:" << endl;
    cout << "a->size = " << a->size << endl;
    cout << "a->coeffs:" << endl;
    for ( int i = 0; i < n; i++ )
        cout << "      " << a->coeffs[i] << endl;
```

```

cout << "b:" << endl;
cout << "b->size = " << b->size << endl;
cout << "b->coeffs:" << endl;
for ( int i = 0; i < n; i++ )
    cout << "          " << b->coeffs[i] << endl;

cout << "c:" << endl;
cout << "c->size = " << c->size << endl;
cout << "c->coeffs:" << endl;
for ( int i = 0; i < n; i++ )
    cout << "          " << c->coeffs[i] << endl;

delete[] a->coeffs;
delete[] b->coeffs;
delete[] c->coeffs;

delete a;
delete b;
delete c;

return 0;
}

```

7.5 br_struct_array.cpp

```
/* program to illustrate using struct array
 *
 * Rajeev Singh
 * 2013-04-03
 *
 */

#include <iostream>
using namespace std;

typedef double real_t;

struct vector_t {
    size_t size;
    real_t * coeffs;
};

void
add_vec ( const vector_t * x,
          const vector_t * y,
          vector_t *      z ) {
    for ( int i = 0; i < x->size; i++ )
        z->coeffs[i] = x->coeffs[i] + y->coeffs[i];
}

int main() {
    int n = 10;
    vector_t * a = new vector_t[3];

    for ( int i = 0; i < 3; i++ ) {
        a[i].size = n;
        a[i].coeffs = new real_t[n];
    }

    for ( int i = 0; i < n; i++ ) {
        a[0].coeffs[i] = i;
        a[1].coeffs[i] = 2*i;
    }

    add_vec( &a[0], &a[1], &a[2] );

    cout << "a[0]:" << endl;
    cout << "a[0].size = " << a[0].size << endl;
    cout << "a[0].coeffs:" << endl;
    for ( int i = 0; i < n; i++ )
        cout << "          " << a[0].coeffs[i] << endl;

    cout << "a[1]:" << endl;
    cout << "a[1].size = " << a[1].size << endl;
    cout << "a[1].coeffs:" << endl;
    for ( int i = 0; i < n; i++ )
        cout << "          " << a[1].coeffs[i] << endl;
```



```

cout << "a[2]:" << endl;
cout << "a[2].size = " << a[2].size << endl;
cout << "a[2].coeffs:" << endl;
for ( int i = 0; i < n; i++ )
    cout << "          " << a[2].coeffs[i] << endl;

for ( int i = 0; i < 3; i++ )
    delete[] a[i].coeffs;

delete[] a;

return 0;
}

```

GO TO THE TALK TO DISCUSS BLAS AND SPARSE MATRICES