

navya@kali: ~

Session Actions Edit View Help

(navya@kali)-[~]

\$ sudo iptables -F

[sudo] password for navya:

(navya@kali)-[~]

\$ sudo iptables -A INPUT -m conntrack --ctstate ESTABLISHED,RELATED -j ACCEPT

(navya@kali)-[~]

\$ sudo iptables -A INPUT -p tcp -m conntrack --ctstate NEW -m recent --name scanner_list --update --seconds 60 -j DROP

(navya@kali)-[~]

\$



Search



navya@kali: ~

Session Actions Edit View Help

(navya@kali)-[~]

```
$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen
1000
    link/ether 08:00:27:cd:48:e2 brd ff:ff:ff:ff:ff:ff
    inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0
        valid_lft 588sec preferred_lft 588sec
    inet6 fe80::a00:27ff:fe0d:48e2/64 scope link noprefixroute
        valid_lft forever preferred_lft forever
```

(navya@kali)-[~]

```
$ nmap -sS -F 10.0.2.15
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-16 11:35 +0530
Nmap scan report for 10.0.2.15
Host is up.
All 100 scanned ports on 10.0.2.15 are in ignored states.
Not shown: 100 filtered tcp ports (no-response)

Nmap done: 1 IP address (1 host up) scanned in 21.02 seconds
```

(navya@kali)-[~]

\$



navya@kali: ~

Session Actions Edit View Help

```
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen
1000
link/ether 08:00:27:cd:48:e2 brd ff:ff:ff:ff:ff:ff
inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0
    valid_lft 588sec preferred_lft 588sec
inet6 fe80::a00:27ff:fe0d:48e2/64 scope link noprefixroute
    valid_lft forever preferred_lft forever
```

```
(navya@kali)-[~]
$ nmap -sS -F 10.0.2.15
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-16 11:35 +0530
Nmap scan report for 10.0.2.15
Host is up.
All 100 scanned ports on 10.0.2.15 are in ignored states.
Not shown: 100 filtered tcp ports (no-response)

Nmap done: 1 IP address (1 host up) scanned in 21.62 seconds
```

```
(navya@kali)-[~]
$ cat /proc/net/xt_recent/scanner_list
```

```
(navya@kali)-[~]
$ nmap -sS -F 10.02.15
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-16 11:40 +0530
Nmap scan report for 10.02.15 (10.2.0.15)
Host is up (0.00052s latency).
All 100 scanned ports on 10.02.15 (10.2.0.15) are in ignored states.
Not shown: 100 filtered tcp ports (no-response)

Nmap done: 1 IP address (1 host up) scanned in 2.86 seconds
```

```
(navya@kali)-[~]
$ sudo iptables -F
[sudo] password for navya:
```

```
(navya@kali)-[~]
$
```


IP TABLES

- utility used to control net filter

Filter Table

- Filters incoming & outgoing traffic
- firewall aspects

NAT Table

- redirect connections to other interfaces on the network

Mangle Table

modifying various aspects of a particular packet

- Input chain ^{incoming packets}
- output chain
- forward chain

forward from one computer to another (packets)

output chain _{outgoing packets}

prerouting chain
(after the packet has entered network interface)

postrouting chain
(just before it leaves your network interface)

input chain

output chain

forward chain

prerouting chain

postrouting chain

Firewall rules

- 1 Block SSH connection
 - 2 Block http connection
- input chain

accept SSH connections ACCEPT ← TARGETS -

drop the packet and send feedback REJECT ← what happens to a particular packet when it matches

drop the packet no packet was sent. DROP ← with a particular rule.