

navya@kali: ~/kali-sqli-demo

```
(navya@kali)~$ cd kali-sqli-demo  
(navya@kali)~/kali-sqli-demo$ mousepad app.js
```



```
21     res.send(`<h1>🔒 Access Granted!</h1><p>Check your backend terminal to see the query string execution.</p>`);
22   } else {
23     res.send(`<h1>❌ Access Denied</h1>`);
24   }
25 });
26 });
27
28 app.post('/login-secure', (req, res) => {
29   const { username, password } = req.body;
30   const secureQueryTemplate = "SELECT * FROM users WHERE username = ? AND password = ?";
31
32   console.log(`\n[BACKEND] Executing Secure Template:\n→ " + secureQueryTemplate);
33   console.log(`[BACKEND] Parameter safely isolated: [" + username + "]`);
34
35   db.get(secureQueryTemplate, [username, password], (err, row) => {
36     if (row) {
37       res.send(`<h1>🔒 Access Granted!</h1>`);
38     } else {
39       res.send(`<h1>❌ Access Denied!</h1><p>Check your backend terminal to see how the parameters were kept separated.</p>`);
40     }
41   });
42 });
43
44 app.get('/', (req, res) => {
45   res.send(`
46     <h2>Kali Linux SQLi Live Logs Demo</h2>
47     <hr>
48     <h3>Form 1: Vulnerable Login (String Concatenation)</h3>
49     <form action="/login-vulnerable" method="POST">
50       Username: <input type="text" name="username" value="" OR 1=1 --><br><br>
51       <input type="submit" value="Attack Vulnerable Form">
52     </form>
53     <hr>
54     <h3>Form 2: Secure Login (Prepared Statements)</h3>
55     <form action="/login-secure" method="POST">
56       Username: <input type="text" name="username" value="" OR 1=1 --><br><br>
57       <input type="submit" value="Attack Secure Form">
58     </form>
59   `);
60 });
61
62 app.listen(3000, () => console.log('Backend listening on http://localhost:3000'));
63
```

Kali Linux [Running] - Oracle VirtualBox

FileMachineViewInputDevicesHelp

navya@kali: ~/kali-sqli-demo

SessionActionsEditViewHelp

(navya@kali)-[~]
\$ cd kali-sqli-demo

(navya@kali)-[~/kali-sqli-demo]
\$ mousepad app.js

(navya@kali)-[~/kali-sqli-demo]
\$ node app.js
Backend listening on http://localhost:3000

Kali Linuxlocalhost:3000/

http://localhost:3000

OffSecKali LinuxKali ToolsKali DocsKali ForumKali NetHunterExploit-DBGoogle Hacking DB

Kali Linux SQLi Live Logs Demo

Form 1: Vulnerable Login (String Concatenation)

Username:

Attack Vulnerable Form

Form 2: Secure Login (Prepared Statements)

Username:

Attack Secure Form

Graphics Controller: VMSVGA
Remote Desktop Server: Disabled
Recording File: C:\Users\nbnav\VirtualBox VMs\Kali Linux\Kali Linux-

```
(navya@kali)-[~]  
$ cd kali-sqli-demo  
  
(navya@kali)-[~/kali-sqli-demo]  
$ mousepad app.js  
  
(navya@kali)-[~/kali-sqli-demo]  
$ node app.js  
Backend listening on http://localhost:3000
```

Kali Linux SQLi Live Logs Demo

Form 1: Vulnerable Login (String Concatenation)

Username:

Attack Vulnerable Form

Form 2: Secure Login (Prepared Statements)

Username:

Attack Secure Form

localhost

Graphics Controller: VMSVGA
Remote Desktop Server: Disabled
Recording File: C:\Users\nbnav\VirtualBox VMs\Kali Linux\Kali Linux-

```
(navya@kali)-[~]  
$ cd kali-sqli-demo  
  
(navya@kali)-[~/kali-sqli-demo]  
$ mousepad app.js  
  
(navya@kali)-[~/kali-sqli-demo]  
$ node app.js  
Backend listening on http://localhost:3000  
  
[BACKEND] Executing Vulnerable Query:  
→ SELECT * FROM users WHERE username = '' OR 1=1 --' AND password = 'undefined'  
□
```

🔒 Access Granted!

Check your backend terminal to see the query string execution.

```
navya@kali: ~/kali-sqli-demo
Session Actions Edit View Help

(navya@kali) - [~]
$ cd kali-sqli-demo

(navya@kali) - [~/kali-sqli-demo]
$ mousepad app.js

(navya@kali) - [~/kali-sqli-demo]
$ node app.js
Backend listening on http://localhost:3000

[BACKEND] Executing Vulnerable Query:
→ SELECT * FROM users WHERE username = '' OR 1=1 --' AND password = 'undefined'
█
```

Kali Linux localhost:3000/

http://localhost:3000

OffSec Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB

Kali Linux SQLi Live Logs Demo

Form 1: Vulnerable Login (String Concatenation)

Username:

Attack Vulnerable Form

Form 2: Secure Login (Prepared Statements)

Username:

Attack Secure Form

Kali Linux [Running] - Oracle VirtualBox

FileMachineViewInputDevicesHelp

navya@kali: ~/kali-sqli-demo

SessionActionsEditViewHelp

(navya@kali)~
\$ cd kali-sqli-demo

(navya@kali)~/kali-sqli-demo
\$ mousepad app.js

(navya@kali)~/kali-sqli-demo
\$ node app.js
Backend listening on http://localhost:3000

[BACKEND] Executing Vulnerable Query:
→ SELECT * FROM users WHERE username = '' OR 1=1 --' AND password = 'undefined'

[BACKEND] Executing Secure Template:
→ SELECT * FROM users WHERE username = ? AND password = ?
[BACKEND] Parameter safely isolated: [' OR 1=1 --']

Kali Linuxlocalhost:3000/login-secure

http://localhost:3000/login-secure

OffSecKali LinuxKali ToolsKali DocsKali ForumsKali NetHunterExploit-DBGoogle Hacking DB

Access Denied!

Check your backend terminal to see how the parameters were kept separated.

Graphics Controller: VMSVGA
Remote Desktop Server: Disabled
Recording File: C:\Users\nbnav\VirtualBox VMs\Kali Linux\Kali Linux-