HUMAIN HACKATHON · CHALLENGE 2: DELIVER AI WITH LESS COMPUTE

OptiRoute

A bilingual (Arabic / English) compute cascade that sends each task to the cheapest tier able to answer it correctly, with every number measured on recorded real model runs.

−79.2%
compute vs always-large-model (kTok × active params)

4.4×
cheaper per successful task (CPS)

84.4%
accuracy on 96 held-out cases (always-14B: 91.7%)

1.8 ms
total CPU overhead per task for all 4 guard components

Nawaf Alduaij

Runs anywhere from a laptop to a cloud API · 4 deployment profiles benchmarked · headline measured on one consumer GPU (RX 7900 XTX) · deterministic replay in 11 s

THE ISSUE

Most enterprise requests overpay for compute

The default setup sends every request to the largest model with the whole document attached.

Measured on our 96 held-out bilingual tasks:

- Always-14B on raw context: 515 kTok·B, 36,785 tokens, 91.7% accuracy
- Always-3B: 79.1% cheaper and only 6.2 pts less accurate, so most tasks never needed the large model
- Pruning alone removes 71.9% of context tokens; with 4× distractor noise, 93.7%
- A naive semantic cache returns the answer for #INV-8841 when asked about #INV-8842: a cheap but wrong result

WHAT THE CHALLENGE ASKS, AND WHERE OPTIROUTE ANSWERS IT

1 **Model choice per task**
route easy work to the 3B model

2 **Context that earns its tokens**
pruning + boilerplate removal


3 **Verification where it pays**
< 1 ms rule checks, escalate only on failure

4 **Cost per successful task**
CPS reported for every configuration

5 **Accuracy & latency floors**
graded by a separate ground-truth scorer

OUR SOLUTION

A 3-tier cascade with deterministic CPU guards between the tiers



Adaptation loop: a W = 20 window of Tier-1 verifier outcomes and P95 latency moves $\tau \in [0.25, 0.75]$. τ tightens by 0.08 when the pass rate drops below 70% or P95 exceeds the SLO, and recovers by 0.05 per step after 5 healthy steps (hysteresis).

Every component is deterministic, CPU-only and individually timed: mean pruner 1.34 ms · cache 0.32 ms · router 0.02 ms · verifier 0.11 ms.

HOW IT WORKS

Four steps, each one measurable and switchable for ablation

1 Context pruning & numeric-guarded cache

- Paragraphs scored: 0.50·cos(char 3–5g) + 0.35·cos(word TF-IDF) + 0.15·shared numbers/IDs
- Arabic: Alef/Teh-Marbuta/Alef-Maksura unified, tashkeel stripped, proclitics (وال، بال، لل...) removed
- Cache key = query wording (digits masked) + hash of top-2 chunks; hit only if entity sets are identical

2 Complexity routing & Tier-1 execution

- C = 0.30 multi-hop + 0.30 arithmetic + 0.25 strict JSON/table + 0.15 relevance dispersion
- C < τ → qwen2.5:3b on the pruned context; C ≥ τ → qwen2.5:14b directly
- Measured: 72 of 96 tasks finished on Tier-1, 6 on Tier-0 cache

3 Verification & full-context escalation


- Refusal/degeneracy · JSON schema · numeric grounding (each output number must appear in, or follow by + − × ÷ % from, the context) · Arabic-in/Arabic-out
- Precision 78% and recall 33% on recorded Tier-1 outputs; never sees ground truth
- Refusal → Tier-2 with full context (recovers pruner misses); other failures → top-4 relaxed context

4 Bidirectional τ adaptation + shadow audit

- Estimated Tier-1 health = verifier pass rate × agreement on sampled Tier-2 audits (every 4th verified answer)
- Tightens when health < 70% or P95 > SLO; recovers +0.05/step after 5 healthy steps (hysteresis)
- Recorded wave: τ 0.55 → 0.39 during the hard burst (first tightening at request 25), back to 0.55 by request 83

IMPLEMENTATION & LIVE DEMO

A working prototype you can click through



Live UI: the #INV-8842 trap is blocked by the entity guard (wording cosine 1.000, IDs differ)

WHAT WAS BUILT

- Cascade engine (src/): pruner, entity-guarded cache, router, verifier, adaptive τ, orchestrator; every component can be switched off for ablation
- Interactive UI: 9 bilingual presets replay recorded runs; custom questions run on the live models; every stage visualised with its cost vs always-14B
- evaluate.py: --record / --replay / --sim, 2 ablation tables, 5 robustness experiments
- 35 unit tests; slides and reports generated from measured results

TECH STACK

Python · any OpenAI-compatible endpoint (Ollama, vLLM, Groq…) · 4 deployment profiles (profiles/*.env) · measured with qwen2.5/3.5, llama3.2, ALLaM-2, gpt-oss-120b · OpenAI-compatible client · tiktoken · FastAPI + Chart.js · pytest · python-pptx

github.com/nawafalduaij/optiroute

EVALUATION METHODOLOGY

Held-out, recorded once, replayed, graded separately

Category	Cases	What it stresses
standard	50	single-chunk policy / invoice lookups
low lexical overlap	12	paraphrased query, almost no shared keywords
multi hop	12	facts from 2 chunks + arithmetic (SLA credit, penalties)
arabic orthographic variants	10	missing hamza, ى/ي, ة/ه, clitics, mixed numerals
cache near duplicates	12	6 paraphrase hits + 6 traps (changed IDs, days, fees)
total	**96**	**48 English / 48 Arabic · separate 10-case dev set**

Record & replay

480 real calls (96 tasks on 11 synthetic documents × raw/pruned/relaxed × tier), temperature 0, models pre-warmed, prompt hash stored to detect drift

No circular metrics

Accuracy comes from a ground-truth scorer (numeric tolerance, required facts, JSON fields). The runtime verifier is graded against it, never used for it.

Measured units

tiktoken o200k token counts · compute = Σ tokens/1000 × active params (3B / 14B, cache = 0) · latency = recorded LLM time + perf_counter CPU time


Reproducible

Full evaluation replays in 10.7 s without a GPU or API keys; 35 unit tests in sim mode

RESULTS: HELD-OUT, RECORDED REAL RUNS

Cumulative build-up: what each component adds

Configuration	Accuracy	Tokens	Compute kTok·B	Δ compute	CPS	P50 ms	Tier 0/1/2	False cache hits
1 Always Tier2 Raw	91.7% (88/96)	36,785	515.0	+0.0%	5.85	462	0/0/96	0/6
2 Always Tier1 Raw	85.4% (82/96)	35,956	107.9	-79.1%	1.32	138	0/96/0	0/6
3 Router Only	89.6% (86/96)	36,494	168.0	-67.4%	1.95	148	0/84/12	0/6
4 Pruner Plus Router	81.2% (78/96)	17,452	84.0	-83.7%	1.08	141	0/84/12	0/6
5 OptiRoute Full	**84.4% (81/96)**	**18,177**	**106.9**	**-79.2%**	**1.32**	**145**	**6/72/18**	**0/6**



Full cascade vs always-14B

- −79.2% compute, −50.6% tokens
- CPS 1.32 vs 5.85 kTok·B per success (4.4× cheaper)
- P50 latency 145 ms vs 462 ms
- Accuracy 84.4% vs 91.7%: 7 fewer correct answers out of 96
- Accuracy-first setting (pruner off): 89.6% at −66% compute

ABLATIONS & ROBUSTNESS

Leave-one-out, other models, and adaptation on real runs

Configuration	Accuracy	Tokens	Compute kTok·B	Δ compute	CPS	P50 ms	Tier 0/1/2	False cache hits
Full OptiRoute	**84.4% (81/96)**	**18,177**	**106.9**	**-79.2%**	**1.32**	**145**	**6/72/18**	**0/6**
LOO No Cache	84.4% (81/96)	19,330	110.3	-78.6%	1.36	149	0/78/18	0/6
LOO No Cache Entity Guard	83.3% (80/96)	17,479	99.3	-80.7%	1.24	141	9/71/16	3/6
LOO No Pruner	89.6% (86/96)	34,960	172.7	-66.5%	2.01	147	6/76/14	0/6
LOO No Verifier	81.2% (78/96)	16,299	80.6	-84.4%	1.03	139	6/78/12	0/6
LOO No Adaptation	84.4% (81/96)	18,177	106.9	-79.2%	1.32	145	6/72/18	0/6

DEPLOYMENT PROFILES: same cascade code, laptop to cloud (all recorded real runs)

Profile	Tier-1 → Tier-2	Tier-1 alone	Always T2	OptiRoute	Sent to T2	T2 tokens
single-gpu	**qwen2.5:3b → qwen2.5:14b**	**85.4%**	**91.7%**	**84.4%**	**18/96**	**-87%**
hybrid	qwen3.5:9b → gpt-oss-120b	94.8%	99.0%	95.8%	19/96	-85%
edge	qwen2.5:0.5b → gpt-oss-120b	57.3%	99.0%	80.2%	25/96	-83%
cloud	allam-2-7b → gpt-oss-120b	90.6%	99.0%	90.6%	20/96	-85%

Entity guard 0/6 vs 3/6 false hits · verifier +3.1 pts · pruner −48% tokens (leave-one-out, single-gpu)

REAL τ(t), WAVE WORKLOAD



Tightens in the burst, then recovers · +34% compute

HONEST LIMITATIONS & ROADMAP

What this prototype does not solve yet

1. Grounded-but-wrong arithmetic slips past the verifier

Recall is 33%: rule checks cannot tell 10% of the fee from 25% when both numbers are in the context. Multi-hop accuracy is 50% for the cascade, and even the 14B gets only 58% (it wrote 900×4 + 1200×3 = 4,500, and switched to Chinese mid-answer in Arabic).

2. A lexical pruner is blind to zero-overlap paraphrases

Low-overlap accuracy is 50% with the pruner vs 100% without it. Recovery only works when the 3B admits it doesn't know, and phrase-based refusal rules miss wordings like "No ... is mentioned". Turning the pruner off gives 89.6% accuracy at −66% compute.

3. Adaptation needs a costly signal; small benchmark

Rule checks miss confident errors: verifier-only health never fell below 75%, so τ stayed flat. Shadow audits make τ react on real runs but cost +34% compute and did not raise accuracy on the wave (72.4% vs 73.5%). n = 96 synthetic cases: ±1 task = 1.0 pts.

PRODUCTION ROADMAP

- Calculator tool + program-of-thought for multi-hop math, with the verifier recomputing the expression
- Per-model verifier calibration on the dev set (refusal phrasing differs between model families)
- Small bilingual embedding re-ranker as a fallback when the lexical scores are flat
- Token-logprob confidence as a 5th verifier signal for confident-but-wrong answers
- Output language guard on Tier-2 (catches code-switching)
- Risk-weighted audit sampling + a larger dev set to calibrate τ, the SLO and the verifier
- Serve with vLLM + batching; swap in HUMAIN/ALLaM models through the same OpenAI-compatible client

TAKEAWAYS

Cheap only counts if it is right, and we measured both

−79.2%
compute vs always-14B

4.4×
cheaper per successful task

0/6
false cache hits with the entity guard

78%
verifier precision (no wasted escalations)

Why this design

- Evaluation first: a held-out set, recorded real runs, and leave-one-out ablations, instead of a prompt wrapper with hand-picked numbers
- Bilingual by construction: Arabic normalization in the pruner, cache and verifier
- Runs fully local on one 24 GB GPU: no rate limits, no API cost, data stays on-premise
- Hardware-agnostic: 4 deployment profiles from laptop to cloud, same code; 8 recorded model pairs
- Every guard is inspectable and costs about 1.8 ms of CPU time

github.com/nawafalduaij/optiroute

```
pip install -r requirements.txt
python evaluate.py --replay data/recorded_runs.jsonl
uvicorn app:app --port 8000   # live demo UI

Re-record on your own hardware:
python evaluate.py --record --fresh
```

Nawaf Alduaij · thank you