



Low Voltage Battery

LB-16D-G3

Description

The LB-16D-G3 is a deep cycle high capacity LFP battery with improved safety, long lifespan, and optimized user experience.

It has superior performance with a capacity of 16.08 kWh for a single unit and a maximum of 257 kWh for 16 batteries in parallel, which can meet the residential electricity demand.

Features

01

LFP with improved safety design

04

Adaptable to environments with temperatures ranging from -20°C to 55°C

02

Provides abundant power with 314 Ah capacity, ensuring long-lasting energy storage

05

Flexible capacity options from 16.08 kWh to 257 kWh

03

Supports wall-mounted, floor-standing, and stackable installation

06

Intelligent BMS with multiple protection functions

Technical Specifications

Model	LB-16D-G3
System Data	
Battery type	LiFePO ₄
Rated capacity (Ah)	314
Total energy (kWh)	16.08
Rated voltage (V)	51.2
Voltage range (V)	44.8-58.4
Max. continuous charging/discharging current (A)	160
Peak charging/discharging current (A)	240 (10s)
Communication	CAN
Recommended depth of discharge (DOD)	90%
Max. parallel quantity	16
Protection	
Overvoltage and undervoltage protection	Integrated
Overcurrent protection	Integrated
Overtemperature and undertemperature protection	Integrated
DC breaker	Integrated
Heating	Optional
General	
Dimensions (W × H × D [mm]) ⁽¹⁾	410 × 770 × 235
Weight (kg) ⁽¹⁾	110
Installation Environment	Indoor/Outdoor
Mounting	Wall mounted/Floor standing/Stackable
Charging temperature (°C)	0 to +55
Discharging temperature (°C)	-20 to +55
Protection degree	IP65
Cooling	Natural convection
Altitude (m)	≤2000
Cycle life (25°C)	8000 Cycles
Certification	IEC 62619, UN 38.3, CE-EMC, CB
Warranty ⁽²⁾	5-10 Years

(1) The actual dimensions and weight may differ. For details, please contact Hoymiles sales.

(2) Please refer to Hoymiles Warranty Terms & Conditions for more details.