# Email Ingestion JSON Payload Specification

We send one JSON object per email. The payload shape does not change based on email content such as attachments, URLs, or quoted history.

If some information does not exist, we still send the same structure, but values may be null, empty string, empty array, or false depending on the field type.

Unused fields on the backend can be safely ignored as long as required ingestion fields are handled.

## Required Routing / Identity Fields

- **mailbox_id**: Internal mailbox identifier used as the main routing key.
- **mailbox_email**: Mailbox email address used for validation.
- **provider_message_id**: Original Gmail message ID for unique identification.

## Recommended Envelope / Message Fields

- **correlation_id**: Internal tracking ID for pipeline tracing.
- **thread_id**: Gmail thread ID to group related emails.
- **subject**: Normalized email subject (may be empty).
- **from**: Sender information (name + email).
- **to**: List of recipient emails.
- **cc**: List of CC recipient emails.
- **sent_at**: Original email timestamp.
- **text_body**: Cleaned semantic email content.
- **html_body**: Currently null.
- **attachment_names**: List of attachment filenames.

## Headers Object

- **Reply-To**: Reply-to header if present.
- **Message-ID**: Original message ID header.
- **In-Reply-To**: Reply reference header.
- **References**: Thread reference header.

## Metadata Object

## metadata.gmail

- **label_ids**: Gmail labels such as INBOX or UNREAD.
- **history_id**: Gmail history identifier.
- **snippet**: Decoded preview text.
- **snippet_raw**: Raw snippet before decoding.
- **raw_body_text**: Full raw body including clutter.
- **original_body_text**: Body before semantic cleaning.