



Technical Data Sheet

Description

Tek-Wash PR is a single component acidic solution specially formulated to remove paint from masonry and metal surfaces without any mechanical methods. **Tek-Wash PR** removes paint and cleans the substrate to receive protective coatings.

Advantages

- Single component
- Easy to use
- Quick results

Uses

- Preparation of walls to receive coatings and paints
- Cleaning of cement and concrete from tools

Physical Properties*

Property	Typical Results
Appearance	Clear liquid
Density	1.30
*The above properties are average laboratory values	

Packing

Tek-Wash PR is available in 1, 5 and 20 liters pails.

Shelf Life

24 months when stored in cool dry environment in factory packed unopened containers between 5°C – 25°C.

Installation Guidelines

Spraytek provides detailed method statements on all its products for use in various applications. These must be referred to prior to starting the work. The information below is a summary intended for guidance only.

Application

Apply to the affected areas and leave the applied surfaces for 15 minutes. The **Tek-Wash PR** applied areas should be cleaned. If paint is still visible, apply the second coat and leave it for another 15 minutes. Clean any loose particles with a light water wash.

Technical Support

Spraytek offers full technical support package to specifiers, contractors and end users, as well as technical assistance on site and after sales consultations.

Health & Safety

As with all chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles, should be worn. See packaging/MSDS for specific instructions.

Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally swallowed, do not induce vomiting, but call for medical assistance immediately.

Reference #	TDS / STC / TWPR
Issue Date:	01/2012
Revision #	0

The information contained herein is to the best of our knowledge, belief, and accuracy. However, hence the conditions of handling and usage beyond our control. We make no warrantee of results, and assume no responsibility or liability for any damages or consequential damage incurred by the use of the product. Our products are sold on the condition that the user shall evaluate them, as well as our recommendations. To determine their suitability for a particular purpose. The user is solely responsible for the selection of Spraytek products.



Spraytek Coatings LLC

P.O. Box 27356, Dubai, U.A.E., Tel.: +9714 2221432, Fax: +9714 2275750, Email: info@spraytek.ae

www.spraytek-me.com