



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

Aim: To study the Object segmentation

Objective: To study Object segmentation using the Watershed and GrabCut algorithms Example of foreground detection with GrabCut, Image segmentation with the Watershed algorithm

Theory: Object segmentation using the Watershed and GrabCut algorithms. Calculating a disparity map can be very useful to detect the foreground of an image, but StereoSGBM is not the only algorithm available to accomplish this, and in fact, StereoSGBM is more about gathering 3D information from 2D pictures, than anything else. GrabCut, however, is a perfect tool for this purpose. The GrabCut algorithm follows a precise sequence of steps:

1. A rectangle including the subject(s) of the picture is defined
2. The area lying outside the rectangle is automatically defined as a background.
3. The data contained in the background is used as a reference to distinguish background areas from foreground areas within the user-defined rectangle.
4. A Gaussians **Mixture Model (GMM)** models the foreground and background pixels as probable background and foregrounds.
5. Each pixel in the image is virtually connected to the surrounding pixels through virtual edges, and each edge gets a probability of being foreground or background, based on how similar it is in color to the pixels surrounding it.
6. Each pixel (or node as it is conceptualized in the algorithm) is connected to either a foreground or a background node



7. after the nodes have been connected to either terminal (background or foreground, also called a source and sink), the edges between nodes belonging to different terminals are cut (the famous cut part of the algorithm), which enables the separation of the parts of the image

Image segmentation with the Watershed algorithm :-

Finally, we take a quick look at the Watershed algorithm. The algorithm is called Watershed, because its conceptualization involves water. Imagine areas with low density (little to no change) in an image as valleys, and areas with high density (lots of change) as peaks. Start filling the valleys with water to the point where water from two different valleys is about to merge. To prevent the merging of water from different valleys, you build a barrier to keep them separated. The resulting barrier is the image segmentation.

Code:

```
import cv2
import numpy as np
from IPython.display import Image, display
from matplotlib import pyplot as plt

# Plot the image
def imshow(img, ax=None):
    if ax is None:
        ret, encoded = cv2.imencode(".jpg", img)
        display(Image(encoded))
    else:
        ax.imshow(cv2.cvtColor(img, cv2.COLOR_BGR2RGB))
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

```
ax.axis('off')
```

```
#Image loading
```

```
img = cv2.imread("image.png")
```

```
#image grayscale conversion
```

```
gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)
```

```
# Show image
```

```
imshow(img)
```

```
#Threshold Processing
```

```
ret, bin_img = cv2.threshold(gray,
```

```
0, 255,
```

```
cv2.THRESH_BINARY_INV + cv2.THRESH_OTSU)
```

```
imshow(bin_img)
```

```
# noise removal
```

```
kernel = cv2.getStructuringElement(cv2.MORPH_RECT, (3, 3))
```

```
bin_img = cv2.morphologyEx(bin_img,
```

```
cv2.MORPH_OPEN,
```

```
kernel,
```

```
iterations=2)
```

```
imshow(bin_img)
```

```
# Create subplots with 1 row and 2 columns
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

```
fig, axes = plt.subplots(nrows=2, ncols=2, figsize=(8, 8))
# sure background area
sure_bg = cv2.dilate(bin_img, kernel, iterations=3)
imshow(sure_bg, axes[0,0])
axes[0, 0].set_title('Sure Background')
# Distance transform
dist = cv2.distanceTransform(bin_img, cv2.DIST_L2, 5)
imshow(dist, axes[0,1])
axes[0, 1].set_title('Distance Transform')
#foreground area
ret, sure_fg = cv2.threshold(dist, 0.5 * dist.max(), 255, cv2.THRESH_BINARY)
sure_fg = sure_fg.astype(np.uint8)
imshow(sure_fg, axes[1,0])
axes[1, 0].set_title('Sure Foreground')

unknown = cv2.subtract(sure_bg, sure_fg)
imshow(unknown, axes[1,1])
axes[1, 1].set_title('Unknown')
plt.show()
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

Input Image:-



Output Image:-





Sure Background



Distance Transform



Sure Foreground



Unknown





Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Academic Year : 2023-24

Conclusion:-

This experiment illustrates the watershed approach for picture segmentation. A good technique for dividing a picture into distinct parts based on intensity and geographic factors is the watershed algorithm. It prepares the image for segmentation by applying thresholding, morphological procedures, and grayscale conversion. After that, the watershed method creates zones of interest, such as "Sure Background" and "Sure Foreground," which are essential for object segmentation. This illustration demonstrates the usefulness of the watershed technique as a tool for a variety of computer vision and image processing applications