

Remote Switch Actuators (RSA)

CBS ArcSafe® Remote Switch Actuators (RSAs) are designed to remotely charge, close, and/or trip various styles and types of electrical equipment. An RSA can be custom built for any electrical device. RSAs are quickly attached by strong magnets, eliminating the need for modifications to your switchgear. This results in safe and efficient operations. Magnets also allow workers to easily move the RSA from one application to another.



RSA-48
Eaton, Cutler-Hammer
Magnum DS, SB (Door
Closed, 800-4000 A)



RSA-113G & RSO-IAR-M18 Operator

OPTIONAL FEATURES

- Radio remote with up to 300-foot range
- Wireless video camera system with LCD monitor
- Rugged protective case assembly

BENEFITS

- Lightweight, portable construction
- Mechanical and/or electrical safety protection
- Adjustable to fit unique electrical equipment configurations
- Fast and easy to set up
- Reduces need for a full-body arc-flash suit
- Adds safety and helps comply with NFPA 70E
- No modifications required

Remote Switch Kits (RSK)



Chicken Switch® Remote Switch Kits (RSK) are portable devices designed to remotely operate circuit breakers, control switches, and motor control centers. RSKs are ideal in environments where weight and portability are a consideration. With no need to purchase a separate power source, the price point and packaging are appealing.

- Complete kit includes actuator, handheld controller, batteries, control cable, instruction manual, and carrying case *RSK only

EC&M
Product of the Year **20** YEARS
2020 Category Winner



RSK-CS01
Electroswitch Series
24, 24P, General
Electric SB, SBM, SB-1,
SB-9, SB-10, Westing-
house Type W, Shallco
Series 26



RSK-K15
ABB, BBC, ITE K-Line (2000
A & below, Electrically
Operated)



RSK-GEPB1L
PowerBreak (with Close
button on left side of
charging handle)



RSK-CS01



POWERED BY
M18 RED LITHIUM

*Wireless control available on most models.

All CBS ArcSafe products are compatible with all switchgear manufacturers, including:

- | | | | |
|------------------|----------------------------|-----------------|-----------------|
| ■ ABB | ■ Eaton | ■ McGraw-Edison | ■ Siemens |
| ■ Allis-Chalmers | ■ Federal Pacific Electric | ■ Merlin Gerin | ■ Siemens-Allis |
| ■ Alstom | ■ Federal Pioneer | ■ Mitsubishi | ■ Square D |
| ■ BBC | ■ General Electric | ■ Powell | ■ Toshiba |
| ■ Cutler-Hammer | ■ Hyundai | ■ Reyrolle | ■ Westinghouse |
| | ■ ITE | | |

NOTE: All manufacturers' names, trademarks, and part numbers are used for reference purposes only. CBS ArcSafe, Inc. is not an authorized distributor or representative of manufacturers shown. Designated trademarks, brand names and brands appearing herein are the property of their respective owners.

RRS-1

Remote Racking System For Rotary Circuit Breakers



By permitting the automatic racking of the circuit breaker from a remote location, the CBS ArcSafe® remote racking system replaces the manual racking operation and removes the operating personnel from manual contact with the circuit breaker. The unique design of the CBS ArcSafe remote racking system, with its specially manufactured drive shafts and tooling, enables the system to operate with all types of circuit breakers produced by the major switchgear manufacturers. The CBS ArcSafe remote racking system can operate with draw-out types of air, SF6, oil, and vacuum circuit breakers that have either a horizontal or vertical racking operation.

BENEFITS

- Remote operation places operator outside the arc-flash protection boundary
- Compatible with low- and medium-voltage circuit breakers produced by all major switchgear manufacturers
- Use with horizontal and vertical types of air, SF6, oil, and vacuum circuit breakers
- Height and angle of the drive is easily adjusted
- Quick-release drive shafts and couplings simplify setup
- Redundant over-racking protection provided
- Seamless transfer of AC/DC power
- Hand-truck design provides easy mobility

SPECIFICATIONS


WEIGHT . . .	200 lbs
BATTERY LIFE . . .	> 50 Operations*
SYSTEM VOLTAGE . . .	24V DC
INPUT VOLTAGE . . .	120±10% VAC, 47-63 Hz†
MAXIMUM AC CURRENT . . .	12.2 A
DRIVE MOTOR POWER . . .	250 W
DRIVE ASSEMBLY SPEED . .	80 RPM
CHARGE TIME . . .	Approx. 6 hours
DIMENSIONS . . .	74" H x 26" W x 38.1" D
OPERATING DISTANCE . . .	35 feet‡

*Number of operations is dependent on the nature of the operation

†May be custom ordered to match different local power standards

‡Standard configuration, contact CBS ArcSafe® for other options

US PATENT NO. 8,151,452B2



Optional Equipment

Remote Racking Systems

For Extraction-Style and Rotary-Type Circuit Breakers


CCM Radio Remote

The Current Control Module (CCM) radio remote option allows users to operate the RRS and monitor the racking status wirelessly from up to 300 feet away. Ideal for users with extended distance requirements or those who wish to monitor the status of the racking operation remotely.



Wireless/Wired Video System

The wireless/wired video system allows users to monitor the remote racking operation from up to 300 feet away using an RRS-mounted camera and stand-alone monitor. Ideal for users who will be visually separated from the RRS during the remote operation.



Power Slide

The power slide system utilizes a motor to raise and lower the drive assembly instead of the standard handle. Ideal for applications requiring users to quickly and easily switch between racking heights for different breakers.



LED Light

The LED light accessory adds a forward-facing, high-intensity light source with pan and tilt capability to the front of the RRS. Ideal for personnel setting up the RRS or installing RRS tooling in low-light environments.



High Lift

The high lift option is required to remotely rack any equipment with a racking mechanism more than 66 inches off the ground. Ideal for users who wish to rack breakers with extremely high racking mechanisms that would otherwise cause issues during manual operation.



Low-Speed/Jog

The low-speed/jog option consists of a high-torque/low-speed gearbox, as well as manual jog control for the RRS operation. Ideal for applications requiring added torque output and/or more precise control.



RRS-2


Remote Racking System For Extraction-Style Circuit Breakers



The CBS ArcSafe RRS-2 is a portable and highly configurable remote racking system built to rack all circuit breakers with non-rotary racking mechanisms while keeping the operator outside of the arc-flash boundary. The operator is able to manipulate the breaker-specific tooling, available for numerous makes and models of switchgear, via either a wired or wireless pendant station from up to 300 feet away. Prior to ordering, CBS ArcSafe recommends an on-site evaluation be performed by a company representative in order to ensure the proper equipment may be provided for each customer based on their particular switchgear and specific requests.

SPECIFICATIONS

WEIGHT	160 lbs
BATTERY LIFE	> 50 Operations*
SYSTEM VOLTAGE	24V DC
INPUT VOLTAGE	120±10% VAC, 47-63 Hz†
MAXIMUM AC CURRENT	12.2 A
EXT. ACTUATOR FORCE	600 lbs
EXT. ACTUATOR SPEED	1.0"/second
CHARGE TIME	Approx. 6 hours
DIMENSIONS	60" H x 26" W x 36" D
OPERATING DISTANCE	35 feet‡



*Number of operations is dependent on the nature of the operation; †May be custom ordered to match different local power standards; ‡Standard configuration, contact CBS ArcSafe® for other options

RRS-2 BE

Remote Racking System For Motor Control Center Buckets Only



The RRS-2 BE is designed specifically for motor control center (MCC) bucket removal applications where users normally would be required to perform the install or remove operation manually — exposing them to the potential hazards of an arc flash and its lethal consequences. Designed to be extremely versatile, the RRS-2 BE is suited for use in all environments — from grueling applications in a power-generation facility to clean rooms at a high-tech manufacturing plant.



BENEFITS

Setup and operation of the RRS-2 BE are very similar to that of the standard RRS-2, allowing users who are familiar with RRS-2 operation to transition between the two easily with no additional training required. RRS-2 BE benefits include:

- Large linear actuator has been replaced with a compact, adjustable travel linear actuator more suited to the forces required for MCC buckets instead of large breakers
- Steel frame of the RRS-2 has been modified to accept the specialized tooling required for MCC bucket install and remove operations
- Dual channel-enabled operation allows users to carefully control the MCC bucket install and remove operations
- Two-station high-reach vertical adjustment is capable of reaching MCC buckets up to 80" high. The included wireless remote control allows users to operate the unit from up to 300 feet away

SPECIFICATIONS

WEIGHT	105 lbs
BATTERY LIFE	> 50 Operations*
SYSTEM VOLTAGE	24V DC
INPUT VOLTAGE	120±10% VAC, 47-63 Hz†
CHARGE TIME	Approx. 4 hours
DIMENSIONS	74" H x 25" W x 32" D
OPERATING DISTANCE	300 feet‡

*Number of operations is dependent on the nature of the operation

†May be custom ordered to match different local power standards

‡Radio remote control standard on RRS-2 BE