

CSE3026: Web Application Development Prototype

Scott Uk-Jin Lee

Reproduced with permission of author. Copyright 2012 Marty Stepp, Jessica Miller, and Victoria Kirst. All rights reserved. Further reproduction or distribution is prohibited without written permission.



Problems with JavaScript

JavaScript is a powerful language, but it has many flaws:

- the DOM can be clunky to use
- the same code doesn't always work the same way in every browser
 - code that works great in Firefox, Safari, ... will fail in IE and vice versa
- many developers work around these problems with hacks (checking if browser is IE, etc.)

Prototype framework

```
<script src="prototype.js" type="text/javascript"></script>
```

```
<script src="http://ajax.googleapis.com/ajax/libs/prototype/1.7.3.0/prototype.js" type="text/javascript"></script>
```

- the [Prototype](#) JavaScript library adds many useful features to JavaScript:
 - many useful [extensions to the DOM](#)
 - added methods to String, Array, Date, Number, Object
 - improves event-driven programming
 - many cross-browser compatibility fixes
 - makes [Ajax programming](#) easier (seen later)
- In order to use Prototype JavaScript library :
 - download Prototype library from [Prototype homepage](#)
 - link to the downloaded Prototype.js in web page or the Google hosted Prototype JavaScript library

The \$ function

```
$( "id" )
```

- returns the DOM object representing the element with the given id
- short for `document.getElementById("id")`
- often used to write more concise DOM code:

```
$( "footer" ).innerHTML = $( "username" ).value.toUpperCase();
```

Prototype's DOM element methods


<code>absolutize</code>	<code>addClassName</code>	<code>classNames</code>	<code>cleanWhitespace</code>	<code>clonePosition</code>
<code>cumulativeOffset</code>	<code>cumulativeScrollOffset</code>	<code>empty</code>	<code>extend</code>	<code>firstDescendant</code>
<code>getDimensions</code>	<code>getHeight</code>	<code>getOffsetParent</code>	<code>getStyle</code> 天天天天	<code>getWidth</code>
<code>hasClassName</code>	<code>hide</code>	<code>identify</code>	<code>insert</code>	<code>inspect</code>
<code>makeClipping</code>	<code>makePositioned</code>	<code>match</code>	<code>positionedOffset</code>	<code>readAttribute</code>
<code>recursivelyCollect</code>	<code>relativize</code>	<code>remove</code>	<code>removeClassName</code>	<code>replace</code>
<code>scrollTo</code>	<code>select</code>	<code>setOpacity</code>	<code>setStyle</code>	<code>show</code>
<code>toggle</code>	<code>toggleClassName</code>	<code>undoClipping</code>	<code>undoPositioned</code>	<code>update</code>
<code>viewportOffset</code>	<code>visible</code>	<code>wrap</code>	<code>writeAttribute</code>	

- categories: CSS classes, DOM tree traversal/manipulation, events, styles

Prototype's DOM tree traversal methods

method(s)	description
<code>ancestors</code> , <code>up</code>	elements above this one
<code>childElements</code> , <code>descendants</code> , <code>down</code>	elements below this one (not text nodes)
<code>siblings</code> , <code>next</code> , <code>nextSiblings</code> , <code>previous</code> , <code>previousSiblings</code> , <code>adjacent</code>	elements with same parent as this one (not text nodes)

```
// alter siblings of "main" that do not contain "Sun"
var sibs = $("main").siblings();
for (var i = 0; i < sibs.length; i++) {
  if (sibs[i].innerHTML.indexOf("Sun") < 0) {
    sibs[i].innerHTML += " Sunshine";
  }
}
```



- Prototype strips out the unwanted text nodes
- notice that these are methods, so you need ()

Selecting groups of DOM objects

- methods in document and other DOM objects for accessing descendents:

name	description
<code>getElementsByTagName</code>	returns array of descendents with the given tag, such as "div"
<code>getElementsByName</code>	returns array of descendents with the given name attribute (mostly useful for accessing form controls)
<code>querySelector</code> *	returns the first element that would be matched by the given CSS selector string
<code>querySelectorAll</code> *	returns an array of all elements that would be matched by the given CSS selector string

* = HTML5 : older browsers did not support `querySelectorAll` methods

Prototype's methods for selecting elements

Prototype adds methods to the document object (and all DOM element objects) for selecting groups of elements:

현재 노트에서 `querySelector`를 할 때 사용한다.

<code>select</code>	array of descendants that match given CSS selector, such as <code>"div#sidebar ul.news > li"</code>
<code>\$\$</code>	equivalent to <code>document.querySelectorAll</code>

```
var gameButtons = $("game").select("button.control");
for (var i = 0; i < gameButtons.length; i++) {
  gameButtons[i].style.color = "yellow";
}
```

The \$\$ function

```
var arrayName = $$("CSS selector");
```

```
// hide all "announcement" paragraphs in the "news" section
var paragraphs = $$("div#news p.announcement");
for (var i = 0; i < paragraphs.length; i++) {
    paragraphs[i].hide();
}
```

- \$\$ returns an array of DOM elements that match the given CSS selector
 - like \$ but returns an array instead of a single DOM object
 - a shorthand for document.select
 - essentially equivalent to document.querySelectorAll
- useful for applying an operation each one of a set of elements

Common \$\$ issues

- many students forget to write . or # in front of a class or id

```
// get all buttons with a class of "control"
var gameButtons = $$("control");
var gameButtons = $$(".control");
```

- \$\$ returns an array, not a single element; must loop over the results

```
// set all buttons with a class of "control" to have red text
$$(".control").style.color = "red";
var gameButtons = $$(".control");
for (var i = 0; i < gameButtons.length; i++) {
    gameButtons[i].style.color = "red";
}
```

- Q: Can I still select a group of elements using \$\$ even if my CSS file doesn't have any style rule for that same group? (A: Yes!)

Problems with reading/changing styles

```
<button id="clickme">Click Me</button>
```

```
window.onload = function() {  
    $("clickme").onclick = biggerFont;  
};  
function biggerFont() {  
    var size = parseInt($(".clickme").style.fontSize);  
    size += 4;  
    $(".clickMe").style.fontSize = size + "pt";  
}
```

Click Me

- `style` property lets you set any CSS style for an element
- problem: you cannot (usually) read existing styles with it

Accessing styles in Prototype

```
function biggerFont() {  
    // turn text yellow and make it bigger  
    var size = parseInt($(".clickme").getStyle("font-size"));  
    $(".clickme").style.fontSize = (size + 4) + "pt";  
}
```

Click Me

- `getStyle` function added to DOM object allows accessing existing styles
- `addClassName`, `removeClassName`, `hasClassName` manipulate CSS classes

Common bug: incorrect usage of existing styles

```
this.style.top = this.getStyle("top") + 100 + "px"; // bad!
```

- the above example computes e.g. "200px" + 100 + "px" , which would evaluate to "200px100px"
- a corrected version:

```
this.style.top = parseInt(this.getStyle("top")) + 100 + "px"; // correct
```

Setting CSS classes in Prototype

```
function highlightField() {  
    // turn text yellow and make it bigger  
    if (!$("text").hasClassName("invalid")) {  
        $("text").addClassName("highlight");  
    }  
}
```

- `addClassName`, `removeClassName`, `hasClassName` manipulate CSS classes
- similar to existing `className` DOM property, but don't have to manually split by spaces

Prototype form shortcuts

```
$( "formID" ) [ "name" ]
```

- gets parameter with given **name** from form with given **id**

```
<form id="contract">
  <input name="company">
</input>
</form>
```

```
$F( "controlID" )
```

- **\$F function** returns the **value** of a form control with the given **id**

```
$("contract")["company"].getValue();
```

```
if ( $F( "username" ).length < 4 ) {
  $( "username" ).clear();
  $( "login" ).disable();
}
```

```
$(input).getValue(); == $F(input)
```