

M.Sc. (Five Year Integrated) in Computer Science (Artificial Intelligence & Data Science)

Fifth Semester

Laboratory Record

21-805-0506: OPTIMIZATION TECHNIQUES LAB

*Submitted in partial fulfillment
of the requirements for the award of degree in
Master of Science (Five Year Integrated)
in Computer Science (Artificial Intelligence & Data Science) of
Cochin University of Science and Technology (CUSAT)
Kochi*



Submitted by

Nazal Nihad T T
(80522015)

DEPARTMENT OF COMPUTER SCIENCE
COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY (CUSAT)
KOCHI-682022

DECEMBER 2024

DEPARTMENT OF COMPUTER SCIENCE
COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY (CUSAT)
KOCHI, KERALA-682022



*This is to certify that the software laboratory record for **21-805-0506: R Programming Lab** is a record of work carried out by **Nazal Nihad T T (80522015)**, in partial fulfillment of the requirements for the award of degree in **Master of Science (Five Year Integrated) in Computer Science (Artificial Intelligence & Data Science)** of Cochin University of Science and Technology (CUSAT), Kochi. The lab record has been approved as it satisfies the academic requirements in respect of the fourth semester laboratory prescribed for the Master of Science (Five Year Integrated) in Computer Science degree.*

Faculty Member in-charge

Dr.Remya K Sasi
Assistant Professor
Department of Computer Science
CUSAT

Dr. Madhu S. Nair
Professor and Head
Department of Computer Science
CUSAT

Table of Content

S.No.	Program Title	Page No.
01	Word Analysis	1
02	String Encryption	3
03	Data Validation	4
04	Password Generator	6
05	Series Summation	8
06	Prime Checker	9
07	Twisted Fibonacci	11
08	Palindrome Checker	13
09	Data Compression	14
10	Data Reversal	15
11	Scatterplot Iris	16
12	Scatterplot MTCars	18
13	Bar Plot	19
14	Histogram MPG	20
15	Box Plot	21
16	Scatterplot Disp	22
17	Time Series	24
18	Titanic EDA	26
19	Iris EDA	31
20	Linear Regression	34
21	Graph Representation	36
22	Correlation Analysis	40
23	ANOVA Test	41
24	COVID Analysis	42
25	Boston Dataset	47

WORD ANALYSIS

AIM

Develop a program to read a paragraph of text and perform the following tasks: a. Count the total number of words. b. Calculate the average word length. c. Identify and print the longest word. d. Replace all occurrences of a specific word with another word of your choice.

PROGRAM

```
para <- 'lorem ipsum dolor hehhe siuuuuuu g hh'
words <- unlist(strsplit(para," "))
len<-0
word_len<-0
for (word in words){
  print(word)
  word_len<-word_len+nchar(word)
  len<-len+1
}

sprintf("number of words = %d" , length(words))
sprintf("avg word length= %.2f" , word_len/len)
sprintf("word with max length = %s , length = %d" , max(words),nchar(max(words)))

to_replace <- "hehhe"
replace <- "hi"
replaced <- gsub(to_replace,replace,para)
print(replaced)
```

OUTPUT

```
> para <- 'lorem ipsum dolor hehhe siuuuuuu g hh'
> words <- unlist(strsplit(para," "))
> len<-0
> word_len<-0
> for (word in words){
+   print(word)
+   word_len<-word_len+nchar(word)
+   len<-len+1
+ }
[1] "lorem"
[1] "ipsum"
[1] "dolor"
[1] "hehhe"
[1] "siuuuuuu"
[1] "g"
[1] "hh"
>
> sprintf("number of words = %d" , length(words))
[1] "number of words = 7"
> sprintf("avg word length= %.2f" , word_len/len)
[1] "avg word length= 4.43"
> sprintf("word with max length = %s , length = %d" , max(words),nchar(max(words)))
[1] "word with max length = siuuuuuu , length = 8"
>
> to_replace <- "hehhe"
> replace <- "hi"
> replaced <- gsub(to_replace,replace,para)
> print(replaced)
[1] "lorem ipsum dolor hi siuuuuuu g hh"
```

STRING ENCRYPTION

AIM

Write a program that reads a sentence from the user and encrypts it using a simple Caesar cipher. The user can specify the shift value. Implement the encryption such that only alphabetic characters are shifted, while maintaining their case.

PROGRAM

```
word <- readline(prompt = "Enter the word : ")
shift <- as.numeric(readline(prompt = "Enter the shift : "))
result<=""

for (i in seq_len(nchar(word))){
  c<-substr(word,i,i)
  if (c>="A" && c<="Z"){
    result<-paste0(result,intToUtf8((utf8ToInt(c)+shift - utf8ToInt("A"))%%26 +
    utf8ToInt("A")))
  }
  else{
    result<-paste0(result,intToUtf8((utf8ToInt(c)+shift - utf8ToInt("a"))%%26 +
    utf8ToInt("a")))
  }
}
print(result)
```

OUTPUT

```
> word <- readline(prompt = "Enter the word : ")
Enter the word : helloworld
> shift <- as.numeric(readline(prompt = "Enter the shift : "))
Enter the shift : 3
> result<=""
> for (i in seq_len(nchar(word))){
+   c<-substr(word,i,i)
+   if (c>="A" && c<="Z"){
+     result<-paste0(result,intToUtf8((utf8ToInt(c)+shift - utf8ToInt("A"))%%26 + utf8ToInt("A")))
+   }
+   else{
+     result<-paste0(result,intToUtf8((utf8ToInt(c)+shift - utf8ToInt("a"))%%26 + utf8ToInt("a")))
+   }
+ }
> print(result)
[1] "QNUUXFXAMU"
```

DATA VALIDATION AND USER INPUT

AIM

Develop a program to read student records with their names, ages, and grades. Implement validation checks: a. Ensure age is a positive integer. b. Ensure grade is a valid letter grade (A, B, C, D, F). c. Calculate and display the average age of students with valid records.

PROGRAM

```
students <- function(){
  number_students <- as.integer(readline(prompt = "Enter the number of
students: "))

  ages <- numeric()
  grades <- character()

  grade_list <- c('A', 'B', 'C', 'D', 'F')
  for (i in 1:number_students){
    name <- readline(prompt = sprintf("Enter name of
student %d: ", i))

    while (TRUE) {
      age <- as.integer(readline(prompt = sprintf("Enter the
age of student %d: ", i)))
      if (age > 0 ){
        ages <- c(ages, age)
        break
      }
      else{
        cat("Invalid age, please enter a positive integer..")
      }
    }

    while (TRUE) {
      grade <- readline(prompt = sprintf("Enter the grade of
student %d: ", i))
      if (grade %in% grade_list){
        grades <- c(grades, grade)
        break
      }
      else{
```

```
        cat("Invalid grade, please enter A, B, C, D or F as  
        the grade..")  
    }  
}  
  
avg_age = mean(ages)  
cat("The average age is: ", avg_age)  
}
```

```
students()
```

OUTPUT

```
Enter the number of students: 2  
Enter name of student 1: Fe  
Enter the age of student 1: 0  
Invalid age, please enter a positive integer..  
Enter the age of student 1: 9  
Enter the grade of student 1: a  
Invalid grade, please enter A, B, C, D or F as the grade..  
Enter the grade of student 1: A  
Enter name of student 2: SO4  
Enter the age of student 2: -3  
Invalid age, please enter a positive integer..  
Enter the age of student 2: 10  
Enter the grade of student 2: D  
The average age is: 9.5
```


PASSWORD GENERATOR

AIM

Write a program to generate a random password for a user. The password should include a mix of uppercase letters, lowercase letters, digits, and special characters. Allow the user to specify the length of the password.

PROGRAM

```
generate<-function(pass_length){
  upper<-unlist(strsplit("ABCDEFGHIJKLMNOPQRSTUVWXYZ",split = ""))
  lower<-unlist(strsplit(tolower("ABCDEFGHIJKLMNOPQRSTUVWXYZ"),split = ""))
  nums<-unlist(strsplit("1234567890",split=""))
  special_chars<-unlist(strsplit("!@#$%^&*()-_+={}:;<[]>,.?\"",split=""))

  if(pass_length<4){
    cat("make sure password length is greater than 4")
    return(NA)
  }
  all<-c(upper,lower,nums,special_chars)
  password<-c(
    sample(upper,1),
    sample(lower,1),
    sample(nums,1),
    sample(special_chars,1)
  )
  len<-pass_length-4
  password<-c(password,sample(all,len,replace = TRUE))
  password<-sample(password)
  password<-paste(password,collapse = "")
  return(password)
}

cat("Enter password length : ")
password_length<-as.numeric(readline())

if (is.na(password_length) || password_length < 4) {
  cat("invalid input. Please enter a number greater than or equal to 4.\n")
} else {
  generated_password <- generate(password_length)
```

```
    if (!is.na(generated_password)) {  
      cat("Generated Password: ", generated_password, "\n")  
    }  
  }  
}
```

OUTPUT

```
Enter password length : > password_length<-as.numeric(readline())  
8  
> if (is.na(password_length) || password_length < 4) {  
+   cat("invalid input. Please enter a number greater than or equal to 4.\n")  
+ } else {  
+   generated_password <- generate(password_length)  
+   if (!is.na(generated_password)) {  
+     cat("Generated Password: ", generated_password, "\n")  
+   }  
+ }  
Generated Password:  s3xNqOY)
```

SERIES SUMMATION

AIM

Develop a program to calculate the sum of the series: $1 - \frac{2}{3} + \frac{3}{5} - \frac{4}{7} + \dots$ up to a specified number of terms. Allow the user to input the number of terms in the series.

PROGRAM

```
series_sum<-function(n){  
  sum<-0  
  i<-1  
  
  for ( j in 1:n){  
    next_term<-i*(j/(2*j-1))  
    sum<-sum+next_term  
    i<- -i  
  }  
  return(sum)  
}  
  
cat("Enter n terms : ")  
n<-as.integer(readline())  
  
if(is.na(n) || n<=0){  
  cat("entr valid input : ")  
}else{  
  sum<-series_sum(n)  
  cat("sum of series upto ",n," terms is : ",sum)  
}
```

OUTPUT

```
Enter the number of terms: 8  
The series is: 1 - 2/3 + 3/5 - 4/7 + 5/9 - 6/11 + 7/13 - 8/15  
The sum of the series is: 0.377134
```

PRIME NUMBER CHECKER

AIM

Write a program to check whether a given number is prime or not. Implement this using both loops and functions. Additionally, allow the user to input a range and identify all prime numbers within that range.

PROGRAM

```
prime <- function(n) {  
  if (n <= 1) {  
    return(FALSE)  
  }  
  if (n == 2){  
    return(TRUE)  
  }  
  for (i in 2:floor(sqrt(n))) {  
    if (n %% i == 0) {  
      return(FALSE)  
    }  
  }  
  return(TRUE)  
}  
  
main <- function(){  
  while (TRUE) {  
    cat("\n\n1. Check if the given number is prime.  
\n2. Print all prime numbers in a given range. \n3. Quit.")  
    choice <- as.integer(readline(prompt = "Enter your choice: "))  
    if (choice == 1){  
      n <- as.integer(readline(prompt = "Enter the integer to check: "))  
      if (prime(n))  
        cat(n, "is a prime number.")  
      else  
        cat(n, "is not a prime number.")  
    }  
    else if (choice == 2){  
      initial <- as.integer(readline(prompt = "Enter the  
initial number for the range: "))  
      end <- as.integer(readline(prompt = "Enter the ending  
number for the range: "))
```

```
p <- c()
for ( i in initial:end){
  if (prime(i))
    p <- c(p, i)
}
if (length(p) == 0)
  cat("No prime numbers exist in the given range..")
else
  cat("The prime numbers in the given range are:\n", p)
}
else if (choice == 3)
  break
else
  cat("Please enter a valid option.")
}
}
main()
```

OUTPUT

1. Check if the given number is prime.
2. Print all prime numbers in a given range.
3. Quit.

Enter your choice: 1

Enter the integer to check: 56

56 is not a prime number.

1. Check if the given number is prime.
2. Print all prime numbers in a given range.
3. Quit.

Enter your choice: 1

Enter the integer to check: 13

13 is a prime number.

1. Check if the given number is prime.
2. Print all prime numbers in a given range.
3. Quit.

Enter your choice: 2

Enter the initial number for the range: 100

Enter the ending number for the range: 180

The prime numbers in the given range are:

101 103 107 109 113 127 131 137 139 149 151 157 163 167 173 179

1. Check if the given number is prime.
2. Print all prime numbers in a given range.
3. Quit.

Enter your choice: 3

> |

FIBONACCI SERIES WITH A TWIST

AIM

Develop a program to generate the Fibonacci series, but with a twist. Allow the user to input the number of terms and generate the series where each term is the sum of the last three terms.

PROGRAM

```
mod_fib<-function(n){
  if(n<=0){
    return(c())
  }
  else if(n == 1){
    return(c(0))
  }
  else if(n==2){
    return(c(0,1))
  }

  nums<-c(0,1,1)
  for (i in 4:n){
    num_next<-nums[i-1]+nums[i-2]+nums[i-3]
    nums<-c(nums,num_next)
  }

  return(nums)
}

cat("Enter the number of terms: ")
n <- as.integer(readline())

if (is.na(n) || n <= 0) {
  cat("invalid input, enter a positive integer.\n")
} else {
  nums <- mod_fib(n)

  cat(" modified Fibonacci series with", n, "terms is:\n", paste(nums, collapse = ", 
"), "\n")
}
```

OUTPUT

```
Enter the number of terms: 13
```

```
The series is:
```

```
0, 1, 2, 3, 6, 11, 20, 37, 68, 125, 230, 423, 778
```

PALINDROME CHECKER

AIM

Write a program that reads a string and checks if it's a palindrome. A palindrome is a string that reads the same forwards and backwards, ignoring spaces and punctuation.

PROGRAM

```
#palindrome checker
check_palindrome<-function(s){
  changed_s<-tolower(gsub("[^a-zA-Z0-9]", "", s))
  string_length<-nchar(changed_s)
  rev_s <- paste(rev(strsplit(changed_s, NULL)[[1]]), collapse="")
  return(changed_s==rev_s)
}

cat("enter a string to check : ")
input <- readline()

if (check_palindrome(input)) {
  cat(input, "is a palindrome.\n")
} else {
  cat(input, "is not a palindrome.\n")
}
```

OUTPUT

```
enter a string to check : > input <- readline()
malayalam
> if (check_palindrome(input)) {
+   cat(input, "is a palindrome.\n")
+ } else {
+   cat(input, "is not a palindrome.\n")
+ }
malayalam is a palindrome.
```


DATA COMPRESSION

AIM

Design a program to read a string and compress it using run-length encoding. In run-length encoding, consecutive repeated characters are replaced with a single character followed by the count of occurrences.

PROGRAM

```
rle<-function(s){
  encoded<-" "
  n<-nchar(s)

  i<-1
  while(i<=n){
    current<-substr(s,i,i)
    flag<-1

    while((i+flag<=n) && (substr(s,i+flag,i+flag)==current)){
      flag<-flag+1
    }
    encoded<-paste0(encoded,current,flag)
    i<-i+flag
  }
  return(encoded)
}

cat("enter a string to compress: ")
s <- readline()

compressed <- rle(s)

cat("Compressed string:", compressed, "\n")
```

OUTPUT

```
enter a string to compress: > s <- readline()
baaabbbuuuummmooonnnnn
> compressed <- rle(s)
>
> cat("Compressed string:", compressed, "\n")
Compressed string: b1a3b3u4m3o3n5
```

DATA REVERSAL

AIM

Write a program to reverse the order of elements in a given list. Implement this without using any built-in functions or loops

PROGRAM

```
#data reversal wihtout using functions or loops

reversal <- function(input){

  if (length(input) <= 1)
    return(input)

  return (c(reversal(input[-1]), input[1]))
}

main <- function(){

  input <- readline(prompt = "Enter space-separated elements: ")
  input <- unlist(strsplit(input, " "))

  reversed <- reversal(input)

  cat("The reversed data is: ", paste(reversed, collapse = " "))
}

main()
```

OUTPUT

```
Enter space-separated elements: 1 2 3 4 5 hehe cat
The reversed data is:  cat hehe 5 4 3 2 1
> |
```

SCATTERPLOT IRIS

AIM

Create a scatterplot of the Sepal.Length and Petal.Length variables in the iris dataset using the plot function? Add appropriate labels and title to the plot. Save the plot as a high-resolution image file.


PROGRAM

```
data("iris")

plot(iris$Sepal.Length, iris$Petal.Length,
     main = "Sepal Length vs Petal Length",
     xlab = "Sepal Length ",
     ylab = "Petal Length ",
     pch = 19,
     col = "blue")

png(filename = "scatterplot_iris.png", width = 1920, height = 1080, res = 300)
```

OUTPUT



SCATTERPLOT MTCARS

AIM

Create a scatterplot of the mpg and disp variables in the mtcars dataset. Use different colors to represent the cyl variable and add a smooth line to show the trend. Add appropriate labels, title, and legend to the plot


PROGRAM

```
data("mtcars")

plot(mtcars$mpg,mtcars$disp,xlab = "MPG",ylab = "DISP",col =
as.factor(mtcars$cyl),pch=19)
lines(loess.smooth(mtcars$mpg,mtcars$disp), col = "yellow", lwd =2)

legend("topright", legend = levels(as.factor(mtcars$cyl)),
      col = 1:3, pch = 19, title = "Cylinders")
```

OUTPUT



BAR PLOT

AIM

Create a bar plot of the number of cylinders (cyl) in the mtcars dataset. Use different colors to represent the transmission type (am). Add appropriate title, labels, and legend to the plot.


PROGRAM

```
data("mtcars")

cyl_am <- table(mtcars$cyl, mtcars$am)

#bar plot
barplot(cyl_am,
        beside = TRUE,
        col = c("red", "blue", "green"),
        legend = rownames(cyl_am),
        xlab = "Transmission (0 = Automatic, 1 = Manual)",
        ylab = "Num Cars", # Y-axis label
        main = "Num Cylinders by Transmission Type",
        args.legend = list(title = "Number of Cylinders"))
```

OUTPUT



HISTOGRAM OF MPG MTCARS

AIM

Create a histogram of the miles per gallon (mpg) in the mtcars dataset. Use different shades of blue to represent the frequency of each bin. Add appropriate title and labels to the plot. Calculate and display the mean and standard deviation of mpg on the plot.

PROGRAM


```
data("mtcars")

hist(mtcars$mpg,col = colorRampPalette(c("lightblue", "darkblue"))(10),
     xlab = "MPG",main = "Mile per Gallon ")

mean_mpg<-mean(mtcars$mpg)
std_mpg<-sd(mtcars$mpg)

text(max(mtcars$mpg) - 5, 10, paste("Mean =", round(mean_mpg, 2)), col = "green", pos = 4)
text(max(mtcars$mpg) - 5, 9, paste("SD =", round(std_mpg, 2)), col = "red", pos = 4)
```

OUTPUT



BOX PLOT

AIM


Create a box plot of the horsepower (hp) in the mtcars dataset. Use different shapes to represent the number of gears (gear). Add appropriate title, labels, and legend to the plot. Identify and label any outliers on the plot.

PROGRAM

```
data("mtcars")
boxplot_hp<-boxplot(mtcars$hp~mtcars$gear,
                    main = "Horsepower by Number of Gears",
                    xlab = "Num of Gears",
                    ylab = "Horsepower",
                    col = "blue",
                    pch = 19)
legend("topright",legend = levels(as.factor(mtcars$gear)),pch=19,title = "num gears")

outliers <- boxplot.stats(mtcars$hp ~ as.factor(mtcars$gear))$out
outlier_indices <- which(mtcars$hp %in% outliers)
text(rep(1:3, each = length(outliers)), outliers, labels = outlier_indices, pos = 3,
     col = "red", cex = 0.8)
```

OUTPUT



SCATTERPLOT OF DISP MTCARS

AIM

Create a scatter plot of the displacement (disp) versus the weight (wt) in the mtcars dataset. Use different colors and sizes to represent the number of carburetors (carb). Add appropriate title, labels, and legend to the plot. Add a smooth line to show the trend of the relationship

PROGRAM

```
data("mtcars")


colors <- rainbow(length(unique(mtcars$carb)))

plot(mtcars$disp, mtcars$wt,
      col = colors[as.factor(mtcars$carb)],
      pch = 19,
      xlab = "Displacement",
      ylab = "Weight ",
      main = "Displacement vs Weight by Num Carburetors")

lines(loess.smooth(mtcars$disp, mtcars$wt), col = "black", lwd = 2)

legend("topleft",
      legend = paste(unique(mtcars$carb)),
      col = colors,
      pch = 19,
      horiz=TRUE,
      title = "Number of Carburetors")
```

OUTPUT



TIME SERIES

AIM

Develop an R program to create a time series plot using real-world data.
(<https://www.kaggle.com/datasets/niketchauhan/covid-19-time-series-data>)

PROGRAM

```
library(ggplot2)
library(dplyr)

data <- read.csv("D:/sem5/R/Lab2/time-series-19-covid-combined.csv")

head(data)


data$Date <- as.Date(data$Date, format="%Y-%m-%d")

daily_data <- data %>%
  group_by(Date) %>%
  summarise(Confirmed = sum(Confirmed, na.rm = TRUE))

head(daily_data)

ggplot(daily_data, aes(x=Date, y=Confirmed)) +
  geom_line(color="blue") +
  labs(title="COVID-19 Confirmed Cases Over Time",
       x="Date",
       y="Number of Confirmed Cases") +
  theme_minimal()
```

OUTPUT



TITANIC EDA

AIM

Perform EDA on "Titanic Dataset". You are given the Titanic dataset, which contains information about passengers on the Titanic, including their survival status, age, class, and gender. a)plot the histogram of Number of parents and children of the passenger aboard(parch). b)Perform a detailed EDA, including advanced statistical analysis, to explore factors influencing survival rates. c)Create a customized box plot to visualize the age distribution of survivors and non-survivors.

PROGRAM

```
library(ggplot2)
library(dplyr)
library(summarytools)

# titanic dataset
titanic <- read.csv("https://raw.githubusercontent.com/
datasciencedojo/datasets/master/titanic.csv")

head(titanic)

# histogram of the number of parents and children aboard (parch)
ggplot(titanic, aes(x = Parch)) +
  geom_histogram(binwidth = 1, fill = "olivedrab", color = "black") +
  labs(title = "Number of Parents and Children Aboard (Parch)",
    x = "Parch", y = "Frequency") + theme_minimal()

# summary of the dataset
summary(titanic)
dfSummary(titanic)

# missing values
colSums(is.na(titanic))



# survival rate by gender
titanic %>%
  group_by(Sex) %>%
  summarise(Survived_Rate = mean(Survived, na.rm = TRUE) * 100) %>%
  ggplot(aes(x = Sex, y = Survived_Rate, fill = Sex)) +
  geom_bar(stat = "identity", color = "black") +
```



```
labs(title = "Survival Rate by Gender", x = "Gender",
y = "Survival Rate (%)") + theme_minimal()


# survival rate by passenger class
titanic %>%
  group_by(Pclass) %>%
  summarise(Survived_Rate = mean(Survived, na.rm = TRUE) * 100) %>%
  ggplot(aes(x = as.factor(Pclass), y = Survived_Rate, fill =
as.factor(Pclass))) + geom_bar(stat = "identity", color = "black") +
  labs(title = "Survival Rate by Passenger Class", x =
"Passenger Class", y = "Survival Rate (%)") + theme_minimal()

# age distribution by survival status
ggplot(titanic, aes(x = Age, fill = as.factor(Survived))) +
  geom_histogram(binwidth = 5, alpha = 0.7, position = "identity") +
  scale_fill_manual(values = c("lightcoral", "lightgreen"),
labels = c("Did Not Survive", "Survived")) + labs(title = "Age
Distribution by Survival Status", x = "Age", y = "Count") +
  theme_minimal()

# box plot of age by survival status
ggplot(titanic, aes(x = as.factor(Survived), y = Age,
  fill = as.factor(Survived))) +
  geom_boxplot(outlier.color = "peru", outlier.shape = 16,
outlier.size = 2, notch = TRUE) +
  scale_fill_manual(values = c("lightcoral", "lightgreen"),
labels = c("Did Not Survive", "Survived")) +
  labs(title = "Age Distribution of Survivors and Non-Survivors",
x = "Survival Status", y = "Age") +
  theme_minimal() +
  theme(legend.position = "none")
```

OUTPUT





IRIS EDA

AIM

EDA on "Iris Dataset" a) For the Iris dataset, which contains measurements of various iris flowers, conduct an EDA. a. Determine if there are statistically significant differences in sepal lengths between different species using a suitable statistical test. b. Create a pair plot to visualize the relationships between all variables.

PROGRAM

```
library(ggplot2)
library(dplyr)

data(iris)

head(iris)

# box plot to see the distribution of sepal length for each species
ggplot(iris, aes(x = Species, y = Sepal.Length, fill = Species)) +
  geom_boxplot() +
  labs(title = "Sepal Length by Species", x = "Species",
       y = "Sepal Length") + theme_minimal()



# ANOVA to see if there are significant differences in
# Sepal.Length across the species
anova_result <- aov(Sepal.Length ~ Species, data = iris)
summary(anova_result)

# if p-value from the ANOVA summary is less than 0.05,
# it suggests significant differences
# between species in terms of Sepal.Length.

# if ANOVA is significant, we use a Tukey test to see which
# species differ in Sepal Length
if(summary(anova_result)[[1]][["Pr(>F)"]][1] < 0.05) {
  post_hoc <- TukeyHSD(anova_result)
  print(post_hoc)
}

# scatter plots between each pair of variables, colored by species
pairs(iris[1:4], col = iris$Species, main = "Pair Plot of Iris Dataset")
```

OUTPUT



Tukey multiple comparisons of means
95% family-wise confidence level

Fit: aov(formula = Sepal.Length ~ Species, data = iris)

\$Species

	diff	lwr	upr	p adj
versicolor-setosa	0.930	0.6862273	1.1737727	0
virginica-setosa	1.582	1.3382273	1.8257727	0
virginica-versicolor	0.652	0.4082273	0.8957727	0

LINEAR REGRESSION

AIM

Suppose you have a dataset containing information about house prices (dependent variable, denoted as price) and the size of the houses (in square feet, independent variable, denoted as size). You want to build a linear regression model to predict house prices based on their size. Write an R code snippet to perform the following steps:

1. Load the dataset Download the dataset from <https://www.kaggle.com/competitions/house-prices-advanced-regression-techniques>
2. Fit a simple linear regression model: Use price as the dependent variable and size as the independent variable.
3. Calculate regression coefficients: Determine the slope and intercept of the regression line.
4. Plot the regression line: Overlay the regression line on the scatter plot of the data points.

PROGRAM

```
#House pricing

library(ggplot2)


path <- "D:/sem5/R/lab3/Q1/train.csv"
data <- read.csv(path)

model <- lm(SalePrice ~ GrLivArea, data = data)

slope <- coef(model)[2]
intercept <- coef(model)[1]

cat("Slope:", slope, "\n")
cat("Intercept:", intercept, "\n")

ggplot(data, aes(x = GrLivArea, y = SalePrice)) +
  geom_point(alpha = 0.5) +
  geom_abline(slope = slope, intercept = intercept, col = 'red',
              linewidth = 1) + labs(title = "Linear Regression of House Prices
vs Size", x = "Size ", y = "Price (SalePrice)") +
  theme_minimal()
```

OUTPUT

```
> cat("Slope:", slope, "\n")
Slope: 107.1304
> cat("Intercept:", intercept, "\n")
Intercept: 18569.03
```

GRAPH REPRESENTATION

AIM

Graph

1. Create an adjacency list representation for a given undirected graph
2. Implement a function to add an edge between two vertices in the graph
3. Write an R function to perform DFS traversal on a graph starting from a specific vertex

References <https://r.igraph.org/index.html>

PROGRAM

```
# Graph

# adjacency list
create_adjacency_list <- function(edges) {
  adj_list <- list()

  # adjacency list for each vertex in edges
  for (edge in edges) {
    v1 <- edge[1]
    v2 <- edge[2]

    # adjacency lists for vertex if they don't exist
    if (is.null(adj_list[[as.character(v1)]]))
      adj_list[[as.character(v1)]] <- c()
    if (is.null(adj_list[[as.character(v2)]]))
      adj_list[[as.character(v2)]] <- c()

    # add edges
    adj_list[[as.character(v1)]] <- c(adj_list[[as.character(v1)]], v2)
    adj_list[[as.character(v2)]] <- c(adj_list[[as.character(v2)]], v1)
  }
  return(adj_list)
}

# add an edge between two vertices
add_edge <- function(adj_list, v1, v2) {
  if (is.null(adj_list[[as.character(v1)]]))
```

```
adj_list[[as.character(v1)]] <- c()
if (is.null(adj_list[[as.character(v2)]]))
adj_list[[as.character(v2)]] <- c()

adj_list[[as.character(v1)]] <- c(adj_list[[as.character(v1)]], v2)
adj_list[[as.character(v2)]] <- c(adj_list[[as.character(v2)]], v1)
return(adj_list)
}

# DFS traversal
dfs_traversal <- function(adj_list, start, visited = NULL) {
  # Convert start to character to match list indexing
  start <- as.character(start)

  # visited
  vertices in adj_list
  if (is.null(visited)) visited <- setNames(rep(FALSE,
length(adj_list)), names(adj_list))

  visited[start] <- TRUE
  cat(start, " ")

  for (neighbor in adj_list[[start]]) {
    neighbor <- as.character(neighbor)
    # Ensure neighbor is a character for indexing
    if (!visited[neighbor]) {
      visited <- dfs_traversal(adj_list, neighbor, visited)
    }
  }
  return(visited)
}

edges <- list(
  c(1, 2), c(1, 5), c(2, 3), c(2, 4),
  c(5, 6), c(6, 7), c(7, 8), c(8, 9),
  c(3, 9), c(3, 10), c(10, 11), c(11, 12),
  c(12, 1))

adj_list <- create_adjacency_list(edges)
print("Initial adjacency list:")
print(adj_list)
```



```
adj_list <- add_edge(adj_list, 9, 12)
print("Adjacency list after adding edge (9, 12):")
print(adj_list)

cat("DFS traversal starting from vertex 1:\n")
visited <- dfs_traversal(adj_list, 1)
```

OUTPUT

```
[1] "Initial adjacency list:"
> print(adj_list)
$`1`
[1] 2 5 12

$`2`
[1] 1 3 4

$`5`
[1] 1 6

$`3`
[1] 2 9 10

$`4`
[1] 2

$`6`
[1] 5 7

$`7`
[1] 6 8

$`8`
[1] 7 9

$`9`
[1] 8 3

$`10`
[1] 3 11

$`11`
[1] 10 12

$`12`
[1] 11 1
```

```
[1] "Adjacency list after adding edge (9, 12):"  
> print(adj_list)  
$`1`  
[1] 2 5 12  
  
$`2`  
[1] 1 3 4  
  
$`5`  
[1] 1 6  
  
$`3`  
[1] 2 9 10  
  
$`4`  
[1] 2  
  
$`6`  
[1] 5 7  
  
$`7`  
[1] 6 8  
  
$`8`  
[1] 7 9  
  
$`9`  
[1] 8 3 12  
  
$`10`  
[1] 3 11  
  
$`11`  
[1] 10 12  
  
$`12`  
[1] 11 1 9
```

```
DFS traversal starting from vertex 1:  
> visited <- dfs_traversal(adj_list, 1)  
1 2 3 9 8 7 6 5 12 11 10 4
```

CORRELATION ANALYSIS

AIM

Suppose we have a dataset of motor trend car road tests (mtcars). The dataset contains information about 32 car brands and 11 attributes. We want to investigate the correlation between the horsepower (hp) and miles per gallon (mpg). Perform a Pearson correlation test to analyze this relationship.

PROGRAM

```
data(mtcars)

head(mtcars)

# pearson correlation test between hp and mpg
hp_mpg_correlation <- cor.test(mtcars$hp, mtcars$mpg, method = "pearson")

print(hp_mpg_correlation)
```

OUTPUT

```
Pearson's product-moment correlation

data:  mtcars$hp and mtcars$mpg
t = -6.7424, df = 30, p-value = 1.788e-07
alternative hypothesis: true correlation is not equal to 0
95 percent confidence interval:
 -0.8852686 -0.5860994
sample estimates:
      cor 
-0.7761684
```

ANOVA TEST

AIM

Suppose we have a dataset of motor trend car road tests (mtcars). The dataset contains information about 32 car brands and 11 attributes. We want to investigate whether there are any significant variations in the average displacement (disp) across different gear types (gear). Perform a one-way ANOVA test to analyze this

PROGRAM

```
data(mtcars)

# convert the gear col to a factor as a categorical variable
mtcars$gear <- as.factor(mtcars$gear)

# one-way ANOVA in disp across different gear categories
gear_disp_anova <- aov(disp ~ gear, data = mtcars)

summary(gear_disp_anova)
```

OUTPUT

```
          Df Sum Sq Mean Sq F value    Pr(>F)
gear         2 280221   140110    20.73 2.56e-06 ***
Residuals    29 195964     6757
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

COVID ANALYSIS

AIM

We want to investigate the behavior of the total positive COVID-19 cases weekly from 22 January 2020 to 15 December 2020 in India. Perform the following tasks:

Data set link <https://raw.githubusercontent.com/datasets/covid-19/master/data/time-series-19-covid-combined.csv>

1. Univariate Time Series Analysis:

- Create a time series object for the total positive COVID-19 cases
- Visualize the time series data using a line chart.

2. Multivariate Time Series Analysis:

- Also, consider the total deaths from COVID-19 during the same period.
- Create a multivariate time series object that includes both the total positive cases and total deaths.
- Plot both series on a single chart.

3. Time Series Forecasting:

- Use the `auto.arima()` function from the forecast library to fit an ARIMA model to the total positive cases.
- Forecast the next 5 data points.
- Plot the forecasted values.

PROGRAM

```
library(forecast)
library(ggplot2)
library(dplyr)

covid_data <- read.csv("https://raw.githubusercontent.com/datasets/covid-
19/master/data/time-series-19-covid-combined.csv")

# data range
india_covid <- covid_data %>%
  filter(Country.Region == "India" & Date >= "2020-01-22" & Date
    <= "2020-12-15")
```

```
india_covid$Date <- as.Date(india_covid$Date)

# weekly data summary
weekly_data <- india_covid %>%
  group_by(Week = format(Date, "%Y-%U")) %>%
  summarise(Confirmed = max(Confirmed), Deaths = max(Deaths)) %>%
  ungroup()

# time series
total_cases_ts <- ts(weekly_data$Confirmed, start = c(2020, 4),
frequency = 52)

# plot total covid cases
ggplot(weekly_data, aes(x = as.Date(paste0(Week, "-1"),
"%Y-%U-%u"), y = Confirmed)) +
  geom_line(color = "slategrey", size = 1) +
  labs(title = "Total COVID-19 Cases in India (Weekly, 2020)",
x = "Date", y = "Total Cases") +
  theme_minimal() +
  theme(plot.title = element_text(hjust = 0.5))

# multivariate
total_deaths_ts <- ts(weekly_data$Deaths, start = c(2020, 4)
, frequency = 52)
multivariate_ts <- ts(cbind(total_cases_ts, total_deaths_ts))

multivariate_df <- data.frame(
  Date = as.Date(paste0(weekly_data$Week, "-1"), "%Y-%U-%u"),
  Cases = weekly_data$Confirmed,
  Deaths = weekly_data$Deaths
)

ggplot(multivariate_df, aes(x = Date)) +
  geom_line(aes(y = Cases, color = "Total Cases"), size = 1) +
  geom_line(aes(y = Deaths, color = "Total Deaths"), size = 1) +
  labs(title = "COVID-19 Cases and Deaths in India (Weekly, 2020)",
x = "Date", y = "Count") +
  scale_color_manual(values = c("Total Cases" = "slategrey",
"Total Deaths" = "olivedrab")) +
  theme_minimal() +
  theme(plot.title = element_text(hjust = 0.5),
```

```
    legend.title = element_blank())



# forecast - ARIMA
arima_model <- auto.arima(total_cases_ts)


# values for next 5 weeks
forecasted_values <- forecast(arima_model, h = 5)

forecast_df <- data.frame(
  Date = seq(as.Date("2020-12-15"), by = "week", length.out = 5),
  Forecast = forecasted_values$mean,
  Lower = forecasted_values$lower[,2],
  Upper = forecasted_values$upper[,2]
)

ggplot() +
  geom_line(data = multivariate_df, aes(x = Date, y = Cases),
    color = "slategrey", size = 1) +
  geom_line(data = forecast_df, aes(x = Date, y = Forecast),
    color = "olivedrab", size = 1, linetype = "dashed") +
  labs(title = "Forecast of COVID-19 Cases in India (Weekly)",
    x = "Date", y = "Total Cases") +
  theme_minimal() +
  theme(plot.title = element_text(hjust = 0.5)) +
  geom_ribbon(data = forecast_df, aes(x = Date, ymin = Lower,
    ymax = Upper),
    fill = "lightblue", alpha = 0.4) # Add confidence interval

print(forecasted_values$mean)
```

OUTPUT



Time Series:

Start = c(2020, 52)

End = c(2021, 4)

Frequency = 52

[1] 9892690 9755875 9537579 9250807 8906490

BOSTON DATASET

AIM

The Boston data set comes from the real estate industry in Boston (US). This is a regression problem. The data has 506 rows and 14 columns.

1. Perform data exploration and visualization using R programming.
2. Perform Regression analysis on the dataset.
3. Predict the median value of owner occupied homes.

<https://www.kaggle.com/code/prasadperera/the-boston-housing-dataset>

PROGRAM

```
install.packages("MASS")
install.packages("ggplot2")
install.packages("corrplot")

library(MASS)
library(ggplot2)
library(corrplot)

# load dataset
data("Boston")
head(Boston)

# data exploration
str(Boston)
summary(Boston)

# missing values
sum(is.na(Boston))

# data visualization - hist for freq dist of all
for (variable in names(Boston)) {
  hist(Boston[[variable]], main = paste("Distribution of", variable),
       col = "lightblue", xlab = variable)
}

# - scatter plot for relationship: each vs medv
for (variable in names(Boston)[-14]) { # take out medv (14th column)
```

```
plot(Boston[[variable]], Boston$medv,
      xlab = variable, ylab = "Median Value (medv)",
      main = paste(variable, "vs medv"))
}

# - correlation matrix
correlation_matrix <- cor(Boston)
corrplot(correlation_matrix, method = "color", tl.cex = 0.8)

# regression analysis
linear_model <- lm(medv ~ ., data = Boston)
summary(linear_model)



# Prediction
predicted_values <- predict(linear_model, newdata = Boston)



# actual vs predicted
results <- data.frame(Actual = Boston$medv, Predicted = predicted_values)
head(results)



# model eval
mse <- mean((results$Actual - results$Predicted)^2)
cat("Mean Squared Error (MSE):", mse, "\n")
r_squared <- summary(linear_model)$r.squared
cat("R-squared:", r_squared, "\n")



# plot predictions
ggplot(results, aes(x = Actual, y = Predicted)) +
  geom_point(color = "olivedrab") +
  geom_abline(intercept = 0, slope = 1, color = "peru",
             linetype = "dashed") +
  labs(title = "Actual vs Predicted Median Home Values",
       x = "Actual Median Value",
       y = "Predicted Median Value") +
  theme_minimal()
```



OUTPUT















Distribution of age**Distribution of dis**















crim vs medv**zn vs medv**














Residual standard error: 4.745 on 492 degrees of freedom
Multiple R-squared: 0.7406, Adjusted R-squared: 0.7338
F-statistic: 108.1 on 13 and 492 DF, p-value: $< 2.2e-16$

	Actual	Predicted
1	24.0	30.00384
2	21.6	25.02556
3	34.7	30.56760
4	33.4	28.60704
5	36.2	27.94352
6	28.7	25.25628

Actual vs Predicted Median Home Values

