




SILVER and WHITE version.



SWAROVSKI version.

Range of axial extractors with airflow rates of 85 m³/h, for connection to 100 mm diameter circular ducting.

Motor mounted on silent-elastic-blocks which absorb the vibrations and allow offering very low noise level. All the fans are manufactured from injection moulded plastic, fitted with automatic shutter and single phase 230V-50Hz, class B low consumption motor equipped with thermal overload protection. All the fans are class II insulation, IP45 rated and suitable to operate with air temperature up to 40°C.



Validated mark of approval
noise abatement society



**WATER
PROTECTED!**



LOW NOISE!



**ENERGY
EFFICIENT!**




Back draft shutter

To prevent air entry and limit heat leakage when the extractor is not operating. It opens due to the pressure of the air.



Silent-blocks

Motor mounted on "Silent-elastic-block" to prevent vibration and noise transmission.



SILENT-100 DESIGN



USUAL EXTRACTOR

Quiet operation

In usual extract fans the vibrations are transmitted to the surrounding areas while in SILENT extractor fans the vibrations are absorbed by the Silent Blocks.

BATHROOM EXTRACT FANS SILENT-100 DESIGN 3C Series



SWAROVSKI versions: Elegant and innovative design.
Supplied with a front grille with a swarovski bar.



WHITE



CHAMPAGNE



SILVER



Models 3C



Black

Grey

Champagne

Gold



Ivory

Red

Marble white

Marble black




Interchangeable colour bars

Interchangeable colour bars. 4 colours to match the decor of the room: blue, red, green and yellow.



SILENT-100 CZ DESIGN 4C: Different colours available.

4C models incorporate 5 interchangeable colour bars (transparent, blue, green, red and yellow).




BARCELONA

MODEL FEATURES

	CZ DESIGN 3C	CRZ DESIGN 3C	CHZ DESIGN 3C
PILOT LIGHT	•	•	•
BACKDRAFT SHUTTER	•	•	•
ADJUSTABLE RUN-ON-TIMER (1-30MIN)		•	•
ADJUSTABLE HUMIDISTAT			•
BALL BEARINGS	•	•	•
KIT BAR LIGHTS 4 COLOURS	•	•	•
WIRING DIAGRAM*	2, 3	4, 5	1, 4

* See section of Wiring Diagrams.

PERFORMANCE CURVE




TECHNICAL CHARACTERISTICS

Model	Absorbed power at free discharge (W)	Voltage (V) 50 Hz	Sound pressure level* (dB(A))	Airflow at free discharge (m³/h)	Insulation/ IP	Ø duct (mm)	Weight (kg)
SILENT-100 DESIGN 3C	8	230	26,5	85	Class II / IP45	100	0,65
KIT SILENT-100 DESIGN 12V** 3C	12	12	26,5	80	Class III / IP57	100	0,65

* Sound pressure level measured at 3 m at free air conditions.

** Delivered with CT-12/14 transformer.

DIMENSIONS (mm)



ACCESSORIES



GSA-M0 100
Flexible aluminium
ducting.



GRA-75
Aluminium exterior
grille.




**FIXED SHUTTER
AND TELESCOPIC
DUCT**
(200 to 420 mm).



CX-80/125
Worm drive ducting
clip.



PER-100W
Back draft shutter.



WINDOW KIT 100
Accessory to allow
SILENT-100 in a
window.

MODEL FEATURES

	CZ DESIGN 3C	CRZ DESIGN 3C	CHZ DESIGN 3C
PILOT LIGHT	•	•	•
BACKDRAFT SHUTTER	•	•	•
ADJUSTABLE RUN-ON-TIMER (1-30MIN)		•	•
ADJUSTABLE HUMIDISTAT			•
BALL BEARINGS	•	•	•
SILVER FRONT COVER	•	•	•
WIRING DIAGRAM*	2, 3	4, 5	1, 4


* See section of Wiring Diagrams.

TECHNICAL CHARACTERISTICS


Model	Maximum absorbed power (W)	Voltage (V) 50 Hz	Sound pressure level* (dB(A))	Airflow at free discharge (m³/h)	Insulation/ IP	Ø duct (mm)	Weight (kg)
SILENT-300 DESIGN	26	230	38	250	Class II/IP45	150-160	1,5
SILENT 300 PLUS DESIGN	22	230	42	300	Class II/IP45	150-160	1,9

* Sound pressure level measured at 3 m at free air conditions.

PERFORMANCE CURVES



DIMENSIONS (mm)



ACCESSORIES



GSA-M0 150
Flexible aluminium
ducting.



GRA-150
Aluminium exterior
grille.



REB
Single phase
electronic speed
controllers.



CX-125/215
Worm drive ducting
clip.



PER-160W
Back draft shutter.