

Nested Queries

Dr Paolo Guagliardo



THE UNIVERSITY of EDINBURGH
informatics

Fall 2020 (v20.2.0)

Aggregate results in WHERE

The right way

Account			
Number	Branch	CustID	Balance
111	London	1	1330.00
222	London	2	1756.00
333	Edinburgh	1	450.00

Accounts with a **higher balance** than the **average of all accounts**

```
SELECT A.number
FROM Account A
WHERE A.balance > ( SELECT AVG(A1.balance)
                   FROM Account A1 );
```

Answer:

Number
111
222

Aggregate results in WHERE

The wrong way

Accounts with a higher balance than the average of all accounts

```
SELECT  A.number
FROM    Account A
WHERE   A.balance > AVG( SELECT  A1.balance
                        FROM    Account A1 );
```

ERROR

Aggregate functions can only be used in **SELECT** and **HAVING**

Comparisons with subquery results

```
SELECT ...
FROM ...
WHERE term op ( subquery ) ;
```

Allowed as long as **subquery** returns a **single value**

```
SELECT ...
FROM ...
WHERE (term1, ..., termn) op ( subquery ) ;
```

Allowed as long as **subquery** returns a **single row** with n columns

The WHERE clause revisited

term := attribute | value

comparison :=

- ▶ (term, ..., term) **op** (term, ..., term)
with **op** ∈ {=, <>, <, >, <=, >=}
- ▶ term **IS** [**NOT**] **NULL**
- ▶ (term, ..., term) **op ANY** (query)
- ▶ (term, ..., term) **op ALL** (query)
- ▶ (term, ..., term) [**NOT**] **IN** (query)
- ▶ **EXISTS** (query)

condition :=

- ▶ comparison
- ▶ condition **AND** condition
- ▶ condition **OR** condition
- ▶ **NOT** condition

Comparisons between tuples

$$(A_1, \dots, A_n) = (B_1, \dots, B_n) \iff A_1 = B_1 \wedge \dots \wedge A_n = B_n$$

$$(A_1, \dots, A_n) <> (B_1, \dots, B_n) \iff A_1 \neq B_1 \vee \dots \vee A_n \neq B_n$$

$$(A_1, A_2, A_3) < (B_1, B_2, B_3) \quad \text{(generalizes to } n \text{ elements)}$$

$$\iff A_1 < B_1 \vee \left(A_1 = B_1 \wedge \left(A_2 < B_2 \vee (A_2 = B_2 \wedge A_3 < B_3) \right) \right)$$

$$(A_1, A_2, A_3) <= (B_1, B_2, B_3) \quad \text{(generalizes to } n \text{ elements)}$$

$$\iff A_1 < B_1 \vee \left(A_1 = B_1 \wedge \left(A_2 < B_2 \vee (A_2 = B_2 \wedge A_3 \leq B_3) \right) \right)$$

ANY

(term, ..., term) **op** **ANY** (query)

True if **there exists** a row \bar{r} in the results of **query** such that (term, ..., term) **op** \bar{r} is true

Examples:

Consider the table T =

A
1
2
3

- ▶ $3 < \text{ANY}(\text{SELECT } A \text{ FROM } T)$ is false
- ▶ $3 < \text{ANY}(\text{SELECT } A+1 \text{ FROM } T)$ is true
- ▶ What about $3 < \text{ANY}(\text{SELECT } A \text{ FROM } T \text{ WHERE } A = 0)$?

ALL

(term, ..., term) **op** **ALL** (query)

True if **for all** rows \bar{r} in the results of **query** (term, ..., term) **op** \bar{r} is true

Examples:

Consider the table T =

A
3
4
5
6

- ▶ $3 < \text{ALL}(\text{SELECT } A \text{ FROM } T \text{ WHERE } A <> 3)$ is true
- ▶ $3 < \text{ALL}(\text{SELECT } A \text{ FROM } T \text{ WHERE } A <> 6)$ is false
- ▶ What about $3 < \text{ALL}(\text{SELECT } A \text{ FROM } T \text{ WHERE } A = 0)$?

Examples with ANY / ALL

Customer: ID, Name, City

Account: Number, Branch, CustID, Balance

ID of customers from London who own an account

```
SELECT C.id
FROM    Customer C
WHERE    C.city = 'London'
AND      C.id = ANY ( SELECT A.custid
                        FROM    Account A );
```

Customers living in cities without a branch

```
SELECT *
FROM    Customer C
WHERE    C.city <> ALL ( SELECT A.branch
                        FROM    Account A );
```

IN / NOT IN

(term, ..., term) **IN** (query)

same as

(term, ..., term) = **ANY** (query)

(term, ..., term) **NOT IN** (query)

same as

(term, ..., term) <> **ALL** (query)

Examples with IN / NOT IN

ID of customers from London who own an account

```
SELECT C.id
FROM   Customer C
WHERE  C.city = 'London'
      AND C.id IN ( SELECT A.custid
                    FROM   Account A );
```

Customers living in cities without a branch

```
SELECT *
FROM   Customer C
WHERE  C.city NOT IN ( SELECT A.branch
                     FROM   Account A );
```

EXISTS

EXISTS (query) is true if the result of query is **non-empty**

(Stupid) Example

Return all the customers if there are some accounts in London

```
SELECT *
FROM   Customer
WHERE  EXISTS ( SELECT 1
                FROM   Account
                WHERE  branch = 'London' );
```

Correlated subqueries

All nested queries can refer to attributes in the **parent queries**

(Smarter) Example

Return customers who have an account in London

```
SELECT *
FROM Customer C
WHERE EXISTS ( SELECT 1
                FROM Account A
                WHERE A.branch = 'London'
                AND   A.custid = C.id );
```

parameters = attributes of a subquery that refer to outer queries

Examples with EXISTS / NOT EXISTS

ID of customers from London who own an account

```
SELECT C.id
FROM Customer C
WHERE C.city = 'London'
      AND EXISTS ( SELECT *
                    FROM Account A
                    WHERE A.custid = C.id);
```

Customers living in cities without a branch

```
SELECT *
FROM Customer C
WHERE NOT EXISTS ( SELECT *
                   FROM Account A
                   WHERE A.branch = C.city );
```

Scoping

A subquery has

- ▶ a **local scope** (its **FROM** clause)
- ▶ n **outer scopes** (where n is the **level of nesting**)
(these are the **FROM** clauses of the parent queries)

For each **reference** to an attribute

1. Look for a binding in the local scope
2. If no binding is found, look in the **closest** outer scope
3. If no binding is found, look in the next closest outer scope
4. ...
5. If no binding is found, give error

Attribute bindings

```
SELECT *  
FROM table1  
WHERE EXISTS ( SELECT 1  
                FROM table2  
                WHERE A = B );
```

What A , B refer to depends on the attributes in **table1** and **table2**

- ▶ Always give aliases to tables
- ▶ Always prefix the attributes with the tables they refer to

```
SELECT *  
FROM table1 T1  
WHERE EXISTS ( SELECT 1  
                FROM table2 T2  
                WHERE T2.A = T1.B );
```


The FROM clause revisited

FROM table₁ [[**AS**] T₁], ..., table_n [[**AS**] T_n]

table :=

- ▶ base-table
- ▶ join-table
- ▶ (query)

join-table :=

- ▶ table **JOIN** table **ON** condition
- ▶ table **NATURAL JOIN** table
- ▶ table **CROSS JOIN** table

Subqueries in FROM

Must always be given a name

SELECT * **FROM** (**SELECT** * **FROM** R);

ERROR: subquery in FROM must have an alias

Cannot refer to attributes of other tables in the same **FROM** clause

SELECT *
FROM R, (**SELECT** * **FROM** S **WHERE** S.a=R.a) S1 ;

ERROR: invalid reference to FROM-clause entry for table "r"

Example: Avoiding HAVING

Branches with a total balance (across accounts) of at least 500

```
SELECT    A.branch
FROM      Account A
GROUP BY  A.branch
HAVING    SUM(A.balance) >= 500 ;
```

Same query without **HAVING**:

```
SELECT subquery.branch
FROM    ( SELECT    A.branch, SUM(A.balance) AS total
          FROM      Account A
          GROUP BY  A.branch ) AS subquery
WHERE   subquery.total >= 500 ;
```

Example: Aggregation on aggregates

Average of the total balances across each customer's accounts

1. Find the total balance across each customer's accounts
2. Take the average of the totals

```
SELECT    AVG(subquery.tot)
FROM      ( SELECT    A.custid, SUM(A.balance) AS tot
          FROM      Account A
          GROUP BY  A.custid ) AS subquery ;
```