What We Do

Allegan County GIS
www.allegancounty.org/gis

December 18, 2018

Contents

Contents **ii**

I Brand **1**

1 Awards **3**
1.1 The GIS Champion Award 3
GIS Champion 3
GIS Champion Award 3
Background 3
Statement of Problem 3
Analysis 4
GIS Champion Award Code 5

II Methods **9**

2 Documentation **11**
2.1 About Documentation 11
How Jalapeño Works 11
Colors 11
Blues 11
Golds 11
Oranges 11
Geens 12
Others 12
General Notes: 13
Project File Structure: 13
Using The Glossary 14
Glossary Requirements 14
Creating a new glossary entry 14

Rebuilding the glossary 14
Using glossary terms in a subdocument: . . 15
To use a glossary term 15
To add the glossary to the subdocument: 15
Using The Bibliography(References) 15
Bibliography requirements 15
Creating a new bibliography entry 16
Rebuilding the bibliography 16
To cite a bibliography source in a subdocument: 16
. 16
Adding the bibliography to the subdocument 16
Using The Index 16
Index requirements: 16
Creating a new index entry 17
Rebuilding the index 17
*Note: 17
Access the index from a subdocument . . . 17
Using an index term 17
To add the index to the subdocument: 18
Using the Appendices 18
2.2 Document Storage Concepts 19
GIS File Standard 19
Folders inside the project folder 19

3 Team Concept **21**
3.1 Team Structure 21
Paired Programming 21

III Service **23**

4 Applications **25**
4.1 Applications for Treasurer Dept. 25
Forfeiture Data Collector 25
Problem and Analysis 25
Background 25
Statement of Problem 25
Analysis 25

Design 26
Overview 26
Forfeiture App Summary 27
Technologies Used in The Forfeiture App . 28
BSA Data 28
ArcGIS Desktop 28
ArcGIS Collector 28
Enterprise Geodatabse 28
ArcGIS Portal 28
Data Details 29
ForfeitureParcels Feature Class 30
Webmap Details 31
Feature Layer Details 31
Basemap Details 32
Hard Copy Record 33
ArcGIS Server 33
Administrative Manual 34
Annual Setup 34
Add Query Layer 35
Details of the Query Layer 36
Select a Unique Identifier 37
Add Parcels Layer to the map 39
Create Join 40
Export Joined Features 41
Load data to forfeitureParcels 42
Match these fields 44
Data Setup 46
Create Attachments 47
Setup Users in ArcGIS 48
Add New User to Feature Dataset 49
Extend Priviliges for New User 50
Setup Users in Portal for ArcGIS 51
Add Members to Portal 52
Enter required info 53
Manage Treasurer Group 54
Share Portal Content 55
Schema Change Procedure 56
Form Edits Procedure 57
User Manual 58
Collection Device Setup 58
Collector Application Setup Details 58

Install Collector for ArcGIS 58
Configure Collector 59
Download the Forfeiture Field Map . . 60
Choose Map Detail 62
Open Camera Application Setup Details . 63
Install Open Camera 63
Configure Open Camera 64
Daily Preprocessing Routine 66
Execute Preprocessing Script 66
Synchronize the Forfeiture Field Map 67
Forfeiture Data Collection 68
Forfeiture Parcels Data Details 68
Device 1 Field Operation 69
Device 2 Field Operation 77
Daily Postprocessing Routine 79
Synchronize Webmap 79
Execute Postprocessing Script 79
Software 82
ESRI Licensed Products 82
ArcDesktop 82
Enterprise ArcGIS Deployment 82
Collector for ArcGIS 82
Other Software 82
Open Camera for Android 82

5 Tools **83**
5.1 BSA Support 83
Adding a Layer to the BSA GIS 83
Add an Imagery Layer 83
BSA Program Setup 83
Setup Map Collections 84
Layers Setup 85
Select Layer Type 86
Add Layer From Local Drive 87
5.2 Core Data 88
Control Points 88
Editing Control Points 88
Fabric Point Move to Feature Addin 88
Configure Addin 88
5.3 ESRI Tools 92
COGO Tools in ArcGIS 92

5.4 GIS Administration 93
New Connections in ArcCatalog 93
Install SQL Server on client machine 93
Connect ArcGIS to a SQL Server Database 95
New Connection Dialog 96
Create Query in ArcGIS to SQL Database 97
Add Query Layer 97
Details of the Query Layer 98
More Details of the Query Layer 99
Open Results Table 100
Enterprise Geodatabase Maintenance 101
Enterprise Geodatabase Compression Routine . . 101
Disconnect Users 101
Rebuild Indexes 103
Recalculate Statistics 103
Compress 105
Rebuild Indexes Again 105
Recalculate Statistics 107
Managing Map Services 108
Stopping the Server 108
Fixing Damaged Services 108
Remove Lock Files 108
Running ArcGIS Server Account utility 109
Managing Geodatabase Replicas 111
Adding A New Feature Class To A Replica 111
Summary 111
Steps 111
Managing Geodatabase Versions 113
Version Queries 113
SQL Queries 113
Orphaned Versions 114
Remove orphaned versions 114
MXD Management 117
Find/Replace Text Object 117
Python Code 117
5.5 LaTeX Packages 118
Common Errors 118
The Form of an Error 118
LaTeX Errors 118
TeX Errors 119
Warnings 119

Underfull 119
Overfull 120
References 120
Beginning and Ending 120
Begin Ended by End 121
End Occurred Inside a Group 121
Ended by End of Line 121
Missing Begin Document 122
Errors Usually Caused by Bad Spelling 122
Unknown Control Sequence 122
Environment Undefined 122
Bad File Name 123
Cannot Find File Name 123
Fatal Errors 123
Runaway Argument 123
Just an * 124
Emergency Stop 124
Please Type a Command or Say End 124
Graphics Errors 125
Too Many Unprocessed Floats 125
Unknown Graphics Extension 125
Division by Zero 125
Math Errors 126
Display Math Should End With $$ 126
Bad Math Environment Delimiter 126
Missing Right 126
Missing Delimiter 127
Missing $ Inserted 127
Tabular Environment Errors 127
Misplaced Alignment Tab Character & 127
Extra Alignment Tab 128
Argument Has an Extra } 128
Errors With Lists 128
Missing Item 128
Too Deeply Nested 129
Miscellaneous Errors 129
Only Used in the Preamble 129
There Is No Line/Page Here to End 129
Command Already Defined 129
Missing Number 130
float Package 131

usepackage 131
Simple Use 131
Options 131
Use with Options 131
Commands 131
Graphics Examples and Notes 132
Curly Frame 132
Rectangle Frame 132
graphicx Package 134
usepackage 134
Simple Use 134
Options 134
Use with Options 134
Commands 134
hyperref Package 134
Introduction 134
Simple Use 135
Options 135
Use with Options 136
Commands 136
import Package 138
usepackage 138
Simple Use 138
Options 138
Use with Options 138
Commands 138
standalone Package 139
Introduction 139
Simple Use 139
Options 140
Use with Options 140
Commands 141
wrapfig Package 142
usepackage 142
Simple Use 142
Options 142
Use with Options 142
Commands 142
5.6 LaTeX Templates 143
LaTeX Section Template 143
LaTeX Subsection Template 143

5.7 PDF Tools 145
PDF Optimizer 146
Pupose and Summary 146
requirements 146
ghostscript 147
About 147
Licensing 147
Download 148
Windows batch files 148
5.8 QGIS Tools 149
Using COGO Tools in QGIS 149
Set up the Azimuth and Distance Plugin 149
Configure Options 151
Using the tool 152
Configure editing environment 153
Locate Point of Commencement 154
Using Reference Layer 154
Using Measuring Tool 155
Search by Parcel Number 156

IVResources **157**
A.1 Geography 101 159
Coordinate Systems for Michigan 159
B.2 ESRI Resources 159
Funcionality Matrices 159
References 161

Glossary **161**

Part I

Brand

1 Awards

1.1 The GIS Champion Award

GIS Champion

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

GIS Champion Award

Background

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Statement of Problem

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel,

semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Analysis

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

GIS Champion Award Code

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
%\geometry{tmargin=.75cm,bmargin=.25cm,
%lmargin=.8cm,rmargin=.2cm}
\geometry{tmargin=.25in,bmargin=.25in,
  lmargin=.25in,rmargin=.25in}
\usepackage{multicol}
\setlength{\columnseprule}{0.4pt}
\columnwidth=0.3\textwidth

\begin{document}
\centering
\scalebox{2.9}{
\color{green!30!black!60}
\begin{minipage}{.33\textwidth}
\font\border=umrandb
\generalframe
{\border \char113} % up left
{\border \char109} % up
{\border \char112} % up right
{\border \char108} % left
{\border \char110} % right
{\border \char114} % lower left
{\border \char111} % bottom
{\border \char115} % lower right
{\centering
\includegraphics[height=1.5cm]{GIS_Logo_better.jpg}

\vspace{-8mm}

\curlyframe[.9\columnwidth]{

\textcolor{green!10!black!90}
```

```
{\small Allegan County GIS Services}
\vspace{.005in}

\textcolor{green!10!black!90}{
\tiny Recognizes}\\
%\smallskip
\vspace{.005in}
\uline{\textcolor{green!30!black!60}
\textcolor{green!30!black!60}{Brian Redmond}}
\\
\smallskip
\tiny Information Services Technician

%\smallskip
\textcolor{green!10!black!90}
{
\\
\tiny for Excellence in
}
\smallskip
\\
\textcolor{black}{\normalsize \textsc{Enabling
 Employee Experiences}}
\\
\vspace{.1in}
\textcolor{green!10!black!90}
{
\tiny on this day
\itshape September 21, 2018
}

\vspace{.1in}

{\color{green!10!black!90}
\scalebox{.6}{

\begin{tabular}{ccc}
\cline{1-1}
\cline{3-3}
\\
Neil Besteman  & &  Bryan May \\
```

```
GIS Manager & & GIS Analyst \\
\end{tabular}

} % closes scalebox{.6} arg
} % closes blue!40!black
} % closes curlyframe arg
} % closes centering
\end{minipage}
} % closes scalebox{2.8} arg

\end{document}
```

Part II

Methods

2 Documentation

2.1 About Documentation

How Jalapeño Works

Colors

Blues

HeaderBlueA
HeaderBlueB
HeaderBlueC
HeaderBlueD
HeaderBlueE

Golds

HeaderGoldA
HeaderGoldB
HeaderGoldC
HeaderGoldD
HeaderGoldE

Oranges

HeaderOrangeA
HeaderOrangeB

HeaderOrangeC
HeaderOrangeD
HeaderOrangeE

Greens

HeaderGreenA
HeaderGreenB
HeaderGreenC
HeaderGreenD
HeaderGreenE

Others

HyperlinkBlue1
graphicOrange

General Notes:

- jalapeno folder is a git package.

  https://github.com/nbesteman/jalapeno

- Project is coded with relative paths and jalapeno can be located anywhere.

Project File Structure:

...\jalapeno\..

folder	description
documentation	resources used in Jalapeño
processing	.tex douments and build folders
source	common image files

...\jalapeno\documentation\..

folder or file	description
moduleTemplates	.tex templates
packageDocs	LaTeX documentation
references	reference and appendix resources
unsorted	catch all for unsorted documentation
BookStructureMM.mm	A mindmap of jalapeno

...\jalapeno\processing\..

folder or file	description
...Part	folders of book *parts*
build	LaTeXfolder for .pdf output and temp files
build\referenceEntries.bib	entries that appear in references
commonTitle.tex	code for all title pages
fullCompile.sh	shell script to compile GISDocumentation.tex
GISDocumentation.tex	master document code
glossaryEntries.tex	entries that appear in glossary
indexEntries.tex	entries that appear in the index
preamble.tex	preamble code for all documents

*Note about referenceEntries.bib

Any reference entries built here can be cited in any .tex document in the project.

Using The Glossary

Glossary Requirements

Glossary commands require a Perl interpreter. Activeperl is a free Perl interpreter and can be downloaded from:
https://www.activestate.com/activeperl/downloads (A typical installation adds Perl to your path). Compiling the glossary requires running the makeglossaries command either in a LaTeX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeglossaries to create an .gls file. After the .gls file is created, PDFLatex must be run again to insert the glossary at the \printglossaries location.

Creating a new glossary entry

To **create a new glossary entry:** Add an entry to glossaryEntries.tex. Save it there and then use the makeglossaries command to recompile the .gls file.

Rebuilding the glossary

To Recompile the .gls. In the (main document)build folder:

- Launch command prompt
- enter command: **makeglossaries GISDocumentation***

*Note:

This command reads the .aux file and creates the .gls file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

Using glossary terms in a subdocument:

In the subdocument you must add code to input the glossaryEntries file. For example:
After the line:

```
\input{../../../preamble}
```

Add the line:

```
\input{../../../glossaryEntries}
```

To use a glossary term in the subdocument:

In place of the term, use code referencing the key (in the glossaryEntries file):

- \gls{key}

To add the glossary to the subdocument:

- Add the line \makeglossaries to the preamble of the subdocument.
- Add the line \printglossaries to the subdocument.
- Run makeglossaries in command line on the subdocument similar to how is described above.

Using The Bibliography(References)

Bibliography requirements

Compiling the bibliography requires running bibtex either in a LaTeX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by bibtex to create a .bbl file. After the .bbl file is created, PDFLatex must be run again to insert the bibliography at the \bibliography location.

For example, the command:...\bibliography{referenceEntries}
...places the bibliography called referenceEntries.bib which must be in the same folder as the project .aux file.

Creating a new bibliography entry

To **create a new bibliography entry:** Add an entry to referenceEntries.bib. Save it there and then use bibtex to recompile the .bbl file.

Rebuilding the bibliography

To Recompile the .bbl. In the (main document)build folder:

- Launch command prompt
- enter command: **bibtex GISDocumentation**

*Note:

This command reads the .aux file and creates the .bbl file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

To cite a bibliography source in a subdocument:

In the place that you want the citation:

- `~\cite[pg.#]{key}`

Adding the bibliography to the subdocument

- Similar to adding to the master document but not documented here.

Using The Index

Index requirements:

Compiling the index requires running the makeindex command either in a LaTeX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeindex to create an .idx file. After the .idx file is created, PDFLatex must be run again to insert the index at the \printindex location.

Creating a new index entry

To **create a new index entry:** Add an entry to indexEntries.tex. Save it there and then use the makeindex command to recompile the .idx file.

Rebuilding the index

To Recompile the .idx In the (main document)build folder:

- Launch command prompt
- enter command: **makeindex GISDocumentation***

*Note:

This command reads the .aux file and creates the .idx file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail. Run PDFLatex first

Access the index from a subdocument

In the subdocument you must add code to input the indexEntries file. For example:
After the line:

```
\input{../../../preamble}
```

Add the line:

```
\input{../../../indexEntries}
```

To use a index term in the subdocument:

In place of the term, use code referencing the key (in the indexEntries file):

- \index {key}

To add the index to the subdocument:

- Add the line \makeindex to the preamble of the subdocument.
- Add the line \printindex to the subdocument.
- Run makeindex in command line on the subdocument similar to how is described above.

Using the Appendices

2.2 Document Storage Concepts

GIS File Standard

Folders inside the project folder

Lets talk about

- archive
- build
- delivered
- documentation
- processing
- source

3 Team Concept

3.1 Team Structure

Paired Programming

A paragraph about pp from Joy Inc.

Part III

Service

4 Applications

4.1 Applications for Treasurer Dept.

Forfeiture Data Collector Application

Problem and Analysis

Background

Treasurer department has an annual responsibility to properly document the tax forfeiture process. The LIS Department built an application in MS Access and MapInfo that consumed a daily export from BSA and was deployed to the field on a laptop. A digital camera was used for site photos and later imported into the laptop.

Statement of Problem

The current Tax Forfeiture workflow is built on MapInfo software and MS Access amd executed on a laptop pc. Both MapInfo and MS Access are no longer supported in county workflows. ESRI software can be used to rebuild the workflow. *Forfeiture Data Collector Application*, (**Forfeiture App**) must be recreated in the ESRI framework.

Analysis

Forfeiture App will facilitate: *Mobile data collection on a handheld device,*: (**Mobile Interface**) and an *in office workflow to complete data processing*, (**Pre and PostProcessing**)

Mobile Interface will:

- Synchronize with data in the office (online)
- Collect data and photos of forfeiture sites (offline)
- Synchronize the collected data with data in the office (online)

Pre and Post Processing will:

- Produce and print a form for each site visited with required data and images

Design

Overview

The key data set : **Forfeiture Parcels**
is used through the workflow

Figure 4.1: Project Design

Forfeiture App Summary

There are three parts to the daily routine:

1. Preprocessing (in the office):
   - Export current forfeiture list from BSA
   - Update Forfeiture Parcels with BSA export
   - Update Forfeiture Parcels with contaminated sites information
   - Synchronize Forfeiture Parcels to Mobile Interface
2. Field data collection with Mobile Interface:
   - Aids in navigation
   - Provides a Checklist of data points for each site
   - Attaches photos for each site
   - Save results for synchronization in post-processing
3. Post-processing (in the office)
   - Synchronize data and images collected in Mobile Interface to Forfeiture Parcels
   - Export form for each site
   - Print form for each site
   - Update BSA data

Technologies Used in The Forfeiture App

BSA Data

Details of parcels in the forfeiture process are managed in BSA Delinquent Tax.net. The Treasurer office does a BSA export of the parcels in need of a site visit in the preprocessing.

ArcGIS Desktop

Tools are designed to preprocess and postprocess forfeiture parcel data for fieldwork. The user will execute a preprocess script tool that prepares the data for field deployment. After fieldwork, a post process script tool syncronizes data from the fieldwork with the live data on the Allegan County network.

ArcGIS Collector

A free mobile application developed and tested on Android is deployed to the field for data collection. The application is configured to work offline(without an internet or cellular connection) by syncronizing before and after fieldwork. The user collects the necessary information on each forfeiture parcel in the field disconnected, and then uploads the changes when reconnected.

Enterprise Geodatabse

Live data from a publishing geodatabase (ACPub), running on SQL Server database server (acintsql01) provides access to Forfeiture Parcels

ArcGIS Portal

Forfeiture Parcels is served as a feature service (REST service) named TaxReversionParcels. A webmap on Portal, called the Forfeiture Field Map consumes the TaxReversionParcels exposing the data to editing. The Forfeiture Field Map is configured to work in the ArcGIS Collector App.

Figure 4.2: Technology Design

Data Details

The data is located in a geodatabase called ACPUB. ACPUB is on SQL Server ACINTSQL01.

Forfeiture Parcels Data

Figure 4.3: Live Data Location

Contamination Data

Figure 4.4: Contamination Feature Class

ForfeitureParcels Feature Class

Attribute Details			
Field Name	Field Alias	Entry Type	Note
PropertyNumber	Property Number	Prefilled	NA
Need2Print	Print Today	Dropdown	Yes or No
InspectionDate	Inspection Date	Autofill or Dropdown	NA
Inspector	Inspector	Dropdown	NA
Address	Address	Prefilled	NA
Status	Status	Dropdown	NA
StatusNotes	Status Notes	Open Entry	120Char
Roadfrontage	Road Frontage	Dropdown	Yes or No
AccessVia	Access Via	Open Entry	30Char
Agent	Agent	Open Entry	30Char
AgentContact	Agent Contact	Open Entry	30Char
PictureComments	Picture Comments	Open Entry	50Char
PropertyInUse	Property In Use	Dropdown	Yes or No
UseNotes	Use Notes	Open Entry	120Char
PropertyMaintained	Property Maintained	Dropdown	Yes or No
PropMaintNotes	Property Maintained Notes	Open Entry	120Char
PropertyContaminated	Property Contaminated	Prefilled	Preprocessing
PropertyContaminatedNotes	PropertyContaminatedNotes	Prefilled	Preprocessing
AdjacentPropertyContaminated	Adjacent Property Contaminated	Prefilled	Preprocessing
AdjPropertyContaminatedNotes	Adj Property Contaminated Notes	Prefilled	Preprocessing
PropertyForSale	Property For Sale	Dropdown	Yes or No
GlobalID	GlobalID	NA	NA
PostedDate	Posted Date	Dropdown	Date
Posted	Posted	Prefilled	NA
InList	In List	Prefilled	Preprocessing
PostedInList	Posted In List	Prefilled	Preprocessing
Acres	Acres	Prefilled	NA
Class	Class	Prefilled	NA

Table 4.1: Dataset Details

Webmap Details

The Forfeiture Field Map is made up of a basemap and a feature layer.

Figure 4.5: Web Map Details

Feature Layer Details

TaxReversionParcels has been configured for offline use.

Figure 4.6: Feature Layer Details

Basemap Details

- A tiled basemap service is used

- The infoserv user credentials are used for sharing

- The url for the shared service is:

```
https://tiledbasemaps.arcgis.com/arcgis/rest/
services/World_Street_Map/MapServer
```

Figure 4.7: Basemap Source Description

Hard Copy Record

screenshots: arcmap map arcmap tools portal screenshots sql server mgt screen shots phone screenshots

ArcGIS Server

Administrative Manual

Annual Setup

A new dataset for forfeiture parcels must be created each year.
The forfeiture information comes from BSA Forfeitures.net and the parcel geometry and other attributes comes from ACParcelsCombined.

To get the BSA Forfeiture data, create a table query for a certain year.

First, clear the features from the existing ForfeitureParcels dataset

- Use the Delete Feature Tools
- In the tool:
  - Select ACPub.DBO.ForfeitureParcels

Figure 4.8: Delete Features

Press OK

Add Query Layer

- In ArcMap ⇒ Open the New Query Layer Dialog
- File ⇒ Add Data ⇒ Add Query Layer
- Select your connection

Figure 4.9: New Query Layer Dialog

```
Query Text:
SELECT [parcelnumber] FROM [D005ALLEGAN].[dbo].[Forfeitures]
WHERE forf_year = 2019
```

Details of the Query Layer

- Choose connection
- Name the query
- Enter SQl query

Figure 4.10: Forfeiture Query Layer Details

- Press Next

Select a Unique Identifier

➢ Press Finish

Figure 4.11: Query Layer Unique ID

Table is added to the map

Figure 4.12: Forfeiture Table Added

Add Parcels Layer to the map

Add ACParcelsCombined to the map to provide parcel geometry and attributes

Figure 4.13: Parcels Layer Added

Create Join

Create new join to ACParcelsCombined of forfeitures based on parcel numbers

Figure 4.14: Join Parcels

Export Joined Features to a temp location

- Right click ➔ on joined feature class in TOC and choose export

Figure 4.15: Export Joined Features

- choose location and press OK

Load data from temp location to forfeitureParcels

Figure 4.16: Load Data 1

push next

Figure 4.17: Load Data 2

Match these fields

Figure 4.18: Match Fields 1

Figure 4.19: Match Fields 2

push next

Figure 4.20: Load Data 3

Push Finish

Data Setup

Register as versioned and Add Global IDs

Right Click ⇒ Manage ⇒ Register as Versioned

and

Right Click ⇒ Manage ⇒ Add Global IDs

Figure 4.21: Setup Data

Create Attachments

Right Click ⇒ Manage ⇒ Add Attachments

Figure 4.22: Create Attachments

Setup Users in ArcGIS

Users that will run Pre and Post processing scripts must be created and given priviliges on ACPub Treasurer Feature Data Set.

For any new users of the geoprocessing tools, use the create Database User tool **or**

In Catalog ⇒ Right click on ACpub ⇒ Administration ⇒ Add User

Figure 4.23: Add Db User

Add New User to Feature Dataset

In Catalog, ⇒ right click on Treasurer Feature Data Set ⇒ Manage ⇒ Priviliges ⇒ Add ⇒ Type new user ⇒ ok

Figure 4.24: Add Feature Dataset User

Extend Priviliges for New User

In Catalog ⇒ right click on Treasurer FDS ⇒ Manage ⇒ Priviliges ⇒ check boxes

Figure 4.25: Extend Feature Dataset Priviliges

Setup Users in Portal for ArcGIS

Users that will use the Collector for ArcGIS must have profiles added to and managed in the Allegan County GIS Portal site.

In Portal go to My Organization

Figure 4.26: Portal Add User 1

Add Members to Portal

Push add members ⇒ built in member

Figure 4.27: Portal Add User 2

Enter required info

Figure 4.28: Portal Add User 3

Manage Treasurer Group

In Portal ⇒ Go to groups ⇒ Invite new user to the group

Figure 4.29: Portal Add User 4

Share Content To The Group

Any content used by the group needs to be shared to the group

Figure 4.30: Portal AddUser 5

Schema Change Procedure

Form Edits Procedure

User Manual

Collection Device Setup

Collector Application Setup Details

Install Collector for ArcGIS

- Available from the Google Play Store

Figure 4.31: Download the App

Configure Collector

for **Organization Website**, Type:

```
{\textcolor{HeaderOrangeC}
https://gis.allegancounty.org/
portal_webadaptor}
```

then:

Press Continue

Figure 4.32: Collector Connection

Enter Credentials

then:

Press SIGN IN

Figure 4.33: Enter Credentials

Download the Forfeiture Field Map

There are 3 different versions of the map

- Forfeiture Field Map
- Forfeiture Field Map For Photos
- Forfeiture Field Map For Attributes

The Download option indicates it is not on the device but is available for offline use

Figure 4.34: Collector Maps Menu

Choose a Map

Press Download

Specify work area

and press

map detail

Note that a larger area takes longer to download but the basemap only needs to be downloaded once

Figure 4.35: Choose Work Area (large)

Choose Map Detail

Zoom into the level of detail desired.

Press Download

Figure 4.36: Choose Map Detail

This area is ready for field data collection.

Figure 4.37: Map on Device

Open Camera Application Setup Details

Install Open Camera

- Available from the Google Play Store

Figure 4.38: Open Camera from Google Play Store

Configure Open Camera

In the Open Camera Application:

Press the gear shaped Settings button to go into the settings menu

Figure 4.39: Find Settings Menu

Press the Photo Settings button

Figure 4.40: Setting Screen

Set Photo Resolution

In photo settings:

Press the Camera resolution button

Figure 4.41: Photo Settings Menu

Select **640 x 480**

Figure 4.42: Camera Resolution Setting

Daily Preprocessing Routine

Execute Preprocessing Script

A tool in ArcGIS that:

- Exports current forfeiture list from BSA
- Updates webmap layers with results from BSA export

In Catalog:

Open the toolbox

Figure 4.43: Processing Tools

Open tool 1

Synchronize the Forfeiture Field Map

Note the date and time:

Press Sync

Figure 4.44: Map Downloaded

Note the date and time:

Map is synchronized

Figure 4.45: Map Synchronized

Forfeiture Data Collection

Forfeiture Parcels Data Details

Attributes are of four entry types:

- prefilled
- autofill
- dropdown
- text box

For each site visited, select the desired parcel, push the edit button and collect attributes.

Device 1 Field Operation

Select a parcel

Figure 4.46: Select Parcel

Push the edit button

Figure 4.47: Parcel Details

Device 1 Field Operation Cont.

Select Yes for Print Today

Figure 4.48: Print Today Yes or No

Select Use Current or enter any date

Figure 4.49: Enter Date

Select Inspector From Drop-down

Figure 4.50: Select Inspector

Device 1 Field Operation Cont.

Select Occupied or Not Occupied

Figure 4.51: Status

Enter status notes up to 120 characters

Figure 4.52: Status Notes

Select Yes or No for Road Frontage

Figure 4.53: Road Frontage

Device 1 Field Operation Cont.

Enter road used for access

Figure 4.54: Access Via

Enter Agent Name

Figure 4.55: Agent

Enter Agent Contact Info

Figure 4.56: Agent Contact

Device 1 Field Operation Cont.

Enter Use Notes up to 120 characters

Figure 4.57: Use Notes

Enter Notes up to 120 characters

Figure 4.58: Notes

Enter property for sale yes or no

Figure 4.59: Property for Sale

Device 1 Field Operation Cont.

Property in Use Yes or No

Figure 4.60: Property in Use

Placeholder

Figure 4.61: Placeholder

prefilled

Figure 4.62: Property Contaminated

Device 1 Field Operation Cont.

Enter notes up to 120 characters

Figure 4.63: Notes up to 120 characters

Adjacent Property Contaminated prefilled

Figure 4.64: Adjacent Property Contaminated

Property Contaminated notes prefilled

Figure 4.65: Property Contaminated

Device 1 Field Operation Cont.

Property Maintained Yes or No

Figure 4.66: Property Maintained

Picture Comments up to 120 characters

Figure 4.67: Picture Comments

Placeholder

Figure 4.68: Placeholder

Device 2 Field Operation

Use photos taken with the Open Camera Application.

Select a parcel from the map

Figure 4.69: Select Parcel

Push Attachment Button

Figure 4.70: Push Attachment Button

Select Gallery

Figure 4.71: Add Attach-

Device 2 Field Operation Cont.

Navigate to the Open Camera Folder

Figure 4.72: Open Camera Folder

Select the appropriate image

Figure 4.73: In the Open Camera Folder

Press the check button to save the image to the parcel

Figure 4.74: Image in the App

Daily Postprocessing Routine

Back at the office

Synchronize Webmap

In Collector for ArcGIS, push the sync button on the Forfeiture Field Map

Execute Postprocessing Script

The Postprocessing Script is A tool in ArcGIS that: Reconciles geodatabase versions

Figure 4.75: Reconcile Versions and Compress Tool

Execute the Reconcile Versions and Compress Tool

Generates forms for each site visited

Execute the Export Report Tool

- Reconciles geodatabase versions
  - Execute the Reconcile Versions and Compress Tool

Figure 4.77: Reconcile Versions and Compress Tool

- Generates forms for each site visited
  - Execute the Export Report Tool

Figure 4.78: Export Report Tool

Software

ESRI Licensed Products

ArcDesktop

Users of this application need a license to ArcGIS Standard level.

Enterprise ArcGIS Deployment

This app uses ArcGIS Server and ArcGIS Portal.

Collector for ArcGIS

Developed and tested on Android(7.0). Collector is available at the Google Play Store.

Other Software

Open Camera for Android

Figure 4.79: Open Camera from Google Play Store

5 Tools

5.1 BSA Support

Adding a Layer to the BSA GIS

Add an Imagery Layer

Go To BSA Program Setup

(BSA Settings)

In **Program Setup** ⇒ Select **GIS Settings...**

Figure 5.1: BSA Program Setup

Setup Map Collections

(BSA Settings)

In **GIS Settings** ⇒ **Map Collections** ⇒

Double click on the map that you want to add a layer to

Figure 5.2: GIS Setup

In Setup Layers

(BSA Settings)

Setup Layers ⇒ Add

Figure 5.3: Layers Setup

Select Layer Type

(BSA Settings)

Setup Layers ⇒ Select Image ⇒ OK

Figure 5.4: Select Layer Type

Add Layer From Local Drive

(BSA Settings)

Navigate to Image File ⇒ Open

Figure 5.5: Add Layer From Drive

The new image is in the map

5.2 Core Data

Control Points

Maintaining Cadastral Control Points

Install the Fabric Point Move to Feature Addin

⇒ Push the Configure Button

Figure 5.6: Fabric Point Move to Feature Addin

Configure Addin

- Set Reference Feature Layer to TargetPoints
- Use point to point matching
- Use point layer field: PointID

Figure 5.7: Addin Configuration Method

```
2
Configure Fabric Point Move to Feature addin Selected Feature Options
Move Fabric Points of the Selected Parcels
Push OK
FabricPointMoveToFeatureConfigSelectedFeatures.png

3
Identify position of new control point
Select TargetPoints in Create Features Templates
Create Target Point at location for new Control Point
createTargetPoint.png

4
Use Identify tool to find ObjectID of Control Point that is to be moved
Select the Target point PointID of the point its moving to
Edit Target Point pointID attribute to match associated fabric control p
updateTargetPointPointID.png

4.5
Push move point button
moveControlPoint.png

5
Open maintain control point tool
Select control Point
push edit button
maintainControlPointTool.png

6
Use Identify Tool to View X and Y vals for the point
copy x and y value from point(attribute window) to Control (maintain con
push update
Save Edits
transferCoordinates.png
```

```
Identify position of new control point
Place Taarget Point
```

```
Update Target Point attributes to associated fabric point OID
Push move point button
Zoom to Control point
Open maintain control point tool
Select control Point
edit button
copy x and y value from
identify tool x and y of points
update button
```

5.3 ESRI Tools

COGO Tools in ArcGIS

TEXT

5.4 GIS Administration

New Connections in ArcCatalog

Install SQL Server on client machine

On client machine:

For any machine to connect to the Enterprise Geodatabase, SQL Server Native Client must be installed locally.

Search for sql server native client download on the internet margin note ⇒

Figure 5.8: SQL Server Client Search

Select appropriate Version

Decide whether to get the 32bit or 64bit version

⇐ **margin note**

Figure 5.9: SQL Server Client Search Choose

Download and Install

Connect ArcGIS to a SQL Server Database

In Catalog:

Double click on add database connection

Figure 5.10: Catalog Add Db Connection

New Connection Dialog

Enter into the tool

- Select Database Platform
- Enter Instance Name
- Enter user name and password
- Check Save user name and password
- Select Database in dropdown

Figure 5.11: Catalog Add Database Connection

Create Query in ArcGIS to SQL Database

Add Query Layer

In ArcMap:

Open the New Query Layer Dialog
Go to ⇒ File ⇒ Add Data ⇒ Add Query Layer In the connection dropdown select your connection

NOTE

Figure 5.12: New Query Layer Dialog

Details of the Query Layer

Enter into the tool

- Choose connection
- Name the query
- Enter SQl query
- Press Next

Figure 5.13: Query Layer Dialog Filled

More Details of the Query Layer

Enter into the tool

- Select unique identifier field
- Click Finish

Figure 5.14: Select Unique Identifier

Open Results Table

Verify the Query by Looking at the Table

pnum	ownername1	ownerstreetaddr	ownercity	ownerstate	ownerzip	ESRI_OID
56-004-001-00	WAGNER LONNIE J & EMMA	792 135TH AVE	WAYLAND	MI	49348	1
56-004-001-10	GUN LAKE COMMUNITY CHURCH	12200 WEST M-179	WAYLAND	MI	49348	2
56-004-002-00	WAYLAND UNION SCHOOLS	850 E SUPERIOR ST	WAYLAND	MI	49348	3
56-004-003-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	4
56-005-001-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	5
56-005-002-00	MAAS WAYLAND LLC	1845 BIRMINGHAM DR	LOWELL	MI	49331	6
56-005-002-10	ELLIOTT BAY HEALTHCARE REALTY II	617 EASTLAKE AVE E	SEATTLE	WA	98109	7
56-005-002-20	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	8
56-005-002-30	RIPARIAN PROPERTIES LLC	879 E SUPERIOR ST	WAYLAND	MI	49348	9
56-005-002-40	RIPARIAN PROPERTIES LLC	879 E SUPERIOR ST STE A	WAYLAND	MI	49348	10
56-005-002-41	VB VENTURES WAYLAND LLC	235 140TH AVE	WAYLAND	MI	49348	11
56-005-003-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	12
56-005-004-00	LATHROP THEODORE W & JUDITH	845 E SUPERIOR ST	WAYLAND	MI	49348	13
56-005-005-00	BREWER SUZANNE M	843 E SUPERIOR ST	WAYLAND	MI	49348	14
56-005-006-00	STORA RODERICK M & MELISSA K	841 E SUPERIOR ST	WAYLAND	MI	49348	15
56-005-006-10	ARY DOUGLAS & JULIE	104 MARLO LN	WAYLAND	MI	49348	16
56-005-006-20	DUBAY DOUGLAS	102 MARLO LN	WAYLAND	MI	49348	17
56-005-007-00	CONNOR MOLLY	815 EAST SUPERIOR	WAYLAND	MI	49348	18
56-005-007-10	BENNETT JILL & CARROW BIANCE	2514 BRIDGEPORT LN	GRAND RAPIDS	MI	49508	19
56-005-007-20	VILELLA MATTHEW	101 MARLO LN	WAYLAND	MI	49348	20
56-005-007-21	JENSEN KRISTEN S	103 MARLO LN	WAYLAND	MI	49348	21
56-005-008-00	WAYLAND CHRISTIAN REF CHURCH	303 E ELM STREET	WAYLAND	MI	49348	22
56-005-009-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	23
56-005-010-00	FINANCING VI HEALTHCARE PROPERTYLLC	8181 WORTHINGTON ROAD	WESTERVILLE	OH	43082	24
56-005-011-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	25
56-005-011-20	FERGUSON ROBERT K	5770 VENTURE PARK	KALAMAZOO	MI	49009	26
56-005-012-00	REDSTONE LAND DEVELOPMENT LLC	3330 GRAND RIDGE DR NE	GRAND RAPIDS	MI	49525	27
56-005-012-10	VANDERVOORD JOHN C & NANCY L	542 FORREST ST	WAYLAND	MI	49348	28
56-005-013-00	L AND M LLC	2645 24TH AVE	HUDSONVILLE	MI	49426	29
56-005-013-10	JESTER LLC	137 124TH AVE	SHELBYVILLE	MI	49344	30
56-005-014-00	OPPERMAN JOHN C	125 OAK ST	WAYLAND	MI	49348	31
56-005-015-00	REDSTONE LAND DEVELOPMENT LLC	3330 GRAND RIDGE DR NE	GRAND RAPIDS	MI	49525	32
56-005-016-00	WALKER MICHAEL	131 OAK ST	WAYLAND	MI	49348	33
56-005-017-00	FLUIT MARK & MARYELLEN	137 OAK ST	WAYLAND	MI	49348	34
56-005-018-00	GUTIERREZ SAUL O & ORTIZ CHRISTINA	119 OAK ST	WAYLAND	MI	49348	35
56-005-019-00	MICHIGAN STATE POLICE #56	544 N MAIN ST	WAYLAND	MI	49348	36
56-005-020-00	WILLIAMS TERESA A	540 N MAIN ST	WAYLAND	MI	49348	37
56-005-021-00	KEMP HOLDINGS LLC	304 108TH ST	CALEDONIA	MI	49316	38
56-005-022-00	SLOAN JOHN L & AMY L	329 WILLOW RUN DR	WAYLAND	MI	49348	39

Figure 5.15: Query Results Table

Enterprise Geodatabase Maintenance

Enterprise Geodatabase Compression Routine

Disconnect All Users

To disconnect the GIS Server, stop all services.

- In ArcGIS Server Manager ⇒ Site ⇒ GIS Server ⇒ Machines ⇒ Stop all Services

Figure 5.16: Stop ArcGIS Server

Use the Search tool to find the Rebuild Indexes Tool

Figure 5.17: Find Rebuild Indexes Tool

Rebuild Indexes

Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK

Figure 5.18: Rebuild Indexes Tool Operation

Recalculate Statistics

In the Analyze Datasets Tool:
Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK

Figure 5.19: Recalculate Statistics

Compress

Select Connection ⇒ Press OK

Figure 5.20: Compress

Rebuild Indexes Again

Figure 5.21: Rebuild Indexes Tool Operation

Recalculate Statistics Again

In the Analyze Datasets Tool:
Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK

Figure 5.22: Recalculate Statistics

Managing Map Services

To stop ArcGIS Server

Launch ArcGIS Server Manager

Figure 5.23: Stop the GIS Server

Fixing Damaged Services

Removing Lock Files

A blog about it https://community.esri.com/thread/103710

```
on juniper
C:\arcgisserver\config-store\services\ParcelViewer2\
PV2Adresses.MapServer\startup\JUNIPER.ALLEGANCOUNTY.ORG

This method works.
```

```
Steps:

1)stop arcgis server services.

2)delete the lock files(*.glock and *.rlock )
    in arcgisserver\config-store.

3) restart arcgis server service.

4)stop the pending stopping service and then start it.
```

Running ArcGIS Server Account utility

Error:

Service is currently being configured by another administrative operation

Remedy: This tech support article applies:

```
https://support.esri.com/en/technical-article/000015549
```

Our instuctions Log into Juniper windows R mstsc juniper Use personal network credentials

Launch the Configure ArcGIS Server account utility ArcGISServerAccountUtility.PNG

Use these credentials

```
PW:  @lleganGIS2015
```

in this: AccountUtilityLogin.PNG

In the utility paste these paths: gisDirectoryLocations.PNG in this:

```
C:\arcgisserver\directories
C:\arcgisserver\config-store
C:\arcgisserver\logs
```

like this:

gisDirectoryLocationsEntered.PNG

Do not export Config File doNotExportConfigFile.PNG

press configure configureAccount.png

Search For service Manger searchForServiceManager.PNG

While the tool runs, open the service manager windows search services openServicesManager.png

When the tool completes, press finish then in services select the ArcGIS Server service and restart the service. (Randy had to do this) arcGisServiceInServicesManager.png

mapservices would not stop so I try this:

`https://support.esri.com/en/technical-article/000012685`

Check permission levels for the arcGIS account ArcGisServerPermissions.PNG

If necessary, add the arcgis user to the permissions on the folders ArcGisServerPermissionsAddUser.PNG

Managing Geodatabase Replicas

Adding A New Feature Class To A Replica

Source: https://support.esri.com/en/technical-article/000010345

Summary

Currently, there is no out-of-the-box tool to add a feature class to an existing replica. With ArcGIS Desktop, one must either recreate the replica or if the workflow allows, replicate the new feature class as a separate replica.

A feature class or table can only be added to an existing replica (without recreating the replica) using ArcObjects code.

Steps:

The steps below outline how the recreate the replica using the Register Existing Data option in Desktop. These steps can be applied to both one-way and two-way replicas.

Synchronize the changes between parent and child replica geodatabases using the existing replica so that the data is identical in each database, then Unregister the replica in both geodatabases. For two-way replicas, ensure that changes are synchronized in both directions and there are no outstanding edits before unregistering the replica. Create/import the new feature class into the parent geodatabase, and add the GlobalID. Register the newly added data as versioned. Copy and paste the new feature class to the child geodatabase using ArcCatalog. Note: that the GlobalIDs must have already been added to the feature class.

For two-way replica or one-way full model, register the newly added data in child geodatabase as versioned. Using the parent geodatabase, add all the data that is to be replicated to a map in ArcMap. Click the 'Create Replica' tool on the Distributed Geodatabase toolbar. Select 'One way replica' or 'Two way replica' and click Next. Select 'Register

existing data only'. Select the child geodatabase and specify a replica name. Click Next and click Finish. A new replica is created that includes the new data.

Managing Geodatabase Versions

Version Queries

SQL Queries

Four queries of SDEversions, SDEstates, sdestatelineages, and SDE-compresslog

```
use AC_Pub
select name, owner, version_id, state_id, parent_name
, parent_owner from
 [AC_Pub].[dbo].[SDE_versions]
select * from [AC_Pub].[dbo].[SDE_states] order by state_id
select * from [AC_Pub].[dbo].[sde_state_lineages] order
 by lineage_name,
 lineage_id
select TOP(5) * from [AC_Pub].[dbo].[SDE_compress_log] order by
 compress_end DESC
```

Query of SDEversions and SDEstates

```
 use AC_Pub
SELECT v.version_id,v.creation_time,v.creation_time,
 s.state_id, s.creation_time
FROM SDE_versions v
INNER JOIN SDE_states s ON v.state_id = s.state_id
```

Finding Orphaned Versions

Remove orphaned versions

Follow the procedure: Link to source
Use SQL Server Management Studio to execute two queries and compare the results.

Step 1:

Execute the query:

```
use AC_Pub
SELECT ObjectID, name from dbo.GDB_ITEMS where
 TYPE='4ED4A58E-621F-4043-95ED-850FBA45FCBC';
```

Step 2:

Execute the query:

```
use AC_Pub
SELECT name from [dbo].[SDE_versions]
order by name
```

Compare the tables

This graphic summarizes elements of the queries. Note the items from step two that have no match in step one.

Figure 5.24: Find Orphan Versions

Orphaned versions can be removed by name in ArcGIS

Figure 5.25: Delete Orphan Versions

MXD Management

Find/Replace Text Object

Python Code

Python Code for finding and replacing a text object in a ArcGIS .mxd file. A snippet of this code may be found in the LayerUpdates/Zoning/processing folder. It is used to edit the .mxd files located there.

```
import arcpy
from arcpy import env

env.workspace = r"J:\Apps\Python\LayerUpdates\zoning\processing"
for mxdname in arcpy.ListFiles("*.mxd"):
    print mxdname
    mxd = arcpy.mapping.MapDocument(r"J:\Apps\Python\
        LayerUpdates\zoning\processing\\" + mxdname)
    for elm in arcpy.mapping.ListLayoutElements
        (mxd, "TEXT_ELEMENT"):
        if elm.text.startswith('As ammended'):
            elm.text = elm.text.replace('As ammended',
                'As amended')
            print elm.text
    mxd.save()
del mxd
```

5.5 LaTeX Packages used by AC GIS

Common Errors

Source:
https://www.ocf.berkeley.edu/~latex/files/commonerrors.tex

If you have every compiled a LaTeX document, chances are high you have received a few error messages. Sometimes they come from something as stupid and as easy to fix as forgetting a parenthesis or forgetting to end an environment. There are also a lot more cases where you have no idea what you have done wrong and it takes you a long time to find or even understand your error.

The purpose of this is to explain some of the common errors that may happen when compiling a LaTeX document and suggestions for what is probably going on and how to debug your document.

The Form of an Error

There are two forms of errors: LaTeX errors and TeX errors. In both types of errors, the part after the error message will tell you where the error occurred. An example:

```
l.15 <offending text>
```

The `l.15` tells you what line the error occurred on and the text will tell you the text that caused the error.

LaTeX Errors

The general form of an error in LaTeX is shown below:

```
! LaTeX error: <error message>

See the LaTeX manual or LaTeX Companion for
explanation.
Type H <return>   for immediate help.
...
```

The ! lets you know that the error has occurred. The error message will tell you what type of error you have committed. After the ellipses, you will find the line at which the error occurred and the text that caused the error (or at least the text where LaTeX found the error).

TeX Errors

Errors may also have the following form:

```
! <error message>
```

These errors are formatted differently because they are error messages that came from TeX instead of LaTeX. After the error, you will still find the line that the error occurred in and the text of the error.

Warnings

There are some error messages that are just warnings and will not stop or change the compilation of the document. Chances are you have seen them many times.

Underfull

The following error results when a line does not extend the width of the page, something LaTeX always tries to accomplish:

```
Underfull \hbox (badness 10000) in paragraph at lines
104--107
```

This error message is just a warning and is not something to worry about. For the most part, when a line does not span the width of the page, it is because you have written something that you want to only cover part of the page.

Overfull

The following error results when a line extends beyond the width of the page:

```
Overfull \hbox (16.04988pt too wide) in paragraph at
lines 30--31 [] [] \OT1/cmtt/m/n/12 I'm trying to put
way too much text into a line in my document.
```

Usually this error comes form when you are using the `verbatim` package because it will not move to the next line if your text does not go to the next line. The easiest way to fix this is to find the place in your document where this is occurring and change the text so that it fits to the page.

This error will still show up if the text is still on the page but outside of the width of text that LaTeX has set. In this case, you are welcome to fix things so that the error does not show up or you can leave the text as it is.

References

The following warnings occur when references are changed when LaTeX was compiled:

```
LaTeX Warning: Label(s) may have changed. Rerun to get
cross-references right.

LaTeX Warning: There were undefined references.

LaTeX Warning: Reference ‘name’ on page 1 undefined on
input line 15.
```

The way to fix these errors is to recompile the document again to correct the page numbers. Sometimes it is necessary to recompile the document twice to fix this error. You also may have defined a reference wrong, so you should check to make sure your label is correct.

Beginning and Ending

Begin Ended by End

This type of error occurs when each environment is not correctly started and ended. When you are missing an `\end` command, the following error will show up:

```
! LaTeX Error: \begin{enumerate} on input line 23
ended by \end{document}.
```

To fix this, you need to end the environment mentioned in the error with the appropriate command.

When you are missing a `\begin` command, the following will appear:

```
! LaTeX Error: \begin{document} ended by
\end{itemize}.
```

To fix this, you basically do the same thing as before, correctly beginning the environment mentioned in the error with the appropriate command.

End Occurred Inside a Group

The following error message will show up at the end of compiling a file if an environment is begun that is not ended:

```
(\end occurred inside a group at level <n>)
```

To fix this error, make sure you end the environment that was begun. The previous error is more helpful in finding the `\begin` statement.

Ended by End of Line

The following error will occur when you try to place a command inside a section heading:

```
! LaTeX Error: \verb ended by end of line.

See the LaTeX manual or LaTeX Companion for
```

```
explanation.
Type H <return>   for immediate help.
...
```

There will be many errors of the same type for this mistake. In order to find where you put the command, look in the output file and find the last heading that shows up.

Missing Begin Document

This error is self-explanatory:

```
! LaTeX Error: Missing \begin{document}
```

Errors Usually Caused by Bad Spelling

Unknown Control Sequence

This error results when you use a command (something that starts with a \) that is not recognized by LaTeX:

```
! Undefined control sequence.
```

Usually this error results from spelling a command incorrectly. Go to the line that is indicated by the error and fix the command.

Environment Undefined

This error results when you begin an environment with a `\begin` command that is not recognized:

```
! LaTeX Error: Environment verbatin undefined.
```

Usually you have just spelled your environment incorrectly, so you just need to fix it.

Bad File Name

This error results when you have mistyped the command `latex` or do not have LaTeX installed on your computer:

```
Bad command or file name
```

To fix this, correctly spell the command to compile your file or make sure that LaTeX is correctly installed on your computer.

Cannot Find File Name

This error occurs when you try to compile a file that the computer cannot find:

```
! I can't find file 'sample'.
<*> sample

Please type another input file name:
```

To fix this error, make sure you have spelled the file name correctly. You also may be in the wrong directory to compile the file, so check to make sure you are in the same directory as your file.

Fatal Errors

Runaway Argument

This error happens when a paragraph ends before a command's argument is done (i.e., LaTeX thinks that there is a missing }):

```
Runaway argument?
```

To fix this, you should use a different command to accomplish what you are trying to do. An example of this is to use `\bfseries` instead of `\bftext` to make bold text in more than one paragraph.

This error can also be caused by a missing mandatory argument to a command.

Just an *

This error normally occurs when you do not end your document with `\end{document}`:

```
*
```

If you are prompted to enter something in, it is best to enter

```
\end{document}
```

and hope it works. Be sure to end your document with the appropriate command.

Emergency Stop

This error happens when LaTeX will stop trying to compile your document due to a serious error:

```
! Emergency stop.
```

To fix this error, you will need to figure out what caused it to stop compiling. Chance are you forgot to end your document with `\end{document}`, but there might also be another reason for the emergency stop.

Please Type a Command or Say End

This error happens when your file has ended prematurely:

```
(Please type a command or say ‘\end’)
```

The best way to deal with this type of error is to type

```
\end
```

or

```
\end{document}
```

in the case that the absence of that command caused the error. Usually if you have ended your document correctly, the error will result from a missing } or forgetting to end a verbatim environment.

Graphics Errors

Too Many Unprocessed Floats

This error occurs when figures or tables (i.e., floats) have not been typeset:

```
! LaTeX Error: Too many unprocessed floats.
```

LaTeX can only have so many floats waiting to be typeset. In order to fix this error, make sure that you are placing your floats where you want them (with a `[h]` option) and not wanting too many on one page in sequence. Using the command `\clearpage` can be very useful in distributing floats correctly.

Unknown Graphics Extension

The following error occurs when you try to use a type of graphic that is not supported by the type of file that you are producing:

```
! LaTeX Error: Unknown graphics extension: .gif
```

In order to fix this error, you should change your graphics to the types that are supported by the type of file you are outputting or you will need to include the correct package to deal with that type of graphic. Sometimes you may have named the graphic poorly so that LaTeX will not recognize it as a graphic file.

Division by Zero

The following error occurs when the height of a graphic object is zero:

```
! Package graphics Error: Division by 0.
```

This is usually caused when you rotate an object with zero depth so that its height becomes zero. The best way to fix this is to use the keyword `totalheight` instead of `height`.

Math Errors

Display Math Should End With $$

This error occurs when the displaymath or equation mode is ended incorrectly:

```
! Display math should end with $$
```

To fix this error, make sure that you end the displaymath or equation mode correctly (ending them with a $ is not acceptable).

Bad Math Environment Delimiter

This error occurs when you do not have your delimiters correct in math mode:

```
! LaTeX Error: Bad math environment delimiter.
```

Usually this occurs when you forget to match a right delimiter with every left delimiter. This error may also happen when you forget to end an array.

Missing Right

This error occurs when you have a missing right parenthesis:

```
! Extra \right.
```

To fix this, you either need to add a `\right` command or you need to end an array.

Missing Delimiter

This error message occurs when a delimiter is missing:

```
! Missing delimiter (. inserted).
```

To fix this error, you need to make sure that you have a right delimiter for every left delimiter. If you do not want a right delimiter matching a left delimiter, you need to use "." to not have an error message show up.

Missing $ Inserted

The following error occurs when you try to use a character that can only be used in math mode, like _ or ^:

```
! Missing $ inserted
```

To fix this error, make sure you change the character to what it should be in text mode.

Tabular Environment Errors

Misplaced Alignment Tab Character &

This error occurs when you use `&` and when you are not in a tabular environment:

```
Misplaced alignment tab character &
```

To fix this error, you need to use `\&` to make a &.

Extra Alignment Tab

This error occurs when you use too many tabs for the number of columns in a table:

```
! Extra alignment tab has been changed to \cr
```

The result of this error is that a new row is formed where the extra tab was. You should go back and fix your table so that the correct number of items in each row would show up.

Argument Has an Extra }

These errors happen when an incorrect number of arguments to a tabular environment have been specified:

```
! Argument of \cline has an extra }.
```

```
! Argument of \multicolumn has an extra }.
```

To fix this error, make sure your arguments to the tabular environment are correct.

Errors With Lists

Missing Item

This error occurs when there is plain text in an environment that takes items:

```
! LaTeX Error: Something's wrong--perhaps a missing
\item.
```

To fix this error, make sure the plain text is changed into an item.

Too Deeply Nested

This error occurs when there are too many lists for LaTeX to handle:

```
! LaTeX Error: Too deeply nested
```

LaTeX can only handle four levels of one type of list and six levels of different types of lists. To fix this, you need to use less levels of lists or define your own list environment.

Miscellaneous Errors Only Used in the Preamble

This error occurs when you place a command in the body of a LaTeX document that should be placed in the preamble:

```
! LaTeX Error: Can be used only in the preamble.
```

To fix this error, just move the command to the preamble.

There Is No Line/Page Here to End

This error occurs when you incorrectly use the commands that make a new line or a new page:

```
! LaTeX Error: There's a no line here to end.
```

You may just leave the command that is making a new line in place or you can take it out. Here, LaTeX is just trying to make sure that everything looks nice.

Command Already Defined

This error occurs when you try to define a command that already exists:

```
! LaTeX Error: Command ... already defined.
```

To fix this, you need to define your command differently.

Missing Number

This error is made when a number is expected as an argument and one is not provided:

```
! Missing number, treated as zero.
```

To fix this error, you need to find where a number is expected so that you can provide the correct one.

float Package

usepackage

```
text
```

Simple Use

```
text
```

Options

```
text
```

Add optional arguments to the usepackage line:
Useful options:

- **OPTION NAME**
  OPTION NOTE
- **OPTION NAME**
  OPTION NOTE

Use with options

```
text
```

Commands

Graphics Examples and Notes

CurlyFrame Example

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
\geometry{tmargin=.75cm,bmargin=.25cm,lmargin=.8cm,rmargin=.2cm}
\usepackage{multicol}

\begin{document}

\curlyframe[.9\columnwidth]{

TEXTTTTTTTTTTTTTTTTT

}
\end{document}
```

RectFrame Example

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
\geometry{tmargin=.75cm,bmargin=.25cm,lmargin=.8cm,rmargin=.2cm}
\usepackage{multicol}

\begin{document}
\begin{minipage}{.33\textwidth}
\centering
\scalebox{3}{\color{green!30!black!60}
```

```
\font\border=umrandb
\generalframe
{\border \char113} % up left
{\border \char109} % up
{\border \char112} % up right
{\border \char108} % left
{\border \char110} % right
{\border \char114} % lower left
{\border \char111} % bottom
{\border \char115} % lower right
{\centering
\includegraphics[height=1.25cm]{GIS_Logo_better.jpg}}}
\end{minipage}
%\vspace{-8mm}

\end{document}
```

graphicx Package

usepackage

```
text
```

Simple Use

```
text
```

Options

```
text
```

Add optional arguments to the usepackage line:
Useful options:

- **OPTION NAME**
  OPTION NOTE
- **OPTION NAME**
  OPTION NOTE

Use with options

```
text
```

Commands

hyperref Package

Introduction

Official hyperref package documentation

Notes:

- Add the *hyperref package* to the preamble **last** [**?**]

- To use Tex in a pdf bookmark: use

  ```
  \texorpdfstring{\\}{}
  ```

  ```
  ie. \paragraph{Sample Text\texorpdfstring{\\}{}}
  ```

  Creates a new line without an error.

```
\usepackage[options]{hyperref}
```

Simple Use

```
Use \href{URL}{DESCRIPTION} to add a link with description
```

```
\href{https://www.latex-tutorial.com}{Website with tutorials}
produces:
```

Website with tutorials

Options

Add optional arguments to the usepackage line:
Useful options:

- **pdftex**
  enables other options like breaklines
- **breaklinks**
  allow links to be broken across several lines
  eg. https://lists.gnu.org/archive/html/emacs-orgmode/2013-06/msg00776.html
- **colorlinks**
  Colors the text of links and anchors.(default is false)
- **linkcolor**
  Color for normal internal links(default is red).
- **anchorcolor**
  Color for anchor text.

- **citecolor**
  Color for bibliographic citations in text.
- **urlcolor**
  Color for linked URLs

Use with options

```
\usepackage[breaklinks,colorlinks,citecolor=blue,
urlcolor=green]{hyperref}
```

Commands

`\href{URL}{text}` Makes text a link to URL.

To put a file path in text:

eg:

Official hyperref package documentation

(documentation Pt.4 pg.15)

`\href[options]{URL}{text}`

Options:

- absolute

  ```
  \href{C:/AC/jalapeno/documentation/packageDocs/hyperref2017.pdf}
      {Official hyperref doc}
  ```

- relative **Note: relative path must be from final pdf location**

  ```
  \href{../../../../../documentation/packageDocs/hyperref2017.pdf}
      {Official hyperref package doc}
  ```

  This path works from main document

  ```
  \href{../../documentation/packageDocs/hyperref2017.pdf}
      {Official hyperref package documentation}
  ```

  This path works from subsection document

```
\hyperref[label]{text}
    Makes text a link to where \ref{label} would point.

\hypertarget{name}{text}
    Sets an anchor on text with the label name.

\hyperlink{name}{text}
    Makes text a link that takes you to the anchor labeled name.
    Pair with \hypertarget.

\phantomsection
    Used in conjunction with

\addcontentsline
    to make the correct link in the Table of Contents.
```

import Package

usepackage

```
text
```

Simple Use

```
text
```

Options

```
text
```

Add optional arguments to the usepackage line:
Useful options:

- **OPTION NAME**
  OPTION NOTE
- **OPTION NAME**
  OPTION NOTE

Use with options

```
text
```

Commands

standalone Package

Introduction

Link to official standalone documentation

standalone provides a **package** and a **class**

- The *standalone* **package** is used for:
  - Main documents that will input or import sub documents.
  - For example:

    ```
    \usepackage[subpreambles=false]{standalone}
    ```

    * Ignores preambles of imported sub documents [**?**, pg.4]
- the *standalone* **class**:
  - Is a document class
  - Provides standalone / subdocument switches and options
  - For example:

    ```
    \documentclass[class=article]{standalone}
    ```

    * behaves as an article when standalone
    * makes document available for import into a master document

Simple Use

- The *standalone* **package**
  - In the main document:

    ```
    \documentclass[openany]{book}

    \preamble...

    \usepackage{standalone}
    ```

- the *standalone* **class**:

- In any subdocument:

```
\documentclass[class=article]{standalone}

\preamble...
```

Options

- The *standalone* **package**
  - **subpreamble**
    - default value of subpreambles is *false*
- the *standalone* **class**:
  - **crop**
  - **titlepage**
  - **twoside**
    - Makes pagination style match book
    - default value is *false*
  - **multi**
    - `multi=true|false`
    - `multi={<environment name>, ...>}`
  - **float**

Use with options

- the *standalone* **package**:
  - `\usepackage[subpreambles=false]{standalone}`
- the *standalone* **class**:
  -
```
\documentclass[class=article , crop=false,
    titlepage, twoside,
    multi={itemize, figure, verbatim},
    float=false]{standalone}
```

Commands

wrapfig Package

usepackage

```
text
```

Simple Use

```
text
```

Options

```
text
```

Add optional arguments to the usepackage line:
Useful options:

- **OPTION NAME**
  OPTION NOTE
- **OPTION NAME**
  OPTION NOTE

Use with options

```
text
```

Commands

5.6 LaTeX Templates

LaTeX Section Template

```
%\documentclass[class=report , crop=false, multi={itemize, figure}, float=false]{stan
\documentclass[class=book , crop=false]{standalone}

\input{../../../preamble}

\def\titlename{Section Template}

\title{\input{../../../commonTitle}}  % closing brace for title

\begin{document}% Document Begins

\input{../../../commonFront} % provides standalone options

\section{SECTION NAME HERE}

\subimport{RELATIVE PATH TO NEW Section/}{NEW SUBSECTION Subsection.tex}

%eg.
%\subimport{latexTemplatesSection/}{subsectionTemplateSubsection.tex}
% etc...

\end{document}
```

LaTeX Subsection Template

```
\documentclass[class=book , crop=false]{standalone}

\input{../../../preamble}

\def\titlename{Subsection Template}

\title{\input{../../../commonTitle}}  % closing brace for title

\begin{document}% Document Begins
```

```
\input{../../../commonFront} % provides standalone options

% NEW INFO GOs HERE.
\subsection{Subsection Template}
\medskip
```

5.7 PDF Tools used by AC GIS

PDF Optimizer

Pupose and Summary

Workflow Purpose: Optimization of a large number of pdf docs.
Workflow Summary: Uses Python to create a list of .pdf docs in a folder and creates a batch file to optimize the pdfs in the list to another location. The batch process calls ghost script for the optimization.

REQUIREMENTS

Opensource software:

- ghostscript
- python 2.7 and a Python IDE
- A text editor

paragraphPython(2.7)

Note:

The output of this script is bdoc.txt, Save as a .bat to execute the optimize.

Script that creates a batch file

```
import os, sys

project = os.path.dirname(os.path.dirname(__file__))
processing = os.path.join(project, 'processing')
#source = os.path.join(project,'source')
build = os.path.join(project,'build')
sourcepdf = os.path.join(build, '20180716')

inString1 = "gswin32 -sDEVICE=pdfwrite -dCompatibilityLevel=1.4
-dPDFSETTINGS=/ebook -dNOPAUSE -dQUIET -dBATCH
```

```
-sOutputFile=J:\\Projects\\2018ParcelAtlas\\build\\optimized\\"

inString2 = " J:\\Projects\\2018ParcelAtlas\\build\\20180716\\"

batchdoc = os.path.join(processing,"bDoc.txt")

#   Main
##############################################

if __name__ == "__main__":

    list1 = os.listdir(sourcepdf)
    l = open(batchdoc,'w')
    for i in list1:
        newi = i[1:]
        print newi
        t = inString1 + newi + inString2 + i + "\n"
        print t
        l.write(t)

    l.close()
```

GHOSTSCRIPT

About

ghostscript is used for the optimization. ghostscript is an interpreter for the PostScript language and for PDF [**?**].

Licensing

ghostscript is available opensource under AGPL conditions. more information can be found here.

Download

ghostscript can be downloaded here.

Windows batch files

A line from the batch file looks like:

```
gswin32 -sDEVICE=pdfwrite -dCompatibilityLevel=1.4
 -dPDFSETTINGS=/ebook -dNOPAUSE -dQUIET -dBATCH
 -sOutputFile=J:\Project\2018ParcelAtlas\build\optimized\
 02-001-001-00.pdf J:\Projects\2018ParcelAtlas\build\20180716
 \_02-001-001-00.pdf
```

5.8 QGIS Tools

Using COGO Tools in QGIS

Set up the Azimuth and Distance Plugin (Azd Plugin).

In the Plugins drop down(1), under the topography group select the **Azd Plugin(2)**(see fig.).

Figure 5.26: launch plugin

Note here which layer is active (see fig.).

Figure 5.27: check active layer

If necessary, left click the layer ***traverse 1*** in Layer Panel to activate it(see fig.).

Figure 5.28: activate layer

Configure Options

On Options Tab: Select Boundary, Bearing, Feet, and Degree radio buttons.

Figure 5.29: Plugin Options

Using the tool

Boundary descriptions are entered into the Drawing Tab. Azimuth (bearing) and Distance are the important boxes (Set Offset = 0 and Zenith = 90 and ignore)(see below).

Figure 5.30: Entering Bounds

Configure editing environment

Use Settings Dropdown and Snapping Options to enable snapping to Sections, Quarter Sections, and or Parcels if desired (see fig.).

Figure 5.31: Configure editing environment

Locate Point of Commencement

To get to the Point of Commencement,

Use **any combination** of the following methods:

- Using Reference Layer
- Using Measuring Tool
- Search by Parcel Number (Search Layers Plugin)
- Draw COGO lines (Azd Plugin)(as described earlier)

Using Reference Layer

Use reference layers; Units, AC_SectionsQu, Sections, and Parcels. Toggle layers on and off in Layers Panel and zoom in and out with mouse wheel.

Using Measuring Tool

Use the measuring tool, make sure to set units to feet. To exit current measurement right click (see fig.).

Figure 5.32: Measuring Tool

Search by Parcel Number

(Search Layers Plugin.)

To Launch Search Layers Plugin:
In Plugins dropdown:
Enable the **Search Layers** Plugin. (see fig.)

Figure 5.33: Search Layers Plugin

Enter parcel number (with dashes), Set layers, and set search field.(see fig.)

Figure 5.34: Search Layers Setup

Part IV

Resources

A.1 Geography 101

Foundations of geography

A Primer on Coordinate Systems Commonly Used in Michigan

A Primer on Coordinate Systems Commonly Used in Michigan

B.2 ESRI Resources

Product Documentation

Funcionality Matrices

arcgis 10.5 Enterprise Functionality Matrix Document Link
arcmap 10.5 Functionality Matrix Document Link