



Jalapeno

How This Book Works

Allegan County GIS
www.allegancounty.org/gis

August 3, 2018

Contents

0.0.1	How Jalapeño Works	1
	General Notes:	1
	Project file structure:	1
	Using the glossary	1
	Glossary requirements:	1
	Creating a new glossary entry	2
	Rebuilding the glossary	2
	Using glossary terms in a subdocument:	2
	Using the bibliography(References)	3
	Bibliography requirements:	3
	Creating a new bibliography entry	3
	Rebuilding the bibliography	3
	To cite a bibliography source in the subdocument:	
	3
	Using the Index	3
	Index requirements:	3
	Creating a new index entry	3
	Rebuilding the index	4
	Using index terms in a subdocument:	4
	Using the Appendices	4

0.0.1 How Jalapeño Works

General Notes:

- jalapeno folder is a git package.
<https://github.com/nbesteman/jalapeno>
- Project is coded with relative paths and jalapeno can be located anywhere.

Project file structure:

...\jalapeno\..

folder	description
documentation	resources used in Jalapeño
processing	.tex documents and build folders
source	common image files

...\jalapeno\documentation\..

folder or file	description
moduleTemplates	.tex templates
packageDocs	L ^A T _E X documentation
references	reference and appendix resources
unsorted	catch all for unsorted documentation
BookStructureMM.mm	A mindmap of jalapeno

...\jalapeno\processing\..

folder or file	description
...Part	folders of book <i>parts</i>
build	L ^A T _E X workspace and location of .pdf output and referenceEntries.bib*
commonTitle.tex	code for all title pages
fullCompile.sh	shell script to compile GISDocumentation.tex
GISDocumentation.tex	master document code
glossaryEntries.tex	entries that appear in glossary
indexEntries.tex	entries that appear in the index
preamble.tex	preamble code for all documents

***Note about referenceEntries.bib** Any reference entries built here can be cited in any .tex document in the project.

Using the glossary

Glossary requirements: Glossary commands require a Perl interpreter. Activeperl is a free Perl interpreter and can be downloaded from:

<https://www.activestate.com/activeperl/downloads> (A typical installation adds Perl to your

`path`). Compiling the glossary requires running the `makeglossaries` command either in a \LaTeX IDE or in command line as described here. PDFLatex must be run first to create a `.aux` file that is used by `makeglossaries` to create an `.gls` file. After the `.gls` file is created, PDFLatex must be run again to insert the glossary at the `\printglossaries` location.

Creating a new glossary entry To create a new glossary entry: Add an entry to `glossaryEntries.tex`. Save it there and then use the `makeglossaries` command to recompile the `.gls` file.

Rebuilding the glossary To Recompile the `.gls`. In the (main document)build folder:

- Launch command prompt
- enter command: `makeglossaries GISDocumentation*`

***Note:** This command reads the `.aux` file and creates the `.gls` file. The `.aux` file is created by compiling with PDFLatex. If there is no `.aux` file the command will fail.

Using glossary terms in a subdocument: In the subdocument you must add code to input the `glossaryEntries` file. For example:
After the line:

```
\input{../../../preamble}
```

Add the line:

```
\input{../../../glossaryEntries}
```

To use a glossary term in the subdocument:

In place of the term, use code referencing the key (in the `glossaryEntries` file):

- `\gls{key}`

To add the glossary to the subdocument:

- Add the line `\makeglossaries` to the preamble of the subdocument.
- Add the line `\printglossaries` to the subdocument.
- Run `makeglossaries` in command line on the subdocument similar to how is described above.

Using the bibliography(References)

Bibliography requirements: Compiling the bibliography requires running bibtex either in a L^AT_EX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by bibtex to create a .bbl file. After the .bbl file is created, PDFLatex must be run again to insert the bibliography at the \bibliography location. For example:

The command: \bibliography{referenceEntries}

Places the bibliography called referenceEntries.bib which must be in the same folder as the project .aux file.

Creating a new bibliography entry To create a new bibliography entry: Add an entry to referenceEntries.bib. Save it there and then use bibtex to recompile the .bbl file.

Rebuilding the bibliography To Recompile the .bbl. In the (main document)build folder:

- Launch command prompt
- enter command: **bibtex GISDocumentation.aux**

***Note:** This command reads the .aux file and creates the .bbl file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

To cite a bibliography source in the subdocument:

In the place that you want the citation:

- \cite[pg.#]{key}

To add the bibliography to the subdocument:

- Similar to adding to the master document but not documented here.

Using the Index

Index requirements: Compiling the index requires running the makeindex command either in a L^AT_EX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeindex to create an .idx file. After the .idx file is created, PDFLatex must be run again to insert the index at the \printindex location.

Creating a new index entry To create a new index entry: Add an entry to indexEntries.tex. Save it there and then use the makeindex command to recompile the .idx file.

Rebuilding the index To Recompile the .idx. In the (main document)build folder:

- Launch command prompt
- enter command: **makeindex GISDocumentation***

***Note:** This command reads the .aux file and creates the .idx file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail. Run PDFLatex first

Using index terms in a subdocument: In the subdocument you must add code to input the indexEntries file. For example:
After the line:

```
\input{../../../preamble}
```

Add the line:

```
\input{../../../indexEntries}
```

To use a index term in the subdocument:

In place of the term, use code referencing the key (in the indexEntries file):

- `\index {key}`

To add the index to the subdocument:

- Add the line `\makeindex` to the preamble of the subdocument.
- Add the line `\printindex` to the subdocument.
- Run `makeindex` in command line on the subdocument similar to how is described above.

Using the Appendices