

## What We Do

---

Allegan County GIS  
[www.allegancounty.org/gis](http://www.allegancounty.org/gis)

November 27, 2018

# Contents


<b>Contents</b>	<b>ii</b>
<b>I Brand</b>	<b>1</b>
<b>1 Awards</b>	<b>3</b>
1.1 The GIS Champion Award . . . . .	3
GIS Champion Award Code . . . . .	3
<b>II Methods</b>	<b>7</b>
<b>2 Documentation</b>	<b>9</b>
2.1 About Documentation . . . . .	9
How Jalapeño Works . . . . .	9
2.2 Document Storage Concepts . . . . .	13
GIS File Standard . . . . .	13
<b>3 Team Concept</b>	<b>15</b>
3.1 Team Structure . . . . .	15
Paired Programming . . . . .	15
<b>III Service</b>	<b>17</b>
<b>4 Applications</b>	<b>19</b>
4.1 Applications for Treasurer Dept. . . . .	19
Forfeiture Data Collection . . . . .	19
<b>5 Tools</b>	<b>77</b>
5.1 BSA Support . . . . .	77
Adding a Layer to the BSA GIS . . . . .	77
5.2 Core Data . . . . .	82
Control Points . . . . .	82
5.3 ESRI Tools . . . . .	85
COGO Tools in ArcGIS . . . . .	85
5.4 GIS Administration . . . . .	86
New Connections in ArcCatalog . . . . .	86
Create Query in ArcGIS to SQL Database . . . . .	90
Enterprise Geodatabase Maintenance . . . . .	94
Managing Map Services . . . . .	98
Managing Geodatabase Replicas . . . . .	99
Managing Geodatabase Versions . . . . .	100
MXD Management . . . . .	103
5.5 LATEX Packages . . . . .	104

Common Errors . . . . .	104
float Package . . . . .	113
Graphics Examples and Notes . . . . .	114
graphicx Package . . . . .	116
hyperref Package . . . . .	116
import Package . . . . .	119
standalone Package . . . . .	120
wrapfig Package . . . . .	122
5.6 L <sup>A</sup> T <sub>E</sub> X Templates . . . . .	123
L <sup>A</sup> T <sub>E</sub> X Section Template . . . . .	123
L <sup>A</sup> T <sub>E</sub> X Subsection Template . . . . .	123
5.7 PDF Tools . . . . .	124
PDF Optimizer . . . . .	125
5.8 QGIS Tools . . . . .	127
Using COGO Tools in QGIS . . . . .	127
<b>IV Resources . . . . .</b>	<b>135</b>
A.1 Geography 101 . . . . .	137
Coordinate Systems for Michigan . . . . .	137
B.2 ESRI Resources . . . . .	137
Funcionality Matrices . . . . .	137
References . . . . .	139
<b>Bibliography . . . . .</b>	<b>139</b>
<b>Glossary . . . . .</b>	<b>139</b>
<b>Index . . . . .</b>	<b>141</b>
<b>Index . . . . .</b>	<b>143</b>



## Part I

## Brand





# Chapter 1

## Awards

### 1.1 The GIS Champion Award

#### GIS Champion Award Code

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
%\geometry{tmargin=.75cm,bmargin=.25cm,
%lmargin=.8cm,rmargin=.2cm}
\geometry{tmargin=.25in,bmargin=.25in,
lmargin=.25in,rmargin=.25in}
\usepackage{multicol}
\setlength{\columnseprule}{0.4pt}
\columnwidth=0.3\textwidth

\begin{document}
\centering
\scalebox{2.9}{
\color{green!30!black!60}
\begin{minipage}{.33\textwidth}
\font\border=umrandb
\generalframe
{\border \char113} % up left
{\border \char109} % up
{\border \char112} % up right
{\border \char108} % left
{\border \char110} % right
{\border \char114} % lower left
{\border \char111} % bottom
{\border \char115} % lower right
\centering
\includegraphics[height=1.5cm]{GIS_Logo_better.jpg}

```

```
\vspace{-8mm}

\curlyframe[.9\columnwidth]{

\textcolor{green!10!black!90}{\small Allegan County GIS Services}
\vspace{.005in}

\textcolor{green!10!black!90}{\tiny Recognizes} \\
%\smallskip
\vspace{.005in}
\underline{\textcolor{green!30!black!60}{\textcolor{green!30!black!60}{Brian Redmond}}}
\\
\smallskip
\tiny Information Services Technician

%\smallskip
\textcolor{green!10!black!90}{{
\\
\tiny for Excellence in
}}
\smallskip
\\
\textcolor{black}{\normalsize \textsc{Enabling
Employee Experiences}}
\\
\vspace{.1in}
\textcolor{green!10!black!90}{{
\\
\tiny on this day
\itshape September 21, 2018
} }

\vspace{.1in}

{\color{green!10!black!90}
\scalebox{.6}{

\begin{tabular}{ccc}
\cline{1-1}
\cline{3-3}
\\
Neil Besteman & & Bryan May \\
GIS Manager & & GIS Analyst \\

```

---

```
\end{tabular}

} % closes scalebox{.6} arg
} % closes blue!40!black
} % closes curlyframe arg
} % closes centering
\end{minipage}
} % closes scalebox{2.8} arg

\end{document}
```



## **Part II**

# **Methods**



# Chapter 2

## Documentation

### 2.1 About Documentation

#### How Jalapeño Works

##### General Notes:

- jalapeno folder is a git package.  
<https://github.com/nbesteman/jalapeno>
- Project is coded with relative paths and jalapeno can be located anywhere.

##### Project file structure:

...\\jalapeno\\..

folder	description
documentation	resources used in Jalapeño
processing	.tex documents and build folders
source	common image files

...\\jalapeno\\documentation\\..

folder or file	description
moduleTemplates	.tex templates
packageDocs	L <small>A</small> T <small>E</small> X documentation
references	reference and appendix resources
unsorted	catch all for unsorted documentation
BookStructureMM.mm	A mindmap of jalapeno

...\\jalapeno\\processing\\..

folder or file	description
...Part	folders of book <i>parts</i>
build	L <small>A</small> T <small>E</small> X folder for .pdf output and temp files
build\\referenceEntries.bib	entries that appear in references
commonTitle.tex	code for all title pages
fullCompile.sh	shell script to compile GISDocumentation.tex
GISDocumentation.tex	master document code
glossaryEntries.tex	entries that appear in glossary
indexEntries.tex	entries that appear in the index
preamble.tex	preamble code for all documents

**\*Note about referenceEntries.bib** Any reference entries built here can be cited in any .tex document in the project.

## Using the glossary

**Glossary requirements:** Glossary commands require a Perl interpreter. Activeperl is a free Perl interpreter and can be downloaded from:

<https://www.activestate.com/activeperl/downloads> (A typical installation adds Perl to your path). Compiling the glossary requires running the makeglossaries command either in a L<sup>A</sup>T<sub>E</sub>X IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeglossaries to create an .gls file. After the .gls file is created, PDFLatex must be run again to insert the glossary at the \printglossaries location.

**Creating a new glossary entry** To **create a new glossary entry**: Add an entry to glossaryEntries.tex. Save it there and then use the makeglossaries command to recompile the .gls file.

**Rebuilding the glossary** To **Recompile the .gls**. In the (main document)build folder:

- Launch command prompt
- enter command: **makeglossaries GISDocumentation\***

**\*Note:** This command reads the .aux file and creates the .gls file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

**Using glossary terms in a subdocument:** In the subdocument you must add code to input the glossaryEntries file. For example:

After the line:

```
\input{../../preamble}
```

Add the line:

```
\input{../../glossaryEntries}
```

### To use a glossary term in the subdocument:

In place of the term, use code referencing the key (in the glossaryEntries file):

- \gls{key}

### To add the glossary to the subdocument:

- Add the line \makeglossaries to the preamble of the subdocument.
- Add the line \printglossaries to the subdocument.
- Run makeglossaries in command line on the subdocument similar to how is described above.

## Using the bibliography(References)

**Bibliography requirements:** Compiling the bibliography requires running bibtex either in a L<sup>A</sup>T<sub>E</sub>X IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by bibtex to create a .bb file. After the .bb file is created, PDFLatex must be run again to insert the bibliography at the \bibliography location.

For example, the command:... \bibliography{referenceEntries}  
...places the bibliography called referenceEntries.bib which must be in the same folder as the project .aux file.

**Creating a new bibliography entry To create a new bibliography entry:** Add an entry to referenceEntries.bib. Save it there and then use bibtex to recompile the .bb file.

**Rebuilding the bibliography To Recompile the .bb.** In the (main document)build folder:

- Launch command prompt
- enter command: **bibtex GISDocumentation**

**\*Note:** This command reads the .aux file and creates the .bb file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

### To cite a bibliography source in a subdocument:

In the place that you want the citation:

- ~\cite[pg. #]{key}

### To add the bibliography to the subdocument:

- Similar to adding to the master document but not documented here.

## Using the Index

**Index requirements:** Compiling the index requires running the makeindex command either in a L<sup>A</sup>T<sub>E</sub>X IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeindex to create an .idx file. After the .idx file is created, PDFLatex must be run again to insert the index at the \printindex location.

**Creating a new index entry To create a new index entry:** Add an entry to indexEntries.tex. Save it there and then use the makeindex command to recompile the .idx file.

### Rebuilding the index

---

**To Recompile the .idx** In the (main document) build folder:

- Launch command prompt
- enter command: **makeindex GISDocumentation\***

**\*Note:** This command reads the .aux file and creates the .idx file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail. Run PDFLatex first

**Using index terms in a subdocument:** In the subdocument you must add code to input the indexEntries file. For example:

After the line:

```
\input{.../.../.../preamble}
```

Add the line:

```
\input{.../.../.../indexEntries}
```

**To use a index term in the subdocument:**

In place of the term, use code referencing the key (in the indexEntries file):

- \index {key}

**To add the index to the subdocument:**

- Add the line \makeindex to the preamble of the subdocument.
- Add the line \printindex to the subdocument.
- Run makeindex in command line on the subdocument similar to how is described above.

## Using the Appendices

---

## 2.2 Document Storage Concepts

### GIS File Standard

#### Folders inside the project folder

Lets talk about map projection

- archive
- build
- delivered
- documentation
- processing
- source



# **Chapter 3**

## **Team Concept**

### **3.1 Team Structure**

#### **Paired Programming**

A paragraph about pp from Joy Inc.



## **Part III**

## **Service**



# Chapter 4

## Applications

### 4.1 Applications for Treasurer Dept.

#### Forfeiture Data Collection

##### Problem and Analysis

**Background** Treasurer department has an annual responsibility to properly document the tax forfeiture process. The LIS Department built an application in MS Access and MapInfo that consumed a daily export from BSA and was deployed to the field on a laptop. A digital camera was used for site photos and later imported into the laptop.

**Statement of Problem** Current Tax Forfeiture workflow is built on Map-Info software which has been replaced by ESRI software. The Forfeiture data collection application must be recreated in the ESRI framework.

**Analysis** Tax Forfeiture Application, referred to here as: **Forfeiture App** will facilitate:

- Mobile data collection on handheld device, referred to here as: **Mobile Interface**
  - Mobile Interface will:
    - \* Synchronize with data in the office (online)
    - \* Navigate to forfeiture sites (offline)
    - \* Collect data and photos of forfeiture sites (offline)
    - \* Synchronize the collected data with data in the office (online)
- Daily form production and printing for each site visited with required data and images

### Design

**Overview** The Forfeiture App documents the Tax Forfeiture process

The key data set, is referred to here as: **Forfeiture Parcels**




Figure 4.1: Project Design

**Forfeiture App Summary** Three parts of the daily routine:

1. Preprocessing (in the office):

- Export current forfeiture list from BSA
- Update Forfeiture Parcels with BSA export
- Update Forfeiture Parcels with contaminated sites information
- Synchronize Forfeiture Parcels to Mobile Interface

2. Field data collection with Mobile Interface:

- Aids in navigation
- Provides a Checklist of data points for each site
- Attaches photos for each site
- Save results for synchronization in post-processing

3. Post-processing (in the office)

- Synchronize data and images collected in Mobile Interface to Forfeiture Parcels
  - Export form for each site
  - Print form for each site
  - Update BSA data
-

### Technologies Used in The Forfeiture App

**BSA Data** Details of parcels in the forfeiture process are managed in BSA Delinquent Tax.net. The Treasurer office does a BSA export of the parcels in need of a site visit in the preprocessing.

**ArcGIS Desktop** Tools are designed to preprocess and postprocess forfeiture parcel data for fieldwork. The user will execute a preprocess script tool that prepares the data for field deployment. After fieldwork, a post process script tool syncronizes data from the fieldwork with the live data on the Allegan County network.

**ArcGIS Collector** A free mobile application developed and tested on Android is deployed to the field for data collection. The application is configured to work offline (without an internet or cellular connection) by syncronizing before and after fieldwork. The user collects the necessary information on each forfeiture parcel in the field disconnected, and then uploads the changes when reconnected.

**ArcGIS Enterprise Geodatabase** Live data from a publishing geodatabase (ACPub), running on SQL Server database server (acintsql01) provides access to Forfeiture Parcels

**ArcGIS Portal Webmaps and Apps** Forfeiture Parcels is served as a feature service (REST service) named TaxReversionParcels. A webmap on Portal, called the Forfeiture Field Map consumes the TaxReversionParcels exposing the data to editing. The Forfeiture Field Map is configured to work in the ArcGIS Collector App.




Figure 4.2: Technology Design

## Data Details

**Data Location** The data is located in ACPUB. ACPUB is a geodatabase on ACINTSQL01.

### Forfeiture Parcels Data




Figure 4.3: Live Data Location

### Contamination Data




Figure 4.4: Contamination Feature Class

**ForfeitureParcels Feature Class Data Details:**

Attribute Details			
Field Name	Field Alias	Entry Type	Note
PropertyNumber	Property Number	Prefilled	NA
Need2Print	Print Today	Dropdown	Yes or No
InspectionDate	Inspection Date	Autofill or Dropdown	NA
Inspector	Inspector	Dropdown	NA
Address	Address	Prefilled	NA
Status	Status	Dropdown	NA
StatusNotes	Status Notes	Open Entry	120Char
Roadfrontage	Road Frontage	Dropdown	Yes or No
AccessVia	Access Via	Open Entry	30Char
Agent	Agent	Open Entry	30Char
AgentContact	Agent Contact	Open Entry	30Char
PictureComments	Picture Comments	Open Entry	50Char
PropertyInUse	Property In Use	Dropdown	Yes or No
UseNotes	Use Notes	Open Entry	120Char
PropertyMaintained	Property Maintained	Dropdown	Yes or No
PropMaintNotes	Property Maintained Notes	Open Entry	120Char
PropertyContaminated	Property Contaminated	Prefilled	Preprocessing
PropertyContaminatedNotes	PropertyContaminatedNotes	Prefilled	Preprocessing
AdjacentPropertyContaminated	Adjacent Property Contaminated	Prefilled	Preprocessing
AdjPropertyContaminatedNotes	Adj Property Contaminated Notes	Prefilled	Preprocessing
PropertyForSale	Property For Sale	Dropdown	Yes or No
GlobalID	GlobalID	NA	NA
PostedDate	Posted Date	Dropdown	Date
Posted	Posted	Prefilled	NA
InList	In List	Prefilled	Preprocessing
PostedInList	Posted In List	Prefilled	Preprocessing
Acres	Acres	Prefilled	NA
Class	Class	Prefilled	NA

Table 4.1: Dataset Details

**Webmap Details** The Forfeiture Field Map is made up of a basemap and a feature layer.




Figure 4.5: Web Map Details

**Feature Layer Details** TaxReversionParcels has been configured for offline use.




Figure 4.6: Feature Layer Details

### Basemap Details

- A tiled basemap service is used
- The infoserv user credentials are used for sharing
- The url for the shared service is:

[https://tiledbasemaps.arcgis.com/arcgis/rest/services/World\\_Street\\_Map/MapServer](https://tiledbasemaps.arcgis.com/arcgis/rest/services/World_Street_Map/MapServer)

The screenshot shows the ArcGIS Online interface for the 'World Street Map (for Export)' layer. At the top, there's a navigation bar with links for ArcGIS, Pricing, Map, Scene, and Help, along with a sign-in button and a search bar. Below the header, the title 'World Street Map (for Export)' is displayed, followed by a 'Overview' tab. The main content area features a thumbnail map of the world with a red bounding box highlighting the Americas. To the right of the map, a detailed description states: 'This layer presents highway-level data for the world and street-level data for many areas around the world. This layer is designed to support export of basemap tiles for offline use. ArcGIS Online Subscription required.' Below this, there are buttons for 'Tile Layer by Esri' and 'Authoritative' and 'Subscriber' status indicators. Further down, the 'Description' section provides information about the layer's purpose and scale levels. The 'Service Information for Developers' section contains instructions for using the layer in developer applications. On the right side of the page, there are sections for 'Open in Map Viewer', 'Open in Scene Viewer', 'Open in ArcGIS Desktop', 'Details' (listing source as 'Map Service' and size as '1 kb'), 'Owner' (Esri), and 'Tags' (including 'World', 'Global', 'Europe', etc.).

Figure 4.7: Basemap Source Description

**Hard Copy Record**

screenshots: arcmap map arcmap tools portal screenshots sql server mgt screen  
shots phone screenshots

**ArcGIS Server**

## Administrative Manual

### Annual Setup

A new dataset for forfeiture parcels must be created each year. The forfeiture information comes from BSA Forfeitures.net and the parcel geometry and other attributes comes from ACParcelsCombined.

To get the BSA Forfeiture data, create a table query for a certain year.

First, clear the features from the existing ForfeitureParcels dataset

- Use the Delete Feature Tools
- In the tool:
  - Select ACPub.DBO.ForfeitureParcels




Figure 4.8: Delete Features

---

Press OK

## Add Query Layer

- In ArcMap ⇒ Open the New Query Layer Dialog
- File ⇒ Add Data ⇒ Add Query Layer
- Select your connection




Figure 4.9: New Query Layer Dialog

### Query Text:

```
SELECT [parcelnumber] FROM [D005ALLEGAN].[dbo].[Forfeitures]
WHERE forf_year = 2019
```

## Details of the Query Layer

Enter into the tool

- Choose connection
- Name the query
- Enter SQL query




Figure 4.10: Forfeiture Query Layer Details

- Press Next

## Select a Unique Identifier




Figure 4.11: Query Layer Unique ID

- Press Finish

Table is added to the map

The screenshot shows the ArcGIS Pro interface with two main windows. On the left is the 'Table Of Contents' window, which displays a hierarchical list of layers. A red box highlights the 'D005ALLEGAN' folder, which contains a single layer named 'D005ALLEGAN.DBO.forfeitures'. On the right is a 'Table' viewer window titled 'D005ALLEGAN.DBO.forfeitures'. This window displays a table with two columns: 'parcelnumber' and 'ESRI\_OID'. The table lists 836 rows of data, starting with 01-007-012-00 and ending with 02-007-035-00. The last row is highlighted in blue. At the bottom of the table viewer, there is a message stating '(0 out of 836 Selected)'.

parcelnumber	ESRI_OID
01-007-012-00	1
01-008-005-00	2
01-016-031-10	3
01-019-001-13	4
01-019-005-97	5
01-025-017-00	6
01-026-020-00	7
01-030-014-10	8
01-030-019-00	9
01-031-031-00	10
01-034-009-00	11
01-034-014-10	12
01-034-055-00	13
01-034-067-00	14
01-034-087-00	15
01-034-108-00	16
01-035-015-00	17
01-035-020-20	18
01-035-030-00	19
01-035-044-00	20
01-035-044-10	21
01-120-004-00	22
01-120-010-00	23
01-120-031-00	24
01-120-032-00	25
01-220-010-00	26
01-250-001-00	27
01-300-004-00	28
01-320-020-00	29
01-320-021-00	30
01-370-016-00	31
01-740-009-00	32
02-001-012-31	33
02-003-018-00	34
02-005-004-20	35
02-007-035-00	36

Figure 4.12: Forfeiture Table Added

---

## Add Parcels Layer to the map

Add ACParcelsCombined to the map to provide parcel geometry and attributes




Figure 4.13: Parcels Layer Added

## Create Join

Create new join to ACParcelsCombined of forfeitures based on parcel numbers




Figure 4.14: Join Parcels

## Export Joined Features to a temp location

- Right click on joined feature class in TOC and choose export




Figure 4.15: Export Joined Features

- choose location and press OK

### Load data from temp location to forfeitureParcels




Figure 4.16: Load Data 1

push next




Figure 4.17: Load Data 2

### Match these fields




Figure 4.18: Match Fields




Figure 4.19: Match Fields

push next




Figure 4.20: Load Data 3

push Finish


**Data Setup** Register as versioned and Add Global IDs

Figure 4.21: Setup Data

push Finish

---

### Create Attachments

Right Click ⇒ Manage ⇒ Add Attachments




Figure 4.22: Create Attachments

### Setup Users in ArcGIS

Users that will run Pre and Post processing scripts must be created and given privileges on ACPub Treasurer Feature Data Set.

For any new users of the geoprocessing tools, use the create Database User tool or

Go to => Right click on ACpub => Administration => Add User




Figure 4.23: Add Db User

### Add New User to Feature Dataset

In Catalog, ⇒ right click on Treasurer Feature Data Set ⇒ Manage ⇒ Privileges ⇒ Add ⇒ Type new user ⇒ ok




Figure 4.24: Add Feature Dataset User

**Extend Privileges for New User**

In Catalog⇒right click on Treasurer FDS ⇒ Manage⇒ Privileges⇒ check boxes





Figure 4.25: Extend Feature Dataset Privileges

---

## Setup Users in Portal for ArcGIS

Users that will use the Collector for ArcGIS must have profiles added to and managed in the Allegan County GIS Portal site.

In Portal go to My Organization



The screenshot shows the 'My Organization' page of the Allegan County GIS Services portal. The URL is https://gis.allegancounty.org/portal\_webadaptor/home/organization.html. The page includes a navigation bar with links like Home, Gallery, Map, Scene, Groups, My Content, and My Organization. A search bar is at the top right. Below the navigation is a banner for 'Allegan County GIS Services'. The main content area displays a table of current members:

Name	Username	Last Login	Level	Role	Action
Bryan May	bmay531	Nov 2, 2018	②	Administrator	[Edit]
Christina Andress	CAndress	Sep 19, 2018	②	Administrator	[Edit]
Jennifer Morris	JMorris	Oct 18, 2018	②	Administrator	[Edit]
Neil Besteman	nbesteman	Oct 29, 2018	②	Administrator	[Edit]
Paula Reed	preed6	Feb 7, 2017	①	Viewer	[Edit]

On the right side, there's a sidebar titled 'Membership' with sections for 'Members per level', 'Total Members: 5 of 35', and links to 'Find...', 'The most viewed items', 'The last items added', and 'Groups'.

Figure 4.26: Portal Add User 1

### Add Members to Portal

Push add members ⇒ built in member




Figure 4.27: Portal Add User 2

**2** Create new Allegan County GIS Services logins one at a time or in batch from a file.  
Select any role for the member to be a part of. You must inform the member of their user name and password. If you do not have an email address for a particular user, use the administrator's email address.

Password may not be less than 6 characters.

Email: \_\_\_\_\_

First Name: \_\_\_\_\_

Last Name: \_\_\_\_\_

Username: \_\_\_\_\_

Password: \_\_\_\_\_

Level       1       2

Role: Publisher

**BACK**    **ADD ANOTHER**    **REVIEW ADDITIONS**

Figure 4.28: Portal Add User 3

Enter required info

---

## Manage Treasurer Group

In Portal ⇒ Go to groups ⇒ Invite new user to the group




Figure 4.29: Portal Add User 4

---

## Share Content To The Group

Any content used by the group needs to be shared to the group




Figure 4.30: Portal AddUser 5

**Schema Change Procedure**

---

**Form Edits Procedure**

---



## User Manual

### Collection Device Setup


#### Collector Application Setup Details

##### Install Collector for ArcGIS

- Available from the Google Play Store



Accurate Data Collection Made Easy



[READ MORE](#)

Figure 4.31: Download the App

## Configure Collector

for Organization Website, Type:

[https://gis.allegancounty.org/portal\\_webadaptor](https://gis.allegancounty.org/portal_webadaptor)

then:

Press Continue




Figure 4.32: Collector Connection

---

Enter Credentials

then:

Press SIGN IN




Figure 4.33: Enter Credentials

**Download the Forfeiture Field Map** There are 3 different versions of the map

- Forfeiture Field Map
- Forfeiture Field Map For Photos
- Forfeiture Field Map For Attributes

The Download option indicates it is not on the device but is available for offline use

Choose a Map

Press Download




Figure 4.34: Collector Maps Menu

Specify work area

and press

map detail

Note that a larger area takes longer to download but the basemap only needs to be downloaded once




Figure 4.35: Choose Work Area (large)

### Choose Map Detail

Zoom into the level of detail desired.

Press Download




Figure 4.36: Choose Map Detail

This area is ready for field data collection.




Figure 4.37: Map on Device

### Open Camera Application Setup Details

#### Install Open Camera

- Available from the Google Play Store




Figure 4.38: Open Camera from Google Play Store

---

### Configure Open Camera

In the Open Camera Application:

Press the gear shaped Settings button to go into the settings menu




Figure 4.39: Find Settings Menu

---

Press the Photo Settings button




Figure 4.40: Setting Screen

---

### Set Photo Resolution

In photo settings:

Press the Camera resolution button




Figure 4.41: Photo Settings Menu

Select **640 x 480**





Figure 4.42: Camera Resolution Setting

### Daily Preprocessing Routine

**Execute Preprocessing Script** A tool in ArcGIS that:

- Exports current forfeiture list from BSA
- Updates webmap layers with results from BSA export

In Catalog:




Open the toolbox

Figure 4.43: Processing Tools

Open tool 1

### Synchronize the Forfeiture Field Map

Note the date and time:




Press Sync

Figure 4.44: Map Downloaded

---

Note the date and time:



Map is synchronized

Figure 4.45: Map Synchronized

---

### Forfeiture Data Collection

**Forfeiture Parcels Data Details** Attributes are of four entry types:

- prefilled
- autofill
- dropdown
- text box

For each site visited, select the desired parcel, push the edit button and collect attributes.

---

**Device 1 Field Operation**  
Select a parcel



Figure 4.46: Select Parcel

Push the edit button




Figure 4.47: Parcel Details

---

**Device 1 Field Operation Cont.** Select Yes for Print Today



Figure 4.48: Print Today Yes or No

Select Use Current or enter any date




Figure 4.49: Enter Date

Select Inspector From Dropdown



Figure 4.50: Select Inspector

**Device 1 Field Operation Cont.**  
Select Occupied or Not Occupied




Figure 4.51: Status

Enter status notes up to 120 characters




Figure 4.52: Status Notes

Select Yes or No for Road Frontage




Figure 4.53: Road Frontage

**Device 1 Field Operation Cont.**  
Enter road used for access




Figure 4.54: Access Via

---

Enter Agent Name




Figure 4.55: Agent

---

Enter Agent Contact Info




Figure 4.56: Agent Contact

**Device 1 Field Operation Cont.**  
Enter Use Notes up to 120 characters




Figure 4.57: Use Notes

Enter Notes up to 120 characters




Figure 4.58: Notes

Enter property for sale yes or no



Figure 4.59: Property for Sale

**Device 1 Field Operation Cont.**  
Property in Use Yes or No




Figure 4.60: Property in Use

Placeholder




Figure 4.61: Placeholder

prefilled




Figure 4.62: Property Contaminated

**Device 1 Field Operation Cont.**  
Enter notes up to 120 characters





Figure 4.63: Notes up to 120 characters

Adjacent Property Contaminated pre-filled



Property Contaminated notes prefilled

Figure 4.64: Adjacent Property Contaminated




Figure 4.65: Property Contaminated

**Device 1 Field Operation Cont.**  
Property Maintained Yes or No




Figure 4.66: Property Maintained

Picture Comments up to 120 characters




Figure 4.67: Picture Comments

Placeholder




Figure 4.68: Placeholder

**Device 2 Field Operation**

Use photos taken with the Open Camera Application.



Select a parcel from the map

Figure 4.69: Select Parcel

---


**Push Attachment Button**

Figure 4.70: Push Attachment Button

**Select Gallery**

---




Figure 4.71: Add Attachment From Gallery

---

**Device 2 Field Operation Cont.**  
Navigate to the Open Camera Folder





Figure 4.72: Open Camera Folder

Select the appropriate image



Press the check button to save the image to the parcel

Figure 4.73: In the Open Camera Folder




Figure 4.74: Image in the App

### Daily Postprocessing Routine


Back at the office

#### Synchronize Webmap

In Collector for ArcGIS, push the sync button on the Forfeiture Field Map

#### Execute Postprocessing Script

The Postprocessing Script is A tool in ArcGIS that: Reconciles geodatabase versions



Execute the Reconcile Versions and Compress Tool

Figure 4.75: Reconcile Versions and Compress Tool

Generates forms for each site visited




Figure 4.76: Export Report Tool

Execute the Export Report

Tool

- Reconciles geodatabase versions
  - Execute the Reconcile Versions and Compress Tool




Figure 4.77: Reconcile Versions and Compress Tool

- Generates forms for each site visited
  - Execute the Export Report Tool




Figure 4.78: Export Report Tool

## Software

### ESRI Licensed Products

**ArcDesktop** Users of this application need a license to ArcGIS Standard level.

**Enterprise ArcGIS Deployment** This app uses ArcGIS Server and ArcGIS Portal.

**Collector for ArcGIS** Developed and tested on Android(7.0). Collector is available at the Google Play Store.

### Other Software




Figure 4.79: Open Camera from Google Play Store



# Chapter 5

## Tools

### 5.1 BSA Support

Adding a Layer to the BSA GIS

Add an Imagery Layer

Go To BSA Program Setup  
(BSA Settings)

In Program Setup ⇒ Select GIS Settings...




Figure 5.1: BSA Program Setup

### Setup Map Collections (BSA Settings)

In GIS Settings ⇒ Map Collections ⇒

Double click on the map that you want to add a layer to




Figure 5.2: GIS Setup

## In Setup Layers (BSA Settings)

Setup Layers ⇒ Add




Figure 5.3: Layers Setup

### Select Layer Type (BSA Settings)

Setup Layers ⇒ Select Image ⇒ OK




Figure 5.4: Select Layer Type

## Add Layer From Local Drive (BSA Settings)

Navigate to Image File ⇒ Open




Figure 5.5: Add Layer From Drive

The new image is in the map

## 5.2 Core Data

### Control Points

#### Maintaining Cadastral Control Points

#### Install the Fabric Point Move to Feature Addin

⇒ Push the Configure Button




Figure 5.6: Fabric Point Move to Feature Addin

### Configure Addin

- Set Reference Feature Layer to TargetPoints
- Use point to point matching
- Use point layer field: PointID




Figure 5.7: Addin Configuration Method

2  
Configure Fabric Point Move to Feature addin Selected Feature Options  
Move Fabric Points of the Selected Parcels  
Push OK  
FabricPointMoveToFeatureConfigSelectedFeatures.png

3  
Identify position of new control point  
Select TargetPoints in Create Features Templates  
Create Target Point at location for new Control Point  
createTargetPoint.png

4  
Use Identify tool to find ObjectId of Control Point that is to be moved  
Select the Target point PointID of the point its moving to  
Edit Target Point pointID attribute to match associated fabric control point OID  
updateTargetPointPointID.png

4.5  
Push move point button  
moveControlPoint.png

5  
Open maintain control point tool  
Select control Point  
push edit button  
maintainControlPointTool.png

6  
Use Identify Tool to View X and Y vals for the point  
copy x and y value from point(attribute window) to Control (maintain control tool)  
push update  
Save Edits  
transferCoordinates.png

---

Identify position of new control point  
Place Taarget Point  
Update Target Point attributes to associated fabric point OID  
Push move point button  
Zoom to Control point  
Open maintain control point tool  
Select control Point  
edit button  
copy x and y value from

identify tool x and y of points  
update button

### **5.3 ESRI Tools**

#### **COGO Tools in ArcGIS**

TEXT

---

## 5.4 GIS Administration

### New Connections in ArcCatalog


#### Install SQL Server on client machine

##### On client machine:

For any machine to connect to the Enterprise Geodatabase, SQL Server Native Client must be installed locally.

margin note⇒

Search for sql server native client download on the internet




Microsoft® SQL Server® 2012 Native Client - QFE



Figure 5.8: SQL Server Client Search

### Select appropriate Version

Decide whether to get the 32bit or 64bit version



Choose the download you want

File Name	Size
ENU\x64\sqlcli.msi	For 64bit OS 4.8 MB
ENU\x86\sqlcli.msi	For 32 bit OS 3.0 MB

Figure 5.9: SQL Server Client Search Choose

Download and Install

## Connect ArcGIS to a SQL Server Database

### In Catalog:

Double click on add database connection




Figure 5.10: Catalog Add Db Connection

---

## New Connection Dialog

### Enter into the tool

- Select Database Platform
- Enter Instance Name
- Enter user name and password
- Check Save user name and password
- Select Database in dropdown




Figure 5.11: Catalog Add Database Connection

**Create Query in ArcGIS to SQL Database****Add Query Layer****In ArcMap:**

Open the New Query Layer Dialog

Go to ⇒ File ⇒ Add Data ⇒ Add Query Layer In the connection dropdown select your connection


**NOTE**

Figure 5.12: New Query Layer Dialog

## Details of the Query Layer

### Enter into the tool

- Choose connection
- Name the query
- Enter SQL query
- Press Next




Figure 5.13: Query Layer Dialog Filled

### More Details of the Query Layer

#### Enter into the tool

- Select unique identifier field
- Click Finish




Figure 5.14: Select Unique Identifier

---

## Open Results Table

The screenshot shows the ArcGIS Pro interface with the 'Open Results Table' dialog open. The 'Table Of Contents' pane on the left has a red box around the 'D001COUNTY WEB 18.DBO.NewQuery' entry under the 'Layers' section. The main window displays a table with 1666 rows. The columns are labeled: prnum, ownername1, ownerstreetaddr, ownercity, ownerstate, ownerzip, and ESRI\_OID. The data includes various property records such as 'WAGNER, LORI & ERIC' at 792 WEST AVENUE, WAYLAND MI 49348, and 'GUN LAKE COMMUNITY CHURCH' at 12200 WEST MILE 179, WAYLAND MI 49348.

prnum	ownername1	ownerstreetaddr	ownercity	ownerstate	ownerzip	ESRI_OID
56-004-001-00	WAGNER, LORI & ERIC	792 WEST AVENUE	WAYLAND	MI	49348	1
56-004-001-10	GUN LAKE COMMUNITY CHURCH	12200 WEST MILE 179	WAYLAND	MI	49348	2
56-004-002-00	WAYLAND UNION SCHOOLS	850 E SUPERIOR ST	WAYLAND	MI	49348	3
56-004-003-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	4
56-005-001-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	5
56-005-002-00	WAYLAND LLC	10454 W HAMPTON DR	LOWELL	MI	49351	6
56-005-002-10	ELLIOTT BAY HEALTHCARE REALTY II	617 EASTLAKE AVE E	SEATTLE	WA	98109	7
56-005-002-20	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	8
56-005-002-30	RIPARAN PROPERTIES LLC	878 E SUPERIOR ST	WAYLAND	MI	49348	9
56-005-002-40	RIPARAN PROPERTIES LLC	878 E SUPERIOR ST STE A	WAYLAND	MI	49348	10
56-005-002-50	THE FORTIFIED WAYLAND LLC	225 15TH AVE	WAYLAND	MI	49348	11
56-005-003-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	12
56-005-004-00	LATHROP THEODORE V & JUDITH	845 E SUPERIOR ST	WAYLAND	MI	49348	13
56-005-005-00	BREWER SUZANNE M	843 E SUPERIOR ST	WAYLAND	MI	49348	14
56-005-006-00	SHAW, KAREN S & HELUSA K	841 E SUPERIOR ST	WAYLAND	MI	49348	15
56-005-006-10	ARY DOUGLAS & JULIE	104 MARLO LN	WAYLAND	MI	49348	16
56-005-006-20	DUBAY DOUGLAS	102 MARLO LN	WAYLAND	MI	49348	17
56-005-007-00	CONNOR MOLLY	815 EAST SUPERIOR	WAYLAND	MI	49348	18
56-005-007-10	BENNETT, KAREN C & CARROW BIANCA	2514 EAST REPORTER LN	GRAND RAPIDS	MI	49508	19
56-005-008-00	DEAN, MARLA MATTHEW	101 MARLO LN	WAYLAND	MI	49348	20
56-005-007-21	JENSEN KRISTEN S	103 MARLO LN	WAYLAND	MI	49348	21
56-005-008-00	WAYLAND CHRISTIAN REF CHURCH	303 E ELM STREET	WAYLAND	MI	49348	22
56-005-009-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	23
56-005-010-00	FINANCIAL CARE/HEALTHCARE PROPERTY LLC	8181 WASHINGTON ROAD	WESTERVILLE	OH	43086	24
56-005-011-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	25
56-005-011-20	FERGUSON ROBERT K	5770 VENTURE PARK	KALAMAZOO	MI	49009	26
56-005-012-00	REDSTONE LAND DEVELOPMENT LLC	3330 GRAND RIDGE DR NE	GRAND RAPIDS	MI	49525	27
56-005-012-10	VANDERVOORD JOHN C & NANCY L	542 FOREST ST	WAYLAND	MI	49348	28
56-005-013-00	REDSTONE LAND LLC	265 OAK ST	WOODBURY	MI	49526	29
56-005-013-10	JESTER LLC	137 54TH AVE	SHERBLYVILLE	MI	49344	30
56-005-014-00	OPPERMAN JOHN C	125 OAK ST	WAYLAND	MI	49348	31
56-005-015-00	REDSTONE LAND DEVELOPMENT LLC	3330 GRAND RIDGE DR NE	GRAND RAPIDS	MI	49525	32
56-005-016-00	WILHELM MEYER LLC	131 OAK ST	WAYLAND	MI	49348	33
56-005-017-00	FULTON, KAREN A & BAIN ELLEN	137 OAK ST	WAYLAND	MI	49348	34
56-005-018-00	GUTIERREZ SAUL & ORTIZ CHRISTINA	119 OAK ST	WAYLAND	MI	49348	35
56-005-019-00	MICHIGAN STATE POLICE #66	544 N MAIN ST	WAYLAND	MI	49348	36
56-005-020-00	WILLIAMS TERESA A	540 N MAIN ST	WAYLAND	MI	49348	37
56-005-021-00	KEMP HOLDINGS LLC	304 108TH ST	CALEDONIA	MI	49716	38
56-005-022-00	SLOAN JOHN L & MARY L	329 WILLOW RUN DR	WAYLAND	MI	49348	

Figure 5.15: Query Results Table

Verify the Query by Looking at the Table

## Enterprise Geodatabase Maintenance

### Enterprise Geodatabase Compression Routine

#### Disconnect All Users

To disconnect the GIS Server, stop all services.

- In ArcGIS Server Manager ⇒ Site ⇒ GIS Server ⇒ Machines  
⇒ Stop all Services



Figure 5.16: Stop ArcGIS Server

Use the Search tool to find the Rebuild Indexes Tool




Figure 5.17: Find Rebuild Indexes Tool

### Rebuild Indexes

Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.18: Rebuild Indexes Tool Operation

### Recalculate Statistics

In the Analyze Datasets Tool:

Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.19: Recalculate Statistics

### Compress

Select Connection ⇒ Press OK




Figure 5.20: Compress




Figure 5.21: Rebuild Indexes Tool Operation

### Rebuild Indexes Again

### Recalculate Statistics Again

In the Analyze Datasets Tool:  
Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.22: Recalculate Statistics

## Managing Map Services

### To stop ArcGIS Server




Figure 5.23: Stop the GIS Server

### Launch ArcGIS Server Manager

### Fixing Damaged Services

#### Removing Lock Files

A blog about it <https://community.esri.com/thread/103710>

```
on juniper
C:\arcgisserver\config-store\services\ParcelViewer2\
PV2Adresses.MapServer\startup\JUNIPER.ALLEGANCOUNTY.ORG
```

This method works.

Steps:

- 1)stop arcgis server services.
- 2)delete the lock files(\*.glock and \*.rlock )  
in arcgisserver\config-store.
- 3) restart arcgis server service.
- 4)stop the pending stopping service and then start it.

## Managing Geodatabase Replicas

### Adding A New Feature Class To A Replica

Source: <https://support.esri.com/en/technical-article/000010345>

#### Summary

Currently, there is no out-of-the-box tool to add a feature class to an existing replica. With ArcGIS Desktop, one must either recreate the replica or if the workflow allows, replicate the new feature class as a separate replica.

A feature class or table can only be added to an existing replica (without recreating the replica) using ArcObjects code.

#### Steps:

The steps below outline how the recreate the replica using the Register Existing Data option in Desktop. These steps can be applied to both one-way and two-way replicas.

Synchronize the changes between parent and child replica geodatabases using the existing replica so that the data is identical in each database, then Unregister the replica in both geodatabases. For two-way replicas, ensure that changes are synchronized in both directions and there are no outstanding edits before unregistering the replica. Create/import the new feature class into the parent geodatabase, and add the GlobalID. Register the newly added data as versioned. Copy and paste the new feature class to the child geodatabase using ArcCatalog. Note: that the GlobalIDs must have already been added to the feature class.

For two-way replica or one-way full model, register the newly added data in child geodatabase as versioned. Using the parent geodatabase, add all the data that is to be replicated to a map in ArcMap. Click the 'Create Replica' tool on the Distributed Geodatabase toolbar. Select 'One way replica' or 'Two way replica' and click Next. Select 'Register existing data only'. Select the child geodatabase and specify a replica name. Click Next and click Finish. A new replica is created that includes the new data.

---

## Managing Geodatabase Versions

### Version Queries

#### SQL Queries

Four queries of SDEversions, SDEstates, sdestatelineages, and SDEcompress-log

```
use AC_Pub
select name, owner, version_id, state_id, parent_name
, parent_owner from
[AC_Pub].[dbo].[SDE_versions]
select * from [AC_Pub].[dbo].[SDE_states] order by state_id
select * from [AC_Pub].[dbo].[sde_state_lineages] order
by lineage_name,
lineage_id
select TOP(5) * from [AC_Pub].[dbo].[SDE_compress_log] order by
compress_end DESC
```

Query of SDEversions and SDEstates

```
use AC_Pub
SELECT v.version_id,v.creation_time,v.creation_time,
s.state_id, s.creation_time
FROM SDE_versions v
INNER JOIN SDE_states s ON v.state_id = s.state_id
```

---

## Finding Orphaned Versions

### ID and delete orphaned geodatabase versions

Follow the procedure: [Link to source](#)

Use SQL Server Management Studio to execute two queries and compare the results.

#### Step 1:

Execute the query:

```
use AC_Pub
SELECT ObjectID, name from dbo.GDB_ITEMS where
TYPE='4ED4A58E-621F-4043-95ED-850FBA45FCBC';
```

#### Step 2:

Execute the query:

```
use AC_Pub
SELECT name from [dbo].[SDE_versions]
order by name
```

Compare the tables

This graphic summarizes elements of the queries. Note the items from step




Figure 5.24: Find Orphan Versions

two that have no match in step one.

Orphaned versions can be removed by name in ArcGIS




Figure 5.25: Delete Orphan Versions

## MXD Management

### Find/Replace Text Object

#### Python Code

Python Code for finding and replacing a text object in a ArcGIS .mxd file. A snippet of this code may be found in the LayerUpdates/Zoning/processing folder. It is used to edit the .mxd files located there.

```
import arcpy
from arcpy import env

env.workspace = r"J:\Apps\Python\LayerUpdates\zoning\processing"
for mxdname in arcpy.ListFiles("*.mxd"):
    print mxdname
    mxd = arcpy.mapping.MapDocument(r"J:\Apps\Python\
        LayerUpdates\zoning\processing\\\" + mxdname)
    for elm in arcpy.mapping.ListLayoutElements
        (mxd, "TEXT_ELEMENT"):
        if elm.text.startswith('As ammended'):
            elm.text = elm.text.replace('As ammended',
                'As amended')
            print elm.text
    mxd.save()
del mxd
```

## 5.5 L<sup>A</sup>T<sub>E</sub>X Packages used by AC GIS

### Common Errors

Source:

<https://www.ocf.berkeley.edu/~latex/files/commonerrors.tex>

If you have every compiled a L<sup>A</sup>T<sub>E</sub>X document, chances are high you have received a few error messages. Sometimes they come from something as stupid and as easy to fix as forgetting a parenthesis or forgetting to end an environment. There are also a lot more cases where you have no idea what you have done wrong and it takes you a long time to find or even understand your error.

The purpose of this is to explain some of the common errors that may happen when compiling a L<sup>A</sup>T<sub>E</sub>X document and suggestions for what is probably going on and how to debug your document.

### The Form of an Error

There are two forms of errors: L<sup>A</sup>T<sub>E</sub>X errors and T<sub>E</sub>X errors. In both types of errors, the part after the error message will tell you where the error occurred. An example:

1.15 <offending text>

The 1.15 tells you what line the error occurred on and the text will tell you the text that caused the error.

### L<sup>A</sup>T<sub>E</sub>X Errors

The general form of an error in L<sup>A</sup>T<sub>E</sub>X is shown below:

! LaTeX error: <error message>

See the LaTeX manual or LaTeX Companion for explanation.

Type H <return> for immediate help.

...

The ! lets you know that the error has occurred. The error message will tell you what type of error you have committed. After the ellipses, you will find the line at which the error occurred and the text that caused the error (or at least the text where L<sup>A</sup>T<sub>E</sub>X found the error).

### T<sub>E</sub>X Errors

Errors may also have the following form:

! <error message>

These errors are formatted differently because they are error messages that came from T<sub>E</sub>X instead of L<sup>A</sup>T<sub>E</sub>X. After the error, you will still find the line that the error occurred in and the text of the error.

### Warnings

There are some error messages that are just warnings and will not stop or change the compilation of the document. Chances are you have seen them many times.

#### Underfull

The following error results when a line does not extend the width of the page, something L<sup>A</sup>T<sub>E</sub>X always tries to accomplish:

```
Underfull \hbox (badness 10000) in paragraph at lines  
104--107
```

This error message is just a warning and is not something to worry about. For the most part, when a line does not span the width of the page, it is because you have written something that you want to only cover part of the page.

#### Overfull

The following error results when a line extends beyond the width of the page:

```
Overfull \hbox (16.04988pt too wide) in paragraph at  
lines 30--31 [] [] \OT1/cmrr/m/n/12 I'm trying to put  
way too much text into a line in my document.
```

Usually this error comes from when you are using the `verbatim` package because it will not move to the next line if your text does not go to the next line. The easiest way to fix this is to find the place in your document where this is occurring and change the text so that it fits to the page.

This error will still show up if the text is still on the page but outside of the width of text that L<sup>A</sup>T<sub>E</sub>X has set. In this case, you are welcome to fix things so that the error does not show up or you can leave the text as it is.

### References

The following warnings occur when references are changed when L<sup>A</sup>T<sub>E</sub>X was compiled:

```
LaTeX Warning: Label(s) may have changed. Rerun to get  
cross-references right.
```

```
LaTeX Warning: There were undefined references.
```

```
LaTeX Warning: Reference 'name' on page 1 undefined on  
input line 15.
```

The way to fix these errors is to recompile the document again to correct the page numbers. Sometimes it is necessary to recompile the document twice to fix this error. You also may have defined a reference wrong, so you should check to make sure your label is correct.

---

**Beginning and Ending****Begin Ended by End**

This type of error occurs when each environment is not correctly started and ended. When you are missing an `\end` command, the following error will show up:

```
! LaTeX Error: \begin{enumerate} on input line 23
ended by \end{document}.
```

To fix this, you need to end the environment mentioned in the error with the appropriate command.

When you are missing a `\begin` command, the following will appear:

```
! LaTeX Error: \begin{document} ended by
\end{itemize}.
```

To fix this, you basically do the same thing as before, correctly beginning the environment mentioned in the error with the appropriate command.

**End Occurred Inside a Group**

The following error message will show up at the end of compiling a file if an environment is begun that is not ended:

```
(\end occurred inside a group at level <n>)
```

To fix this error, make sure you end the environment that was begun. The previous error is more helpful in finding the `\begin` statement.

**Ended by End of Line**

The following error will occur when you try to place a command inside a section heading:

```
! LaTeX Error: \verb ended by end of line.
```

```
See the LaTeX manual or LaTeX Companion for
explanation.
```

```
Type H <return> for immediate help.
```

```
...
```

There will be many errors of the same type for this mistake. In order to find where you put the command, look in the output file and find the last heading that shows up.

**Missing Begin Document**

This error is self-explanatory:

```
! LaTeX Error: Missing \begin{document}
```

---

### Errors Usually Caused by Bad Spelling

#### Unknown Control Sequence

This error results when you use a command (something that starts with a `\`) that is not recognized by L<sup>A</sup>T<sub>E</sub>X:

```
! Undefined control sequence.
```

Usually this error results from spelling a command incorrectly. Go to the line that is indicated by the error and fix the command.

#### Environment Undefined

This error results when you begin an environment with a `\begin` command that is not recognized:

```
! LaTeX Error: Environment verbatim undefined.
```

Usually you have just spelled your environment incorrectly, so you just need to fix it.

#### Bad File Name

This error results when you have mistyped the command `latex` or do not have L<sup>A</sup>T<sub>E</sub>X installed on your computer:

```
Bad command or file name
```

To fix this, correctly spell the command to compile your file or make sure that L<sup>A</sup>T<sub>E</sub>X is correctly installed on your computer.

#### Cannot Find File Name

This error occurs when you try to compile a file that the computer cannot find:

```
! I can't find file `sample'.  
<*> sample
```

```
Please type another input file name:
```

To fix this error, make sure you have spelled the file name correctly. You also may be in the wrong directory to compile the file, so check to make sure you are in the same directory as your file.

#### Fatal Errors

#### Runaway Argument

This error happens when a paragraph ends before a command's argument is done (i.e., L<sup>A</sup>T<sub>E</sub>X thinks that there is a missing `}`):

```
Runaway argument?
```

---

To fix this, you should use a different command to accomplish what you are trying to do. An example of this is to use `\bfseries` instead of `\bfseries` to make bold text in more than one paragraph.

This error can also be caused by a missing mandatory argument to a command.

### **Just an \***

This error normally occurs when you do not end your document with `\end{document}`:

\*

If you are prompted to enter something in, it is best to enter

`\end{document}`

and hope it works. Be sure to end your document with the appropriate command.

### **Emergency Stop**

This error happens when L<sup>A</sup>T<sub>E</sub>X will stop trying to compile your document due to a serious error:

**! Emergency stop.**

To fix this error, you will need to figure out what caused it to stop compiling. Chances are you forgot to end your document with `\end{document}`, but there might also be another reason for the emergency stop.

### **Please Type a Command or Say End**

This error happens when your file has ended prematurely:

(Please type a command or say ‘\end’)

The best way to deal with this type of error is to type

`\end`

or

`\end{document}`

in the case that the absence of that command caused the error. Usually if you have ended your document correctly, the error will result from a missing } or forgetting to end a verbatim environment.

---

### Graphics Errors

#### Too Many Unprocessed Floats

This error occurs when figures or tables (i.e., floats) have not been typeset:

```
! LaTeX Error: Too many unprocessed floats.
```

L<sup>A</sup>T<sub>E</sub>X can only have so many floats waiting to be typeset. In order to fix this error, make sure that you are placing your floats where you want them (with a [h] option) and not wanting too many on one page in sequence. Using the command \clearpage can be very useful in distributing floats correctly.

#### Unknown Graphics Extension

The following error occurs when you try to use a type of graphic that is not supported by the type of file that you are producing:

```
! LaTeX Error: Unknown graphics extension: .gif
```

In order to fix this error, you should change your graphics to the types that are supported by the type of file you are outputting or you will need to include the correct package to deal with that type of graphic. Sometimes you may have named the graphic poorly so that L<sup>A</sup>T<sub>E</sub>X will not recognize it as a graphic file.

#### Division by Zero

The following error occurs when the height of a graphic object is zero:

```
! Package graphics Error: Division by 0.
```

This is usually caused when you rotate an object with zero depth so that its height becomes zero. The best way to fix this is to use the keyword `totalheight` instead of `height`.

### Math Errors

#### Display Math Should End With \$\$

This error occurs when the displaymath or equation mode is ended incorrectly:

```
! Display math should end with $$
```

To fix this error, make sure that you end the displaymath or equation mode correctly (ending them with a \$ is not acceptable).

#### Bad Math Environment Delimiter

This error occurs when you do not have your delimiters correct in math mode:

```
! LaTeX Error: Bad math environment delimiter.
```

Usually this occurs when you forget to match a right delimiter with every left delimiter. This error may also happen when you forget to end an array.

---

**Missing Right**

This error occurs when you have a missing right parenthesis:

```
! Extra \right.
```

To fix this, you either need to add a `\right` command or you need to end an array.

**Missing Delimiter**

This error message occurs when a delimiter is missing:

```
! Missing delimiter (. inserted).
```

To fix this error, you need to make sure that you have a right delimiter for every left delimiter. If you do not want a right delimiter matching a left delimiter, you need to use “.” to not have an error message show up.

**Missing \$ Inserted**

The following error occurs when you try to use a character that can only be used in math mode, like `_` or `^`:

```
! Missing $ inserted
```

To fix this error, make sure you change the character to what it should be in text mode.

**Tabular Environment Errors****Misplaced Alignment Tab Character &**

This error occurs when you use `&` and when you are not in a tabular environment:

```
Misplaced alignment tab character &
```

To fix this error, you need to use `\&` to make a `\&`.

**Extra Alignment Tab**

This error occurs when you use too many tabs for the number of columns in a table:

```
! Extra alignment tab has been changed to \cr
```

The result of this error is that a new row is formed where the extra tab was. You should go back and fix your table so that the correct number of items in each row would show up.

---

### Argument Has an Extra }

These errors happen when an incorrect number of arguments to a tabular environment have been specified:

```
! Argument of \cline has an extra }.
```

```
! Argument of \multicolumn has an extra }.
```

To fix this error, make sure your arguments to the tabular environment are correct.

## Errors With Lists

### Missing Item

This error occurs when there is plain text in an environment that takes items:

```
! LaTeX Error: Something's wrong--perhaps a missing
\item.
```

To fix this error, make sure the plain text is changed into an item.

### Too Deeply Nested

This error occurs when there are too many lists for L<sup>A</sup>T<sub>E</sub>X to handle:

```
! LaTeX Error: Too deeply nested
```

L<sup>A</sup>T<sub>E</sub>X can only handle four levels of one type of list and six levels of different types of lists. To fix this, you need to use less levels of lists or define your own list environment.

## Miscellaneous Errors

### Only Used in the Preamble

This error occurs when you place a command in the body of a L<sup>A</sup>T<sub>E</sub>X document that should be placed in the preamble:

```
! LaTeX Error: Can be used only in the preamble.
```

To fix this error, just move the command to the preamble.

### There Is No Line/Page Here to End

This error occurs when you incorrectly use the commands that make a new line or a new page:

```
! LaTeX Error: There's a no line here to end.
```

You may just leave the command that is making a new line in place or you can take it out. Here, L<sup>A</sup>T<sub>E</sub>X is just trying to make sure that everything looks nice.

---

### Command Already Defined

This error occurs when you try to define a command that already exists:

**! LaTeX Error: Command ... already defined.**

To fix this, you need to define your command differently.

### Missing Number

This error is made when a number is expected as an argument and one is not provided:

**! Missing number, treated as zero.**

To fix this error, you need to find where a number is expected so that you can provide the correct one.

---

## float Package

usepackage

text

Simple Use

text

Options

text

Add optional arguments to the usepackage line:

Useful options:

- **OPTION NAME**

OPTION NOTE

- **OPTION NAME**

OPTION NOTE

Use with options

text

Commands

**Graphics Examples and Notes****CurlyFrame Example**

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
\geometry{tmargin=.75cm,bmargin=.25cm,lmargin=.8cm,rmargin=.2cm}
\usepackage{multicol}

\begin{document}

\curlyframe[.9\columnwidth]{

TEXTTTTTTTTTTTTTTTTTT

}

\end{document}
```

**RectFrame Example**

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
\geometry{tmargin=.75cm,bmargin=.25cm,lmargin=.8cm,rmargin=.2cm}
\usepackage{multicol}

\begin{document}
\begin{minipage}{.33\textwidth}
\centering
\scalebox{3}{\color{green!30!black!60}
\font\border=umrandb
\generalframe
{\border \char113} \% up left
{\border \char109} \% up
{\border \char112} \% up right
{\border \char108} \% left
{\border \char110} \% right
{\border \char114} \% lower left
{\border \char111} \% bottom
{\border \char115} \% lower right

```

---

```
{\centering
\includegraphics[height=1.25cm]{GIS_Logo_better.jpg}}
\end{minipage}
%\vspace{-8mm}

\end{document}
```

## graphicx Package

### usepackage

text

### Simple Use

text

### Options

text

Add optional arguments to the usepackage line:  
Useful options:

- **OPTION NAME**  
OPTION NOTE
- **OPTION NAME**  
OPTION NOTE

### Use with options

text

### Commands

## hyperref Package

### Introduction

Official [hyperref package documentation](#)

#### Notes:

- Add the *hyperref package* to the preamble **last** [2]
- To use Tex in a pdf bookmark: use

`\texorpdfstring{\\"}{}`

ie. `\paragraph{Sample Text\texorpdfstring{\\"}{}}`

Creates a new line without an error.

`\usepackage[options]{hyperref}`

---

## Simple Use

Use `\href{URL}{DESCRIPTION}` to add a link with description

`\href{https://www.latex-tutorial.com}{Website with tutorials}`  
produces:

Website with tutorials

## Options

Add optional arguments to the `\usepackage` line:

Useful options:

- **pdftex**  
enables other options like breaklines
- **breaklinks**  
allow links to be broken across several lines  
eg. <https://lists.gnu.org/archive/html/emacs-orgmode/2013-06/msg00776.html>
- **colorlinks**  
Colors the text of links and anchors.(default is false)
- **linkcolor**  
Color for normal internal links(default is red).
- **anchorcolor**  
Color for anchor text.
- **citecolor**  
Color for bibliographic citations in text.
- **urlcolor**  
Color for linked URLs

## Use with options

```
\usepackage[breaklinks,colorlinks,citecolor=blue,
urlcolor=green]{hyperref}
```

## Commands

`\href{URL}{text}` Makes text a link to URL.

To put a file path in text:

eg:

[Official hyperref package documentation](#)  
(documentation Pt.4 pg.15)

`\href[options]{URL}{text}`

---

Options:

- absolute

```
\href{C:/AC/jalapeno/documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref doc}
```

- relative **Note: relative path must be from final pdf location**

```
\href{../../../../documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref package doc}
```

\*This path works from main document

```
\href{../../documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref package documentation}
```

\*This path works from subsection document

`\hyperref[label]{text}`

Makes text a link to where `\ref{label}` would point.

`\hypertarget{name}{text}`

Sets an anchor on text with the label name.

`\hyperlink{name}{text}`

Makes text a link that takes you to the anchor labeled name.

\*Pair with `\hypertarget`.

`\phantomsection`

Used in conjunction with

`\addcontentsline`

to make the correct link in the Table of Contents.

---

**import Package****usepackage**

text

**Simple Use**

text

**Options**

text

Add optional arguments to the usepackage line:

Useful options:

- **OPTION NAME**

OPTION NOTE

- **OPTION NAME**

OPTION NOTE

**Use with options**

text

**Commands**

## standalone Package

### Introduction

[Link to official standalone documentation](#)

*standalone* provides a **package** and a **class**

- The *standalone* **package** is used for:

- Main documents that will input or import sub documents.
- For example:

```
\usepackage[subpreambles=false]{standalone}
```

\* Ignores preambles of imported sub documents [3, pg.4]

- the *standalone* **class**:

- Is a document class
- Provides standalone / subdocument switches and options
- For example:

```
\documentclass[class=article]{standalone}
```

\* behaves as an article when standalone  
 \* makes document available for import into a master document

### Simple Use

- The *standalone* **package**

- In the main document:

```
\documentclass[openany]{book}
```

```
\preamble...
```

```
\usepackage{standalone}
```

- the *standalone* **class**:

- In any subdocument:

```
\documentclass[class=article]{standalone}
```

```
\preamble...
```

## Options

- The *standalone* package
  - **subpreamble**
    - \* default value of subpreambles is *false*
- the *standalone* class:
  - **crop**
  - **titlepage**
  - **twoside**
    - \* Makes pagination style match book
    - \* default value is *false*
  - **multi**
    - \* `multi=true|false`
    - \* `multi={<environment name>, ...>}`
  - **float**

### Use with options

- the *standalone* package:
  - `\usepackage[subpreambles=false]{standalone}`
- the *standalone* class:
  - `\documentclass[class=article , crop=false, titlepage, twoside, multi={itemize, figure, verbatim}, float=false]{standalone}`

## Commands

---

## wrapfig Package

### usepackage

text

### Simple Use

text

### Options

text

Add optional arguments to the usepackage line:  
Useful options:

- **OPTION NAME**  
OPTION NOTE
- **OPTION NAME**  
OPTION NOTE

### Use with options

text

### Commands

## 5.6 L<sup>A</sup>T<sub>E</sub>X Templates

### L<sup>A</sup>T<sub>E</sub>X Section Template

```
\documentclass[class=report , crop=false, multi={itemize, figure}, float=false]{standalone}%Experiment  
\documentclass[class=book , crop=false]{standalone}  
  
\input{../../../../../preamble}  
  
\def\titlename{Section Template}  
  
\title{\input{../../../../commonTitle}} % closing brace for title  
  
\begin{document}% Document Begins  
  
\input{../../../../commonFront} % provides standalone options  
  
\section{SECTION NAME HERE}  
  
\subimport{RELATIVE PATH TO NEW Section/}{NEW SUBSECTION Subsection.tex}  
  
%eg.  
\subimport{latexTemplatesSection/}{subsectionTemplateSubsection.tex}  
% etc...  
  
\end{document}
```

### L<sup>A</sup>T<sub>E</sub>X Subsection Template

```
\documentclass[class=book , crop=false]{standalone}  
  
\input{../../../../../preamble}  
  
\def\titlename{Subsection Template}  
  
\title{\input{../../../../commonTitle}} % closing brace for title  
  
\begin{document}% Document Begins  
  
\input{../../../../commonFront} % provides standalone options  
  
% NEW INFO GOs HERE.  
\subsection{Subsection Template}  
\medskip
```

---

**5.7 PDF Tools used by AC GIS**

---

## PDF Optimizer

### Purpose and Summary

**Workflow Purpose:** Optimization of a large number of pdf docs.

**Workflow Summary:** Uses Python to create a list of .pdf docs in a folder and creates a batch file to optimize the pdfs in the list to another location. The batch process calls ghost script for the optimization.

### requirements

Open source software:

- ghostscript
- python 2.7 and a Python IDE
- A text editor

paragraphPython(2.7)

**Note:** The output of this script is bdoc.txt, Save as a .bat to execute the optimize.

### Script that creates a batch file

```
import os, sys

project = os.path.dirname(os.path.dirname(__file__))
processing = os.path.join(project, 'processing')
#source = os.path.join(project, 'source')
build = os.path.join(project, 'build')
sourcepdf = os.path.join(build, '20180716')

inString1 = "gswin32 -sDEVICE=pdfwrite -dCompatibilityLevel=1.4
-dPDFSETTINGS=/ebook -dNOPAUSE -dQUIET -dBATCH
-sOutputFile=J:\\\\Projects\\\\2018ParcelAtlas\\\\build\\\\optimized\\\\"

inString2 = " J:\\\\Projects\\\\2018ParcelAtlas\\\\build\\\\20180716\\\\"

batchdoc = os.path.join(processing, "bDoc.txt")

# Main
#####
if __name__ == "__main__":
    list1 = os.listdir(sourcepdf)
    l = open(batchdoc, 'w')
    for i in list1:
```

---

```
newi = i[1:]
print newi
t = inString1 + newi + inString2 + i + "\n"
print t
l.write(t)

l.close()
```

### ghostscript

**About** ghostscript is used for the optimization. ghostscript is an interpreter for the PostScript language and for PDF [1].

**Licensing** ghostscript is available opensource under AGPL conditions. more information can be found [here](#).

**Download** ghostscript can be downloladed [here](#).

### Windows batch files

A line from the batch file looks like:

```
gswin32 -sDEVICE=pdfwrite -dCompatibilityLevel=1.4
-dPDFSETTINGS=/ebook -dNOPAUSE -dQUIET -dBATCH
-sOutputFile=J:\Project\2018ParcelAtlas\build\optimized\
02-001-001-00.pdf J:\Projects\2018ParcelAtlas\build\20180716
\_02-001-001-00.pdf
```

---

## 5.8 QGIS Tools

### Using COGO Tools in QGIS

#### Set up the Azimuth and Distance Plugin (Azd Plugin).

In the Plugins drop down(1), under the topography group select the **Azd Plugin(2)**(see fig.).




Figure 5.26: launch plugin

Note here which layer is active (see fig.).




Figure 5.27: check active layer

If necessary, left click the layer ***traverse 1*** in Layer Panel to activate it(see fig.).




Figure 5.28: activate layer

**Configure Options** On Options Tab: Select Boundary, Bearing, Feet, and Degree radio buttons.




Figure 5.29: Plugin Options

**Using the tool** Boundary descriptions are entered into the Drawing Tab. Azimuth (bearing) and Distance are the important boxes (Set Offset = 0 and Zenith = 90 and ignore)(see below).




Figure 5.30: Entering Bounds

### Configure editing environment

Use Settings Dropdown and Snapping Options to enable snapping to Sections, Quarter Sections, and or Parcels if desired (see fig.).




Figure 5.31: Configure editing environment

### Locate Point of Commencement

To get to the Point of Commencement,

Use **any combination** of the following methods:

- Using Reference Layer
- Using Measuring Tool
- Search by Parcel Number (Search Layers Plugin)
- Draw COGO lines (Azd Plugin)(as described earlier)

**Using Reference Layer** Use reference layers; Units, AC\_SectionsQu, Sections, and Parcels. Toggle layers on and off in Layers Panel and zoom in and out with mouse wheel.

**Using Measuring Tool** Use the measuring tool, make sure to set units to feet. To exit current measurement right click (see fig.).




Figure 5.32: Measuring Tool

### Search by Parcel Number (Search Layers Plugin.)

To Launch Search Layers Plugin:  
 In Plugins dropdown:  
 Enable the **Search Layers** Plugin. (see fig.)




Figure 5.33: Search Layers Plugin

Enter parcel number (with dashes), Set layers, and set search field.(see fig.)




Figure 5.34: Search Layers Setup

## **Part IV**

## **Resources**



## A.1 Geography 101

Foundations of geography

### A Primer on Coordinate Systems Commonly Used in Michigan

[A Primer on Coordinate Systems Commonly Used in Michigan](#)

## B.2 ESRI Resources

Product Documentation

### Functionality Matrices

arcgis 10.5 Enterprise Functionality Matrix [Document](#) [Link](#)  
arcmap 10.5 Functionality Matrix [Document](#) [Link](#)



# Bibliography

- [1] Artiflex, *ghostscript.com*, 2018. 126
- [2] na, *The hyperref package*, CTAN, na ed., na na. 116
- [3] Martin Scharrer, *The standalone package*, CTAN, 1.3a ed., 03 2018. 120



# Glossary

**IDE** Integrated Development Environment. 106

**map projection** Representing a sphere on a flat surface. 11, 106

**sample** an example. 106



# **Index**

ArcGIS Enterprise 10.5 functionality matrix, 105

ArcMap 10.5 functionality matrix, 105

coordinate systems, 105

ESRI Product documentation, 105

functionality matrix, 105

georef, 105

map projections, 11

Michigan, 105

State Plane, 105