

What We Do

Allegan County GIS
www.allegancounty.org/gis

December 20, 2018

Contents

Contents	ii
I Brand	1
1 Awards	3
1.1 The GIS Champion Award	3
GIS Champion	3
GIS Champion Award	3
Background	3
Statement of Problem	4
Analysis	4
GIS Champion Award Code	5
II Methods	9
2 Documentation	11
2.1 About Documentation	11
How Jalapeño Works	11
Colors	11
Blues	11
Golds	11
Oranges	11
Geens	12
Others	12
General Notes:	13
Project File Structure:	13
Using The Glossary	14
Glossary Requirements	14
Creating a new glossary entry	14
Rebuilding the glossary	14
Using glossary terms in a subdocument:	14

To use a glossary term	15
To add the glossary to the subdocument:	15
Using The Bibliography(References)	15
Bibliography requirements	15
Creating a new bibliography entry	15
Rebuilding the bibliography	15
To cite a bibliography source in a subdocument:	16
.	16
Adding the bibliography to the subdocument	16
Using The Index	16
Index requirements:	16
Creating a new index entry	16
Rebuilding the index	17
*Note:	17
Access the index from a subdocument	17
Using an index term	17
To add the index to the subdocument:	17
Using the Appendices	17
2.2 Document Storage Concepts	18
GIS File Standard	18
Folders inside the project folder	18
3 Team Concept	19
3.1 Team Structure	19
Paired Programming	19
III Service	21
4 Applications	23
4.1 Applications for Treasurer Dept.	23
Forfeiture Data Collector	23
Problem and Analysis	23
Background	23
Statement of Problem	23
Analysis	23
Design	24
Overview	24
Forfeiture App Summary	25
Technologies Used in The Forfeiture App .	26

BSA Data	26
ArcGIS Desktop	26
ArcGIS Collector	26
Enterprise Geodatabse	26
ArcGIS Portal	26
Data Details	28
ForfeitureParcels Feature Class	29
Webmap Details	30
Feature Layer Details	30
Basemap Details	31
Hard Copy Record	32
ArcGIS Server	32
Administrative Manual	33
Annual Setup	33
Add Query Layer	34
Details of the Query Layer	35
Select a Unique Identifier	36
Add Parcels Layer to the map	38
Create Join	39
Export Joined Features	40
Load data to forfeitureParcels	41
Match these fields	43
Data Setup	45
Create Attachments	46
Setup Users in ArcGIS	47
Add New User to Feature Dataset	48
Extend Privileges for New User	49
Setup Users in Portal for ArcGIS	50
Add Members to Portal	51
Enter required info	52
Manage Treasurer Group	53
Share Portal Content	54
Schema Change Procedure	55
Form Edits Procedure	56
User Manual	57
Collection Device Setup	57
Collector Application Setup Details	57
Install Collector for ArcGIS	57
Configure Collector	58
Download the Forfeiture Field Map	59
Choose Map Detail	61
Open Camera Application Setup Details	62
Install Open Camera	62

Configure Open Camera	63
Daily Preprocessing Routine	65
Execute Preprocessing Script	65
Synchronize the Forfeiture Field Map	66
Forfeiture Data Collection	67
Forfeiture Parcels Data Details	67
Device 1 Field Operation	68
Device 2 Field Operation	76
Daily Postprocessing Routine	78
Synchronize Webmap	78
Execute Postprocessing Script	78
Software	81
ESRI Licensed Products	81
ArcDesktop	81
Enterprise ArcGIS Deployment	81
Collector for ArcGIS	81
Other Software	81
Open Camera for Android	81
5 Tools	83
5.1 BSA Support	83
Adding a Layer to the BSA GIS	83
Add an Imagery Layer	83
BSA Program Setup	83
Setup Map Collections	84
Layers Setup	85
Select Layer Type	86
Add Layer From Local Drive	87
5.2 Core Data	88
Control Points	88
Editing Control Points	88
Fabric Point Move to Feature Addin	88
Configure Addin	88
5.3 ESRI Tools	92
COGO Tools in ArcGIS	92
5.4 GIS Administration	93
New Connections in ArcCatalog	93
Install SQL Server on client machine	93
Connect ArcGIS to a SQL Server Database	95
New Connection Dialog	96
Create Query in ArcGIS to SQL Database	97
Add Query Layer	97
Details of the Query Layer	98

More Details of the Query Layer	99
Open Results Table	100
Enterprise Geodatabase Maintenance	101
Enterprise Geodatabase Compression Routine .	101
Disconnect Users	101
Rebuild Indexes	103
Recalculate Statistics	104
Compress	105
Rebuild Indexes Again	106
Recalculate Statistics	107
Managing Map Services	108
Stopping the GIS Server	108
Fixing Damaged Services	109
Use the ArcGIS Server Account Utility .	109
Remove Lock Files	115
Managing Geodatabase Replicas	116
Adding A New Feature Class To A Replica .	116
Summary	116
Steps	116
Managing Geodatabase Versions	118
Version Queries	118
SQL Queries	118
Orphaned Versions	119
Remove orphaned versions	119
MXD Management	122
Find/Replace Text Object	122
Python Code	122
5.5 L ^A T _E X Packages	123
Common Errors	123
The Form of an Error	123
L ^A T _E X Errors	123
T _E X Errors	124
Warnings	124
Underfull	124
Overfull	124
References	125
Beginning and Ending	125
Begin Ended by End	125
End Occurred Inside a Group	126
Ended by End of Line	126
Missing Begin Document	127
Errors Usually Caused by Bad Spelling . . .	127
Unknown Control Sequence	127


Environment Undefined	127
Bad File Name	127
Cannot Find File Name	128
Fatal Errors	128
Runaway Argument	128
Just an *	128
Emergency Stop	129
Please Type a Command or Say End	129
Graphics Errors	129
Too Many Unprocessed Floats	129
Unknown Graphics Extension	130
Division by Zero	130
Math Errors	130
Display Math Should End With \$\$	130
Bad Math Environment Delimiter	131
Missing Right	131
Missing Delimiter	131
Missing \$ Inserted	132
Tabular Environment Errors	132
Misplaced Alignment Tab Character &	132
Extra Alignment Tab	132
Argument Has an Extra }	133
Errors With Lists	133
Missing Item	133
Too Deeply Nested	133
Miscellaneous Errors	133
Only Used in the Preamble	134
There Is No Line/Page Here to End	134
Command Already Defined	134
Missing Number	134
float Package	135
usepackage	135
Simple Use	135
Options	135
Use with Options	135
Commands	135
Graphics Examples and Notes	136
Curly Frame	136
Rectangle Frame	136
graphicx Package	138
usepackage	138
Simple Use	138
Options	138

	Use with Options	138
	Commands	138
	hyperref Package	138
	Introduction	138
	Simple Use	139
	Options	139
	Use with Options	140
	Commands	140
	import Package	142
	usepackage	142
	Simple Use	142
	Options	142
	Use with Options	142
	Commands	142
	standalone Package	143
	Introduction	143
	Simple Use	143
	Options	144
	Use with Options	144
	Commands	144
	wrapfig Package	145
	usepackage	145
	Simple Use	145
	Options	145
	Use with Options	145
	Commands	145
5.6	L ^A T _E X Templates	146
	L ^A T _E X Section Template	146
	L ^A T _E X Subsection Template	146
5.7	PDF Tools	148
	PDF Optimizer	149
	Pupose and Summary	149
	requirements	149
	ghostscript	150
	About	150
	Licensing	150
	Download	150
	Windows batch files	151
5.8	QGIS Tools	152
	Using COGO Tools in QGIS	152
	Set up the Azimuth and Distance Plugin	152
	Configure Options	154
	Using the tool	155

Configure editing environment	156
Locate Point of Commencement	157
Using Reference Layer	157
Using Measuring Tool	158
Search by Parcel Number	159
IVResources	161
A.1 Geography 101	163
Coordinate Systems for Michigan	163
B.2 ESRI Resources	163
Funcionality Matrices	163
References	165
Glossary	165

Part I

Brand



1

Awards

1.1 THE GIS CHAMPION AWARD

GIS CHAMPION

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

GIS CHAMPION AWARD

Background

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique

neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Statement of Problem Analysis

lem

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

GIS Champion Award Code

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
%\geometry{tmargin=.75cm,bmargin=.25cm,
%lmargin=.8cm,rmargin=.2cm}
\geometry{tmargin=.25in,bmargin=.25in,
    lmargin=.25in,rmargin=.25in}
\usepackage{multicol}
\setlength{\columnseprule}{0.4pt}
\columnwidth=0.3\textwidth

\begin{document}
\centering
\scalebox{2.9}{
\color{green!30!black!60}
\begin{minipage}{.33\textwidth}
\font\border=umrandb
\generalframe
{\border \char113} % up left
{\border \char109} % up
{\border \char112} % up right
{\border \char108} % left
{\border \char110} % right
{\border \char114} % lower left
{\border \char111} % bottom
{\border \char115} % lower right
\centering
\includegraphics[height=1.5cm]{GIS_Logo_better.jpg}

\vspace{-8mm}

\curlyframe[.9\columnwidth]{

\textcolor{green!10!black!90}{\small Allegan County GIS Services}
\vspace{.005in}
}
```

```
\textcolor{green!10!black!90}{  
  \tiny Recognizes}\  
  \%\\smallskip  
  \\vspace{.005in}  
  \\underline{\textcolor{green!30!black!60}{  
    \textcolor{green!30!black!60}{Brian Redmond}}}  
  \\  
  \%\\smallskip  
  \\tiny Information Services Technician  
  
  \%\\smallskip  
  \textcolor{green!10!black!90}{  
    {  
      \\  
      \\tiny for Excellence in  
    }  
    \%\\smallskip  
    \\  
    \\textcolor{black}{\\normalsize \\textsc{Enabling  
      Employee Experiences}}  
    \\  
    \\vspace{.1in}  
    \\textcolor{green!10!black!90}{  
      {  
        \\tiny on this day  
        \\itshape September 21, 2018  
      }  
  
      \\vspace{.1in}  
  
      {\\color{green!10!black!90}  
        \\scalebox{.6}{  
          \\begin{tabular}{ccc}  
            \\cline{1-1}  
            \\cline{3-3}  
            \\  
            Neil Besteman & & Bryan May \  
            GIS Manager & & GIS Analyst \  
            \\end{tabular}  
        } % closes scalebox{.6} arg
```

```
} % closes blue!40!black
} % closes curlyframe arg
} % closes centering
\end{minipage}
} % closes scalebox{2.8} arg

\end{document}
```


Part II

Methods

— 2 Documentation

2.1 ABOUT DOCUMENTATION

HOW JALAPEÑO WORKS

COLORS

Blues

HeaderBlueA _____
HeaderBlueB _____
HeaderBlueC _____
HeaderBlueD _____
HeaderBlueE _____

Golds

HeaderGoldA _____
HeaderGoldB _____
HeaderGoldC _____
HeaderGoldD _____
HeaderGoldE _____

Oranges

HeaderOrangeA _____
HeaderOrangeB _____
HeaderOrangeC _____
HeaderOrangeD _____

HeaderOrangeE _____

Greens

HeaderGreenA _____

HeaderGreenB _____

HeaderGreenC _____

HeaderGreenD _____

HeaderGreenE _____

Others

HyperlinkBlue1 _____

graphicOrange _____

GENERAL NOTES:

- jalapeno folder is a git package.
<https://github.com/nbesteman/jalapeno>
- Project is coded with relative paths and jalapeno can be located anywhere.

PROJECT FILE STRUCTURE:

...\\jalapeno\\..

folder	description
documentation	resources used in Jalapeño
processing	.tex documents and build folders
source	common image files

...\\jalapeno\\documentation\\..

folder or file	description
moduleTemplates	.tex templates
packageDocs	L ^A T _E X documentation
references	reference and appendix resources
unsorted	catch all for unsorted documentation
BookStructureMM.mm	A mindmap of jalapeno

...\\jalapeno\\processing\\..

folder or file	description
...Part	folders of book <i>parts</i>
build	L ^A T _E X folder for .pdf output and temp files
build\\referenceEntries.bib	entries that appear in references
commonTitle.tex	code for all title pages
fullCompile.sh	shell script to compile GISDocumentation.tex
GISDocumentation.tex	master document code
glossaryEntries.tex	entries that appear in glossary
indexEntries.tex	entries that appear in the index
preamble.tex	preamble code for all documents

*Note about referenceEntries.bib

Any reference entries built here can be cited in any .tex document in the project.

USING THE GLOSSARY

Glossary Requirements

Glossary commands require a Perl interpreter. Activeperl is a free Perl interpreter and can be downloaded from:

<https://www.activestate.com/activeperl/downloads> (A typical installation adds Perl to your path). Compiling the glossary requires running the makeglossaries command either in a L^AT_EX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeglossaries to create an .gls file. After the .gls file is created, PDFLatex must be run again to insert the glossary at the \printglossaries location.

Creating a new glossary entry

To **create a new glossary entry**: Add an entry to glossaryEntries.tex. Save it there and then use the makeglossaries command to recompile the .gls file.

Rebuilding the glossary

To Recompile the .gls. In the (main document)build folder:

- Launch command prompt
- enter command: **makeglossaries GISDocumentation***

*Note:

This command reads the .aux file and creates the .gls file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

Using glossary terms in a subdocument:

In the subdocument you must add code to input the glossaryEntries file. For example:

After the line:

```
\input{../../../../../preamble}
```

Add the line:

```
\input{../../../../glossaryEntries}
```

To use a glossary term in the subdocument:

In place of the term, use code referencing the key (in the glossaryEntries file):

- \gls{key}

To add the glossary to the subdocument:

- Add the line \makeglossaries to the preamble of the subdocument.
- Add the line \printglossaries to the subdocument.
- Run makeglossaries in command line on the subdocument similar to how is described above.

USING THE BIBLIOGRAPHY(REFERENCES)

Bibliography requirements

Compiling the bibliography requires running bibtex either in a L^AT_EX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by bibtex to create a .bbl file. After the .bbl file is created, PDFLatex must be run again to insert the bibliography at the \bibliography location.

For example, the command:...\\bibliography{referenceEntries}
...places the bibliography called referenceEntries.bib which must be in the same folder as the project .aux file.

Creating a new bibliography entry

To create a new bibliography entry: Add an entry to referenceEntries.bib. Save it there and then use bibtex to recompile the .bbl file.

Rebuilding the bibliography

To Recompile the .bbl. In the (main document)build folder:

- Launch command prompt
- enter command: **bibtex GISDocumentation**

*Note:

This command reads the .aux file and creates the .bbl file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

To cite a bibliography source in a subdocument:

In the place that you want the citation:

- `\cite[pg. #]{key}`

Adding the bibliography to the subdocument

- Similar to adding to the master document but not documented here.

USING THE INDEX

Index requirements:

Compiling the index requires running the makeindex command either in a L^AT_EX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeindex to create an .idx file. After the .idx file is created, PDFLatex must be run again to insert the index at the \printindex location.

Creating a new index entry

To create a new index entry: Add an entry to indexEntries.tex. Save it there and then use the makeindex command to recompile the .idx file.

Rebuilding the index

To Recompile the .idxIn the (main document)build folder:

- Launch command prompt
- enter command: **makeindex GISDocumentation***

*Note:

This command reads the .aux file and creates the .idx file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail. Run PDFLatex first

Access the index from a subdocument

In the subdocument you must add code to input the indexEntries file.

For example:

After the line:

```
\input{../../../../../preamble}
```

Add the line:

```
\input{../../../../../indexEntries}
```

To use a index term in the subdocument:

In place of the term, use code referencing the key (in the indexEntries file):

- \index {key}

To add the index to the subdocument:

- Add the line \makeindex to the preamble of the subdocument.
- Add the line \printindex to the subdocument.
- Run makeindex in command line on the subdocument similar to how is described above.

USING THE APPENDICES

2.2 DOCUMENT STORAGE CONCEPTS

GIS FILE STANDARD

FOLDERS INSIDE THE PROJECT FOLDER

Lets talk about

- archive
- build
- delivered
- documentation
- processing
- source

— 3 —

Team Concept

3.1 TEAM STRUCTURE

PAIRED PROGRAMMING

A paragraph about pp from Joy Inc.

Part III

Service

4

Applications

4.1 APPLICATIONS FOR TREASURER DEPT.

FORFEITURE DATA COLLECTOR APPLICATION

PROBLEM AND ANALYSIS

Background

Treasurer department has an annual responsibility to properly document the tax forfeiture process. The LIS Department built an application in MS Access and MapInfo that consumed a daily export from BSA and was deployed to the field on a laptop. A digital camera was used for site photos and later imported into the laptop.

Analysis

Forfeiture App will facilitate: *Mobile data collection on a handheld device,; (Mobile Interface)* and an *in office workflow to complete data processing, (Pre and PostProcessing)*

Mobile Interface

- Synchronize with data in the office (online)
- Collect data and photos of forfeiture sites (offline)
- Synchronize the collected data with data in the office (online)

Pre & Post Processing

- Produce and print a form for each site visited with required data and images

DESIGN

Overview

The key data set : **Forfeiture Parcels**
is used through the workflow




Figure 4.1: Project Design

Forfeiture App Summary

There are three parts to the daily routine:

1. Preprocessing (in the office):
 - Export current forfeiture list from BSA
 - Update Forfeiture Parcels with BSA export
 - Update Forfeiture Parcels with contaminated sites information
 - Synchronize Forfeiture Parcels to Mobile Interface
2. Field data collection with Mobile Interface:
 - Aids in navigation
 - Provides a Checklist of data points for each site
 - Attaches photos for each site
 - Save results for synchronization in post-processing
3. Post-processing (in the office)
 - Synchronize data and images collected in Mobile Interface to Forfeiture Parcels
 - Export form for each site
 - Print form for each site
 - Update BSA data

Technologies Used in The Forfeiture App

BSA Data

Details of parcels in the forfeiture process are managed in BSA Delinquent Tax.net. The Treasurer office does a BSA export of the parcels in need of a site visit in the preprocessing.

figured to work offline (without an internet or cellular connection) by syncronizing before and after fieldwork. The user collects the necessary information on each forfeiture parcel in the field disconnected, and then uploads the changes when reconnected.

ArcGIS Desktop

Tools are designed to preprocess and postprocess forfeiture parcel data for fieldwork. The user will execute a preprocess script tool that prepares the data for field deployment. After fieldwork, a post process script tool synchronizes data from the fieldwork with the live data on the Allegan County network.

Enterprise Geodatabase

Live data from a publishing geodatabase (ACPub), running on SQL Server database server (acintsql01) provides access to Forfeiture Parcels

ArcGIS Portal

Forfeiture Parcels is served as a feature service (REST service) named TaxReversionParcels. A webmap on Portal, called the Forfeiture Field Map consumes the TaxReversionParcels exposing the data to editing. The Forfeiture Field Map is configured to work in the ArcGIS Collector App.

ArcGIS Collector

A free mobile application developed and tested on Android is deployed to the field for data collection. The application is con-




Figure 4.2: Technology Design

DATA DETAILS

The data is located in a geodatabase called ACPUB. ACPUB is on SQL Server ACINTSQL01.

Forfeiture Parcels Data



Figure 4.3: Live Data Location

Contamination Data




Figure 4.4: Contamination Feature Class

ForfeitureParcels Feature Class

Attribute Details			
Field Name	Field Alias	Entry Type	Note
PropertyNumber	Property Number	Prefilled	NA
Need2Print	Print Today	Dropdown	Yes or No
InspectionDate	Inspection Date	Autofill or Dropdown	NA
Inspector	Inspector	Dropdown	NA
Address	Address	Prefilled	NA
Status	Status	Dropdown	NA
StatusNotes	Status Notes	Open Entry	120Char
Roadfrontage	Road Frontage	Dropdown	Yes or No
AccessVia	Access Via	Open Entry	30Char
Agent	Agent	Open Entry	30Char
AgentContact	Agent Contact	Open Entry	30Char
PictureComments	Picture Comments	Open Entry	50Char
PropertyInUse	Property In Use	Dropdown	Yes or No
UseNotes	Use Notes	Open Entry	120Char
PropertyMaintained	Property Maintained	Dropdown	Yes or No
PropMaintNotes	Property Maintained Notes	Open Entry	120Char
PropertyContaminated	Property Contaminated	Prefilled	Preprocessing
PropertyContaminatedNotes	PropertyContaminatedNotes	Prefilled	Preprocessing
AdjacentPropertyContaminated	Adjacent Property Contaminated	Prefilled	Preprocessing
AdjPropertyContaminatedNotes	Adj Property Contaminated Notes	Prefilled	Preprocessing
PropertyForSale	Property For Sale	Dropdown	Yes or No
GlobalID	GlobalID	NA	NA
PostedDate	Posted Date	Dropdown	Date
Posted	Posted	Prefilled	NA
InList	In List	Prefilled	Preprocessing
PostedInList	Posted In List	Prefilled	Preprocessing
Acres	Acres	Prefilled	NA
Class	Class	Prefilled	NA

Table 4.1: Dataset Details

Webmap Details

The Forfeiture Field Map is made up of a basemap and a feature layer.



Figure 4.5: Web Map Details

Feature Layer Details

TaxReversionParcels has been configured for offline use.




Figure 4.6: Feature Layer Details

Basemap Details

- A tiled basemap service is used
- The infoserv user credentials are used for sharing
- The url for the shared service is:

https://tiledbasemaps.arcgis.com/arcgis/rest/services/World_Street_Map/MapServer

The screenshot shows the ArcGIS online interface for the "World Street Map (for Export)" layer. At the top, there's a navigation bar with links for ArcGIS, Pricing, Map, Scene, and Help. On the right side of the header are "Sign In" and a search bar. Below the header, the title "World Street Map (for Export)" is displayed, along with a small thumbnail image of a map and a "Overview" button.

The main content area contains a detailed description of the layer, stating it presents highway-level data for the world and street-level data for many areas around the world. It mentions support for exporting basemap tiles for offline use and requires an ArcGIS Online Subscription. Below this, there are buttons for "Tile Layer by Esri" and "Authoritative".

Below the description, there are sections for "Created: Oct 15, 2013 Updated: Aug 15, 2018 View Count: 39,772" and "Details". The "Details" section includes information about the source being a Map Service, its size (1 kb), and a five-star rating. It also features social sharing icons for Facebook, Twitter, and LinkedIn.

On the right side of the page, there are sections for "Owner" (listing Esri as the owner) and "Tags" (listing various geographical and thematic terms like World, Global, Europe, North America, United States, Southern Africa, Asia, South America, Australia, streets, street map, tile package, basemap, highways, roads, transportation, landmarks, parks, community, and general availability, export).

Figure 4.7: Basemap Source Description

HARD COPY RECORD

screenshots: arcmap map arcmap tools portal screenshots sql server
mgt screen shots phone screenshots

ArcGIS Server

ADMINISTRATIVE MANUAL

Annual Setup

A new dataset for forfeiture parcels must be created each year. The forfeiture information comes from BSA Forfeitures.net and the parcel geometry and other attributes comes from ACParcelsCombined.

To get the BSA Forfeiture data, create a table query for a certain year.

First, clear the features from the existing ForfeitureParcels dataset

- Use the Delete Feature Tools
- In the tool:
 - Select ACPub.DBO.ForfeitureParcels




Figure 4.8: Delete Features

Press OK

Add Query Layer

- In ArcMap ⇒ Open the New Query Layer Dialog
- File ⇒ Add Data ⇒ Add Query Layer
- Select your connection




Figure 4.9: New Query Layer Dialog

Query Text:

```
SELECT [parcelnumber] FROM [D005ALLEGAN].[dbo].[Forfeitures]
WHERE forf_year = 2019
```

Details of the Query Layer

- Choose connection
- Name the query
- Enter SQL query




Figure 4.10: Forfeiture Query Layer Details

- Press Next

Select a Unique Identifier

➤ Press Finish




Figure 4.11: Query Layer Unique ID

Table is added to the map

The screenshot shows the ArcGIS Pro interface. On the left, the Table of Contents pane displays a hierarchical list of layers. A red box highlights the 'D005ALLEGAN' folder, which contains a layer named 'D005ALLEGAN.DBO.forfeitures'. This layer is currently selected, as indicated by a blue selection bar at the bottom of the list. To the right of the Table of Contents is a 'Table' viewer window. The title bar of this window says 'D005ALLEGAN.DBO.forfeitures'. The viewer displays a table with two columns: 'parcelnumber' and 'ESRI_OID'. The table lists 836 rows of data, starting with '01-007-012-00' and ending with '02-007-025-00'. The last row is highlighted with a blue selection bar. At the bottom of the table viewer, there is a status bar that reads '(0 out of 836 Selected)'.

parcelnumber	ESRI_OID
01-007-012-00	1
01-008-005-00	2
01-016-031-10	3
01-019-001-13	4
01-019-005-97	5
01-025-017-00	6
01-026-020-00	7
01-030-014-10	8
01-030-019-00	9
01-031-031-00	10
01-034-009-00	11
01-034-014-10	12
01-034-055-00	13
01-034-067-00	14
01-034-087-00	15
01-034-108-00	16
01-035-015-00	17
01-035-020-20	18
01-035-030-00	19
01-035-044-00	20
01-035-044-10	21
01-120-004-00	22
01-120-010-00	23
01-120-031-00	24
01-120-032-00	25
01-220-010-00	26
01-250-001-00	27
01-300-004-00	28
01-320-020-00	29
01-320-021-00	30
01-370-016-00	31
01-740-009-00	32
02-001-012-31	33
02-003-018-00	34
02-005-004-20	35
02-007-025-00	36

Figure 4.12: Forfeiture Table Added

Add Parcels Layer to the map

Add ACParcelsCombined to the map to provide parcel geometry and attributes




Figure 4.13: Parcels Layer Added

Create Join

Create new join to ACParcelsCombined of forfeitures based on parcel numbers




Figure 4.14: Join Parcels

Export Joined Features to a temp location

- Right click ➔ on joined feature class in TOC and choose export




Figure 4.15: Export Joined Features

- choose location and press OK

Load data from temp location to forfeitureParcels




Figure 4.16: Load Data 1

push next




Figure 4.17: Load Data 2

Match these fields




Figure 4.18: Match Fields 1




Figure 4.19: Match Fields 2

push next




Figure 4.20: Load Data 3

Push Finish

Data Setup

Register as versioned and Add Global IDs

Right Click ⇒ Manage ⇒ Register as Versioned

and

Right Click ⇒ Manage ⇒ Add Global IDs




Figure 4.21: Setup Data

Create Attachments

Right Click ⇒ Manage ⇒ Add Attachments




Figure 4.22: Create Attachments

Setup Users in ArcGIS

Users that will run Pre and Post processing scripts must be created and given privileges on ACPub Treasurer Feature Data Set.

For any new users of the geoprocessing tools, use the create Database User tool or

In Catalog ⇒ Right click on ACpub ⇒ Administration ⇒ Add User




Figure 4.23: Add Db User

Add New User to Feature Dataset

In Catalog, ⇒ right click on Treasurer Feature Data Set ⇒ Manage ⇒ Privileges ⇒ Add ⇒ Type new user ⇒ ok




Figure 4.24: Add Feature Dataset User

Extend Privileges for New User

In Catalog ⇒ right click on Treasurer FDS ⇒ Manage ⇒ Privileges ⇒ check boxes




Figure 4.25: Extend Feature Dataset Privileges

Setup Users in Portal for ArcGIS

Users that will use the Collector for ArcGIS must have profiles added to and managed in the Allegan County GIS Portal site.

In Portal go to My Organization

The screenshot shows the 'My Organization' page of the Allegan County GIS Services portal. The URL is https://gis.allegancounty.org/portal_webadaptor/home/organization.html. The page has a header with navigation links like Home, Gallery, Map, Scene, Groups, My Content, and My Organization. A search bar is at the top right. Below the header is a banner for 'Allegan County GIS Services'. The main content area is titled 'Members' and shows a table of current members:

Name	Username	Last Login	Level	Role	Action
Bryan May	bmay531	Nov 2, 2018	2	Administrator	[Edit]
Christina Andress	CAndress	Sep 19, 2018	2	Administrator	[Edit]
Jennifer Morris	JMorris	Oct 18, 2018	2	Administrator	[Edit]
Neil Besteman	nbesteman	Oct 29, 2018	2	Administrator	[Edit]
Paula Reed	preed6	Feb 7, 2017	1	Viewer	[Edit]

On the right side, there is a 'Membership' sidebar with statistics: 'Members per level' (1 of 30, 4 of 5), 'Total Members: 5 of 35', and links for 'Find...', 'The most viewed items', 'The last items added', 'Groups', and 'The organization's registered apps'.

Figure 4.26: Portal Add User 1

Add Members to Portal

Push add members ⇒ built in member




Figure 4.27: Portal Add User 2

Enter required info

The screenshot shows a web-based application titled "Add Members". At the top left is the Allegan County GIS Services logo. The main title "Add Members" is centered above a form area. A blue circular icon with the number "2" is positioned to the left of the instructions. The instructions read: "Create new Allegan County GIS Services logins one at a time or in batch from a file. Select any role for the member to be a part of. You must inform the member of their user name and password. If you do not have an email address for a particular user, use the administrator's email address." Below the instructions, a red error message states: "Password may not be less than 8 characters." There are two tabs at the top of the form: "One at a time" (selected) and "From a file". The form fields include: Email, First Name, Last Name, Username, Password, Level (radio buttons for 1 or 2), and Role (dropdown menu showing "Publisher"). At the bottom of the form are three buttons: "BACK", "ADD ANOTHER" (highlighted in green), and "REVIEW ADDITIONS".

Figure 4.28: Portal Add User 3

Manage Treasurer Group

In Portal ⇒ Go to groups ⇒ Invite new user to the group




Figure 4.29: Portal Add User 4

Share Content To The Group

Any content used by the group needs to be shared to the group




Figure 4.30: Portal AddUser 5

Schema Change Procedure

Form Edits Procedure

USER MANUAL

Collection Device Setup

Collector Application Setup Details

Install Collector for ArcGIS

- Available from the Google Play Store




Figure 4.31: Download the App

Configure Collector

for Organization Website, Type:

```
{\textcolor{HeaderOrangeC}
https://gis.allegancounty.org/
portal_webadaptor}
```

then:

Press Continue




Figure 4.32: Collector Connection

Enter Credentials

then:

Press SIGN IN




Figure 4.33: Enter Credentials

Download the Forfeiture Field Map

There are 3 different versions of the map

- Forfeiture Field Map
- Forfeiture Field Map For Photos
- Forfeiture Field Map For Attributes

The Download option indicates it is not on the device but is available for offline use

Choose a Map

Press Download




Figure 4.34: Collector Maps Menu

Specify work area

and press

map detail

Note that a larger area takes longer to download but the basemap only needs to be downloaded once




Figure 4.35: Choose Work Area (large)

Choose Map Detail

Zoom into the level of detail desired.

Press Download




Figure 4.36: Choose Map Detail

This area is ready for field data collection.




Figure 4.37: Map on Device

Open Camera Application Setup Details

Install Open Camera

- Available from the Google Play Store



Figure 4.38: Open Camera from Google Play Store

Configure Open Camera

In the Open Camera Application:

Press the gear shaped Settings button to go into the settings menu




Figure 4.39: Find Settings Menu

Press the Photo Settings button




Figure 4.40: Setting Screen

Set Photo Resolution

In photo settings:

Press the Camera resolution button




Figure 4.41: Photo Settings Menu

Select **640 x 480**




Figure 4.42: Camera Resolution Setting

Daily Preprocessing Routine

Execute Preprocessing Script

A tool in ArcGIS that:

- Exports current forfeiture list from BSA
- Updates webmap layers with results from BSA export

In Catalog:

Open the tool-box





Figure 4.43: Processing Tools

Open tool 1

Synchronize the Forfeiture Field Map


Note the date and time:



Press Sync

Figure 4.44: Map Downloaded

Note the date and _____
time:



Map is synchronized

Figure 4.45: Map Synchronized

Forfeiture Data Collection

Forfeiture Parcels Data Details

Attributes are of four entry types:

- prefilled
- autofill
- dropdown
- text box

For each site visited, select the desired parcel, push the edit button and collect attributes.

Device 1 Field Operation

Select a parcel



Figure 4.46: Select Parcel

Push the edit button




Figure 4.47: Parcel Details

Device 1 Field Operation Cont.

Select Yes for Print Today




Figure 4.48: Print Today
Yes or No

Select Use Current or enter
any date




Figure 4.49: Enter Date

Select Inspector From Drop-
down



Figure 4.50: Select Inspec-
tor

Device 1 Field Operation Cont.

Select Occupied or Not Occupied




Figure 4.51: Status

Enter status notes up to 120 characters




Figure 4.52: Status Notes

Select Yes or No for Road Frontage




Figure 4.53: Road Frontage

Device 1 Field Operation Cont.

Enter road used for access




Figure 4.54: Access Via

Enter Agent Name




Figure 4.55: Agent

Enter Agent Contact Info




Figure 4.56: Agent Contact

Device 1 Field Operation Cont.

Enter Use Notes up to 120 characters




Figure 4.57: Use Notes

Enter Notes up to 120 characters




Figure 4.58: Notes

Enter property for sale yes or no




Figure 4.59: Property for Sale

Device 1 Field Operation Cont.

Property in Use Yes or No




Figure 4.60: Property in Use

Placeholder




Figure 4.61: Placeholder

prefilled




Figure 4.62: Property Contaminated

Device 1 Field Operation Cont.

Enter notes up to 120 characters





Figure 4.63: Notes up to 120 characters

Adjacent Property Contaminated prefilled



Property Contaminated notes prefilled

Figure 4.64: Adjacent Property Contaminated




Figure 4.65: Property Contaminated

Device 1 Field Operation Cont.

Property Maintained Yes or No




Figure 4.66: Property Maintained

Picture Comments up to 120 characters




Figure 4.67: Picture Comments

Placeholder




Figure 4.68: Placeholder

Device 2 Field Operation

Use photos taken with the Open Camera Application.

Select a parcel from the map



Figure 4.69: Select Parcel

Push Attachment Button




Figure 4.70: Push Attachment Button

Select Gallery




Figure 4.71: Add Attachment From Gallery

Device 2 Field Operation Cont.

Navigate to the Open Camera Folder





Figure 4.72: Open Camera Folder

Select the appropriate image



Press the check button to save the image to the parcel

Figure 4.73: In the Open Camera Folder




Figure 4.74: Image in the App

Daily Postprocessing Routine


Back at the office

Synchronize Webmap

In Collector for ArcGIS, push the sync button on the Forfeiture Field Map


Execute Postprocessing Script

The Postprocessing Script is A tool in ArcGIS that:
Reconciles geodatabase
versions



Execute the Reconcile
Versions and Compress
Tool

Figure 4.75: Reconcile Versions and Compress Tool



Generates forms for

Figure 4.76: Export Report Tool

each site visited

Execute the Export
Report Tool

- Reconciles geodatabase versions
 - Execute the Reconcile Versions and Compress Tool




Figure 4.77: Reconcile Versions and Compress Tool

- Generates forms for each site visited
 - Execute the Export Report Tool




Figure 4.78: Export Report Tool

SOFTWARE

ESRI Licensed Products

ArcDesktop

Users of this application need a license to ArcGIS Standard level.

Enterprise ArcGIS Deployment

This app uses ArcGIS Server and ArcGIS Portal.

Collector for ArcGIS

Developed and tested on Android(7.0). Collector is available at the Google Play Store.

Other Software

Open Camera for Android



Figure 4.79: Open Camera from Google Play Store

5

Tools

5.1 BSA SUPPORT

ADDING A LAYER TO THE BSA GIS

ADD AN IMAGERY LAYER

Go To BSA Program Setup

(BSA Settings)

In Program Setup ⇒ Select GIS Settings...




Figure 5.1: BSA Program Setup

Setup Map Collections

(BSA Settings)

In GIS Settings ⇒ Map Collections
⇒

Double click on the map that you want to add a layer to




Figure 5.2: GIS Setup

In Setup Layers

(BSA Settings)

Setup Layers ⇒ Add




Figure 5.3: Layers Setup

Select Layer Type

(BSA Settings)

Setup Layers ⇒ Select Image ⇒ OK




Figure 5.4: Select Layer Type

Add Layer From Local Drive

(BSA Settings)

Navigate to Image File ⇒ Open




Figure 5.5: Add Layer From Drive

The new image is in the map

5.2 CORE DATA

CONTROL POINTS

MAINTAINING CADASTRAL CONTROL POINTS

Install the Fabric Point Move to Feature Addin

⇒ Push the Configure Button




Figure 5.6: Fabric Point Move to Feature Addin

Configure Addin

- Set Reference Feature Layer to TargetPoints
 - Use point to point matching
 - Use point layer field: PointID
-




Figure 5.7: Addin Configuration Method

2

Configure Fabric Point Move to Feature addin Selected Feature Options
Move Fabric Points of the Selected Parcels

Push OK

FabricPointMoveToFeatureConfigSelectedFeatures.png

3

Identify position of new control point

Select TargetPoints in Create Features Templates

Create Target Point at location for new Control Point

createTargetPoint.png

4

Use Identify tool to find ObjectId of Control Point that is to be moved

Select the Target point PointID of the point its moving to

Edit Target Point pointID attribute to match associated fabric control poi

updateTargetPointPointID.png

4.5

Push move point button

moveControlPoint.png

5

Open maintain control point tool

Select control Point

push edit button

maintainControlPointTool.png

6

Use Identify Tool to View X and Y vals for the point

copy x and y value from point(attribute window) to Control (maintain contr

push update

Save Edits

transferCoordinates.png

Identify position of new control point

Place Target Point

Update Target Point attributes to associated fabric point OID

Push move point button

Zoom to Control point
Open maintain control point tool
Select control Point
edit button
copy x and y value from
identify tool x and y of points
update button

5.3 ESRI TOOLS**COGO TOOLS IN ARCGIS****TEXT**

5.4 GIS ADMINISTRATION

NEW CONNECTIONS IN ARCCATALOG


INSTALL SQL SERVER ON CLIENT MACHINE

On client machine:

For any machine to connect to the Enterprise Geodatabase, SQL Server Native Client must be installed locally.

Search for sql server native client download on the internet

margin note ⇒



Microsoft® SQL Server® 2012 Native Client - QFE




Figure 5.8: SQL Server Client Search

Select appropriate Version

Decide whether to get the 32bit or 64bit version

← margin note



Choose the download you want

File Name	Size
ENU\x64\sqlIncli.msi	For 64bit OS 4.8 MB
ENU\x86\sqlIncli.msi	For 32 bit OS 3.0 MB

Figure 5.9: SQL Server Client Search Choose

Download and Install

CONNECT ARCGIS TO A SQL SERVER DATABASE

In Catalog:

Double click on add database connection




Figure 5.10: Catalog Add Db Connection

NEW CONNECTION DIALOG

Enter into the tool

- Select Database Platform
- Enter Instance Name
- Enter user name and password
- Check Save user name and password
- Select Database in dropdown




Figure 5.11: Catalog Add Database Connection

CREATE QUERY IN ARCGIS TO SQL DATABASE

ADD QUERY LAYER

In ArcMap:

Open the New Query Layer Dialog

Go to ⇒ File ⇒ Add Data ⇒ Add Query Layer In the connection dropdown select your connection

NOTE




Figure 5.12: New Query Layer Dialog

DETAILS OF THE QUERY LAYER

Enter into the tool

- Choose connection
- Name the query
- Enter SQL query
- Press Next




Figure 5.13: Query Layer Dialog Filled

MORE DETAILS OF THE QUERY LAYER

Enter into the tool

- Select unique identifier field
- Click Finish




Figure 5.14: Select Unique Identifier

OPEN RESULTS TABLE

Verify the Query by Looking at the Table

The screenshot shows the ArcGIS Pro interface with the 'Table Of Contents' panel on the left. A red box highlights the 'Layers' section, which contains a single item: 'D001COUNTY WEB 18.DBO.NewQuery'. This layer is expanded, showing a table view with 1666 selected rows. The table has columns: ownername1, ownerstreetaddr, ownercity, ownerstate, ownerzip, and ESR_OID. The data includes various names like 'WAGNER, LONIE S & ERICA', 'GULI LAKE UNION COMMUNITY CHURCH', and 'CITY OF WAYLAND'. The 'ownercity' column shows entries like 'WAYLAND MI', 'LOWELL MI', and 'WESTLAKE OH'. The 'ownerstate' column shows mostly 'MI' with one entry for 'WA'. The 'ownerzip' column shows various zip codes. The 'ESR_OID' column lists IDs from 1 to 39. At the bottom of the table view, it says '(0 out of 1666 Selected)'.

ownername1	ownerstreetaddr	ownercity	ownerstate	ownerzip	ESR_OID
WAGNER, LONIE S & ERICA	782 13TH AVE	WAYLAND	MI	49348	1
GULI LAKE UNION COMMUNITY CHURCH	12200 WEST MI-179	WAYLAND	MI	49348	2
WAYLAND UNION SCHOOLS	850 E SUPERIOR ST	WAYLAND	MI	49348	3
CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	4
CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	5
ELMAS WAYLAND LLC	1645 BIRMINGHAM DR	LOWELL	MI	49331	6
ELMAS WAYLAND MEDICAL CARE REALTY I	1645 BIRMINGHAM DR, AVE E	SEATTLE	WA	98109	7
CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	8
RIPARIAN PROPERTIES LLC	879 E SUPERIOR ST	WAYLAND	MI	49348	9
RIPARIAN PROPERTIES LLC	879 E SUPERIOR ST STE A	WAYLAND	MI	49348	10
VB VENTURES WAYLAND LLC	235 140TH AVE	WAYLAND	MI	49348	11
CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	12
LATIMER, ROBERT W & JUDITH	801 S SUPERIOR ST	WAYLAND	MI	49348	13
BREWER SUZANNE M	845 E SUPERIOR ST	WAYLAND	MI	49348	14
STORA RODERICK M & MELISSA K	841 E SUPERIOR ST	WAYLAND	MI	49348	15
ARY DOUGLAS & JULIE	104 MARLO LN	WAYLAND	MI	49348	16
DUBAY DOUGLAS	102 MARLO LN	WAYLAND	MI	49348	17
COOPER, JEFF	811 S SUPERIOR	WAYLAND	MI	49348	18
BENNETT, JILL A & CARRON BIANCE	2514 BROOKSCLIFF LN	GRAND RAPIDS	MI	49508	19
VILLELLA MATTHEW	101 MARLO LN	WAYLAND	MI	49348	20
JENSEN KRISTEN S	103 MARLO LN	WAYLAND	MI	49348	21
WAYLAND CHRISTIAN REF CHURCH	303 E ELM STREET	WAYLAND	MI	49348	22
CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	23
PRIMEDAY MEDICAL & HEALTHCARE PROPERTY LLC	1000 WASHINGTON ROAD	WESTLAKE	OH	44107	24
CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	25
FERGUSON, ROBERT K	5770 VENTURE PARK	KALAMAZOO	MI	49009	26
REDSTONE LAND DEVELOPMENT LLC	3330 GRAND RIDGE DR NE	GRAND RAPIDS	MI	49525	27
VANDERVORD JOHN C & NANCY L	542 FOREST ST	WAYLAND	MI	49348	28
LAMB B LLC	2645 24TH AVE	HUDSONVILLE	MI	49426	29
COPPERMAN, JOHN C	175 OAK ST	SHELBURNE	MI	49344	30
REDSTONE LAND DEVELOPMENT LLC	125 OAK ST	WAYLAND	MI	49348	31
WALKER MICHAEL	3330 GRAND RIDGE DR NE	GRAND RAPIDS	MI	49525	32
FLUIT MARK & MARYELLEN	131 OAK ST	WAYLAND	MI	49348	33
GUTIERREZ, SAUL O & ORTIZ CHRISTINA	137 OAK ST	WAYLAND	MI	49348	34
MEDELLIN, JESUS & MARIA #56	119 OAK ST	WAYLAND	MI	49348	35
	103 S MAIN ST	WAYLAND	MI	49348	36
WILLIAMS TERESA A	540 N MAIN ST	WAYLAND	MI	49348	37
KEMP HOLDINGS LLC	304 108TH ST	CALEDONIA	MI	49316	38
SLOAN JOHN L & AMY L	329 WILLOW RUN DR	WAYLAND	MI	49348	39

Figure 5.15: Query Results Table

ENTERPRISE GEODATABASE MAINTENANCE

ENTERPRISE GEODATABASE COMPRESSION ROUTINE

Disconnect All Users

To disconnect the GIS Server, stop all services

- In ArcGIS Server Manager ⇒ Site ⇒ GIS Server ⇒ Machines ⇒ Stop all Services




Figure 5.16: Stop ArcGIS Server

Use the Search tool to find the Rebuild Indexes Tool




Figure 5.17: Find Rebuild Indexes Tool

Rebuild Indexes

Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.18: Rebuild Indexes Tool Operation

Recalculate Statistics

In the Analyze Datasets Tool:
Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.19: Recalculate Statistics

Compress

Select Connection ⇒ Press OK




Figure 5.20: Compress

Rebuild Indexes Again




Figure 5.21: Rebuild Indexes Tool Operation

Recalculate Statistics Again

In the Analyze Datasets Tool:

Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.22: Recalculate Statistics

MANAGING MAP SERVICES

To STOP ARCGIS SERVER

Launch ArcGIS Server Manager

Site ⇒ GIS Server ⇒ Machines ⇒ Stop the Server




Figure 5.23: Stop the GIS Server

FIXING DAMAGED SERVICES

Error:

Service is currently being configured by another administrative operation

Remedy:

This tech support article applies:

<https://support.esri.com/en/technical-article/000015549>

There are at least 2 ways to fix:

- Use the ArcGIS Server Account Utility
- Remove Lock Files

Use the ArcGIS Server Account Utility

Access the GIS Server

To Log in to Juniper

windows R ⇒ mstsc

⇒ juniper

Use personal network credentials

On the GIS Server (Juniper)

In Windows Search, find:

Configure ArcGIS Server Account Utility




Figure 5.24: ArcGIS Server Account Utility

Use credentials:

PW: @lleganGxxxxxx




Figure 5.25: Account Utility Login

In the utility, paste these paths:

C:\arcgisserver\directories
C:\arcgisserver\config-store
C:\arcgisserver\logs




Figure 5.26: GIS Directory Locations Filled

Push Next

Select option **Do not export Configuration File**




Figure 5.27: Do not Export Config File

Push Next




Figure 5.28: Configure Account

Push Configure

While the tool runs, open the service manager

In Windows Search, find:

Service Manger Launch **Service Manger**




Figure 5.29: Search For Service Manager

When the tool completes, **Press Finish**




Figure 5.30: Finish On Configure

Services Manager




Figure 5.31: Open Services Manager

In services, select the ArcGIS Server service and restart the service. (Randy had to do this)




Figure 5.32: arcGis Service In Services Manager

Quick and dirty fix

When a service get hung up in som admin process, you may get an error like:

Error:

Service is currently being configured by another administrative operation

Removing Lock Files

This may work, here is a blog about it

<https://community.esri.com/thread/103710> Network location for an example service

```
on juniper
C:\arcgisserver\config-store\services\ParcelViewer2\
PV2Adresses.MapServer\startup\JUNIPER.ALLEGANCOUNTY.ORG
```

Suggested Steps:

- 1)stop arcgis server services.
- 2)delete the lock files(*.glock and *.rlock)
 (in arcgisserver\config-store).
- 3) restart arcgis server service.
- 4)stop the pending stopping service and then start it.

mapservices would not stop so I try this:

<https://support.esri.com/en/technical-article/000012685>

Check permission levels for the arcGIS account ArcGisServerPermissions.PNG

If necessary, add the arcgis user to the permissions on the folders
ArcGisServerPermissionsAddUser.PNG

MANAGING GEODATABASE REPLICAS

ADDING A NEW FEATURE CLASS TO A REPLICA

Source: <https://support.esri.com/en/technical-article/000010345>

Summary

Currently, there is no out-of-the-box tool to add a feature class to an existing replica. With ArcGIS Desktop, one must either recreate the replica or if the workflow allows, replicate the new feature class as a separate replica.

A feature class or table can only be added to an existing replica (without recreating the replica) using ArcObjects code.

Steps:

The steps below outline how to recreate the replica using the Register Existing Data option in Desktop. These steps can be applied to both one-way and two-way replicas.

Synchronize the changes between parent and child replica geodatabases using the existing replica so that the data is identical in each database, then Unregister the replica in both geodatabases. For two-way replicas, ensure that changes are synchronized in both directions and there are no outstanding edits before unregistering the replica. Create/import the new feature class into the parent geodatabase, and add the GlobalID. Register the newly added data as versioned. Copy and paste the new feature class to the child geodatabase using ArcCatalog. Note: that the GlobalIDs must have already been added to the feature class.

For two-way replica or one-way full model, register the newly added data in child geodatabase as versioned. Using the parent geodatabase, add all the data that is to be replicated to a map in ArcMap. Click the 'Create Replica' tool on the Distributed Geodatabase toolbar. Select 'One way replica' or 'Two way replica' and click Next. Select 'Register existing data only'. Select the child geodatabase and specify a replica

name. Click Next and click Finish. A new replica is created that includes the new data.

MANAGING GEODATABASE VERSIONS

VERSION QUERIES

SQL Queries

Four queries of SDEversions, SDEstates, sdestatelineages, and SDEcompresslog

```
use AC_Pub
select name, owner, version_id, state_id, parent_name
, parent_owner from
[AC_Pub].[dbo].[SDE_versions]
select * from [AC_Pub].[dbo].[SDE_states] order by state_id
select * from [AC_Pub].[dbo].[sde_state_lineages] order
by lineage_name,
lineage_id
select TOP(5) * from [AC_Pub].[dbo].[SDE_compress_log] order by
compress_end DESC
```

Query of SDEversions and SDEstates

```
use AC_Pub
SELECT v.version_id,v.creation_time,v.creation_time,
s.state_id, s.creation_time
FROM SDE_versions v
INNER JOIN SDE_states s ON v.state_id = s.state_id
```

FINDING ORPHANED VERSIONS

Remove orphaned versions

Follow the procedure: [Link to source](#)

Use SQL Server Management Studio to execute two queries and compare the results.

Step 1:

Execute the query:

```
use AC_Pub
SELECT ObjectID, name from dbo.GDB_ITEMS where
TYPE='4ED4A58E-621F-4043-95ED-850FBA45FCBC' ;
```

Step 2:

Execute the query:

```
use AC_Pub
SELECT name from [dbo].[SDE_versions]
order by name
```

Compare the tables

This graphic summarizes elements of the queries. Note the items from step two that have no match in step one.

code for versions
in gdbItems

replica ID

generation #

Matches

No Matches

ObjectID	name
16497	ProtoPubParcelPubReplica
16520	ProtoPubLandUsePlanningReplica
17074	SchoolsReplica
17542	BIReplica
17893	EmergencyMgmt
19323	AddressessReplica
40149	EnvHealthReplica

name
CAddress_Tbl_ReversionParc
DEFAULT
JWMS_Trace/Tbl_ReversionParc
SYNC_SEND 17893 0
SYNC_SEND 40955 12
SYNC_SEND 40965 7

Figure 5.33: Find Orphan Versions

Orphaned versions can be removed by name in ArcGIS




Figure 5.34: Delete Orphan Versions

MXD MANAGEMENT

FIND/REPLACE TEXT OBJECT

Python Code

Python Code for finding and replacing a text object in a ArcGIS .mxd file. A snippet of this code may be found in the LayerUpdates/Zoning/processing folder. It is used to edit the .mxd files located there.

```
import arcpy
from arcpy import env

env.workspace = r"J:\Apps\Python\LayerUpdates\zoning\processing"
for mxdname in arcpy.ListFiles("*.mxd"):
    print mxdname
    mxd = arcpy.mapping.MapDocument(r"J:\Apps\Python\
        LayerUpdates\zoning\processing\\\" + mxdname)
    for elm in arcpy.mapping.ListLayoutElements
        (mxd, "TEXT_ELEMENT"):
        if elm.text.startswith('As ammended'):
            elm.text = elm.text.replace('As ammended',
                'As amended')
            print elm.text
    mxd.save()
del mxd
```

5.5 L^AT_EX PACKAGES USED BY AC GIS

COMMON ERRORS

Source:

<https://www.ocf.berkeley.edu/~latex/files/commonerrors.tex>

If you have every compiled a L^AT_EX document, chances are high you have received a few error messages. Sometimes they come from something as stupid and as easy to fix as forgetting a parenthesis or forgetting to end an environment. There are also a lot more cases where you have no idea what you have done wrong and it takes you a long time to find or even understand your error.

The purpose of this is to explain some of the common errors that may happen when compiling a L^AT_EX document and suggestions for what is probably going on and how to debug your document.

THE FORM OF AN ERROR

There are two forms of errors: L^AT_EX errors and T_EX errors. In both types of errors, the part after the error message will tell you where the error occurred. An example:

1.15 <offending text>

The 1.15 tells you what line the error occurred on and the text will tell you the text that caused the error.

L^AT_EX ERRORS

The general form of an error in L^AT_EX is shown below:

! LaTeX error: <error message>

See the LaTeX manual or LaTeX Companion for explanation.

Type H <return> for immediate help.

...

The ! lets you know that the error has occurred. The error message will tell you what type of error you have committed. After the ellipses,

you will find the line at which the error occurred and the text that caused the error (or at least the text where L^AT_EX found the error).

T_EX ERRORS

Errors may also have the following form:

```
! <error message>
```

These errors are formatted differently because they are error messages that came from T_EX instead of L^AT_EX. After the error, you will still find the line that the error occurred in and the text of the error.

WARNINGS

There are some error messages that are just warnings and will not stop or change the compilation of the document. Chances are you have seen them many times.

UNDERFULL

The following error results when a line does not extend the width of the page, something L^AT_EX always tries to accomplish:

```
Underfull \hbox (badness 10000) in paragraph at lines  
104--107
```

This error message is just a warning and is not something to worry about. For the most part, when a line does not span the width of the page, it is because you have written something that you want to only cover part of the page.

OVERFULL

The following error results when a line extends beyond the width of the page:

```
Overfull \hbox (16.04988pt too wide) in paragraph at
lines 30--31 [] [] \OT1/cmtt/m/n/12 I'm trying to put
way too much text into a line in my document.
```

Usually this error comes from when you are using the `verbatim` package because it will not move to the next line if your text does not go to the next line. The easiest way to fix this is to find the place in your document where this is occurring and change the text so that it fits to the page.

This error will still show up if the text is still on the page but outside of the width of text that L^AT_EX has set. In this case, you are welcome to fix things so that the error does not show up or you can leave the text as it is.

REFERENCES

The following warnings occur when references are changed when L^AT_EX was compiled:

LaTeX Warning: Label(s) may have changed. Rerun to get cross-references right.

LaTeX Warning: There were undefined references.

LaTeX Warning: Reference ‘name’ on page 1 undefined on input line 15.

The way to fix these errors is to recompile the document again to correct the page numbers. Sometimes it is necessary to recompile the document twice to fix this error. You also may have defined a reference wrong, so you should check to make sure your label is correct.

BEGINNING AND ENDING BEGIN ENDED BY END

This type of error occurs when each environment is not correctly started and ended. When you are missing an `\end` command, the following error will show up:

```
! LaTeX Error: \begin{enumerate} on input line 23
ended by \end{document}.
```

To fix this, you need to end the environment mentioned in the error with the appropriate command.

When you are missing a `\begin` command, the following will appear:

```
! LaTeX Error: \begin{document} ended by
\end{itemize}.
```

To fix this, you basically do the same thing as before, correctly beginning the environment mentioned in the error with the appropriate command.

END OCCURRED INSIDE A GROUP

The following error message will show up at the end of compiling a file if an environment is begun that is not ended:

```
(\end occurred inside a group at level <n>)
```

To fix this error, make sure you end the environment that was begun. The previous error is more helpful in finding the `\begin` statement.

ENDED BY END OF LINE

The following error will occur when you try to place a command inside a section heading:

```
! LaTeX Error: \verb ended by end of line.
```

```
See the LaTeX manual or LaTeX Companion for
explanation.
Type H <return> for immediate help.
...
```

There will be many errors of the same type for this mistake. In order to find where you put the command, look in the output file and find the last heading that shows up.

MISSING BEGIN DOCUMENT

This error is self-explanatory:

```
! LaTeX Error: Missing \begin{document}
```

ERRORS USUALLY CAUSED BY BAD SPELLING

UNKNOWN CONTROL SEQUENCE

This error results when you use a command (something that starts with a \) that is not recognized by L^AT_EX:

```
! Undefined control sequence.
```

Usually this error results from spelling a command incorrectly. Go to the line that is indicated by the error and fix the command.

ENVIRONMENT UNDEFINED

This error results when you begin an environment with a \begin command that is not recognized:

```
! LaTeX Error: Environment verbatim undefined.
```

Usually you have just spelled your environment incorrectly, so you just need to fix it.

BAD FILE NAME

This error results when you have mistyped the command `latex` or do not have L^AT_EX installed on your computer:

```
Bad command or file name
```

To fix this, correctly spell the command to compile your file or make sure that L^AT_EX is correctly installed on your computer.

CANNOT FIND FILE NAME

This error occurs when you try to compile a file that the computer cannot find:

```
! I can't find file 'sample'.
<*> sample
```

Please type another input file name:

To fix this error, make sure you have spelled the file name correctly. You also may be in the wrong directory to compile the file, so check to make sure you are in the same directory as your file.

FATAL ERRORS

RUNAWAY ARGUMENT

This error happens when a paragraph ends before a command's argument is done (i.e., L^AT_EX thinks that there is a missing }):

Runaway argument?

To fix this, you should use a different command to accomplish what you are trying to do. An example of this is to use `\bfseries` instead of `\bftext` to make bold text in more than one paragraph.

This error can also be caused by a missing mandatory argument to a command.

JUST AN *

This error normally occurs when you do not end your document with `\end{document}`:

*

If you are prompted to enter something in, it is best to enter `\end{document}`

and hope it works. Be sure to end your document with the appropriate command.

EMERGENCY STOP

This error happens when L^AT_EX will stop trying to compile your document due to a serious error:

`! Emergency stop.`

To fix this error, you will need to figure out what caused it to stop compiling. Chance are you forgot to end your document with `\end{document}`, but there might also be another reason for the emergency stop.

PLEASE TYPE A COMMAND OR SAY END

This error happens when your file has ended prematurely:

`(Please type a command or say '\end')`

The best way to deal with this type of error is to type

`\end`

or

`\end{document}`

in the case that the absence of that command caused the error. Usually if you have ended your document correctly, the error will result from a missing } or forgetting to end a verbatim environment.

GRAPHICS ERRORS TOO MANY UNPROCESSED FLOATS

This error occurs when figures or tables (i.e., floats) have not been typeset:

`! LaTeX Error: Too many unprocessed floats.`

\LaTeX can only have so many floats waiting to be typeset. In order to fix this error, make sure that you are placing your floats where you want them (with a [h] option) and not wanting too many on one page in sequence. Using the command `\clearpage` can be very useful in distributing floats correctly.

UNKNOWN GRAPHICS EXTENSION

The following error occurs when you try to use a type of graphic that is not supported by the type of file that you are producing:

```
! LaTeX Error: Unknown graphics extension: .gif
```

In order to fix this error, you should change your graphics to the types that are supported by the type of file you are outputting or you will need to include the correct package to deal with that type of graphic. Sometimes you may have named the graphic poorly so that \LaTeX will not recognize it as a graphic file.

DIVISION BY ZERO

The following error occurs when the height of a graphic object is zero:

```
! Package graphics Error: Division by 0.
```

This is usually caused when you rotate an object with zero depth so that its height becomes zero. The best way to fix this is to use the keyword `totalheight` instead of `height`.

MATH ERRORS DISPLAY MATH SHOULD END WITH \$\$

This error occurs when the `displaymath` or `equation` mode is ended incorrectly:

```
! Display math should end with $$
```

To fix this error, make sure that you end the displaymath or equation mode correctly (ending them with a \$ is not acceptable).

BAD MATH ENVIRONMENT DELIMITER

This error occurs when you do not have your delimiters correct in math mode:

```
! LaTeX Error: Bad math environment delimiter.
```

Usually this occurs when you forget to match a right delimiter with every left delimiter. This error may also happen when you forget to end an array.

MISSING RIGHT

This error occurs when you have a missing right parenthesis:

```
! Extra \right.
```

To fix this, you either need to add a \right command or you need to end an array.

MISSING DELIMITER

This error message occurs when a delimiter is missing:

```
! Missing delimiter (. inserted).
```

To fix this error, you need to make sure that you have a right delimiter for every left delimiter. If you do not want a right delimiter matching a left delimiter, you need to use “.” to not have an error message show up.

MISSING \$ INSERTED

The following error occurs when you try to use a character that can only be used in math mode, like $_$ or $^$:

```
! Missing $ inserted
```

To fix this error, make sure you change the character to what it should be in text mode.

TABULAR ENVIRONMENT ERRORS

MISPLACED ALIGNMENT TAB CHARACTER &

This error occurs when you use $\&$ and when you are not in a tabular environment:

```
Misplaced alignment tab character &
```

To fix this error, you need to use $\backslash\&$ to make a $\&$.

EXTRA ALIGNMENT TAB

This error occurs when you use too many tabs for the number of columns in a table:

```
! Extra alignment tab has been changed to \cr
```

The result of this error is that a new row is formed where the extra tab was. You should go back and fix your table so that the correct number of items in each row would show up.

ARGUMENT HAS AN EXTRA }

These errors happen when an incorrect number of arguments to a tabular environment have been specified:

```
! Argument of \cline has an extra }.  
! Argument of \multicolumn has an extra }.
```

To fix this error, make sure your arguments to the tabular environment are correct.

ERRORS WITH LISTS

MISSING ITEM

This error occurs when there is plain text in an environment that takes items:

```
! LaTeX Error: Something's wrong--perhaps a missing  
\item.
```

To fix this error, make sure the plain text is changed into an item.

TOO DEEPLY NESTED

This error occurs when there are too many lists for L^AT_EX to handle:

```
! LaTeX Error: Too deeply nested
```

L^AT_EX can only handle four levels of one type of list and six levels of different types of lists. To fix this, you need to use less levels of lists or define your own list environment.

MISCELLANEOUS ERRORS

ONLY USED IN THE PREAMBLE

This error occurs when you place a command in the body of a L^AT_EX document that should be placed in the preamble:

! LaTeX Error: Can be used only in the preamble.

To fix this error, just move the command to the preamble.

THERE IS NO LINE/PAGE HERE TO END

This error occurs when you incorrectly use the commands that make a new line or a new page:

! LaTeX Error: There's a no line here to end.

You may just leave the command that is making a new line in place or you can take it out. Here, L^AT_EX is just trying to make sure that everything looks nice.

COMMAND ALREADY DEFINED

This error occurs when you try to define a command that already exists:

! LaTeX Error: Command ... already defined.

To fix this, you need to define your command differently.

MISSING NUMBER

This error is made when a number is expected as an argument and one is not provided:

! Missing number, treated as zero.

To fix this error, you need to find where a number is expected so that you can provide the correct one.

FLOAT PACKAGE

USEPACKAGE

text

SIMPLE USE

text

OPTIONS

text

Add optional arguments to the usepackage line:

Useful options:

- **OPTION NAME**
OPTION NOTE
- **OPTION NAME**
OPTION NOTE

USE WITH OPTIONS

text

COMMANDS

GRAPHICS EXAMPLES AND NOTES**CURLYFRAME EXAMPLE**

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
\geometry{tmargin=.75cm,bmargin=.25cm,lmargin=.8cm,rmargin=.2cm}
\usepackage{multicol}

\begin{document}

\curlyframe[.9\columnwidth]{

TEXTTTTTTTTTTTTTTTTTT

}

\end{document}
```

RECTFRAME EXAMPLE

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
\geometry{tmargin=.75cm,bmargin=.25cm,lmargin=.8cm,rmargin=.2cm}
\usepackage{multicol}

\begin{document}
\begin{minipage}{.33\textwidth}
\centering
\scalebox{3}{\color{green!30!black!60}
\font\border=umrandb
\generalframe
```

```
{\border \char113} % up left
{\border \char109} % up
{\border \char112} % up right
{\border \char108} % left
{\border \char110} % right
{\border \char114} % lower left
{\border \char111} % bottom
{\border \char115} % lower right
{\centering
\includegraphics[height=1.25cm]{GIS_Logo_better.jpg}}
\end{minipage}
%\vspace{-8mm}

\end{document}
```

GRAPHICX PACKAGE

USEPACKAGE

text

SIMPLE USE

text

OPTIONS

text

Add optional arguments to the usepackage line:
Useful options:

- **OPTION NAME**
OPTION NOTE
- **OPTION NAME**
OPTION NOTE

USE WITH OPTIONS

text

COMMANDS

HYPERREF PACKAGE

INTRODUCTION

Official hyperref package documentation

Notes:

- Add the *hyperref package* to the preamble **last** [?]
 - To use Tex in a pdf bookmark: use
-

```
\texorpdfstring{\{}{}\}
ie. \paragraph{Sample Text\texorpdfstring{\{}{}\}}
```

Creates a new line without an error.

```
\usepackage[options]{hyperref}
```

SIMPLE USE

Use `\href{URL}{DESCRIPTION}` to add a link with description

`\href{https://www.latex-tutorial.com}{Website with tutorials}`
produces:

[Website with tutorials](https://www.latex-tutorial.com)

OPTIONS

Add optional arguments to the usepackage line:

Useful options:

- **pdftex**
enables other options like breaklines
 - **breaklinks**
allow links to be broken across several lines
eg. <https://lists.gnu.org/archive/html/emacs-orgmode/2013-06/msg00776.html>
 - **colorlinks**
Colors the text of links and anchors.(default is false)
 - **linkcolor**
Color for normal internal links(default is red).
 - **anchorcolor**
Color for anchor text.
 - **citecolor**
Color for bibliographic citations in text.
 - **urlcolor**
Color for linked URLs
-

USE WITH OPTIONS

```
\usepackage[breaklinks,colorlinks,citecolor=blue,
urlcolor=green]{hyperref}
```

COMMANDS

`\href{URL}{text}` Makes text a link to URL.

To put a file path in text:

eg:

`\Official hyperref package documentation`

(documentation Pt.4 pg.15)

`\href[options]{URL}{text}`

Options:

- absolute

```
\href{C:/AC/jalapeno/documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref doc}
```

- relative Note: relative path must be from final pdf location

```
\href{../../../../documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref package doc}
```

This path works from main document

```
\href{../../../documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref package documentation}
```

This path works from subsection document

`\hyperref[label]{text}`

Makes text a link to where `\ref{label}` would point.

`\hypertarget{name}{text}`

Sets an anchor on text with the label name.

`\hyperlink{name}{text}`

Makes text a link that takes you to the anchor labeled name.
Pair with `\hypertarget`.

`\phantomsection`

Used in conjunction with

```
\addcontentsline  
    to make the correct link in the Table of Contents.
```

IMPORT PACKAGE

USEPACKAGE

text

SIMPLE USE

text

OPTIONS

text

Add optional arguments to the usepackage line:

Useful options:

➢ **OPTION NAME**

OPTION NOTE

➢ **OPTION NAME**

OPTION NOTE

USE WITH OPTIONS

text

COMMANDS

STANDALONE PACKAGE

INTRODUCTION

[Link to official standalone documentation](#)

standalone provides a **package** and a **class**

➤ The *standalone package* is used for:

- Main documents that will input or import sub documents.
- For example:

```
\usepackage[subpreambles=false]{standalone}
* Ignores preambles of imported sub documents [?, pg.4]
```

➤ the *standalone class*:

- Is a document class
- Provides standalone / subdocument switches and options
- For example:

```
\documentclass[class=article]{standalone}
* behaves as an article when standalone
* makes document available for import into a master document
```

SIMPLE USE

➤ The *standalone package*

- In the main document:

```
\documentclass[openany]{book}
\preamble...
\usepackage{standalone}
```

➤ the *standalone class*:

- In any subdocument:

```
\documentclass[class=article]{standalone}
\preamble...
```

OPTIONS

- The *standalone* package
 - **subpreamble**
 - * default value of subpreambles is *false*
- the *standalone* class:
 - **crop**
 - **titlepage**
 - **twoside**
 - * Makes pagination style match book
 - * default value is *false*
 - **multi**
 - * `multi=true|false`
 - * `multi={<environment name>, ...>}`
 - **float**

USE WITH OPTIONS

- the *standalone* package:
 - `\usepackage[subpreambles=false]{standalone}`
- the *standalone* class:
 - `\documentclass[class=article , crop=false, titlepage, twoside, multi={itemize, figure, verbatim}, float=false]{standalone}`

COMMANDS

WRAPFIG PACKAGE

USEPACKAGE

text

SIMPLE USE

text

OPTIONS

text

Add optional arguments to the usepackage line:

Useful options:

- **OPTION NAME**
OPTION NOTE
- **OPTION NAME**
OPTION NOTE

USE WITH OPTIONS

text

COMMANDS

5.6 LATEX TEMPLATES

LATEX SECTION TEMPLATE

```
%\documentclass[class=report , crop=false, multi={itemize, figure}, float=fa
\documentclass[class=book , crop=false]{standalone}

\input{../../../../../preamble}

\def\titlename{Section Template}

\title{\input{../../../../commonTitle}} % closing brace for title

\begin{document}% Document Begins

\input{../../../../commonFront} % provides standalone options

\section{SECTION NAME HERE}

\subimport{RELATIVE PATH TO NEW Section/}{NEW SUBSECTION Subsection.tex}

%eg.
%\subimport{latexTemplatesSection/}{subsectionTemplateSubsection.tex}
% etc...

\end{document}
```

LATEX SUBSECTION TEMPLATE

```
\documentclass[class=book , crop=false]{standalone}

\input{../../../../../preamble}

\def\titlename{Subsection Template}

\title{\input{../../../../commonTitle}} % closing brace for title

\begin{document}% Document Begins

\input{../../../../commonFront} % provides standalone options
```

```
% NEW INFO GOs HERE.  
\subsection{Subsection Template}  
\medskip
```

5.7 PDF TOOLS USED BY AC GIS

PDF OPTIMIZER

PUPOSE AND SUMMARY

Workflow Purpose: Optimization of a large number of pdf docs.

Workflow Summary: Uses Python to create a list of .pdf docs in a folder and creates a batch file to optimize the pdfs in the list to another location. The batch process calls ghost script for the optimization.

REQUIREMENTS

Opensource software:

- ghostscript
- python 2.7 and a Python IDE
- A text editor

paragraphPython(2.7)

Note:

The output of this script is bdoc.txt, Save as a .bat to execute the optimize.

Script that creates a batch file

```
import os, sys

project = os.path.dirname(os.path.dirname(__file__))
processing = os.path.join(project, 'processing')
#source = os.path.join(project, 'source')
build = os.path.join(project, 'build')
sourcepdf = os.path.join(build, '20180716')

inString1 = "gswin32 -sDEVICE=pdfwrite -dCompatibilityLevel=1.4
-dPDFSETTINGS=/ebook -dNOPAUSE -dQUIET -dBATCH
-sOutputFile=J:\\\\Projects\\\\2018ParcelAtlas\\\\build\\\\optimized\\\\"
```

```
inString2 = " J:\\Projects\\2018ParcelAtlas\\build\\20180716\\"

batchdoc = os.path.join(processing, "bDoc.txt")

# Main
#####
#####

if __name__ == "__main__":
    list1 = os.listdir(sourcepdf)
    l = open(batchdoc, 'w')
    for i in list1:
        newi = i[1:]
        print newi
        t = inString1 + newi + inString2 + i + "\n"
        print t
        l.write(t)

    l.close()
```

GHOSTSCRIPT

About

ghostscript is used for the optimization. ghostscript is an interpreter for the PostScript language and for PDF [?].

Licensing

ghostscript is available opensource under AGPL conditions. more information can be found [here](#).

Download

ghostscript can be downloladed [here](#).

WINDOWS BATCH FILES

A line from the batch file looks like:

```
gswin32 -sDEVICE=pdfwrite -dCompatibilityLevel=1.4  
-DPDFSETTINGS=/ebook -dNOPAUSE -dQUIET -dBATCH  
-sOutputFile=J:\Project\2018ParcelAtlas\build\optimized\  
02-001-001-00.pdf J:\Projects\2018ParcelAtlas\build\20180716  
\_02-001-001-00.pdf
```

5.8 QGIS TOOLS

USING COGO TOOLS IN QGIS

SET UP THE AZIMUTH AND DISTANCE PLUGIN (AZD PLUGIN).

In the Plugins drop down(1), under the topography group select the **Azd Plugin(2)**(see fig.).




Figure 5.35: launch plugin

Note here which layer is active (see fig.).




Figure 5.36: check active layer

If necessary, left click the layer *traverse 1* in Layer Panel to activate it(see fig.).




Figure 5.37: activate layer

Configure Options

On Options Tab: Select Boundary, Bearing, Feet, and Degree radio buttons.




Figure 5.38: Plugin Options

Using the tool

Boundary descriptions are entered into the Drawing Tab. Azimuth (bearing) and Distance are the important boxes (Set Offset = 0 and Zenith = 90 and ignore)(see below).




Figure 5.39: Entering Bounds

CONFIGURE EDITING ENVIRONMENT

Use Settings Dropdown and Snapping Options to enable snapping to Sections, Quarter Sections, and or Parcels if desired (see fig.).




Figure 5.40: Configure editing environment

LOCATE POINT OF COMMENCEMENT

To get to the Point of Commencement,

Use **any combination** of the following methods:

- Using Reference Layer
- Using Measuring Tool
- Search by Parcel Number (Search Layers Plugin)
- Draw COGO lines (Azd Plugin)(as described earlier)

Using Reference Layer

Use reference layers; Units, AC_SectionsQu, Sections, and Parcels. Toggle layers on and off in Layers Panel and zoom in and out with mouse wheel.

Using Measuring Tool

Use the measuring tool, make sure to set units to feet. To exit current measurement right click (see fig.).




Figure 5.41: Measuring Tool

Search by Parcel Number

(Search Layers Plugin.)

To Launch Search Layers Plugin:

In Plugins dropdown:

Enable the **Search Layers** Plugin. (see fig.)




Figure 5.42: Search Layers Plugin

Enter parcel number (with dashes), Set layers, and set search field.(see fig.)




Figure 5.43: Search Layers Setup

Part IV

Resources

A.1 GEOGRAPHY 101

Foundations of geography

A PRIMER ON COORDINATE SYSTEMS COMMONLY USED IN MICHIGAN

A Primer on Coordinate Systems Commonly Used in Michigan

B.2 ESRI RESOURCES

Product Documentation

FUNCIONALITY MATRICES

arcgis 10.5 Enterprise Functionality Matrix Document Link
arcmap 10.5 Functionality Matrix Document Link
