

What We Do

Allegan County GIS
www.allegancounty.org/gis

December 21, 2018

Contents

Contents	ii
I Brand	1
1 Awards	3
1.1 The GIS Champion Award	3
GIS Champion	3
GIS Champion Award	3
Background	3
Statement of Problem	3
Analysis	3
GIS Champion Award Code	4
II Methods	7
2 Documentation	9
2.1 About Documentation	9
How Jalapeño Works	9
Colors	9
Blues	9
Golds	9
Oranges	9
Geens	10
Others	10
General Notes:	11
Project File Structure:	11
Using The Glossary	12
Glossary Requirements	12
Creating a new glossary entry	12
Rebuilding the glossary	12
Using glossary terms in a subdocument:	12

To use a glossary term	13
To add the glossary to the subdocument:	13
Using The Bibliography(References)	13
Bibliography requirements	13
Creating a new bibliography entry	13
Rebuilding the bibliography	13
To cite a bibliography source in a subdocument:	14
.	14
Adding the bibliography to the subdocument	14
Using The Index	14
Index requirements:	14
Creating a new index entry	14
Rebuilding the index	14
*Note:	15
Access the index from a subdocument	15
Using an index term	15
To add the index to the subdocument:	15
Using the Appendices	15
2.2 Document Storage Concepts	16
GIS File Standard	16
Folders inside the project folder	16
3 Team Concept	17
3.1 Team Structure	17
Paired Programming	17
III Service	19
4 Applications	21
4.1 Applications for Treasurer Dept.	21
Forfeiture Data Collector	21
Problem and Analysis	21
Background	21
Statement of Problem	21
Analysis	21
Design	22
Overview	22
Forfeiture App Summary	23
Technologies Used in The Forfeiture App .	24

BSA Data	24
ArcGIS Desktop	24
ArcGIS Collector	24
Enterprise Geodatabse	24
ArcGIS Portal	24
Data Details	25
ForfeitureParcels Feature Class	26
Webmap Details	27
Feature Layer Details	27
Basemap Details	28
Hard Copy Record	29
ArcGIS Server	29
Administrative Manual	30
Annual Setup	30
Add Query Layer	31
Details of the Query Layer	32
Select a Unique Identifier	33
Add Parcels Layer to the map	35
Create Join	36
Export Joined Features	37
Load data to forfeitureParcels	38
Match these fields	40
Data Setup	42
Create Attachments	43
Setup Users in ArcGIS	44
Add New User to Feature Dataset	45
Extend Privileges for New User	46
Setup Users in Portal for ArcGIS	47
Add Members to Portal	48
Enter required info	49
Manage Treasurer Group	50
Share Portal Content	51
Schema Change Procedure	52
Form Edits Procedure	53
User Manual	54
Collection Device Setup	54
Collector Application Setup Details	54
Install Collector for ArcGIS	54
Configure Collector	55
Download the Forfeiture Field Map	56
Choose Map Detail	58
Open Camera Application Setup Details	59
Install Open Camera	59

Configure Open Camera	60
Daily Preprocessing Routine	62
Execute Preprocessing Script	62
Synchronize the Forfeiture Field Map	63
Forfeiture Data Collection	64
Forfeiture Parcels Data Details	64
Device 1 Field Operation	65
Device 2 Field Operation	73
Daily Postprocessing Routine	75
Synchronize Webmap	75
Execute Postprocessing Script	75
Software	78
ESRI Licensed Products	78
ArcDesktop	78
Enterprise ArcGIS Deployment	78
Collector for ArcGIS	78
Other Software	78
Open Camera for Android	78
5 Tools	79
5.1 BSA Support	79
Adding a Layer to the BSA GIS	79
Add an Imagery Layer	79
BSA Program Setup	79
Setup Map Collections	80
Layers Setup	81
Select Layer Type	82
Add Layer From Local Drive	83
5.2 Core Data	84
Control Points	84
Editing Control Points	84
Fabric Point Move to Feature Addin	84
Configure Addin	84
5.3 ESRI Tools	88
COGO Tools in ArcGIS	88
5.4 GIS Administration	89
New Connections in ArcCatalog	89
Install SQL Server on client machine	89
Connect ArcGIS to a SQL Server Database	91
New Connection Dialog	92
Create Query in ArcGIS to SQL Database	93
Add Query Layer	93
Details of the Query Layer	94

More Details of the Query Layer	95
Open Results Table	96
Enterprise Geodatabase Maintenance	97
Enterprise Geodatabase Compression Routine .	97
Disconnect Users	97
Rebuild Indexes	99
Recalculate Statistics	100
Compress	101
Rebuild Indexes Again	102
Recalculate Statistics	103
Managing Map Services	104
Stopping the GIS Server	104
Fixing Damaged Services	105
Use the ArcGIS Server Account Utility .	105
Remove Lock Files	111
Managing Geodatabase Replicas	112
Adding A New Feature Class To A Replica .	112
Summary	112
Steps	112
Managing Geodatabase Versions	114
Version Queries	114
SQL Queries	114
Orphaned Versions	115
Remove orphaned versions	115
MXD Management	118
Find/Replace Text Object	118
Python Code	118
5.5 L ^A T _E X Packages	119
Common Errors	119
The Form of an Error	119
L ^A T _E X Errors	119
T _E X Errors	120
Warnings	120
Underfull	120
Overfull	120
References	121
Beginning and Ending	121
Begin Ended by End	121
End Occurred Inside a Group	122
Ended by End of Line	122
Missing Begin Document	123
Errors Usually Caused by Bad Spelling . . .	123
Unknown Control Sequence	123

Environment Undefined	123
Bad File Name	123
Cannot Find File Name	124
Fatal Errors	124
Runaway Argument	124
Just an *	124
Emergency Stop	125
Please Type a Command or Say End	125
Graphics Errors	125
Too Many Unprocessed Floats	125
Unknown Graphics Extension	126
Division by Zero	126
Math Errors	126
Display Math Should End With \$\$	126
Bad Math Environment Delimiter	127
Missing Right	127
Missing Delimiter	127
Missing \$ Inserted	128
Tabular Environment Errors	128
Misplaced Alignment Tab Character &	128
Extra Alignment Tab	128
Argument Has an Extra }	129
Errors With Lists	129
Missing Item	129
Too Deeply Nested	129
Miscellaneous Errors	129
Only Used in the Preamble	130
There Is No Line/Page Here to End	130
Command Already Defined	130
Missing Number	130
float Package	131
usepackage	131
Simple Use	131
Options	131
Use with Options	131
Commands	131
Graphics Examples and Notes	132
Curly Frame	132
Rectangle Frame	132
graphicx Package	134
usepackage	134
Simple Use	134
Options	134

	Use with Options	134
	Commands	134
	hyperref Package	134
	Introduction	134
	Simple Use	135
	Options	135
	Use with Options	136
	Commands	136
	import Package	138
	usepackage	138
	Simple Use	138
	Options	138
	Use with Options	138
	Commands	138
	standalone Package	139
	Introduction	139
	Simple Use	139
	Options	140
	Use with Options	140
	Commands	140
	wrapfig Package	141
	usepackage	141
	Simple Use	141
	Options	141
	Use with Options	141
	Commands	141
5.6	L ^A T _E X Templates	142
	L ^A T _E X Section Template	142
	L ^A T _E X Subsection Template	142
5.7	PDF Tools	144
	PDF Optimizer	145
	Pupose and Summary	145
	requirements	145
	ghostscript	146
	About	146
	Licensing	146
	Download	146
	Windows batch files	147
5.8	QGIS Tools	148
	Using COGO Tools in QGIS	148
	Set up the Azimuth and Distance Plugin	148
	Configure Options	150
	Using the tool	151

Configure editing environment	152
Locate Point of Commencement	153
Using Reference Layer	153
Using Measuring Tool	154
Search by Parcel Number	155
IVResources	157
A.1 Geography 101	159
Coordinate Systems for Michigan	159
B.2 ESRI Resources	159
Funcionality Matrices	159
References	161
Glossary	161

Part I

Brand

1

Awards

1.1 THE GIS CHAMPION AWARD

GIS CHAMPION

Proactive promotion of the use of GIS

GIS CHAMPION AWARD

Background

Though Allegan County has had a formal GIS department for over 20 years, very few people in the government have learned to use it.

in its government. Currently there is no formal recognition of individuals that promote GIS.

Statement of Problem

GIS is underutilized in Allegan County government. The county would benefit from more GIS use

Analysis

A simple method of recognizing those that promote GIS in the county is the idea behind the GIS Champion Award. The award is a certificate created and presented by ACGIS Services to anyone for any reason.

GIS Champion Award Code

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
%\geometry{tmargin=.75cm,bmargin=.25cm,
%lmargin=.8cm,rmargin=.2cm}
\geometry{tmargin=.25in,bmargin=.25in,
    lmargin=.25in,rmargin=.25in}
\usepackage{multicol}
\setlength{\columnseprule}{0.4pt}
\columnwidth=0.3\textwidth

\begin{document}
\centering
\scalebox{2.9}{
\color{green!30!black!60}
\begin{minipage}{.33\textwidth}
\font\border=umrandb
\generalframe
{\border \char113} % up left
{\border \char109} % up
{\border \char112} % up right
{\border \char108} % left
{\border \char110} % right
{\border \char114} % lower left
{\border \char111} % bottom
{\border \char115} % lower right
\centering
\includegraphics[height=1.5cm]{GIS_Logo_better.jpg}

\vspace{-8mm}

\curlyframe[.9\columnwidth]{

\textcolor{green!10!black!90}{\small Allegan County GIS Services}
\vspace{.005in}
}
```

```
\textcolor{green!10!black!90}{  
  \tiny Recognizes}\\  
  \%smallskip  
  \vspace{.005in}  
  \underline{\textcolor{green!30!black!60}{  
    \textcolor{green!30!black!60}{Brian Redmond}}}  
  \\  
  \%smallskip  
  \tiny Information Services Technician  
  
  \%smallskip  
  \textcolor{green!10!black!90}{  
  {  
  \\  
  \tiny for Excellence in  
  }  
  \%smallskip  
  \\  
  \textcolor{black}{\normalsize \textsc{Enabling  
    Employee Experiences}}  
  \\  
  \vspace{.1in}  
  \textcolor{green!10!black!90}{  
  {  
  \tiny on this day  
  \itshape September 21, 2018  
  }  
  
  \vspace{.1in}  
  
  {\color{green!10!black!90}  
  \scalebox{.6}{
```

```
\begin{tabular}{ccc}
\cline{1-1}
\cline{3-3}
\\
Neil Besteman & & Bryan May \\
GIS Manager & & GIS Analyst \\
\end{tabular}

} % closes scalebox{.6} arg
} % closes blue!40!black
} % closes curlyframe arg
} % closes centering
\end{minipage}
} % closes scalebox{2.8} arg

\end{document}
```

Part II

Methods

— 2 Documentation

2.1 ABOUT DOCUMENTATION

HOW JALAPEÑO WORKS

COLORS

Blues

HeaderBlueA _____
HeaderBlueB _____
HeaderBlueC _____
HeaderBlueD _____
HeaderBlueE _____

Golds

HeaderGoldA _____
HeaderGoldB _____
HeaderGoldC _____
HeaderGoldD _____
HeaderGoldE _____

Oranges

HeaderOrangeA _____
HeaderOrangeB _____
HeaderOrangeC _____
HeaderOrangeD _____

HeaderOrangeE _____

Greens

HeaderGreenA _____

HeaderGreenB _____

HeaderGreenC _____

HeaderGreenD _____

HeaderGreenE _____

Others

HyperlinkBlue1 _____

graphicOrange _____

GENERAL NOTES:

- jalapeno folder is a git package.
<https://github.com/nbesteman/jalapeno>
- Project is coded with relative paths and jalapeno can be located anywhere.

PROJECT FILE STRUCTURE:

...\\jalapeno\\..

folder	description
documentation	resources used in Jalapeño
processing	.tex documents and build folders
source	common image files

...\\jalapeno\\documentation\\..

folder or file	description
moduleTemplates	.tex templates
packageDocs	L ^A T _E X documentation
references	reference and appendix resources
unsorted	catch all for unsorted documentation
BookStructureMM.mm	A mindmap of jalapeno

...\\jalapeno\\processing\\..

folder or file	description
...Part	folders of book <i>parts</i>
build	L ^A T _E X folder for .pdf output and temp files
build\\referenceEntries.bib	entries that appear in references
commonTitle.tex	code for all title pages
fullCompile.sh	shell script to compile GISDocumentation.tex
GISDocumentation.tex	master document code
glossaryEntries.tex	entries that appear in glossary
indexEntries.tex	entries that appear in the index
preamble.tex	preamble code for all documents

*Note about referenceEntries.bib

Any reference entries built here can be cited in any .tex document in the project.

USING THE GLOSSARY

Glossary Requirements

Glossary commands require a Perl interpreter. Activeperl is a free Perl interpreter and can be downloaded from:

<https://www.activestate.com/activeperl/downloads> (A typical installation adds Perl to your path). Compiling the glossary requires running the makeglossaries command either in a L^AT_EX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeglossaries to create an .gls file. After the .gls file is created, PDFLatex must be run again to insert the glossary at the \printglossaries location.

Creating a new glossary entry

To **create a new glossary entry**: Add an entry to glossaryEntries.tex. Save it there and then use the makeglossaries command to recompile the .gls file.

Rebuilding the glossary

To Recompile the .gls. In the (main document)build folder:

- Launch command prompt
- enter command: **makeglossaries GISDocumentation***

*Note:

This command reads the .aux file and creates the .gls file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

Using glossary terms in a subdocument:

In the subdocument you must add code to input the glossaryEntries file. For example:

After the line:

```
\input{../../../../../preamble}
```

Add the line:

```
\input{../../../../glossaryEntries}
```

To use a glossary term in the subdocument:

In place of the term, use code referencing the key (in the glossaryEntries file):

➢ \gls{key}

To add the glossary to the subdocument:

- Add the line \makeglossaries to the preamble of the subdocument.
- Add the line \printglossaries to the subdocument.
- Run makeglossaries in command line on the subdocument similar to how is described above.

USING THE BIBLIOGRAPHY(REFERENCES)

Bibliography requirements

Compiling the bibliography requires running bibtex either in a L^AT_EX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by bibtex to create a .bbl file. After the .bbl file is created, PDFLatex must be run again to insert the bibliography at the \bibliography location.

For example, the command:...\\bibliography{referenceEntries}
...places the bibliography called referenceEntries.bib which must be in the same folder as the project .aux file.

Creating a new bibliography entry

To create a new bibliography entry: Add an entry to referenceEntries.bib. Save it there and then use bibtex to recompile the .bbl file.

Rebuilding the bibliography

To Recompile the .bbl. In the (main document)build folder:

- Launch command prompt
 - enter command: **bibtex GISDocumentation**
-

*Note:

This command reads the .aux file and creates the .bbl file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail.

To cite a bibliography source in a subdocument:

In the place that you want the citation:

➢ `\cite[pg.#]{key}`

Adding the bibliography to the subdocument

➢ Similar to adding to the master document but not documented here.

USING THE INDEX

Index requirements:

Compiling the index requires running the makeindex command either in a L^AT_EX IDE or in command line as described here. PDFLatex must be run first to create a .aux file that is used by makeindex to create an .idx file. After the .idx file is created, PDFLatex must be run again to insert the index at the \printindex location.

Creating a new index entry

To create a new index entry: Add an entry to indexEntries.tex. Save it there and then use the makeindex command to recompile the .idx file.

Rebuilding the index

To Recompile the .idx In the (main document) build folder:

- Launch command prompt
- enter command: **makeindex GISDocumentation***

*Note:

This command reads the .aux file and creates the .idx file. The .aux file is created by compiling with PDFLatex. If there is no .aux file the command will fail. Run PDFLatex first

Access the index from a subdocument

In the subdocument you must add code to input the indexEntries file.

For example:

After the line:

```
\input{../../../../../preamble}
```

Add the line:

```
\input{../../../../indexEntries}
```

To use a index term in the subdocument:

In place of the term, use code referencing the key (in the indexEntries file):

- \index {key}

To add the index to the subdocument:

- Add the line \makeindex to the preamble of the subdocument.
- Add the line \printindex to the subdocument.
- Run makeindex in command line on the subdocument similar to how is described above.

USING THE APPENDICES

2.2 DOCUMENT STORAGE CONCEPTS

GIS FILE STANDARD

FOLDERS INSIDE THE PROJECT FOLDER

Lets talk about

- archive
- build
- delivered
- documentation
- processing
- source

— 3 —

Team Concept

3.1 TEAM STRUCTURE

PAIRED PROGRAMMING

A paragraph about pp from Joy Inc.

Part III

Service

4

Applications

4.1 APPLICATIONS FOR TREASURER DEPT.

FORFEITURE DATA COLLECTOR APPLICATION

PROBLEM AND ANALYSIS

Background

Treasurer department has an annual responsibility to properly document the tax forfeiture process. The LIS Department built an application in MS Access and MapInfo that consumed a daily export from BSA and was deployed to the field on a laptop. A digital camera was used for site photos and later imported into the laptop.

must be recreated in the ESRI framework.

Analysis

Forfeiture App will facilitate: *Mobile data collection on a handheld device; (Mobile Interface)* and an *in office workflow to complete data processing, (Pre and PostProcessing)*

Mobile Interface

- Synchronize with data in the office (online)
- Collect data and photos of forfeiture sites (offline)
- Synchronize the collected data with data in the office (online)

Pre & Post Processing

- Produce and print a form for each site visited with required data and images

Statement of Problem

The current Tax Forfeiture workflow is built on MapInfo software and MS Access and executed on a laptop pc. Both MapInfo and MS Access are no longer supported in county workflows. ESRI software can be used to rebuild the workflow. *Forfeiture Data Collector Application, (Forfeiture App)*

DESIGN

Overview

The key data set : **Forfeiture Parcels**
is used through the workflow




Figure 4.1: Project Design

Forfeiture App Summary

There are three parts to the daily routine:

1. Preprocessing (in the office):
 - Export current forfeiture list from BSA
 - Update Forfeiture Parcels with BSA export
 - Update Forfeiture Parcels with contaminated sites information
 - Synchronize Forfeiture Parcels to Mobile Interface
2. Field data collection with Mobile Interface:
 - Aids in navigation
 - Provides a Checklist of data points for each site
 - Attaches photos for each site
 - Save results for synchronization in post-processing
3. Post-processing (in the office)
 - Synchronize data and images collected in Mobile Interface to Forfeiture Parcels
 - Export form for each site
 - Print form for each site
 - Update BSA data

Technologies Used in The Forfeiture App

BSA Data

Details of parcels in the forfeiture process are managed in BSA Delinquent Tax.net. The Treasurer office does a BSA export of the parcels in need of a site visit in the preprocessing.

ArcGIS Desktop

Tools are designed to preprocess and postprocess forfeiture parcel data for fieldwork. The user will execute a preprocess script tool that prepares the data for field deployment. After fieldwork, a post process script tool synchronizes data from the fieldwork with the live data on the Allegan County network.

ArcGIS Collector

A free mobile application developed and tested on Android is deployed to the field for data collection. The application is con-

figured to work offline (without an internet or cellular connection) by syncronizing before and after fieldwork. The user collects the necessary information on each forfeiture parcel in the field disconnected, and then uploads the changes when reconnected.

Enterprise Geodatabase

Live data from a publishing geodatabase (ACPUB), running on SQL Server database server (acintsql01) provides access to Forfeiture Parcels

ArcGIS Portal

Forfeiture Parcels is served as a feature service (REST service) named TaxReversionParcels. A webmap on Portal, called the Forfeiture Field Map consumes the TaxReversionParcels exposing the data to editing. The Forfeiture Field Map is configured to work in the ArcGIS Collector App.




Figure 4.2: Technology Design

DATA DETAILS

The data is located in a geodatabase called ACPUB. ACPUB is on SQL Server ACINTSQL01.

Forfeiture Parcels Data




Figure 4.3: Live Data Location

Contamination Data




Figure 4.4: Contamination Feature Class

ForfeitureParcels Feature Class

Attribute Details			
Field Name	Field Alias	Entry Type	Note
PropertyNumber	Property Number	Prefilled	NA
Need2Print	Print Today	Dropdown	Yes or No
InspectionDate	Inspection Date	Autofill or Dropdown	NA
Inspector	Inspector	Dropdown	NA
Address	Address	Prefilled	NA
Status	Status	Dropdown	NA
StatusNotes	Status Notes	Open Entry	120Char
Roadfrontage	Road Frontage	Dropdown	Yes or No
AccessVia	Access Via	Open Entry	30Char
Agent	Agent	Open Entry	30Char
AgentContact	Agent Contact	Open Entry	30Char
PictureComments	Picture Comments	Open Entry	50Char
PropertyInUse	Property In Use	Dropdown	Yes or No
UseNotes	Use Notes	Open Entry	120Char
PropertyMaintained	Property Maintained	Dropdown	Yes or No
PropMaintNotes	Property Maintained Notes	Open Entry	120Char
PropertyContaminated	Property Contaminated	Prefilled	Preprocessing
PropertyContaminatedNotes	PropertyContaminatedNotes	Prefilled	Preprocessing
AdjacentPropertyContaminated	Adjacent Property Contaminated	Prefilled	Preprocessing
AdjPropertyContaminatedNotes	Adj Property Contaminated Notes	Prefilled	Preprocessing
PropertyForSale	Property For Sale	Dropdown	Yes or No
GlobalID	GlobalID	NA	NA
PostedDate	Posted Date	Dropdown	Date
Posted	Posted	Prefilled	NA
InList	In List	Prefilled	Preprocessing
PostedInList	Posted In List	Prefilled	Preprocessing
Acres	Acres	Prefilled	NA
Class	Class	Prefilled	NA

Table 4.1: Dataset Details

Webmap Details

The Forfeiture Field Map is made up of a basemap and a feature layer.




Figure 4.5: Web Map Details

Feature Layer Details

TaxReversionParcels has been configured for offline use.




Figure 4.6: Feature Layer Details


Basemap Details

- A tiled basemap service is used

- The infoserv user credentials are used for sharing

- The url for the shared service is:

[https://tiledbasemaps.arcgis.com/arcgis/rest/
services/World_Street_Map/MapServer](https://tiledbasemaps.arcgis.com/arcgis/rest/services/World_Street_Map/MapServer)



The screenshot shows the ArcGIS Online interface for the 'World Street Map (for Export)' layer. At the top, there's a navigation bar with links for ArcGIS, Pricing, Map, Scene, and Help, along with a Sign In button and a search bar. Below the navigation is a blue header bar with the title 'World Street Map (for Export)'. Underneath the header, there's a sub-header 'Overview' and a detailed description of the layer. The description states: 'This layer presents highway-level data for the world and street-level data for many areas around the world. This layer is designed to support export of basemap tiles for offline use. ArcGIS Online Subscription required.' It also includes a thumbnail image of a map showing a red highlighted area, and information about its creation date (Oct 15, 2013), last update (Aug 15, 2018), and view count (39,772). There are two status buttons: 'Authoritative' and 'Subscriber'. To the right of the description, there are three buttons: 'Open in Map Viewer', 'Open in Scene Viewer', and 'Open in ArcGIS Desktop'. Further down, there's a 'Details' section with a 'Source: Map Service' link, a size indicator ('Size: 1 kB'), and a five-star rating. Below that is an 'Owner' section showing 'Esri' as the owner and 'Managed by: Esri'. Finally, there's a 'Tags' section listing various geographical and thematic terms.

Figure 4.7: Basemap Source Description

HARD COPY RECORD

screenshots: arcmap map arcmap tools portal screenshots sql server
mgt screen shots phone screenshots

ArcGIS Server

ADMINISTRATIVE MANUAL

Annual Setup

A new dataset for forfeiture parcels must be created each year. The forfeiture information comes from BSA Forfeitures.net and the parcel geometry and other attributes comes from ACParcelsCombined.

To get the BSA Forfeiture data, create a table query for a certain year.

First, clear the features from the existing ForfeitureParcels dataset

- Use the Delete Feature Tools
- In the tool:
 - Select ACPub.DBO.ForfeitureParcels




Figure 4.8: Delete Features

Press OK

Add Query Layer

- In ArcMap ⇒ Open the New Query Layer Dialog
- File ⇒ Add Data ⇒ Add Query Layer
- Select your connection




Figure 4.9: New Query Layer Dialog

Query Text:

```
SELECT [parcelnumber] FROM [D005ALLEGAN].[dbo].[Forfeitures]
WHERE forf_year = 2019
```

Details of the Query Layer

- Choose connection
- Name the query
- Enter SQL query




Figure 4.10: Forfeiture Query Layer Details

- Press Next

Select a Unique Identifier

- Press Finish




Figure 4.11: Query Layer Unique ID

Table is added to the map

The screenshot shows the ArcGIS interface with two windows open:

- Table Of Contents:** This window lists the layers in the map. It includes the "dbo.DEFAULT (ac-intsql01)" layer, the "AC_Pub.DBO.Treasurer" layer, the "AC_Pub.DBO.ForfeitureParcels" layer, and the "D005ALLEGAN" feature dataset. Within "D005ALLEGAN", the "D005ALLEGAN.DBO.forfeitures" table is listed and highlighted with a red box.
- Table:** This window displays the contents of the "D005ALLEGAN.DBO.forfeitures" table. The table has two columns: "parcelnumber" and "ESRI_OID". The data consists of 836 rows of parcel numbers and their corresponding ESRI_OIDs. The first few rows are as follows:

parcelnumber	ESRI_OID
01-007-012-00	1
01-008-005-00	2
01-016-031-10	3
01-019-001-13	4
01-019-005-97	5
01-025-017-00	6
01-026-020-00	7
01-030-014-10	8
01-030-019-00	9
01-031-031-00	10
01-034-009-00	11
01-034-014-10	12
01-034-055-00	13
01-034-067-00	14
01-034-087-00	15
01-034-108-00	16
01-035-015-00	17
01-035-020-20	18
01-035-030-00	19
01-035-044-00	20
01-035-044-10	21
01-120-004-00	22
01-120-010-00	23
01-120-031-00	24
01-120-032-00	25
01-220-010-00	26
01-250-001-00	27
01-300-004-00	28
01-320-020-00	29
01-320-021-00	30
01-370-016-00	31
01-740-009-00	32
02-001-012-31	33
02-003-018-00	34
02-005-004-20	35
02-007-025-00	36

At the bottom of the Table window, it says "(0 out of 836 Selected)".

Figure 4.12: Forfeiture Table Added

Add Parcels Layer to the map

Add ACParcelsCombined to the map to provide parcel geometry and attributes




Figure 4.13: Parcels Layer Added

Create Join

Create new join to ACParcelsCombined of forfeitures based on parcel numbers




Figure 4.14: Join Parcels

Export Joined Features to a temp location

- Right click ➔ on joined feature class in TOC and choose export




Figure 4.15: Export Joined Features

- choose location and press OK

Load data from temp location to forfeitureParcels




Figure 4.16: Load Data 1

push next




Figure 4.17: Load Data 2

Match these fields




Figure 4.18: Match Fields 1




Figure 4.19: Match Fields 2

push next




Figure 4.20: Load Data 3

Push Finish

Data Setup

Register as versioned and Add Global IDs

Right Click ⇒ Manage ⇒ Register as Versioned

and

Right Click ⇒ Manage ⇒ Add Global IDs




Figure 4.21: Setup Data

Create Attachments

Right Click ⇒ Manage ⇒ Add Attachments




Figure 4.22: Create Attachments

Setup Users in ArcGIS

Users that will run Pre and Post processing scripts must be created and given privileges on ACPub Treasurer Feature Data Set.

For any new users of the geoprocessing tools, use the create Database User tool **or**

In Catalog ⇒ Right click on ACpub ⇒ Administration ⇒ Add User




Figure 4.23: Add Db User

Add New User to Feature Dataset

In Catalog, ⇒ right click on Treasurer Feature Data Set ⇒ Manage ⇒ Privileges ⇒ Add ⇒ Type new user ⇒ ok




Figure 4.24: Add Feature Dataset User

Extend Privileges for New User

In Catalog ⇒ right click on Treasurer FDS ⇒ Manage ⇒ Privileges ⇒ check boxes




Figure 4.25: Extend Feature Dataset Privileges

Setup Users in Portal for ArcGIS

Users that will use the Collector for ArcGIS must have profiles added to and managed in the Allegan County GIS Portal site.

In Portal go to My Organization

The screenshot shows the 'My Organization' page of the Allegan County GIS Services portal. At the top, there's a navigation bar with links for Home, Gallery, Map, Scene, Groups, My Content, and My Organization. The 'My Organization' link is underlined, indicating it's the active page. Below the navigation is a search bar with the name 'Bryan' entered. The main content area is titled 'Allegan County GIS Services'. It features a table titled 'Members' with the following data:

Name	Username	Last Login	Level	Role	Action
Bryan May	bmay31	Nov 2, 2018	②	Administrator	
Christina Andress	candress	Sep 19, 2018	②	Administrator	
Jennifer Morris	jMorris	Oct 18, 2018	②	Administrator	
Neil Besteman	nbesteman	Oct 29, 2018	②	Administrator	
Paula Reed	preed6	Feb 7, 2017	①	Viewer	

On the right side of the page, there's a sidebar titled 'Membership' with the following information:

- Members per level:
 - 1 of 30
 - 2 of 5
- Total Members: 5 of 35
- Find...
- The most viewed items
- The last items added
- Groups
- The organization's registered apps

Figure 4.26: Portal Add User 1

Add Members to Portal

Push add members ⇒ built in member




Figure 4.27: Portal Add User 2

Enter required info

The screenshot shows a web-based application titled "Add Members". At the top left is the Allegan County GIS Services logo. The main title "Add Members" is centered above a form area. A blue circular icon with the number "2" is positioned to the left of the instructions. The instructions read: "Create new Allegan County GIS Services logins one at a time or in batch from a file. Select any role for the member to be a part of. You must inform the member of their user name and password. If you do not have an email address for a particular user, use the administrator's email address." Below the instructions, a note says "Password may not be less than 8 characters." There are two tabs at the top of the form: "One at a time" (selected) and "From a file". The form fields include: Email (text input), First Name (text input), Last Name (text input), Username (text input), Password (text input), Level (radio buttons for 1 or 2, with 2 selected), Role (dropdown menu showing "Publisher"), and three buttons at the bottom: "BACK", "ADD ANOTHER" (green button), and "REVIEW ADDITIONS".

Figure 4.28: Portal Add User 3

Manage Treasurer Group

In Portal ⇒ Go to groups ⇒ Invite new user to the group




Figure 4.29: Portal Add User 4

Share Content To The Group

Any content used by the group needs to be shared to the group




Figure 4.30: Portal AddUser 5

Schema Change Procedure

Form Edits Procedure

USER MANUAL

Collection Device Setup

Collector Application Setup Details

Install Collector for ArcGIS

- Available from the Google Play Store




Figure 4.31: Download the App

Configure Collector

for Organization Website, Type:

{\textcolor{HeaderOrange}{HeaderC}}
`https://gis.allegancounty.org/portal_webadaptor}`

then:

Press Continue




Figure 4.32: Collector Connection

Enter Credentials

then:

Press SIGN IN




Figure 4.33: Enter Credentials

Download the Forfeiture Field Map

There are 3 different versions of the map

- Forfeiture Field Map
- Forfeiture Field Map For Photos
- Forfeiture Field Map For Attributes

The Download option indicates it is not on the device but is available for offline use

Choose a Map

Press Download




Figure 4.34: Collector Maps Menu

Specify work area

and press

map detail

Note that a larger area takes longer to download but the basemap only needs to be downloaded once




Figure 4.35: Choose Work Area (large)

Choose Map Detail

Zoom into the level of detail desired.

Press Download




Figure 4.36: Choose Map Detail

This area is ready for field data collection.




Figure 4.37: Map on Device

Open Camera Application Setup Details

Install Open Camera

- Available from the Google Play Store




Figure 4.38: Open Camera from Google Play Store

Configure Open Camera

In the Open Camera Application:

Press the gear shaped Settings button to go into the settings menu




Figure 4.39: Find Settings Menu

Press the Photo Settings button




Figure 4.40: Setting Screen

Set Photo Resolution

In photo settings:

Press the Camera resolution button




Figure 4.41: Photo Settings Menu

Select **640 x 480**




Figure 4.42: Camera Resolution Setting

Daily Preprocessing Routine

Execute Preprocessing Script

A tool in ArcGIS that:

- Exports current forfeiture list from BSA
- Updates webmap layers with results from BSA export

In Catalog:

Open the tool-box




Figure 4.43: Processing Tools

Open tool 1

Synchronize the Forfeiture Field Map

Note the date and time:





Figure 4.44: Map Downloaded

Note the date and _____
time:



Map is synchronized

Figure 4.45: Map Synchronized

Forfeiture Data Collection

Forfeiture Parcels Data Details

Attributes are of four entry types:

- prefilled
- autofill
- dropdown
- text box

For each site visited, select the desired parcel, push the edit button and collect attributes.

Device 1 Field Operation

Select a parcel



Figure 4.46: Select Parcel

Push the edit button




Figure 4.47: Parcel Details

Device 1 Field Operation Cont.

Select Yes for Print Today





Figure 4.48: Print Today
Yes or No

Select Use Current or enter
any date



Select Inspector From Drop-
down

Figure 4.49: Enter Date




Figure 4.50: Select Inspec-
tor

Device 1 Field Operation Cont.

Select Occupied or Not Occupied




Figure 4.51: Status

Enter status notes up to 120 characters




Figure 4.52: Status Notes

Select Yes or No for Road Frontage





Figure 4.53: Road Frontage


Device 1 Field Operation Cont.

Enter road used for access



Enter Agent Name

Figure 4.54: Access Via



Enter Agent Contact Info

Figure 4.55: Agent




Figure 4.56: Agent Contact

Device 1 Field Operation Cont.

Enter Use Notes up to 120 characters




Figure 4.57: Use Notes

Enter Notes up to 120 characters




Figure 4.58: Notes

Enter property for sale yes or no




Figure 4.59: Property for Sale

Device 1 Field Operation Cont.

Property in Use Yes or No




Figure 4.60: Property in Use

Placeholder




Figure 4.61: Placeholder

prefilled




Figure 4.62: Property Contaminated

Device 1 Field Operation Cont.

Enter notes up to 120 characters





Figure 4.63: Notes up to 120 characters

Adjacent Property Contaminated prefilled



Property Contaminated notes prefilled

Figure 4.64: Adjacent Property Contaminated




Figure 4.65: Property Contaminated

Device 1 Field Operation Cont.

Property Maintained Yes or
No




Figure 4.66: Property Maintained

Picture Comments up to 120 characters




Figure 4.67: Picture Comments

Placeholder




Figure 4.68: Placeholder

Device 2 Field Operation

Use photos taken with the Open Camera Application.

Select a parcel from the map



Figure 4.69: Select Parcel

Push Attachment Button




Figure 4.70: Push Attachment Button

Select Gallery




Figure 4.71: Add Attachment From Gallery

Device 2 Field Operation Cont.

Navigate to the Open Camera Folder





Figure 4.72: Open Camera Folder

Select the appropriate image



Press the check button to save the image to the parcel

Figure 4.73: In the Open Camera Folder




Figure 4.74: Image in the App

Daily Postprocessing Routine

Back at the office

Synchronize Webmap

In Collector for ArcGIS, push the sync button on the Forfeiture Field Map

Execute Postprocessing Script

The Postprocessing Script is A tool in ArcGIS that:
Reconciles geodatabase
versions





Figure 4.75: Reconcile Versions and
Execute the Reconcile
Versions and Compress
Tool



Generates forms for each site visited

Figure 4.76: Export Report Tool

Execute the Export
Report Tool

- Reconciles geodatabase versions
 - Execute the Reconcile Versions and Compress Tool




Figure 4.77: Reconcile Versions and Compress Tool

- Generates forms for each site visited
 - Execute the Export Report Tool




Figure 4.78: Export Report Tool

SOFTWARE

ESRI Licensed Products

ArcDesktop

Users of this application need a license to ArcGIS Standard level.

Enterprise ArcGIS Deployment

This app uses ArcGIS Server and ArcGIS Portal.

Collector for ArcGIS

Developed and tested on Android(7.0). Collector is available at the Google Play Store.

Other Software

Open Camera for Android




Figure 4.79: Open Camera from Google Play Store

5

Tools

5.1 BSA SUPPORT

ADDING A LAYER TO THE BSA GIS

ADD AN IMAGERY LAYER

BSA Program Setup

(BSA Settings)

In Program Setup ⇒ Select GIS Settings...




Figure 5.1: BSA Program Setup

Setup Map Collections

(BSA Settings Cont.)

In **GIS Settings** ⇒ **Map Collections** ⇒

Double click on the map that you want to add a layer to




Figure 5.2: GIS Setup

In Setup Layers

(BSA Settings Cont.)

Setup Layers ⇒ Add




Figure 5.3: Layers Setup

Select Layer Type

(BSA Settings Cont.)

Setup Layers ⇒ Select Image ⇒ OK




Figure 5.4: Select Layer Type

Add Layer From Local Drive

(BSA Settings Cont.)

Navigate to Image File ⇒ Open




Figure 5.5: Add Layer From Drive

The new image is in the map

5.2 CORE DATA

CONTROL POINTS

MAINTAINING CADASTRAL CONTROL POINTS

Install the Fabric Point Move to Feature Addin

⇒ Push the Configure Button




Figure 5.6: Fabric Point Move to Feature Addin

Configure Addin

- Set Reference Feature Layer to TargetPoints
 - Use point to point matching
 - Use point layer field: PointID
-




Figure 5.7: Addin Configuration Method

2

Configure Fabric Point Move to Feature addin Selected Feature Options
Move Fabric Points of the Selected Parcels

Push OK

FabricPointMoveToFeatureConfigSelectedFeatures.png

3

Identify position of new control point

Select TargetPoints in Create Features Templates

Create Target Point at location for new Control Point

createTargetPoint.png

4

Use Identify tool to find ObjectId of Control Point that is to be moved

Select the Target point PointID of the point its moving to

Edit Target Point pointID attribute to match associated fabric control poi

updateTargetPointPointID.png

4.5

Push move point button

moveControlPoint.png

5

Open maintain control point tool

Select control Point

push edit button

maintainControlPointTool.png

6

Use Identify Tool to View X and Y vals for the point

copy x and y value from point(attribute window) to Control (maintain contr

push update

Save Edits

transferCoordinates.png

Identify position of new control point

Place Target Point

Update Target Point attributes to associated fabric point OID

Push move point button

Zoom to Control point
Open maintain control point tool
Select control Point
edit button
copy x and y value from
identify tool x and y of points
update button

5.3 ESRI TOOLS

COGO TOOLS IN ARCGIS

TEXT

5.4 GIS ADMINISTRATION

NEW CONNECTIONS IN ARCCATALOG


INSTALL SQL SERVER ON CLIENT MACHINE

On client machine:

For any machine to connect to the Enterprise Geodatabase, SQL Server Native Client must be installed locally.

Search for sql server native client download on the internet

margin note ⇒



Microsoft® SQL Server® 2012 Native Client - QFE




Figure 5.8: SQL Server Client Search

Select appropriate Version

Decide whether to get the 32bit or 64bit version

← margin note



Choose the download you want

File Name	Size
ENU\x64\sqlIncli.msi	For 64bit OS 4.8 MB
ENU\x86\sqlIncli.msi	For 32 bit OS 3.0 MB

Figure 5.9: SQL Server Client Search Choose

Download and Install

CONNECT ARCGIS TO A SQL SERVER DATABASE

In Catalog:

Double click on add database connection




Figure 5.10: Catalog Add Db Connection

NEW CONNECTION DIALOG

Enter into the tool

- Select Database Platform
- Enter Instance Name
- Enter user name and password
- Check Save user name and password
- Select Database in dropdown




Figure 5.11: Catalog Add Database Connection

CREATE QUERY IN ARCGIS TO SQL DATABASE

ADD QUERY LAYER

In ArcMap:

Open the New Query Layer Dialog

Go to ⇒ File ⇒ Add Data ⇒ Add Query Layer In the connection dropdown select your connection

NOTE




Figure 5.12: New Query Layer Dialog

DETAILS OF THE QUERY LAYER

Enter into the tool

- Choose connection
- Name the query
- Enter SQL query
- Press Next




Figure 5.13: Query Layer Dialog Filled

MORE DETAILS OF THE QUERY LAYER

Enter into the tool

- Select unique identifier field
- Click Finish




Figure 5.14: Select Unique Identifier

OPEN RESULTS TABLE

Verify the Query by Looking at the Table

The screenshot shows the ArcGIS Pro interface with the 'Table Of Contents' panel open. Inside, there is a 'Layers' section containing a single item: 'D001COUNTY WEB 18.DBO.NewQuery'. This item is highlighted with a red box. To the right of the layers is a 'Table' view showing the results of the query. The table has the following structure:

propertyid	ownername1	ownerstreetaddr	ownercity	ownerstate	ownerzip	ESRID
56-004-001-00	WAGNER LOINNE S & ERICA	782 13TH AVE	WAYLAND	MI	49348	1
56-004-001-10	GULI LAKE COMMUNITY CHURCH	12200 WEST MI-179	WAYLAND	MI	49348	2
56-004-002-00	WAYLAND UNION SCHOOLS	850 E SUPERIOR ST	WAYLAND	MI	49348	3
56-004-003-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	4
56-005-001-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	5
56-005-002-00	ELIAS WAYLAND LLC	1645 BIRMINGHAM DR	LOWELL	MI	49331	6
56-005-002-00	ELIAS WAYLAND MEDICAL CARE REALTY I	1645 BIRMINGHAM DR AVE E	SEALT RIVER WA	WA	98109	7
56-005-002-20	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	8
56-005-002-30	RIPARIAN PROPERTIES LLC	879 E SUPERIOR ST	WAYLAND	MI	49348	9
56-005-002-40	RIPARIAN PROPERTIES LLC	879 E SUPERIOR ST STE A	WAYLAND	MI	49348	10
56-005-002-41	VB VENTURES WAYLAND LLC	235 140TH AVE	WAYLAND	MI	49348	11
56-005-002-42	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	12
56-005-002-43	LATIMER, ROBERT W & JUDITH	841 E SUPERIOR ST	WAYLAND	MI	49348	13
56-005-005-00	BREWER SUZANNE M	841 E SUPERIOR ST	WAYLAND	MI	49348	14
56-005-006-00	STORA RODERICK M & MELISSA K	841 E SUPERIOR ST	WAYLAND	MI	49348	15
56-005-006-10	ARY DOUGLAS & JULIE	104 MARLO LN	WAYLAND	MI	49348	16
56-005-006-20	DUBAY DOUGLAS	102 MARLO LN	WAYLAND	MI	49348	17
56-005-006-30	COOPERMAN JEFF	811 E SUPERIOR	WAYLAND	MI	49348	18
56-005-007-10	BENNETT JILL & CARRON BIANCE	2514 BROOKSCT LN	GRAND RAPIDS	MI	49508	19
56-005-007-20	VILLELLA MATTHEW	101 MARLO LN	WAYLAND	MI	49348	20
56-005-007-21	JENSEN KRISTEN S	103 MARLO LN	WAYLAND	MI	49348	21
56-005-008-00	WAYLAND CHRISTIAN REF CHURCH	303 E ELM STREET	WAYLAND	MI	49348	22
56-005-008-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	23
56-005-008-00	PROGRESSIVE MEDICAL CARE PROPERTY LLC	1000 WASHINGTON ROAD	WESTFIELD OH	OH	45062	24
56-005-011-00	CITY OF WAYLAND	103 S MAIN ST	WAYLAND	MI	49348	25
56-005-011-20	FERGUSON, ROBERT K	5770 VENTURE PARK	KALAMAZOO	MI	49009	26
56-005-012-00	REDSTONE LAND DEVELOPMENT LLC	3330 GRAND RIDGE DR NE	GRAND RAPIDS	MI	49525	27
56-005-012-10	VANDERVORD JOHN C & NANCY L	542 FOREST ST	WAYLAND	MI	49348	28
56-005-012-50	LAMB B LLC	2645 24TH AVE	HUDSONVILLE	MI	49426	29
56-005-013-00	ELIAS WAYLAND LLC	103 S MAIN ST	SHELDON IA	IA	50664	30
56-005-014-00	COPPERMAN JOHN C	125 OAK ST	WAYLAND	MI	49348	31
56-005-015-00	REDSTONE LAND DEVELOPMENT LLC	3330 GRAND RIDGE DR NE	GRAND RAPIDS	MI	49525	32
56-005-016-00	WALKER MICHAEL	131 OAK ST	WAYLAND	MI	49348	33
56-005-017-00	FLUIT MARK & MARYELLEN	137 OAK ST	WAYLAND	MI	49348	34
56-005-018-00	GUTIERREZ SAUL O & ORTIZ CHRISTINA	119 OAK ST	WAYLAND	MI	49348	35
56-005-018-00	MEDELLIN, GREGORY & THERESA #56	103 S MAIN ST	WAYLAND	MI	49348	36
56-005-020-00	WILLIAMS TERESA A	540 N MAIN ST	WAYLAND	MI	49348	37
56-005-021-00	KEMP HOLDINGS LLC	304 108TH ST	CALEDONIA	MI	49316	38
56-005-022-00	SLOAN JOHN L & AMY L	329 WILLOW RUN DR	WAYLAND	MI	49348	39

(0 out of 1666 Selected)

D001COUNTY WEB 18.DBO.NewQuery |

Figure 5.15: Query Results Table

ENTERPRISE GEODATABASE MAINTENANCE

ENTERPRISE GEODATABASE COMPRESSION ROUTINE

Disconnect All Users

To disconnect the GIS Server, stop all services

- In ArcGIS Server Manager ⇒ Site ⇒ GIS Server ⇒ Machines ⇒ Stop all Services




Figure 5.16: Stop ArcGIS Server

Use the Search tool to find the Rebuild Indexes Tool




Figure 5.17: Find Rebuild Indexes Tool

Rebuild Indexes

Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.18: Rebuild Indexes Tool Operation

Recalculate Statistics

In the Analyze Datasets Tool:
Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.19: Recalculate Statistics

Compress

Select Connection ⇒ Press OK




Figure 5.20: Compress

Rebuild Indexes Again




Figure 5.21: Rebuild Indexes Tool Operation

Recalculate Statistics Again

In the Analyze Datasets Tool:

Select Connection ⇒ Include System Tables ⇒ Select All ⇒ Press OK




Figure 5.22: Recalculate Statistics

MANAGING MAP SERVICES

To STOP ARCGIS SERVER

Launch ArcGIS Server Manager

Site ⇒ GIS Server ⇒ Machines ⇒ Stop the Server




Figure 5.23: Stop the GIS Server

FIXING DAMAGED SERVICES

Error:

Service is currently being configured by another administrative operation

Remedy:

This tech support article applies:

<https://support.esri.com/en/technical-article/000015549>

There are at least 2 ways to fix:

- Use the ArcGIS Server Account Utility
- Remove Lock Files

Use the ArcGIS Server Account Utility

Access the GIS Server

To Log in to Juniper

windows R ⇒ mstsc

⇒ juniper

Use personal network credentials

On the GIS Server (Juniper)

In Windows Search, find:

Configure ArcGIS Server Account Utility




Figure 5.24: ArcGIS Server Account Utility

Use credentials:

PW: @lleganGxxxxxx




Figure 5.25: Account Utility Login

In the utility, paste these paths:

C:\arcgisserver\directories
C:\arcgisserver\config-store
C:\arcgisserver\logs




Figure 5.26: GIS Directory Locations Filled

Push Next

Select option **Do not export Configuration File**




Figure 5.27: Do not Export Config File

Push Next




Figure 5.28: Configure Account

Push Configure

While the tool runs, open the service manager

In Windows Search, find: **Service Manger**

Launch **Service Manger**




Figure 5.29: Search For Service Manager

When the tool completes, **Press Finish**




Figure 5.30: Finish On Configure

Services Manager




Figure 5.31: Open Services Manager

In services, select the ArcGIS Server service and restart the service.
(Randy had to do this)




Figure 5.32: arcGis Service In Services Manager

Quick and dirty fix

When a service get hung up in som admin process, you may get an error like:

Error:

Service is currently being configured by another administrative operation

Removing Lock Files

This may work, here is a blog about it

<https://community.esri.com/thread/103710> Network location for an example service

```
on juniper
C:\arcgisserver\config-store\services\ParcelViewer2\
PV2Adresses.MapServer\startup\JUNIPER.ALLEGANCOUNTY.ORG
```

Suggested Steps:

- 1)stop arcgis server services.
- 2)delete the lock files(*.glock and *.rlock)
 (in arcgisserver\config-store).
- 3) restart arcgis server service.
- 4)stop the pending stopping service and then start it.

mapservices would not stop so I try this:

<https://support.esri.com/en/technical-article/000012685>

Check permission levels for the arcGIS account ArcGisServerPermissions.PNG

If necessary, add the arcgis user to the permissions on the folders
ArcGisServerPermissionsAddUser.PNG

MANAGING GEODATABASE REPLICAS

ADDING A NEW FEATURE CLASS TO A REPLICA

Source: <https://support.esri.com/en/technical-article/000010345>

Summary

Currently, there is no out-of-the-box tool to add a feature class to an existing replica. With ArcGIS Desktop, one must either recreate the replica or if the workflow allows, replicate the new feature class as a separate replica.

Steps:

The steps below outline how the recreate the replica using the Register Existing Data option in Desktop. These steps can be applied to both one-way and two-way replicas.

- Synchronize the changes between parent and child replica geodatabases using the existing replica so that the data is identical in each database, then Unregister the replica in both geodatabases. For two-way replicas, ensure that changes are synchronized in both directions and there are no outstanding edits before unregistering the replica.
- Create or import the new feature class into the parent geodatabase, and add the GlobalID.
- Register the newly added data as versioned.
- Copy and paste the new feature class to the child geodatabase using ArcCatalog.
- Note: that the GlobalIDs must have already been added to the feature class.
- For two-way replica or one-way full model, register the newly added data in child geodatabase as versioned.
- Using the parent geodatabase, add all the data that is to be replicated to a map in ArcMap.
- Click the 'Create Replica' tool on the Distributed Geodatabase toolbar.
- Select 'One way replica' or 'Two way replica' and click Next.
- Select 'Register existing data only'.
- Select the child geodatabase and specify a replica name.

- Click Next and click Finish.
- A new replica is created that includes the new data.

MANAGING GEODATABASE VERSIONS

VERSION QUERIES

SQL Queries

Four queries of SDEversions, SDEstates, sdestatelineages, and SDEcompresslog

```
use AC_Pub
select name, owner, version_id, state_id, parent_name
, parent_owner from
[AC_Pub].[dbo].[SDE_versions]
select * from [AC_Pub].[dbo].[SDE_states] order by state_id
select * from [AC_Pub].[dbo].[sde_state_lineages] order
by lineage_name,
lineage_id
select TOP(5) * from [AC_Pub].[dbo].[SDE_compress_log] order by
compress_end DESC
```

Query of SDEversions and SDEstates

```
use AC_Pub
SELECT v.version_id,v.creation_time,v.creation_time,
s.state_id, s.creation_time
FROM SDE_versions v
INNER JOIN SDE_states s ON v.state_id = s.state_id
```

FINDING ORPHANED VERSIONS

Remove orphaned versions

Follow the procedure: [Link to source](#)

Use SQL Server Management Studio to execute two queries and compare the results.

Step 1:

Execute the query:

```
use AC_Pub
SELECT ObjectID, name from dbo.GDB_ITEMS where
TYPE='4ED4A58E-621F-4043-95ED-850FBA45FCBC';
```

Step 2:

Execute the query:

```
use AC_Pub
SELECT name from [dbo].[SDE_versions]
order by name
```

Compare the tables

This graphic summarizes elements of the queries. Note the items from step two that have no match in step one.

code for versions
in gdbItems

replica ID

generation #

Matches

No Matches

ObjectID	name
16497	ProtoPubParcelPubReplica
16520	ProtoPubLandUsePlanningReplica
17074	SchoolsReplica
17542	BIReplica
17893	EmergencyMgmt
19323	AddressessReplica
40149	EnvHealthReplica

name
CAddress_Tbl_ReversionParc
DEFAULT
JWMS_Trace/Tbl_ReversionParc
SYNC_SEND 17893 0
SYNC_SEND 40955 12
SYNC_SEND 40965 7

Figure 5.33: Find Orphan Versions

Orphaned versions can be removed by name in ArcGIS




Figure 5.34: Delete Orphan Versions

MXD MANAGEMENT

FIND/REPLACE TEXT OBJECT

Python Code

Python Code for finding and replacing a text object in a ArcGIS .mxd file. A snippet of this code may be found in the LayerUpdates/Zoning/processing folder. It is used to edit the .mxd files located there.

```
import arcpy
from arcpy import env

env.workspace = r"J:\Apps\Python\LayerUpdates\zoning\processing"
for mxdname in arcpy.ListFiles("*.mxd"):
    print mxdname
    mxd = arcpy.mapping.MapDocument(r"J:\Apps\Python\
        LayerUpdates\zoning\processing\\\" + mxdname)
    for elm in arcpy.mapping.ListLayoutElements
        (mxd, "TEXT_ELEMENT"):
        if elm.text.startswith('As ammended'):
            elm.text = elm.text.replace('As ammended',
                'As amended')
            print elm.text
    mxd.save()
del mxd
```

5.5 L^AT_EX PACKAGES USED BY AC GIS

COMMON ERRORS

Source:

<https://www.ocf.berkeley.edu/~latex/files/commonerrors.tex>

If you have every compiled a L^AT_EX document, chances are high you have received a few error messages. Sometimes they come from something as stupid and as easy to fix as forgetting a parenthesis or forgetting to end an environment. There are also a lot more cases where you have no idea what you have done wrong and it takes you a long time to find or even understand your error.

The purpose of this is to explain some of the common errors that may happen when compiling a L^AT_EX document and suggestions for what is probably going on and how to debug your document.

THE FORM OF AN ERROR

There are two forms of errors: L^AT_EX errors and T_EX errors. In both types of errors, the part after the error message will tell you where the error occurred. An example:

1.15 <offending text>

The 1.15 tells you what line the error occurred on and the text will tell you the text that caused the error.

L^AT_EX ERRORS

The general form of an error in L^AT_EX is shown below:

! LaTeX error: <error message>

See the LaTeX manual or LaTeX Companion for explanation.

Type H <return> for immediate help.

...

The ! lets you know that the error has occurred. The error message will tell you what type of error you have committed. After the ellipses,

you will find the line at which the error occurred and the text that caused the error (or at least the text where L^AT_EX found the error).

T_EX ERRORS

Errors may also have the following form:

```
! <error message>
```

These errors are formatted differently because they are error messages that came from T_EX instead of L^AT_EX. After the error, you will still find the line that the error occurred in and the text of the error.

WARNINGS

There are some error messages that are just warnings and will not stop or change the compilation of the document. Chances are you have seen them many times.

UNDERFULL

The following error results when a line does not extend the width of the page, something L^AT_EX always tries to accomplish:

```
Underfull \hbox (badness 10000) in paragraph at lines  
104--107
```

This error message is just a warning and is not something to worry about. For the most part, when a line does not span the width of the page, it is because you have written something that you want to only cover part of the page.

OVERFULL

The following error results when a line extends beyond the width of the page:

```
Overfull \hbox (16.04988pt too wide) in paragraph at
lines 30--31 [] [] \OT1/cmtt/m/n/12 I'm trying to put
way too much text into a line in my document.
```

Usually this error comes from when you are using the `verbatim` package because it will not move to the next line if your text does not go to the next line. The easiest way to fix this is to find the place in your document where this is occurring and change the text so that it fits to the page.

This error will still show up if the text is still on the page but outside of the width of text that \LaTeX has set. In this case, you are welcome to fix things so that the error does not show up or you can leave the text as it is.

REFERENCES

The following warnings occur when references are changed when \LaTeX was compiled:

```
\LaTeX\ Warning: Label(s) may have changed. Rerun to get
cross-references right.
```

```
\LaTeX\ Warning: There were undefined references.
```

```
\LaTeX\ Warning: Reference 'name' on page 1 undefined on
input line 15.
```

The way to fix these errors is to recompile the document again to correct the page numbers. Sometimes it is necessary to recompile the document twice to fix this error. You also may have defined a reference wrong, so you should check to make sure your label is correct.

BEGINNING AND ENDING BEGIN ENDED BY END

This type of error occurs when each environment is not correctly started and ended. When you are missing an `\end` command, the following error will show up:

```
! LaTeX Error: \begin{enumerate} on input line 23
ended by \end{document}.
```

To fix this, you need to end the environment mentioned in the error with the appropriate command.

When you are missing a `\begin` command, the following will appear:

```
! LaTeX Error: \begin{document} ended by
\end{itemize}.
```

To fix this, you basically do the same thing as before, correctly beginning the environment mentioned in the error with the appropriate command.

END OCCURRED INSIDE A GROUP

The following error message will show up at the end of compiling a file if an environment is begun that is not ended:

```
(\end occurred inside a group at level <n>)
```

To fix this error, make sure you end the environment that was begun. The previous error is more helpful in finding the `\begin` statement.

ENDED BY END OF LINE

The following error will occur when you try to place a command inside a section heading:

```
! LaTeX Error: \verb ended by end of line.
```

```
See the LaTeX manual or LaTeX Companion for
explanation.
Type H <return> for immediate help.
...
```

There will be many errors of the same type for this mistake. In order to find where you put the command, look in the output file and find the last heading that shows up.

MISSING BEGIN DOCUMENT

This error is self-explanatory:

```
! LaTeX Error: Missing \begin{document}
```

ERRORS USUALLY CAUSED BY BAD SPELLING

UNKNOWN CONTROL SEQUENCE

This error results when you use a command (something that starts with a \) that is not recognized by L^AT_EX:

```
! Undefined control sequence.
```

Usually this error results from spelling a command incorrectly. Go to the line that is indicated by the error and fix the command.

ENVIRONMENT UNDEFINED

This error results when you begin an environment with a \begin command that is not recognized:

```
! LaTeX Error: Environment verbatim undefined.
```

Usually you have just spelled your environment incorrectly, so you just need to fix it.

BAD FILE NAME

This error results when you have mistyped the command `latex` or do not have L^AT_EX installed on your computer:

```
Bad command or file name
```

To fix this, correctly spell the command to compile your file or make sure that L^AT_EX is correctly installed on your computer.

CANNOT FIND FILE NAME

This error occurs when you try to compile a file that the computer cannot find:

```
! I can't find file 'sample'.
<*> sample
```

Please type another input file name:

To fix this error, make sure you have spelled the file name correctly. You also may be in the wrong directory to compile the file, so check to make sure you are in the same directory as your file.

FATAL ERRORS

RUNAWAY ARGUMENT

This error happens when a paragraph ends before a command's argument is done (i.e., L^AT_EX thinks that there is a missing }):

Runaway argument?

To fix this, you should use a different command to accomplish what you are trying to do. An example of this is to use `\bfseries` instead of `\bftext` to make bold text in more than one paragraph.

This error can also be caused by a missing mandatory argument to a command.

JUST AN *

This error normally occurs when you do not end your document with `\end{document}`:

*

If you are prompted to enter something in, it is best to enter `\end{document}`

and hope it works. Be sure to end your document with the appropriate command.

EMERGENCY STOP

This error happens when L^AT_EX will stop trying to compile your document due to a serious error:

`! Emergency stop.`

To fix this error, you will need to figure out what caused it to stop compiling. Chance are you forgot to end your document with `\end{document}`, but there might also be another reason for the emergency stop.

PLEASE TYPE A COMMAND OR SAY END

This error happens when your file has ended prematurely:

`(Please type a command or say '\end')`

The best way to deal with this type of error is to type

`\end`

or

`\end{document}`

in the case that the absence of that command caused the error. Usually if you have ended your document correctly, the error will result from a missing } or forgetting to end a verbatim environment.

GRAPHICS ERRORS TOO MANY UNPROCESSED FLOATS

This error occurs when figures or tables (i.e., floats) have not been typeset:

`! LaTeX Error: Too many unprocessed floats.`

\LaTeX can only have so many floats waiting to be typeset. In order to fix this error, make sure that you are placing your floats where you want them (with a [h] option) and not wanting too many on one page in sequence. Using the command `\clearpage` can be very useful in distributing floats correctly.

UNKNOWN GRAPHICS EXTENSION

The following error occurs when you try to use a type of graphic that is not supported by the type of file that you are producing:

```
! LaTeX Error: Unknown graphics extension: .gif
```

In order to fix this error, you should change your graphics to the types that are supported by the type of file you are outputting or you will need to include the correct package to deal with that type of graphic. Sometimes you may have named the graphic poorly so that \LaTeX will not recognize it as a graphic file.

DIVISION BY ZERO

The following error occurs when the height of a graphic object is zero:

```
! Package graphics Error: Division by 0.
```

This is usually caused when you rotate an object with zero depth so that its height becomes zero. The best way to fix this is to use the keyword `totalheight` instead of `height`.

MATH ERRORS DISPLAY MATH SHOULD END WITH \$\$

This error occurs when the `displaymath` or `equation` mode is ended incorrectly:

```
! Display math should end with $$
```

To fix this error, make sure that you end the displaymath or equation mode correctly (ending them with a \$ is not acceptable).

BAD MATH ENVIRONMENT DELIMITER

This error occurs when you do not have your delimiters correct in math mode:

```
! LaTeX Error: Bad math environment delimiter.
```

Usually this occurs when you forget to match a right delimiter with every left delimiter. This error may also happen when you forget to end an array.

MISSING RIGHT

This error occurs when you have a missing right parenthesis:

```
! Extra \right.
```

To fix this, you either need to add a \right command or you need to end an array.

MISSING DELIMITER

This error message occurs when a delimiter is missing:

```
! Missing delimiter (. inserted).
```

To fix this error, you need to make sure that you have a right delimiter for every left delimiter. If you do not want a right delimiter matching a left delimiter, you need to use “.” to not have an error message show up.

MISSING \$ INSERTED

The following error occurs when you try to use a character that can only be used in math mode, like _ or ^:

```
! Missing $ inserted
```

To fix this error, make sure you change the character to what it should be in text mode.

TABULAR ENVIRONMENT ERRORS

MISPLACED ALIGNMENT TAB CHARACTER &

This error occurs when you use & and when you are not in a tabular environment:

```
Misplaced alignment tab character &
```

To fix this error, you need to use \& to make a &.

EXTRA ALIGNMENT TAB

This error occurs when you use too many tabs for the number of columns in a table:

```
! Extra alignment tab has been changed to \cr
```

The result of this error is that a new row is formed where the extra tab was. You should go back and fix your table so that the correct number of items in each row would show up.

ARGUMENT HAS AN EXTRA }

These errors happen when an incorrect number of arguments to a tabular environment have been specified:

```
! Argument of \cline has an extra }.  
! Argument of \multicolumn has an extra }.
```

To fix this error, make sure your arguments to the tabular environment are correct.

ERRORS WITH LISTS

MISSING ITEM

This error occurs when there is plain text in an environment that takes items:

```
! LaTeX Error: Something's wrong--perhaps a missing  
\item.
```

To fix this error, make sure the plain text is changed into an item.

TOO DEEPLY NESTED

This error occurs when there are too many lists for L^AT_EX to handle:

```
! LaTeX Error: Too deeply nested
```

L^AT_EX can only handle four levels of one type of list and six levels of different types of lists. To fix this, you need to use less levels of lists or define your own list environment.

MISCELLANEOUS ERRORS

ONLY USED IN THE PREAMBLE

This error occurs when you place a command in the body of a L^AT_EX document that should be placed in the preamble:

! LaTeX Error: Can be used only in the preamble.

To fix this error, just move the command to the preamble.

THERE IS NO LINE/PAGE HERE TO END

This error occurs when you incorrectly use the commands that make a new line or a new page:

! LaTeX Error: There's a no line here to end.

You may just leave the command that is making a new line in place or you can take it out. Here, L^AT_EX is just trying to make sure that everything looks nice.

COMMAND ALREADY DEFINED

This error occurs when you try to define a command that already exists:

! LaTeX Error: Command ... already defined.

To fix this, you need to define your command differently.

MISSING NUMBER

This error is made when a number is expected as an argument and one is not provided:

! Missing number, treated as zero.

To fix this error, you need to find where a number is expected so that you can provide the correct one.

FLOAT PACKAGE

USEPACKAGE

text

SIMPLE USE

text

OPTIONS

text

Add optional arguments to the usepackage line:

Useful options:

- **OPTION NAME**
OPTION NOTE
- **OPTION NAME**
OPTION NOTE

USE WITH OPTIONS

text

COMMANDS

GRAPHICS EXAMPLES AND NOTES**CURLYFRAME EXAMPLE**

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
\geometry{tmargin=.75cm,bmargin=.25cm,lmargin=.8cm,rmargin=.2cm}
\usepackage{multicol}

\begin{document}

\curlyframe[.9\columnwidth]{

TEXTTTTTTTTTTTTTTTTTT

}

\end{document}
```

RECTFRAME EXAMPLE

```
\documentclass[landscape]{article}
\usepackage{wallpaper}
\usepackage{niceframe}
\usepackage{xcolor}
\usepackage{ulem}
\usepackage{graphicx}
\usepackage{geometry}
\geometry{tmargin=.75cm,bmargin=.25cm,lmargin=.8cm,rmargin=.2cm}
\usepackage{multicol}

\begin{document}
\begin{minipage}{.33\textwidth}
\centering
\scalebox{3}{\color{green!30!black!60}
\font\border=umrandb
\generalframe
```

```
{\border \char113} % up left
{\border \char109} % up
{\border \char112} % up right
{\border \char108} % left
{\border \char110} % right
{\border \char114} % lower left
{\border \char111} % bottom
{\border \char115} % lower right
{\centering
\includegraphics[height=1.25cm]{GIS_Logo_better.jpg}}
\end{minipage}
%\vspace{-8mm}

\end{document}
```

GRAPHICX PACKAGE

USEPACKAGE

text

SIMPLE USE

text

OPTIONS

text

Add optional arguments to the usepackage line:
Useful options:

- **OPTION NAME**
OPTION NOTE
- **OPTION NAME**
OPTION NOTE

USE WITH OPTIONS

text

COMMANDS

HYPERREF PACKAGE

INTRODUCTION

Official hyperref package documentation

Notes:

- Add the *hyperref package* to the preamble **last** [?]
 - To use Tex in a pdf bookmark: use
-

```
\texorpdfstring{\{}{}\}
ie. \paragraph{Sample Text\texorpdfstring{\{}{}\}}
```

Creates a new line without an error.

```
\usepackage[options]{hyperref}
```

SIMPLE USE

Use `\href{URL}{DESCRIPTION}` to add a link with description

`\href{https://www.latex-tutorial.com}{Website with tutorials}`
produces:

[Website with tutorials](https://www.latex-tutorial.com)

OPTIONS

Add optional arguments to the usepackage line:

Useful options:

- **pdftex**
enables other options like breaklines
 - **breaklinks**
allow links to be broken across several lines
eg. <https://lists.gnu.org/archive/html/emacs-orgmode/2013-06/msg00776.html>
 - **colorlinks**
Colors the text of links and anchors.(default is false)
 - **linkcolor**
Color for normal internal links(default is red).
 - **anchorcolor**
Color for anchor text.
 - **citecolor**
Color for bibliographic citations in text.
 - **urlcolor**
Color for linked URLs
-

USE WITH OPTIONS

```
\usepackage[breaklinks,colorlinks,citecolor=blue,
urlcolor=green]{hyperref}
```

COMMANDS

`\href{URL}{text}` Makes text a link to URL.

To put a file path in text:

eg:

`\Official hyperref package documentation`

(documentation Pt.4 pg.15)

`\href[options]{URL}{text}`

Options:

- absolute

```
\href{C:/AC/jalapeno/documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref doc}
```

- relative Note: relative path must be from final pdf location

```
\href{../../../../documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref package doc}
```

This path works from main document

```
\href{../../../documentation/packageDocs/hyperref2017.pdf}
    {Official hyperref package documentation}
```

This path works from subsection document

`\hyperref[label]{text}`

Makes text a link to where `\ref{label}` would point.

`\hypertarget{name}{text}`

Sets an anchor on text with the label name.

`\hyperlink{name}{text}`

Makes text a link that takes you to the anchor labeled name.
Pair with `\hypertarget`.

`\phantomsection`

Used in conjunction with

```
\addcontentsline  
    to make the correct link in the Table of Contents.
```

IMPORT PACKAGE

USEPACKAGE

text

SIMPLE USE

text

OPTIONS

text

Add optional arguments to the usepackage line:

Useful options:

➢ **OPTION NAME**

OPTION NOTE

➢ **OPTION NAME**

OPTION NOTE

USE WITH OPTIONS

text

COMMANDS

STANDALONE PACKAGE

INTRODUCTION

[Link to official standalone documentation](#)

standalone provides a **package** and a **class**

➤ The *standalone package* is used for:

- Main documents that will input or import sub documents.
- For example:

```
\usepackage[subpreambles=false]{standalone}
* Ignores preambles of imported sub documents [?, pg.4]
```

➤ the *standalone class*:

- Is a document class
- Provides standalone / subdocument switches and options
- For example:

```
\documentclass[class=article]{standalone}
* behaves as an article when standalone
* makes document available for import into a master document
```

SIMPLE USE

➤ The *standalone package*

- In the main document:

```
\documentclass[openany]{book}
\preamble...
\usepackage{standalone}
```

➤ the *standalone class*:

- In any subdocument:

```
\documentclass[class=article]{standalone}
\preamble...
```

OPTIONS

- The *standalone* package
 - **subpreamble**
 - * default value of subpreambles is *false*
- the *standalone* class:
 - **crop**
 - **titlepage**
 - **twoside**
 - * Makes pagination style match book
 - * default value is *false*
 - **multi**
 - * `multi=true|false`
 - * `multi={<environment name>, ...>}`
 - **float**

USE WITH OPTIONS

- the *standalone* package:
 - `\usepackage[subpreambles=false]{standalone}`
- the *standalone* class:
 - `\documentclass[class=article , crop=false, titlepage, twoside, multi={itemize, figure, verbatim}, float=false]{standalone}`

COMMANDS

WRAPFIG PACKAGE

USEPACKAGE

text

SIMPLE USE

text

OPTIONS

text

Add optional arguments to the usepackage line:

Useful options:

- **OPTION NAME**
OPTION NOTE
- **OPTION NAME**
OPTION NOTE

USE WITH OPTIONS

text

COMMANDS

5.6 LATEX TEMPLATES

LATEX SECTION TEMPLATE

```
%\documentclass[class=report , crop=false, multi={itemize, figure}, float=fa
\documentclass[class=book , crop=false]{standalone}

\input{../../../../../preamble}

\def\titlename{Section Template}

\title{\input{../../../../../commonTitle}} % closing brace for title

\begin{document}% Document Begins

\input{../../../../../commonFront} % provides standalone options

\section{SECTION NAME HERE}

\subimport{RELATIVE PATH TO NEW Section/}{NEW SUBSECTION Subsection.tex}

%eg.
%\subimport{latexTemplatesSection/}{subsectionTemplateSubsection.tex}
% etc...

\end{document}
```

LATEX SUBSECTION TEMPLATE

```
\documentclass[class=book , crop=false]{standalone}

\input{../../../../../preamble}

\def\titlename{Subsection Template}

\title{\input{../../../../../commonTitle}} % closing brace for title

\begin{document}% Document Begins

\input{../../../../../commonFront} % provides standalone options
```

```
% NEW INFO GOs HERE.  
\subsection{Subsection Template}  
\medskip
```

5.7 PDF TOOLS USED BY AC GIS

PDF OPTIMIZER

PUPOSE AND SUMMARY

Workflow Purpose: Optimization of a large number of pdf docs.

Workflow Summary: Uses Python to create a list of .pdf docs in a folder and creates a batch file to optimize the pdfs in the list to another location. The batch process calls ghost script for the optimization.

REQUIREMENTS

Opensource software:

- ghostscript
- python 2.7 and a Python IDE
- A text editor

paragraphPython(2.7)

Note:

The output of this script is bdoc.txt, Save as a .bat to execute the optimize.

Script that creates a batch file

```
import os, sys

project = os.path.dirname(os.path.dirname(__file__))
processing = os.path.join(project, 'processing')
#source = os.path.join(project, 'source')
build = os.path.join(project, 'build')
sourcepdf = os.path.join(build, '20180716')

inString1 = "gswin32 -sDEVICE=pdfwrite -dCompatibilityLevel=1.4
-dPDFSETTINGS=/ebook -dNOPAUSE -dQUIET -dBATCH
-sOutputFile=J:\\\\Projects\\\\2018ParcelAtlas\\\\build\\\\optimized\\\\"
```

```
inString2 = " J:\\Projects\\2018ParcelAtlas\\build\\20180716\\"

batchdoc = os.path.join(processing, "bDoc.txt")

# Main
#####
if __name__ == "__main__":
    list1 = os.listdir(sourcepdf)
    l = open(batchdoc, 'w')
    for i in list1:
        newi = i[1:]
        print newi
        t = inString1 + newi + inString2 + i + "\n"
        print t
        l.write(t)

    l.close()
```

GHOSTSCRIPT

About

ghostscript is used for the optimization. ghostscript is an interpreter for the PostScript language and for PDF [?].

Licensing

ghostscript is available opensource under AGPL conditions. more information can be found [here](#).

Download

ghostscript can be downloladed [here](#).

WINDOWS BATCH FILES

A line from the batch file looks like:

```
gswin32 -sDEVICE=pdfwrite -dCompatibilityLevel=1.4  
-DPDFSETTINGS=/ebook -dNOPAUSE -dQUIET -dBATCH  
-sOutputFile=J:\Project\2018ParcelAtlas\build\optimized\  
02-001-001-00.pdf J:\Projects\2018ParcelAtlas\build\20180716  
\_02-001-001-00.pdf
```

5.8 QGIS TOOLS

USING COGO TOOLS IN QGIS

SET UP THE AZIMUTH AND DISTANCE PLUGIN (AZD PLUGIN).

In the Plugins drop down(1), under the topography group select the **Azd Plugin(2)**(see fig.).




Figure 5.35: launch plugin

Note here which layer is active (see fig.).




Figure 5.36: check active layer

If necessary, left click the layer *traverse 1* in Layer Panel to activate it(see fig.).




Figure 5.37: activate layer

Configure Options

On Options Tab: Select Boundary, Bearing, Feet, and Degree radio buttons.




Figure 5.38: Plugin Options

Using the tool

Boundary descriptions are entered into the Drawing Tab. Azimuth (bearing) and Distance are the important boxes (Set Offset = 0 and Zenith = 90 and ignore)(see below).




Figure 5.39: Entering Bounds

CONFIGURE EDITING ENVIRONMENT

Use Settings Dropdown and Snapping Options to enable snapping to Sections, Quarter Sections, and or Parcels if desired (see fig.).




Figure 5.40: Configure editing environment

LOCATE POINT OF COMMENCEMENT

To get to the Point of Commencement,

Use **any combination** of the following methods:

- Using Reference Layer
- Using Measuring Tool
- Search by Parcel Number (Search Layers Plugin)
- Draw COGO lines (Azd Plugin)(as described earlier)

Using Reference Layer

Use reference layers; Units, AC_SectionsQu, Sections, and Parcels. Toggle layers on and off in Layers Panel and zoom in and out with mouse wheel.

Using Measuring Tool

Use the measuring tool, make sure to set units to feet. To exit current measurement right click (see fig.).




Figure 5.41: Measuring Tool

Search by Parcel Number

(Search Layers Plugin.)

To Launch Search Layers Plugin:

In Plugins dropdown:

Enable the **Search Layers** Plugin. (see fig.)




Figure 5.42: Search Layers Plugin

Enter parcel number (with dashes), Set layers, and set search field.(see fig.)




Figure 5.43: Search Layers Setup

Part IV

Resources

A.1 GEOGRAPHY 101

Foundations of geography

A PRIMER ON COORDINATE SYSTEMS COMMONLY USED IN MICHIGAN

A Primer on Coordinate Systems Commonly Used in Michigan

B.2 ESRI RESOURCES

Product Documentation

FUNCIONALITY MATRICES

arcgis 10.5 Enterprise Functionality Matrix Document Link
arcmap 10.5 Functionality Matrix Document Link
