

# Foveating sensing with KNN-convolutional neural networks based on isotropic cortical magnification

Nicholas M. Blauch, George A. Alvarez, Talia Konkle


Harvard University, Department of Psychology and Kempner Institute for Natural and Artificial Intelligence

correspondence: [nblauch@fas.harvard.edu](mailto:nblauch@fas.harvard.edu), [talia\\_konkle@harvard.edu](mailto:talia_konkle@harvard.edu)



Kempner  
INSTITUTE

For the Study of Natural  
& Artificial Intelligence  
at Harvard University



Vision Sciences Lab

## Introduction

Human vision is foveated

Foveation profoundly shapes cortical organization and visual cognition

Retinotopic organization & cortical magnification

Eccentricity

Magnification (mm/deg)

Watson, 2014

Optimized active eye movements

A Identification Emotion Gender Happy/Neutral

ROI

B FIO Proportion correct

Peterson & Eckstein, 2012

Computer vision models lack mechanisms for realistic foveation

Prior foveation methods distort the visual field

Can we integrate realistic foveation into computational vision models?

## Foveated sensing based on isotropic cortical magnification

Sampling in visual space

$r = \sqrt{x^2 + y^2}$

$\theta = \text{atan} 2(y, x)$

Sensor manifold

Rovamo & Virsu, 1984

$\phi$

$\rho = M(r) \sin(r)$

$z = \int_0^w [M(r)^2 - (dp/dr)^2]^{0.5} dr$

$\phi = \theta$

Flat sensor manifold (visualization only)

right visual field left hemisphere

left visual field right hemisphere

$Im(w)$

$Re(w)$

$z = x + iy$

$w = \log(z + a)$

Note: this is the famous Schwartz (1980) model

## K-Nearest-Neighbor ConvNets (KNN-CNNs)

layer 1

layer 2

layer 3

unit  $i$

KNNs





Note: sampling on curved sensor manifold allows RFs to span visual hemifields

## Result 2: strong performance in foveated networks

Original image (256x256)

Fixation target area

"16°" field-of-view (FOV)



## Result 1: foveated model accounts for biological receptive field properties

Receptive fields (RFs) are uniform circular samples on sensor manifold

right visual field

lower

left visual field

fovea

periphery

$W_i^* = Q_i W \dots \rightarrow s$

$Q_i = \text{softmax}\left(\frac{1}{D_i + \epsilon}, \text{axis} = 1\right)$

$W_i^*$ : weight in  $i$ th neighborhood

$Q_i$ : mapping matrix

$D_i$ : distance from normalized neighborhood coords to reference coords

Visual RF size increases with eccentricity and hierarchical level

Macaque V4

Human V1-V3

Model

$pRF \text{ size (deg)}$

$fov = 15.18 \text{ deg}$

$RF \text{ diameter (deg)}$

Eccentricity (deg)

$n_r = n_\theta$

$w = \log(r + a)$

(grid-like simplification of Schwartz (1980) model)

## References:

Da Costa, D., Kornemann, L., Goebel, R., & Senden, M. (2024). Scientific Reports, 14(1), 8980.

Jérémie, J.-N., Daucé, E., & Perrinet, L. U. (2024). arXiv.

Motter, B. C. (2009). The Journal of Neuroscience, 29(18), 5749–5757.

Rovamo, J., & Virsu, V. (1984). Vision Research, 24(3), 283–286.

Schwartz, E. L. (1980). Vision Research, 20(8), 645–669.

Watson, A. B. (2014). Journal of Vision, 14(7), 15.

Watson, A. B. (2014). Journal of Vision, 14(7), 15.

Groen, I. I. A., Dekker, T. M., Knapen, T., & Silson, E. H. (2022). Trends in Cognitive Sciences, 26(1), 81–96.

Peterson, M. F., & Eckstein, M. P. (2012). PNAS, 109(48).


## Existing grid-like foveated sensors warp receptive fields

$M(r) = \frac{1}{r + a}$

$n_r = n_\theta$

$w = \log(r + a)$

(grid-like simplification of Schwartz (1980) model)



Log-polar image foveation

e.g. Jérémie et al., 2024

Sampling is locally anisotropic

Eccentricity-dependent RF aspect ratios

$a = 0.001$

$a = 1000$

$a = 1000$