

School of Artificial Intelligence
Anhui Agricultural University
Hefei 230036, China
Email: wqy@ahau.edu.cn; glc@ahau.edu.cn

May 9, 2026

Editorial Office
Briefings in Bioinformatics
Oxford University Press
Great Clarendon Street
Oxford OX2 6DP
United Kingdom

Dear Editor,

We are pleased to submit our manuscript entitled:

“Paired prediction of GPCR–G protein coupling specificity using protein language models and topology-aware feature engineering”

for consideration as an **Original Research Article** in *Briefings in Bioinformatics*.

Highlights

- Reformulates GPCR–G protein coupling as a paired binary classification over 1,647 (GPCR, G protein family) pairs—incorporating G protein identity as explicit input rather than a class label.
- Cross-attention + ESM-2 650M embeddings + topology-aware ICL features achieves AUC 0.862 (cluster-aware CV), with Brier score 0.008 indicating well-calibrated, deployment-ready probabilities.
- Critical dimension-alignment finding: ICL local features must match global embedding dimension—mixing dimensions degrades performance across all architectures.
- AlphaFold structural descriptors provide zero incremental gain beyond ESM-2 650M, demonstrating that large protein language models implicitly encode structural information.
- Open-source tool `gpcr-coupling` with pre-trained models and tuto-

rial; all code, data, and results at <https://github.com/nblvguohao/gpcr-coupling-leakage-benchmark>.

Summary

G protein-coupled receptors (GPCRs) mediate cellular responses by coupling to heterotrimeric G proteins, yet computational prediction of coupling specificity—which determines downstream signaling—remains an open challenge with direct implications for orphan receptor deorphanization and rational drug design. Existing approaches predominantly treat this as single-protein classification, neglecting the paired nature of the interaction.

In this study, we present a comprehensive framework that reformulates GPCR–G protein coupling prediction as a pairwise binary classification problem over 1,647 experimentally validated (GPCR, G protein family) pairs spanning 431 GPCRs across four G protein families. Our approach integrates protein language model embeddings (ESM-2, up to 650M parameters), topology-aware intracellular loop features, and a cross-attention architecture with systematic comparison against five baseline methods.

Key contributions:

1. **Comprehensive benchmarking:** First systematic comparison of SVM, MLP, Random Forest, XGBoost, and cross-attention architectures for GPCR coupling prediction under multiple evaluation protocols (random CV, cluster-aware CV, leave-one-G-protein-family-out).
2. **Novel methodological findings:** (i) A dimension alignment requirement for local-global protein language model feature fusion—mixing heterogeneous embedding dimensions systematically degrades performance. (ii) Evidence that AlphaFold structural descriptors provide no incremental benefit beyond ESM-2 650M embeddings, justifying sequence-only pipelines for large-scale screening.
3. **Rigorous evaluation:** The cross-attention model achieves AUC 0.862 under strict cluster-aware cross-validation, with substantially better calibration than SVM (Brier score 0.008 vs. 0.039). LOGPSO evaluation reveals a ~ 0.60 AUC ceiling across *all* tested architectures, which we propose as a community benchmark for tracking cross-family generalization progress.
4. **Practical deployment:** An open-source command-line tool (`gpcr-coupling`) with pre-trained models and a step-by-step tutorial enables both re-

production and application to novel GPCRs, including a case study on orphan receptor deorphanization.

5. **Educational value:** The manuscript includes practical guidelines distilled from the systematic evaluation and a tutorial section, consistent with BIB’s mission of providing actionable briefings for the bioinformatics community.

Why Briefings in Bioinformatics?

We believe this work aligns closely with *Briefings in Bioinformatics* for several reasons. First, the comprehensive benchmarking framework serves as a reference for future GPCR coupling prediction studies—a briefing function that the journal’s readership values. Second, the methodological findings (dimension alignment, AlphaFold redundancy) are generalizable beyond GPCRs and provide practical guidance for researchers working with protein language model embeddings across scales. Third, the accompanying software tool and tutorial lower the barrier to adoption, consistent with BIB’s emphasis on methodological accessibility. Fourth, the LOGPSO benchmark proposal and systematic calibration analysis address gaps in the current literature that the BIB community is well-positioned to advance.

Manuscript specifications:

- Main text: ~7,000 words, 6 figures, 3 tables
- Supplementary: 5 additional tables, 3 supplementary figures, parameter sensitivity analysis
- References: 45
- All code, data, and pre-trained models publicly available

Data and Code Availability

All source code, curated datasets, pre-computed features, and trained model weights are freely available at <https://github.com/nblvguohao/gpcr-coupling-leakage-benchmark> under the MIT license.

Author Contributions

G.L. and Y.X. conceived the study and designed experiments. G.L. implemented models and performed analyses. H.L. contributed to data curation. L.G. and Q.W. supervised the research. All authors reviewed and approved the manuscript.

Conflict of Interest

The authors declare no competing financial or non-financial interests.

Suggested Reviewers

1. David E. Gloriam (University of Copenhagen) — GPCRdb lead, expertise in GPCR bioinformatics
2. Bonnie Berger (MIT) — Protein language models and protein-protein interaction prediction
3. Arne Elofsson (Stockholm University) — Protein structure prediction and bioinformatics methods
4. Johannes Söding (Max Planck Institute) — Sequence-based protein bioinformatics

Thank you for considering our submission. We look forward to your response.

Qingyong Wang and Lichuan Gu

Sincerely,

Qingyong Wang and Lichuan Gu

On behalf of all co-authors