MACS

MACS v0.4.8 | Settings | ▶ Capture | REC | Sync integration | Downsample analysis (≤10kHz) | 00:00.0 | ▶ Start | Mark | Reset | Markers

Lofargram | Mode: Classic · left click = confirm · right click = clear

Palette: Thermal | FFT: 32768 | ≈1.35 Hz/bin

Cursor: + Classic | ♦ Harmonic | ↔ Sideband | Fmin: 0 | Fmax: 3000 Hz | Floor: -123 | Dyn.: 113 dB | Norm | Integrate | Box | Noise sub.

10 dBFS

-123

0 500 1000 1500 2000 2500 3000

Database Management Panel

Live monitor

Speed: 1x

Vol 100%

Listen

Compare against database

Compare marks against database

MARKED FREQUENCIES

— None —

Suggest groups...

NEW CONTACT

Contact name (e.g. Type 209) *

Optional description

+ Create with marked frequencies

CONTACTS 48 in library

Browse all contacts... | Import... | Export...

Pin contacts to keep them in the sidebar.

Psd

Palette: Thermal | FFT: 32768 | ≈1.35 Hz/bin | Power Spectral Density (PSD) | Integrate | Box

Level (dB)

10 9 8 7 6 5 4 3 2 1 0 -1 -2 -3 -4 -5 -6 -7 -8 -9 -10

-10 -9.5 -9 -8.5 -8 -7.5 -7 -6.5 -6 -5.5 -5 -4.5 -4 -3.5 -3 -2.5 -2 -1.5 -1 -0.5 0 0.5 1 1.5 2 2.5 3 3.5 4 4.5 5 5.5 6 6.5 7 7.5 8 8.5 9 9.5 10

Frequency (Hz)

Recordings Management Panel

RECORDINGS

Ready — 875 frames

PLAYBACK OUTPUT

Bandpass filter

Loop 100%

Speed: 1x

WAA 1kyd

TLTA 180 4kyd

t55_snrkatat

t55_lab

t55_fatline

t55_demon

sabre_flank_28kt

Oshira_WAA

Oshira_TB34

Oshira_TB29A

Noise reference ready: C-0910-Background (875 frames)