
System Dynamics and Control

Modeling in Time Domain - Problems

System Dynamics and Control

Modeling in Time Domain - Problems

3.1 Represent the electrical network in state space with output \emph{v}_0



 ${\bf 3.2}$ Represent the electrical network in state space with output i_R



HCM City Univ. of Technology, Faculty of Mechanical Engineering

Nguyen Tan Tien


HCM City Univ. of Technology, Faculty of Mechanical Engineering

Nguyen Tan Tien

System Dynamics and Control

Modeling in Time Domain - Problems

3.3 Find the state-space representation of the network with output v_0



System Dynamics and Control

Modeling in Time Domain - Problems

3.4 Represent the system in state space with output $x_3(t)$



$$\begin{split} &M_1 = 2kg,\, M_2 = M_3 = 1kg,\, K = 2N/m\\ &f_{v_1} = f_{v_2} = f_{v_3} = f_{v_4} = f_{v_5} = 1Ns/m \end{split}$$

HCM City Univ. of Technology, Faculty of Mechanical Engineering

Nguyen Tan Tien

HCM City Univ. of Technology, Faculty of Mechanical Engineering

Nguyen Tan Tien


System Dynamics and Control

Modeling in Time Domain - Problems

System Dynamics and Control 6 Modeling in Time Domain - Problems

3.5 Represent the translational mechanical system in state space, $x_1(t)$: output $x_2(t) = x_1(t) = x_2(t) = x_1(t) = x_1(t) = x_2(t) = x_1(t) =$

3.6 Represent the rotational mechanical system in state space, $\theta_1(t)$: output, $J_1=50kgm^2$, $J_2=100kgm^2$, $K_2=100Nm/rad$, $D_2=100Nms/rad$, $N_1=30$, $N_2=100$



System Dynamics and Control Modeling in Time Domain - Problems Modeling in Time Domain - Problems System Dynamics and Control 3.7 Represent the system in state space with output $\theta_L(t)$ 3.8 Show that the system yields a fourth-order TF if we relate the displacement of either mass to the applied force, and a third-order one if we relate the velocity of either mass to the applied force HCM City Univ. of Technology, Faculty of Mechanical Engineering HCM City Univ. of Technology, Faculty of Mechanical Engineering Nguyen Tan Tien Nguyen Tan Tien System Dynamics and Control System Dynamics and Control 10 Modeling in Time Domain - Problems Modeling in Time Domain - Problems 3.9 Find the state-space representation in phase-variable form for 3.10 Find the state-space representation in phase-variable form using matlab C(s) b. R(s)HCM City Univ. of Technology, Faculty of Mechanical Engineering Nguven Tan Tien HCM City Univ. of Technology, Faculty of Mechanical Engineering Nguyen Tan Tien System Dynamics and Control Modeling in Time Domain - Problems System Dynamics and Control Modeling in Time Domain - Problems 3.11 For each system write the state equations and the output 3.12 For each system write the state equations and the output equation for the phase-variable representation equation for the phase-variable representation using matlab b. $\frac{R(s)}{\frac{s^4 + 2s^3 + 12s^2 + 7s + 6}{s^5 + 9s^4 + 13s^3 + 8s^2}}$ b. $\frac{R(s)}{s^4 + 2s^2 + 12s^2 + 7s + 6}$ $\frac{s^4 + 2s^3 + 12s^2 + 7s + 6}{s^5 + 9s^4 + 13s^3 + 8s^2}$ a. R(s)C(s)a. R(s)C(s) 8s + 108s + 10HCM City Univ. of Technology, Faculty of Mechanical Engineering Nguyen Tan Tien HCM City Univ. of Technology, Faculty of Mechanical Engineering Nguyen Tan Tien

Modeling in Time Domain - Problems

System Dynamics and Control

Modeling in Time Domain - Problems

3.13 Represent the following TF in state space. Give your answer in vector-matrix form

$${\mathsf{m}}_{T(s)} = \frac{s^2 + 3s + 8}{(s+1)(s^2 + 5s + 5)}$$

3.14 Find the TF G(s) = Y(s)/X(s) for each of the following systems represented in state space

systems represented in state space
$$a.\dot{x} = \begin{bmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -3 & -2 & -5 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 10 \end{bmatrix} r, \quad y = \begin{bmatrix} 1 & 0 & 0 \end{bmatrix} x$$

$$b.\dot{x} = \begin{bmatrix} 2 & -3 & -8 \\ 0 & 5 & 3 \\ -3 & -5 & -4 \end{bmatrix} x + \begin{bmatrix} 1 \\ 4 \\ 6 \end{bmatrix} r, \quad y = \begin{bmatrix} 1 & 3 & 6 \end{bmatrix} x$$

$$c.\dot{x} = \begin{bmatrix} 3 & -5 & 2 \\ 1 & -8 & 7 \\ -3 & -6 & -2 \end{bmatrix} x + \begin{bmatrix} 5 \\ -3 \\ 2 \end{bmatrix} r, \quad y = \begin{bmatrix} 1 & -4 & 3 \end{bmatrix} x$$

HCM City Univ. of Technology, Faculty of Mechanical Engineering

Nguyen Tan Tien

HCM City Univ. of Technology, Faculty of Mechanical Engineering

Nguyen Tan Tien

System Dynamics and Control

Modeling in Time Domain - Problems

System Dynamics and Control

Modeling in Time Domain - Problems

15 **3.15** Use matlab to find the TF G(s) = Y(s)/X(s) for each of the following systems represented in state space

b.
$$\dot{x} = \begin{bmatrix} 0 & 1 & 5 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ -7 & -9 & -2 & -3 \end{bmatrix} x + \begin{bmatrix} 0 \\ 5 \\ 8 \\ 2 \end{bmatrix} r, \quad y = \begin{bmatrix} 1 & 3 & 6 & 6 \end{bmatrix} x$$

$$b. \dot{x} = \begin{bmatrix} 3 & 1 & 0 & 4 & -2 \\ -3 & 5 & -5 & 2 & -1 \\ 0 & 1 & -1 & 2 & 8 \\ -7 & 6 & -3 & -4 & 0 \\ -6 & 0 & 4 & -3 & 1 \end{bmatrix} x + \begin{bmatrix} 2 \\ 7 \\ 8 \\ 5 \\ 4 \end{bmatrix} r, \quad y = \begin{bmatrix} 1 & -2 & -9 & 7 & 6 \end{bmatrix} x$$

16 3.16 Use matlab, the Symbolic Math Toolbox, and Eq.3.73 to find the TF G(s) = Y(s)/X(s) for each of the following systems

$$\mathbf{a}.\dot{\mathbf{x}} = \begin{bmatrix} 0 & 1 & 5 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ -7 & -9 & -2 & -3 \end{bmatrix} \mathbf{x} + \begin{bmatrix} 0 \\ 5 \\ 8 \\ 2 \end{bmatrix} r, \quad y = \begin{bmatrix} 1 & 3 & 6 & 6 \end{bmatrix} \mathbf{x}$$

$$\mathbf{b}.\dot{\mathbf{x}} = \begin{bmatrix} 3 & 1 & 0 & 4 & -2 \\ -3 & 5 & -5 & 2 & -1 \\ 0 & 1 & -1 & 2 & 8 \\ -7 & 6 & -3 & -4 & 0 \\ -6 & 0 & 4 & -3 & 1 \end{bmatrix} \mathbf{x} + \begin{bmatrix} 2 \\ 7 \\ 8 \\ 5 \\ 4 \end{bmatrix} r, \quad y = \begin{bmatrix} 1 & -2 & -9 & 7 & 6 \end{bmatrix} \mathbf{x}$$

HCM City Univ. of Technology, Faculty of Mechanical Engineering

Nguven Tan Tien

HCM City Univ. of Technology, Faculty of Mechanical Engineering

Nguven Tan Tien