

# Perahub Gateway

## Developers Guide

Version 1.9

July 2017

## Confidentiality

This document is a confidential property of Petnet, Inc. It is intended solely for use by employees, authorized vendors and authorized sub-agents of Petnet and shall not be reproduced or disclosed to ANY OTHER PARTY without the express written consent of Petnet. The use, disclosure, reproduction, modification, transfer, or transmittal of this document for any purpose in any form or by any means without the written permission of Petnet is strictly prohibited.

**CONFIDENTIAL PROPERTY OF PETNET, INC.**

**USE AND DISTRIBUTION LIMITED SOLELY TO AUTHORIZED PERSONNEL.**

## Document version History

| Version | Date          | Author  | Description   |
|---------|---------------|---------|---|
| 1.0     | Apr 26, 2017  | Vox Dei | Initial Release   |
| 1.1     | May 08, 2017  | Vox Dei | Added details for ReceiveMoney Search and ReceiveMoney Pay  |
| 1.2     | May 20, 2017  | Vox Dei | Added details for<br>ReceiveMoneyStageSearch<br>ReceiveMoneyStageHold<br>SendMoneyStageValidate<br>SendMoneyStageStore<br>Signin<br>Register<br>Signature computation<br>Added Logical Transactions<br>QuickPayValidate<br>QUickPayStore  |
| 1.3     | May 29, 2017  | Vox Dei | Added Fee Survey<br>Added Compliance Lookup   |
| 1.4     | May 31, 2017  | Vox Dei | Get Secret Question<br>Reset Password<br>Acrivate Card<br>Balance Inquiry<br>Debit Account<br>Credit Account<br>Transaction History   |
| 1.5     | June 01, 2017 | Vox Dei | Added "exchange_rate" on SendMoney Store<br>Added "exchange_rate" on QuickPay Store<br>Added "exchange_rate" on SendMoney Stage Hold<br><br>Revision during Self Certification, as pointed out by WU  |
| 1.6     | June 16, 2017 | Vox Dei | Updated some parameters for registration module,  |
| 1.7     | June 18, 2017 | Vox Dei | Updated some parameters for registration module,  |
| 1.8     | June 22, 2017 | Vox Dei | Documentation for Direct to Bank<br>Documentation for Cash to Mobile/ Mobile Money Transfer<br><br>Revision during Self Certification, as pointed out by WU<br>*promotions details in SendMoneyStore, SendMoneyStoreHold, QuickPayStore<br>*sender_name_type, receiver_name_type in all Validate and Store<br>*GEN_III_Indicator,ack_flag in all Validate<br>*mywu_enroll_tag in all Validate<br>*pd_destination_currency in ReceiveMoneySearch |
| 1.9     | July 21, 2017 | Vox Dei | Transactional API for UBP<br>*Balance Inquiry   |

# PERA HUB

|  |  |  |  |
|--|--|--|--|
|  |  |  | Debit Account<br>Credit Account<br>Transaction History<br>Send SMS<br>Logical Transactions<br>Update information |
|--|--|--|--|

## 1 Contents

|   |    |
|---|----|
| 1. Introduction.....                      | 6  |
| 1.1. Purpose.....                         | 6  |
| 1.2. Scope .....                          | 6  |
| 1.3. Limitations .....                    | 6  |
| 1.4. Target Audience.....                 | 6  |
| 2. Overview.....                          | 6  |
| 2.2. Communication protocol.....          | 6  |
| 2.3. Definitions .....                    | 6  |
| 2.4. Syntax .....                         | 6  |
| 2.5. Data Request and Data Response ..... | 7  |
| 2.6. HTTP Request .....                   | 8  |
| 2.7. Assumptions .....                    | 8  |
| 2.8. Logical Transactions.....            | 8  |
| 3. API Functions .....                    | 9  |
| 3.1. Prerequisites.....                   | 9  |
| 3.1.1. Sign-on.....                       | 9  |
| 3.2. Money Remittance .....               | 10 |
| 3.2.1. References .....                   | 10 |
| 3.2.2. Common Functions.....              | 11 |
| 3.2.3. SendMoney.....                     | 19 |
| 3.2.4. QuickPay .....                     | 41 |
| 3.2.5. ReceiveMoney .....                 | 51 |
| 3.2.6. Stage and Pay .....                | 60 |
| 3.3. E-Wallet .....                       | 79 |
| 3.3.1. Common Functions.....              | 79 |
| 3.3.2. Transactional .....                | 85 |

## 1. Introduction

### 1.1.Purpose

PeraHUB Gateway is an API platform developed for Petnet, Inc. to accommodate host-to-host integration for its Western Union money remittance service and E-Wallet facility for loyal customers

This document serves as a reference material for interested parties/sub-agents how to implement interface with PeraHUB Gateway in processing Money Remittance and E-Wallet transactions. Its main purpose is to discuss definitions and detailed specifications of available processes in the platform.

### 1.2.Scope

### 1.3.Limitations

### 1.4.Target Audience

This document is intended to technical personnel or developers seeking to interface and connect to transact money remittance or e-wallet facility.

## 2. Overview

### 2.2.Communication protocol

PeraHUB Gateway uses standard protocols and data structures. The system exposes RESTful API functions over HTTPS(*temporarily http*). All communications between hosts is done via JSON data submitted to an HTTPS(*temporarily http*) endpoint using POST action. Replies to requests are returned synchronously on the same connection from which the request originated. All reply contain standard HTTP response codes along with is a JSON response containing the requested data.

### 2.3.Definitions

### 2.4.Syntax

The following must be considered when formatting JSON request

- Enumerations must use the value exactly as specified
- Parameters that do not contain a value should be removed from the request.

# PERA HUB

## 2.5.Data Request and Data Response

JSON Data below applies to ALL requests with EXCEPTION to “Sign-on” request.

### JSON Data request

```
{
  "uspuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "partner location code",
      "user_code": "partner user code",
      "clientip": "IP Address of user/mobile",
      "isweb": "1"
    },
    "body": {
      "module": "module name",
      "request": "specific function name",
      "param": {
      }
    },
    "signature": ""
  }
}
```

JSON Data request should be encoded to base64 string format before submit.

### Wherein:

| Attribute Name | Description   |
|----------------|---|
| coy            | Partner Code, to be provided by Petnet, Inc.<br><br>available values : yundu, lbc   |
| token          | Is a concatenated string of <b>PARTNERID</b> + <b>YOURSERVERIP</b> + <b>CLIENTKEY</b> converted to MD5<br><br>For Development Purposes please use<br><b>PARTNERID = client_01</b><br><b>CLIENTKEY= de9462831b</b> |
| location_code  | Refers to location code of the partner  |
| user_code      | Refers to user code/teller code of the partner  |
| clientip       | IP address source of the user/mobile  |
| module         | Get the module name from each API function  |
| request        | Specific function name, also can be found in each API function  |
| param          | Is an array of REQUEST parameters depending on module and request type. Refer to complete list of parameters per module found in each API function  |
| signature      | Signature is a computation using a PKCS#12 certificate and to be provided to partner.<br><br><b>Value to sign is the value of param variable</b>  |

### JSON Data response:

```
{
  "uspuapi": {
```

# PERA HUB

```
"header": {
  "errorcode": "1",
  "message": "good"
},
"body": {
  "mywu_number": "183706030"
}
}
```

## Wherein:

| Attribute Name | Description  |
|----------------|--|
| errorcode      | Error group code response from PeraHUB Gateway<br>"1" denotes successful request<br>"USP", error prompt from PeraHUB Gateway<br>"WU", error prompt from Western Union<br>"SYS", Technical error<br><br>available values : yundu, lbc |
| message        | Description about the error code   |
| body           | Contains an array of RESPONSE parameters depending on the last submitted request.  |

## 2.6.HTTP Request

Endpoint: <http://gateway.perahub.com.ph/gateway/{module}>

Method: "POST"

Note: {module} can be found from definitions of each API functions

Required Query String variable: **hash**

Value of "hash" is the **JSON Data request encoded in base64 string** format




## 2.7.Assumptions

Below are assumptions that should be considered during the development

- All the amounts fields **BOTH ON REQUEST and RESPONSE**(Principal Amount, Charges, Taxes, etc...) have their last 2 digits as decimal places Ex: Principal Amount in PHP is 10010 which are 100 Pesos & 10 cents
- There might be cases where some fields do not contain any data at a given point of time. Such fields might be received as empty attributes or sometimes might not at all be displayed in JSON response from PerHUB Gateway. Such fields should be ignored by partner systems and should not cause any error scenario.

## 2.8.Logical Transactions

Logical transactions are the set of transactions that will take place in completing a full service. Few examples of logical transaction would be

- > FeelInquiry -> SendMoney Validate -> **Debit Amount UB->** SendMoney Store 
- > FeelInquiry -> QuickPay Validate -> **Debit Amount UB->** QuickPay Store 
- > ReceiveMoney Search -> ReceiveMoney Pay->**SendSMS->** **Credit Amount UB** 

If Resonse->error\_code = SYS then

PayStatus If Response->paystatus\_description = W/C then ReceiveMoney Pay



# PERA HUB

- -> FeelInquiry -> FeeSurvey -> SendMoney Stage Validate -> SendMoney Stage Hold
- -> SendMoney Staged Search -> SendMoney Staged Release
- -> ReceiveMoney Stage Search -> ReceiveMoneyPayHold
  - If Resonse->error\_code = SYS then
    - PayStatus If Response->paystatus\_description = W/C then
      - ReceiveMoneyPayHold
- -> HoldTransactionSearch -> ReceiveMoneyPayRelease
  - If Resonse->error\_code = SYS then
    - PayStatus If Response->paystatus\_description = W/C then
      - HoldTransactionSearch

## 3. API Functions

### 3.1. Prerequisites

#### 3.1.1. Sign-on



Use this API function to get the details of customers. Provides several search options for MyWU customers.

Module: **signin**

Request: **login**

REQUEST Parameters:

| Name     | Type     | Required | Description  |
|----------|----------|----------|--|
| username | text:15  | M        | Search Parameters required for card email mobile search option |
| password | text:128 | M        | password should be in SHA512 format                            |

Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "yundu",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "1",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "signin",
      "request": "login",
      "param": {
        "username" : "RN052480W",
        "password":
"6700713fac9f035fbc0cf5e9e0b245dd4eea74e930530f0faf0993446435bc298c8fc9c6f35e
6c0a741a88490db2735e758810288025c700bf5fa72c775ddf08"
      }
    }
  }
}
```

```
    },
    "signature": "anyvaluesfornow"
  }
}
```

## RESPONSE Parameters:

| Name                 | Type         | Required | Description                              |
|----------------------|--------------|----------|--|
| foreign_reference_no | alpha-num:50 | M        | Mandatory for all requests except login. |
| customer             | array        | M        | Full Details of Customers                |

## Sample JSON Data response:

```
{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "foreign_reference_no":
"d13400918208a58b4e42869316e55963994b6031",
      "customer": {
        "surname": "",
        "givenname": "",
        "Birthdate": "",
        "Nationality": "",
        "PresentAddress": "",
        "Occupation": "",
        "NameOfEmployer": "",
        "ValidIdentification": "",
        "WuCardNo": "",
        "DebitCardNo": "",
        "LoyaltyCardNo": ""
      }
    }
  }
}
```

## 3.2. Money Remittance



### 3.2.1. References

Data Response of API functions under this category are recommended to be stored on partners system. Stored data can be updated at least once a day.

## 3.2.1.1. *ISOCountries*

## 3.2.1.2. *ISOCurrencies*

## 3.2.1.3. *USState*

## 3.2.1.4. *MexicoCityState*

## 3.2.1.5. *QuickPayCompanies*

## 3.2.1.6. *BankList*

## 3.2.1.7. *CountryInformation*

## 3.2.2. Common Functions

### 3.2.2.1. *MyWU Search*



Use this API function to get the details of customers. Provides several search options for MyWU customers.

Module: **prreq**

Request: **mywusearch**

REQUEST Parameters:

| Name                 | Type         | Required | Description  |
|----------------------|--------------|----------|--|
| foreign_reference_no | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value)  |
| searchparam          | text:50      | C        | Search Parameters required for card email mobile search option   |
| searchtype           | alpha:6      | M        | card = search by MyWU number<br>email = search by email address<br>mobile = search by mobile no.<br>name = search by sender/receiver |
| sender_first_name    | alpha:100    | C        | required if search by name   |
| sender_last_name     | alpha:100    | C        | required if search by name   |
| operator_id          | alpha-num:10 | M        | Operator ID will be provided Petnet per partner teller/user  |
| terminal_id          | alpha-num:10 | M        | Terminal ID will be provided by Petnet per partner location  |

Sample JSON Data request:

```
{
  "uspuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "1",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    }
  }
}
```

```

    },
    "body": {
      "module": "prereq",
      "request": "mywusearch",
      "param": {
        "foreign_reference_no" : "LBCTrackingNO01",
        "searchparam": "",
        "searchtype": "name",
        "sender_first_name": "MIGUEL",
        "sender_last_name": "FADRIQUELA",
        "operator_id": "001",
        "terminal_id": "WBPt",
      }
    },
    "signature": "anyvaluesfornow"
  }
}

```

## Sample Parameters:

by email : MAZELTOV1324@YAHOO.COM

by mobile : 9998947210

by card : 183907555

by name : firsnmae=MIGUEL, lastname=FADRIQUELA

## Other samples by card:

183704489

183702776

### 3.2.2.2. *MyWU Enrollment*

Use this API to enroll or add customer to MyWU program. This is a stand-alone function that can be called outside Logical Transactions.

Module: **prereq**

Request: **mywuenroll**

## REQUEST Parameters:

| Name                      | Type         | Required | Description   |
|---------------------------|--------------|----------|---|
| foreign_reference_no      | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value) |
| sender_first_name         | alpha:100    | M        | First Name  |
| sender_last_name          | alpha:100    | M        | Last Name   |
| sender_addr_line1         | text:200     | M        |   |
| sender_addr_line2         | text:200     | O        |   |
| sender_city               | text:50      | M        | City / Municipality   |
| sender_state              | text:100     | M        | State / Province / Region   |
| sender_postal_code        | num:10       | M        |   |
| sender_addr_country_code  | alpha:2      | M        | 2 letter ISO country code   |
| sender_addr_currency_code | alpha:3      | M        | 3 letter ISO currency code  |
| email                     | email        | O        | Valid email format  |

# PERA HUB

|                            |              |   |   |
|----------------------------|--------------|---|---|
| sender_contact_phone       | num:30       | O | Format should be Mobile Country Code + phone number         |
| sender_mobile_country_code | num:3        | O | Mobile Country Code   |
| sender_mobile_no           | num:20       | O | Mobile Number   |
| operator_id                | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user |
| terminal_id                | alpha-num:10 | M | Terminal ID will be provided by Petnet per partner location |

## Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "1",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "prereq",
      "request": "mywuenroll",
      "param": {
        "sender_first_name": "NICOLAS",
        "sender_last_name": "FADRIQUELA",
        "sender_addr_line1": "Phase 5 Block 4 Lot 7",
        "sender_addr_line2": "Camella Prove",
        "sender_city": "MALOLOS",
        "sender_state": "REGION 3",
        "sender_postal_code": "3000",
        "sender_addr_country_code": "PH",
        "sender_addr_currency_code": "PHP",
        "email": "nickfadriquila@yahoo.com",
        "sender_contact_phone": "639177654321",
        "sender_mobile_country_code": "63",
        "sender_mobile_no": "9177654321",
        "operator_id": "001",
        "terminal_id": "WBPt"
      }
    },
    "signature": "anyvaluesfornow"
  }
}
```

## REPOSE Parameters:

| Name        | Type         | Required | Description                            |
|-------------|--------------|----------|--|
| mywu_number | alpha-num:20 | M        | MyWU Number of newly enrolled customer |

## Sample JSON Data response:

```
{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
```

```

    "message": "good"
  },
  "body": {
    "mywu_number": "183706030"
  }
}

```

### 3.2.2.3. Compliance Lookup

Compliance Look can be used both for SEND and RECEIVE money to check ID details of sender or receiver.

Module: **prereq**

Request: **compliance**

REQUEST Parameters:

| Name                 | Type         | Required | Description   |
|----------------------|--------------|----------|---|
| foreign_reference_no | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value)   |
| first_name           | num          | M        | Amount to Send  |
| last_name            | alpha:1      | M        | <b>F</b> if customer want a fixed principal amount in the destination country and will not be subject to currency fluctuation. Otherwise <b>N</b> |
| id_type              | alpha:2      | M        | 2 letter ISO country code   |
| id_country_of_issue  | alpha:3      | M        | 3 letter ISO currency code  |
| id_number            | num          | M        |   |
| transaction_type     |              | M        | SO = SendMoney/ D2B/ MMT/ Quickpay<br>PO=ReceiveMoney   |
| operator_id          | alpha-num:10 | M        | Operator ID will be provided Petnet per partner teller/user   |
| terminal_id          | alpha-num:10 | M        | Terminal ID will be provided by Petnet per partner location   |

Sample JSON Data request:

```

{
  "uspwuapi": {
    "header": {
      "coy": "yundu",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "prereq",
      "request": "compliance",

```

# PERA HUB

```
        "param": {
            "foreign_reference_no": "123123sadasd",
            "first_name": "DIVYA",
            "last_name": "BHARATHI",
            "id_type": "B",
            "id_country_of_issue": "Philippines",
            "id_number": "1729389908236",
            "transaction_type": "SO",
            "terminal_id": "WBPt",
            "operator_id": "001"
        },
        "signature": " anyvaluesfornow"
    }
}
```

## REPONSE Parameters:

| Name               | Type  | Required | Description             |
|--------------------|-------|----------|-------------------------|
| compliance_details | array | M        | Full compliance details |

## Sample JSON Data response:

```
{
    "uspwuapi": {
        "header": {
            "errorcode": "1",
            "message": "good"
        },
        "body": {
            "name": {
                "name_type": "D",
                "first_name": "DIVYA",
                "last_name": "BHARATHI"
            },
            "compliance_details": {
                "template_id": "2PH_02_S",
                "id_details": {
                    "id_type": "B",
                    "id_country_of_issue": "PHILIPPINES",
                    "id_number": "1729389908236"
                },
                "compliance_flags_buffer":
                "004YYZY01400ZY024Y0YY034Y0YY06400ZY074Y0ZY084Y0ZY09400ZY104Y0ZY33400ZY344Y0Z
                Y444Z0YY67400ZY704Z0YY744Y0ZY",
                "id_issue_date": "10102010",
                "id_expiration_date": "11112020",
                "date_of_birth": "08031995",
                "occupation": "Student",
                "Country_of_Birth": "PHILIPPINES",
                "nationality": "PHILIPPINES",
                "Source_of_Funds": "Charitable/Fund Raising",
                "Name_of_Employer_Business": "mgcv school",
                "Relationship_to_Receiver_Sender": "Donor/Receiver of
                Ch",
                "Does_the_ID_have_an_expiration_date": "N",
                "GEN_III_Indicator": "1"
            }
        }
    }
}
```

```

    }
  }
}

```

### 3.2.2.4. *FeeInquiry*

Fee Inquiry provides appropriate fees applicable to transfer information provided.

Module: **prereq**

Request: **feeinquiry**

REQUEST Parameters:

| Name                      | Type         | Required | Description   |
|---------------------------|--------------|----------|---|
| foreign_reference_no      | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value)   |
| principal_amount          | num          | M        | Amount to Send  |
| fixed_amount_flag         | alpha:1      | M        | <b>F</b> if customer want a fixed principal amount in the destination country and will not be subject to currency fluctuation. Otherwise <b>N</b> |
| destination_country_code  | alpha:2      | M        | 2 letter ISO country code   |
| destination_currency_code | alpha:3      | M        | 3 letter ISO currency code  |
| transaction_type          |              | M        | SO = SendMoney/D2B/MMT<br>QP=QuickPay   |
| promo_code                | alpha-num:20 | O        | Promo code  |
| message                   | text:array   | O        | Optional Message from SENDER to RECEIVER<br>Maximum Length per line is 79 characters<br>Maximum array length is 14                                |
| operator_id               | alpha-num:10 | M        | Operator ID will be provided Petnet per partner teller/user   |
| terminal_id               | alpha-num:10 | M        | Terminal ID will be provided by Petnet per partner location   |

Sample JSON Data request:

```

{
  "uspuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "prereq",
      "request": "feeinquiry",
      "param": {

```



# PERA HUB

```
        "foreign_reference_no": "123123sadasd",
        "principal_amount": "100000",
        "fixed_amount_flag": "N",
        "destination_country_code": "PH",
        "destination_currency_code": "PHP",
        "transaction_type": "SO",
        "promo_code": "",
        "message": [],
        "message_line_count": "0",
        "terminal_id": "WBPt",
        "operator_id": "001"
    },
    },
    "signature": "anyvaluesfornow"
}
```

## RESPONSE Parameters:

| Name   | Type | Required | Description   |
|--|------|----------|---|
| originators_principal_amount                       | num  | M        | Principal Amount at the originating country   |
| destination_principal_amount                       | num  | M        | Amount to Receive at the destination country  |
| gross_total_amount                                 | num  | M        | Total Amount that should be collected from the customer   |
| charges  | num  | M        | Total Charges of SendMoney including message charges and net of promo discount should the bee any |
| exchange_rate                                      | num  | M        | Currency exchange rate of PHP vs Currency of destination country                                  |
| Other RESPONSE Parameters are for reference only a |      |          |   |

## Sample JSON Data response:

```
{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "taxes": {
        "municipal_tax": 0,
        "state_tax": 0,
        "county_tax": 0,
        "tax_worksheet": ""
      },
      "originators_principal_amount": 100000,
      "destination_principal_amount": 100000,
      "gross_total_amount": 101500,
      "plus_charges_amount": 0,
      "pay_amount": 100000,
      "charges": 1500,
      "tolls": 0,
    }
  }
}
```

```

        "originating_currency_principal": "",
        "canadian_dollar_exchange_fee": 0,
        "message_charge": 0,
        "promo_code_description": "",
        "promo_sequence_no": "",
        "promo_name": "",
        "promo_discount_amount": 0,
        "exchange_rate": 1,
        "base_message_charge": "5000",
        "base_message_limit": "10",
        "incremental_message_charge": "500",
        "incremental_message_limit": "10"
    }
}
}

```

### 3.2.2.5. FeeSurvey

Fee Survey provides should be used to get staging buffer needed for SendMoneyValidate stage option.

Module: **prereq**

Request: **feesurvey**

REQUEST Parameters:

| Name                      | Type         | Required | Description   |
|---------------------------|--------------|----------|---|
| foreign_reference_no      | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value)   |
| principal_amount          | num          | M        | Amount to Send  |
| fixed_amount_flag         | alpha:1      | M        | <b>F</b> if customer want a fixed principal amount in the destination country and will not be subject to currency fluctuation. Otherwise <b>N</b> |
| destination_country_code  | alpha:2      | M        | 2 letter ISO country code   |
| destination_currency_code | alpha:3      | M        | 3 letter ISO currency code  |
| transaction_type          |              | M        | SO = SendMoney/D2B/MMT<br>QP=QuickPay   |
| promo_code                | alpha-num:20 | O        | Promo code  |
| message                   | text:array   | O        | Optional Message from SENDER to RECEIVER<br><b>Maximum Length per line is 79 characters</b><br><b>Maximum array length is 14</b>                  |
| operator_id               | alpha-num:10 | M        | Operator ID will be provided Petnet per partner teller/user   |
| terminal_id               | alpha-num:10 | M        | Terminal ID will be provided by Petnet per partner location   |

Sample JSON Data request:

```

{
    "uspuwapi": {

```

# PERA HUB

```
"header": {
  "coy": "yondu",
  "token": "b0dd9378fb63749c462a66d209b06454",
  "location_code": "6",
  "user_code": "1",
  "clientip": "::1",
  "isweb": "1"
},
"body": {
  "module": "prereq",
  "request": "feeinquiry",
  "param": {
    "foreign_reference_no": "123123sadasd",
    "principal_amount": "100000",
    "fixed_amount_flag": "N",
    "destination_country_code": "PH",
    "destination_currency_code": "PHP",
    "transaction_type": "SO",
    "promo_code": "",
    "message": [],
    "message_line_count": "0",
    "terminal_id": "WBPt",
    "operator_id": "001"
  }
},
"signature": "anyvaluesfornow"
}
```

## RESPONSE Parameters:

| Name           | Type | Required | Description  |
|----------------|------|----------|--|
| staging_buffer | text | M        | Staging buffer required for SendMoneyValidate stage option |

## Sample JSON Data response:

```
{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "staging_buffer": "0101C0202MB0303PIL"
    }
  }
}
```

### 3.2.3. SendMoney

#### 3.2.3.1. SendMoney Validate

Use this function to validate transaction Send Money data.

Module: **wuso**

Request: **SMvalidate**

## REQUEST Parameters:

| Name                       | Type              | Required | Description   |
|----------------------------|-------------------|----------|---|
| foreign_reference_no       | alpha-num:50      | M        | This will be provided upon Sign-on (for the meantime, please use any value)   |
| sender_name_type           | alpha:1           | M        | D = Firstname/LastName<br>M = Paternal/Maternal (WU)<br>Advised to use option D in case customer or teller encountered this name type)  |
| sender_first_name          | alpha:100         | M        | First Name  |
| sender_middle_name         | alpha:100         | M        |   |
| sender_last_name           | text:200          | M        | Last Name   |
| sender_addr_line1          | text:200          | M        |   |
| sender_addr_line2          | text:200          | O        |   |
| sender_city                | text:50           | M        | City / Municipality   |
| sender_state               | text:100          | M        | State / Province / Region   |
| sender_postal_code         | num:10            | M        |   |
| sender_addr_country_code   | alpha:2           | M        | 2 letter ISO country code   |
| sender_addr_currency_code  | alpha:3           | M        | 3 letter ISO currency code  |
| sender_contact_phone       | num:30            | O        | Format should be Mobile Country Code + phone number   |
| sender_mobile_country_code | num:3             | O        | Mobile Country Code   |
| sender_mobile_no           | num:20            | O        | Mobile Number   |
| mywu_number                | num:20            | O        | MyWU number   |
| mywu_enroll_tag            | alpha:10          | M        | mywu = when customer has MyWU Number<br><br>enroll = when customer want to enroll in MyWU Program. This is another way to enroll customer into MyWU aside from stand-alone enrollment<br><br>none=when customer does not want to enroll to MyWU |
| id_type                    | text:20           | M        | Refer to IDTypeList   |
| id_country_of_issue        | text:100          | M        | of Sender   |
| id_number                  | text:50           | M        | of Sender   |
| id_issue_date              | date:<br>ddmmyyyy | M        | of Sender   |
| id_expiration_date         | date:<br>ddmmyyyy | C        | of Sender (required depends on ID Type)   |
| date_of_birth              | date:<br>ddmmyyyy | M        | of Sender   |
| occupation                 | text:100          | M        | of Sender   |
| Country_of_Birth           | text:100          | M        | of Sender   |
| nationality                | text:100          | M        | of Sender   |
| Gender                     | text:1            | M        | of Sender   |
| Source_of_Funds            | text:50           | M        | of Sender   |

# PERA HUB

|                              |           |   |   |
|------------------------------|-----------|---|---|
| Sender_Employeer             | text:50   | M | of Sender   |
| Relationship_to_Receiver     | text:50   | M | of Sender   |
| reason_for_send              | text:50   | M | of Sender   |
| GEN_III_Indicator            | num:1     | M | Value should be "1" if compliance lookup is successful<br><br>Otherwise BLANK or NULL<br><br>Adjustment required by WU during PI certification                  |
| ack_flag                     | alpha:1   | M | Acknowledgement Flag that users has entered correct values, Required by WU<br><br>Value to pass is "X"<br><br>Adjustment required by WU during PI certification |
| email                        | email     | O | of Sender   |
| receiver_name_type           | alpha:1   | M | D = Firstname/LastName<br>M = Paternal/Maternal (WU Advised to use option D in case customer or teller encountered this name type)                              |
| receiver_first_name          | alpha:100 | M |   |
| receiver_middle_name         | alpha:100 | O |   |
| receiver_last_name           | alpha:100 | M |   |
| receiver_addr_line1          | text:200  | C | Required if Destination Country is US, INDIA  |
| receiver_addr_line2          | text:200  | O |   |
| receiver_city                | text:50   | C | Required if Destination Country is US, INDIA  |
| receiver_state               | text:100  | C | Required if Destination Country is US, INDIA  |
| receiver_postal_code         | num:10    |   | Required if Destination Country is US, INDIA  |
| receiver_addr_country_code   | alpha:2   | O | 2 letter ISO country code   |
| receiver_addr_currency_code  | alpha:3   | O | 3 letter ISO currency code  |
| receiver_contact_phone       | num:30    | C | Required if Destination Country is CHINA, INDIA, NIGERIA, USA and transaction type is D2B   |
| receiver_mobile_country_code | num:3     | C | Required if transactions type is MMT<br><br>Required if Destination Country is CHINA, INDIA, NIGERIA, USA and transaction type is D2B                           |
| receiver_mobile_no           | num:20    | C | Required if transactions type is MMT<br><br>Required if Destination Country   |

# PERA HUB

|                           |              |   |  |
|---------------------------|--------------|---|--|
|                           |              |   | is CHINA, INDIA, NIGERIA, USA and transaction type is D2B  |
| destination_country_code  | alpha:2      | M | 2 letter ISO country code  |
| destination_currency_code | alpha:3      | M | 3 letter ISO currency code   |
| destination_state_code    | alpha-num:20 | C | Required if Destination Country is USA and Mexico  |
| destination_city_name     | text:50      | C | Required if Destination Country is USA and Mexico  |
| transaction_type          | alpha-num:3  | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer   |
| principal_amount          | num          | M | Amount to Send   |
| fixed_amount_flag         | alpha:1      | M | <b>F</b> if customer wants a fixed principal amount in the destination country and will not be subject to currency fluctuation. Otherwise <b>N</b> |
| promo_code                | alpha-num:20 | O | Promo code   |
| message                   | text:array   | O | Optional Message from SENDER to RECEIVER<br>Maximum Length per line is 79 characters<br>Maximum array length is 14                                 |
| bank_name                 | text:100     |   | Required when transaction type = D2B   |
| account_number            | num:50       |   | Required when transaction type = D2B   |
| bank_code                 | alpha-num:20 |   | Required when transaction type = D2B   |
| bank_location             | alpha-num:20 |   | Required when transaction type = D2B   |
| account_suffix            | alpha-num:10 |   | Required when transaction type = D2B   |
| operator_id               | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user  |
| terminal_id               | alpha-num:10 | M | Terminal ID will be provided by Petnet per partner location  |

## Sample JSON Data request:

```
{
  "uspuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "wuso",
      "request": "SMvalidate",
      "param": {
```

```
"foreign_reference_no": "123123sadasd",
"sender_name_type": "D",
"sender_first_name": "WINNIE",
"sender_middle_name": "",
"sender_last_name": "CONSTANTINO",
"sender_addr_line1": "CALUMPIT",
"sender_addr_line2": "",
"sender_city": "CALUMPIT",
"sender_state": "REGION 3",
"sender_postal_code": "3003",
"sender_addr_country_code": "PH",
"sender_addr_currency_code": "PHP",
"sender_contact_phone": "6329446115",
"sender_mobile_country_code": "",
"sender_mobile_no": "",
"mywu_number": "185015541",
"mywu_enroll_tag": "mywu",
"id_type": "S",
"id_country_of_issue": "Philippines",
"id_number": "14789654",
"id_issue_date": "02072015",
"id_expiration_date": "12072017",
"date_of_birth": "06041992",
"occupation": "Programmer",
"Country_of_Birth": "Philippines",
"nationality": "Filipino",
"Gender": "F",
"Source_of_Funds": "Personal Loan",
"Sender_Employeer": "Abaris",
"Relationship_to_Receiver": "Father",
"reason_for_send": "228990",
"GEN_III_Indicator": "",
"ack_flag": "X",
"email": "WINNIEANN.CONSTANTINO@VOXDEISYSTEMS.COM",
"receiver_name_type": "D",
"receiver_first_name": "William",
"receiver_middle_name": "",
"receiver_last_name": "Constantino",
"receiver_addr_line1": "",
"receiver_addr_line2": "",
"receiver_city": "",
"receiver_state": "",
"receiver_postal_code": "",
"receiver_addr_country_code": "PH",
"receiver_addr_currency_code": "PHP",
"receiver_contact_phone": "",
"receiver_mobile_country_code": "",
"receiver_mobile_no": "",
"destination_country_code": "PH",
"destination_currency_code": "PHP",
"destination_state_code": "",
"destination_city_name": "",
"transaction_type": "SO",
"principal_amount": 100000,
"fixed_amount_flag": "N",
"promo_code": "A0027",
```

# PERA HUB

```
        "message": [""],
        "bank_name": "",
        "account_number": "",
        "bank_code": "",
        "bank_location": "",
        "account_suffix": "",
        "terminal_id": "WBPT",
        "operator_id": "001"
    },
    "signature": "anyvaluesfornow"
}
```

## REPOSE Parameters:

| Name                   | Type          | Required | Description  |
|------------------------|---------------|----------|--|
| addl_service_charges   | text:200      | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| compliance_data_buffer | alpha-num:200 | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| originating_city       | alpha-num:50  | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| originating_state      | alpha-num:10  | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| financials             | array         | M        | The whole array should be preserved as is  |
| promotions             | array         | M        | The whole array should be preserved as is<br><br>Adjustment required by WU during PI certification             |
| mtcn                   | num:10        | M        | Money Transfer Control Number<br>Must be preserve as is since this will be use as parameter in SendMoney Store |
| new_mtcn               | num:16        | M        | Money Transfer Control Number<br>Must be preserve as is since this will be use as parameter in SendMoney Store |

## Sample JSON Data response:

```
{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "service_code": {
```



# PERA HUB

```
        "addl_service_charges":
"1103FEE12041500130415000103MSG0201003010210300022010230109001096210104500002
021003035009703NNN9806PILPIL"
    },
    "compliance": {
        "compliance_data_buffer":
"01082PH_02_S0201S0308147896540611Philippines0708060419920810Programmer090802
0720151008120720179901X3311Philippines3408Filipino3501F4413Personal
Loan6706Abaris7006Father7401Y"
    },
    "payment_details": {
        "originating_city": "METRO MANILA",
        "originating_state": "MA"
    },
    "financials": {
        "taxes": {
            "municipal_tax": 0,
            "state_tax": 0,
            "county_tax": 0
        },
        "originators_principal_amount": 100000,
        "destination_principal_amount": 100000,
        "gross_total_amount": 101500,
        "plus_charges_amount": 0,
        "charges": 1500,
        "message_charge": 0
    },
    "promotions": {
        "promo_code_description": "T3001 Valid promotion with
discount.",
        "promo_name": "A0027 50% OFF CHARGES",
        "promo_message": "A0027 Special 50% Off Charges Intro",
        "promo_discount_amount": 250,
        "sender_promo_code": "A0027"
    },
    "new_details": {
        "mtcn": "9231430092",
        "new_mtcn": "1711689231430092",
        "filing_date": "04-26",
        "filing_time": "1030P EDT "
    }
}
}
```

### 3.2.3.2. SendMoney Store

Use this API function to save and confirm Send Money Transaction.

Module: **wuso**

Request: **SMstore**

REQUEST Parameters:

# PERA HUB

| Name                       | Type              | Required | Description   |
|----------------------------|-------------------|----------|---|
| foreign_reference_no       | alpha-num:50      | M        | This will be provided upon Sign-on (for the meantime, please use any value)   |
| sender_name_type           | alpha:1           | M        | D = Firstname/LastName<br>M = Paternal/Maternal (WU<br>Advised to use option D in case customer or teller encountered this name type) |
| sender_first_name          | alpha:100         | M        | First Name  |
| sender_middle_name         | alpha:100         | M        |   |
| sender_last_name           | text:200          | M        | Last Name   |
| sender_addr_line1          | text:200          | M        |   |
| sender_addr_line2          | text:200          | O        |   |
| sender_city                | text:50           | M        | City / Municipality   |
| sender_state               | text:100          | M        | State / Province / Region   |
| sender_postal_code         | num:10            | M        |   |
| sender_addr_country_code   | alpha:2           | M        | 2 letter ISO country code   |
| sender_addr_currency_code  | alpha:3           | M        | 3 letter ISO currency code  |
| sender_contact_phone       | num:30            | O        | Format should be Mobile Country Code + phone number   |
| sender_mobile_country_code | num:3             | O        | Mobile Country Code   |
| sender_mobile_no           | num:20            | O        | Mobile Number   |
| mywu_number                | num:20            | O        | MyWU number   |
| id_type                    | text:20           | M        | Refer to IDTypeList   |
| id_country_of_issue        | text:100          | M        | of Sender   |
| id_number                  | text:50           | M        | of Sender   |
| id_issue_date              | date:<br>ddmmyyyy | M        | of Sender   |
| id_expiration_date         | date:<br>ddmmyyyy | C        | of Sender (required depends on ID Type)   |
| date_of_birth              | date:<br>ddmmyyyy | M        | of Sender   |
| occupation                 | text:100          | M        | of Sender   |
| Country_of_Birth           | text:100          | M        | of Sender   |
| nationality                | text:100          | M        | of Sender   |
| Gender                     | text:1            | M        | of Sender   |
| Source_of_Funds            | text:50           | M        | of Sender   |
| Sender_Employeer           | text:50           | M        | of Sender   |
| Relationship_to_Receiver   | text:50           | M        | of Sender   |
| reason_for_send            | text:50           | M        | of Sender   |
| email                      | email             | O        | of Sender   |
| receiver_name_type         | alpha:1           | M        | D = Firstname/LastName<br>M = Paternal/Maternal (WU<br>Advised to use option D in case customer or teller encountered this name type) |
| receiver_first_name        | alpha:100         | M        |   |
| receiver_middle_name       | alpha:100         | O        |   |
| receiver_last_name         | alpha:100         | M        |   |

# PERA HUB

|                              |              |   |   |
|------------------------------|--------------|---|---|
| receiver_addr_line1          | text:200     | C | Required if Destination Country is US, INDIA  |
| receiver_addr_line2          | text:200     | O |   |
| receiver_city                | text:50      | C | Required if Destination Country is US, INDIA  |
| receiver_state               | text:100     | C | Required if Destination Country is US, INDIA  |
| receiver_postal_code         | num:10       |   | Required if Destination Country is US, INDIA  |
| receiver_addr_country_code   | alpha:2      | O | 2 letter ISO country code   |
| receiver_addr_currency_code  | alpha:3      | O | 3 letter ISO currency code  |
| receiver_contact_phone       | num:30       | C | Required if Destination Country is CHINA, INDIA, NIGERIA, USA and transaction type is D2B   |
| receiver_mobile_country_code | num:3        | C | Required if transactions type is MMT  |
| receiver_mobile_no           | num:20       | C | Required if transactions type is MMT  |
| destination_country_code     | alpha:2      | M | 2 letter ISO country code   |
| destination_currency_code    | alpha:3      | M | 3 letter ISO currency code  |
| destination_state_code       | alpha-num:20 | C | Required if Destination Country is USA and Mexico   |
| destination_city_name        | text:50      | C | Required if Destination Country is USA and Mexico   |
| transaction_type             | alpha-num:3  | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer  |
| principal_amount             | num          | M | Amount to Send  |
| fixed_amount_flag            | alpha:1      | M | <b>F</b> if customer wants a fixed principal amount in the destination country and will not be subject to currency fluctuation.<br>Otherwise <b>N</b> |
| exchange_rate                | num          | M | Currency exchange rate of PHP vs Currency of destination country  |
| promo_code                   | alpha-num:20 | O | Promo code  |
| message                      | text:array   | O | Optional Message from SENDER to RECEIVER<br>Maximum Length per line is 79 characters<br>Maximum array length is 14                                    |
| bank_name                    | text:100     | C | Required when transaction type = D2B  |
| account_number               | num:50       | C | Required when transaction type = D2B  |
| bank_code                    | alpha-num:20 | C | Required when transaction type = D2B  |
| bank_location                | alpha-num:20 | C | Required when transaction type = D2B  |
| account_suffix               | alpha-num:10 | C | Required when transaction type = D2B  |
| operator_id                  | alpha-num:10 | M | Operator ID will be provided  |

# PERA HUB

|                        |               |   |   |
|------------------------|---------------|---|---|
|                        |               |   | Petnet per partner teller/user  |
| terminal_id            | alpha-num:10  | M | Terminal ID will be provided by Petnet per partner location   |
| addl_service_charges   | text:200      | M | Derive value from SendMoney validate  |
| compliance_data_buffer | alpha-num:200 | M | Derive value from SendMoney validate  |
| originating_city       | alpha-num:50  | M | Derive value from SendMoney validate  |
| originating_state      | alpha-num:10  | M | Derive value from SendMoney validate  |
| financials             | array         | M | Derive value from SendMoney validate  |
| promotions             | array         | M | Derive value from SendMoney validate  |
| mtcn                   | num:10        | M | Derive value from SendMoney validate  |
| new_mtcn               | num:16        | M | Derive value from SendMoney validate  |
| mywu_enroll_tag        | alpha:10      | M | <p><b>mywu</b> = when customer has MyWU Number</p> <p><b>enroll</b> = when customer want to enroll in MyWU Program. This is another way to enroll customer into MyWU aside from stand-alone enrollment</p> <p><b>none</b>=when customer does not want to enroll to MyWU</p> |

## Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "wuso",
      "request": "SMstore",
      "param": {
        "foreign_reference_no": "123123sadasd",
        "sender_name_type": "D",
        "sender_first_name": "WINNIE",
        "sender_middle_name": "",
        "sender_last_name": "CONSTANTINO",
        "sender_addr_line1": "CALUMPIT",
        "sender_addr_line2": "",
        "sender_city": "CALUMPIT",
        "sender_state": "REGION 3",
        "sender_postal_code": "3003",

```

# PERA HUB

```
"sender_addr_country_code": "PH",
"sender_addr_currency_code": "PHP",
"sender_contact_phone": "6329446115",
"sender_mobile_country_code": "",
"sender_mobile_no": "",
"mywu_number": "185015541",
"id_type": "S",
"id_country_of_issue": "Philippines",
"id_number": "14789654",
"id_issue_date": "02072015",
"id_expiration_date": "12072017",
"date_of_birth": "06041992",
"occupation": "Programmer",
"Country_of_Birth": "Philippines",
"nationality": "Filipino",
"Gender": "F",
"Source_of_Funds": "Personal Loan",
"Sender_Employee": "Abaris",
"Relationship_to_Receiver": "Father",
"reason_for_send": "228990",
"email": "WINNIEANN.CONSTANTINO@VOXDEISYSTEMS.COM",
"receiver_name_type": "D",
"receiver_first_name": "William",
"receiver_middle_name": "",
"receiver_last_name": "Constantino",
"receiver_addr_line1": "",
"receiver_addr_line2": "",
"receiver_city": "",
"receiver_state": "",
"receiver_postal_code": "",
"receiver_addr_country_code": "PH",
"receiver_addr_currency_code": "PHP",
"receiver_contact_phone": "",
"receiver_mobile_country_code": "",
"receiver_mobile_no": "",
"destination_country_code": "PH",
"destination_currency_code": "PHP",
"destination_state_code": "",
"destination_city_name": "",
"transaction_type": "SO",
"principal_amount": 100000,
"fixed_amount_flag": "N",
"promo_code": "",
"message": [],
"bank_name": "",
"account_number": "",
"bank_code": "",
"bank_location": "",
"account_suffix": "",
"terminal_id": "WBPT",
"operator_id": "001",
"addl_service_charges":
"1103FEE12041500130415000103MSG0201003010210300022010230109001096210104500002
021003035009703NNN9806PILPIL",
"compliance_data_buffer":
"01082PH_02_S0201S0308147896540611Philippines0708060419920810Programmer090802
```

# PERA HUB

```

0720151008120720179901X3311Philippines3408Filipino3501F4413Personal
Loan6706Abaris7006Father7401Y",
    "originating_city": "METRO MANILA",
    "originating_state": "MA",
    "financials": {
        "taxes": {
            "municipal_tax": 0,
            "state_tax": 0,
            "county_tax": 0
        },
        "originators_principal_amount": 100000,
        "destination_principal_amount": 100000,
        "gross_total_amount": 101500,
        "plus_charges_amount": 0,
        "charges": 1500,
        "message_charge": 0
    },
    "promotions": {
        "promo_code_description": "T3001 Valid promotion with
discount.",
        "promo_name": "A0027 50% OFF CHARGES",
        "promo_message": "A0027 Special 50% Off Charges Intro",
        "promo_discount_amount": 250,
        "sender_promo_code": "A0027"
    },
    "mtcn": "9231430092",
    "new_mtcn": "1711689231430092",
    "mywu_enroll_tag": "mywu"
},
"signature": "anyvaluesfornow"
}
}

```

## REPONSE Parameters:

| Name               | Type         | Required | Description                                       |
|--------------------|--------------|----------|---|
| advisory_text      | alpha-num:50 | M        | Transaction Date and Time                         |
| mtcn               | num:10       | M        | Returned MTCN value                               |
| new_mtcn           | Num:16       | M        | Returned NEW MTCN value                           |
| filing_date        | text         | M        | Transaction Date                                  |
| filing_time        | text         | M        | Transaction Time                                  |
| pin_message        | text-array   | M        | Text array to be printed in Proof of Sendout Form |
| promo_text_message | text-array   | M        | Text array to be printed in Proof of Sendout Form |
| mywu_number        | alpha-num:20 | C        | With value if provided before submit              |
| new_points_earned  | num          | C        | With value if MyWU provided before submit         |
| other_message_1    | text-array   | O        | Text array to be printed in Proof of Sendout Form |
|                    |              |          | Reserved field                                    |

# PERA HUB

|                 |            |   |   |
|-----------------|------------|---|---|
| other_message_2 | text-array | O | Text array to be printed in Proof of Sendout Form<br><br>Reserved field |
|-----------------|------------|---|---|

Sample JSON Data response:

```
{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "confirmed_details": {
        "advisory_text": "04\26\17 22:31",
        "mtcn": "9231430092",
        "new_mtcn": "1711689231430092",
        "filing_date": "04-26",
        "filing_time": "1031P EDT ",
        "pin_message": ["Thank you for joining My WU
program.",
        "Watch out for exciting benefits & exclusive member
offers!",
        "Coming soon! Visit www.westernunion.com.ph for more
information."],
        "promo_text_message": ["Mahalaga sa amin ang iyong
opinyon!",
        "Pumunta sa westernunion.com\ nakikinig at ipaalam sa
amin ang iyong",
        "masasabi tungkol sa aming serbisyo.",
        "",
        "",
        ""],
        "mywu_number": "185015541",
        "new_points_earned": 10,
        "other_message_1": ["",
        "",
        ""],
        "other_message_2": ["",
        "",
        ""]
      }
    }
  }
}
```

### 3.2.3.3. SendMoney : Direct to Bank Validate

Use this function to validate transaction Direct To Bank data.

Module: **wuso**

Request: **SMvalidate**

REQUEST Parameters: (Basically the same with SendMoney validate)

# PERA HUB

Below are parameters to look out:

|                  |              |   |  |
|------------------|--------------|---|--|
| transaction_type | alpha-num:3  | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer |
| bank_name        | text:100     | C | Required when transaction type = D2B                                   |
| account_number   | num:50       | C | Required when transaction type = D2B                                   |
| bank_code        | alpha-num:20 | C | Required when transaction type = D2B                                   |
| bank_location    | alpha-num:20 | C | Required when transaction type = D2B                                   |
| account_suffix   | alpha-num:10 | C | Required when transaction type = D2B                                   |

Country Specific REQUIRED FIELDS:

US, INDIA

|                      |          |   |  |
|----------------------|----------|---|--|
| receiver_addr_line1  | text:200 | C | Required if Destination Country is US, INDIA |
| receiver_addr_line2  | text:200 | O |  |
| receiver_city        | text:50  | C | Required if Destination Country is US, INDIA |
| receiver_state       | text:100 | C | Required if Destination Country is US, INDIA |
| receiver_postal_code | num:10   |   | Required if Destination Country is US, INDIA |

CHINA, INDIA

|                 |         |   |           |
|-----------------|---------|---|-----------|
| reason_for_send | text:50 | M | of Sender |
|-----------------|---------|---|-----------|

NEW ZEALAND

|                |              |  |                                      |
|----------------|--------------|--|--------------------------------------|
| bank_location  | alpha-num:20 |  | Required when transaction type = D2B |
| account_suffix | alpha-num:10 |  | Required when transaction type = D2B |

Sample JSON Data request:

```
{
  "uspuapi": {
    "header": {
      "coy": "yundu",
      "token": "2c50721f977156fa99cbaeddcf33edcf",
      "location_code": 6,
      "user_code": 1,
      "clientip": "120.28.158.206",
      "isweb": "1"
    },
    "body": {
      "module": "wuso",
      "request": "SMvalidate",
      "param": {
        "foreign_reference_no": "398e81a36e6418062337",
        "sender_name_type": "D",

```



```
"sender_first_name": "JEEVITHA",
"sender_middle_name": "",
"sender_last_name": "RAJESH",
"sender_addr_line1": "7TH AVENUE",
"sender_addr_line2": "",
"sender_city": "EKKATUTHANGAL",
"sender_state": "",
"sender_postal_code": "600032",
"sender_addr_country_code": "PH",
"sender_addr_currency_code": "PHP",
"sender_contact_phone": "9659215933",
"sender_mobile_country_code": "",
"sender_mobile_no": "",
"mywu_number": "",
"id_type": "B",
"id_country_of_issue": "Algeria",
"id_number": "14785236987",
"id_issue_date": "09022017",
"id_expiration_date": "09022019",
"date_of_birth": "09071992",
"occupation": "CIVILSERVANT",
"Country_of_Birth": "Philippines",
"nationality": "Philippines",
"Gender": "F",
"Source_of_Funds": "GIFT",
"Sender_Employeer": "PHILIPPINESGOVT",
"Relationship_to_Receiver": "BROTHER",
"GEN_III_Indicator": "",
"ack_flag": "X",
"reason_for_send": "P102",
"mywu_enroll_tag": "enroll",
"email": "",
"receiver_name_type": "D",
"receiver_first_name": "NARENDRA",
"receiver_middle_name": "",
"receiver_last_name": "MODI",
"receiver_addr_line1": "7th floor",
"receiver_addr_line2": "",
"receiver_city": "kolkata",
"receiver_state": "UTTARAKHAND",
"receiver_postal_code": "58746",
"receiver_addr_country_code": "IN",
"receiver_addr_currency_code": "INR",
"receiver_contact_phone": "919486877788",
"receiver_mobile_country_code": "91",
"receiver_mobile_no": "9486877788",
"destination_country_code": "IN",
"destination_currency_code": "INR",
"destination_state_code": "",
"destination_city_name": "",
"transaction_type": "D2B",
"principal_amount": 14500,
"fixed_amount_flag": "N",
"promo_code": "",
"message": [],
"bank_name": "ICIC",
```

# PERA HUB

```

        "account_number": "023201513864",
        "bank_code": "ICIC0000232",
        "bank_location": "",
        "account_suffix": "",
        "terminal_id": "WBPT",
        "operator_id": "001",
        "remote_terminal_id": "",
        "remote_operator_id": ""
    },
    "signature": "anyvalues"
}

```

## REPOSE Parameters:

| Name                   | Type          | Required | Description  |
|------------------------|---------------|----------|--|
| addl_service_charges   | text:200      | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| compliance_data_buffer | alpha-num:200 | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| originating_city       | alpha-num:50  | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| originating_state      | alpha-num:10  | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| financials             | array         | M        | The whole array should be preserved as is  |
| promotions             | array         | M        | The whole array should be preserved as is<br><br>Adjustment required by WU during PI certification             |
| mtcn                   | num:10        | M        | Money Transfer Control Number<br>Must be preserve as is since this will be use as parameter in SendMoney Store |
| new_mtcn               | num:16        | M        | Money Transfer Control Number<br>Must be preserve as is since this will be use as parameter in SendMoney Store |

## Sample JSON Data response:

```

{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "service_code": {

```

# PERA HUB

```
      "addl_service_charges":
"1103FEE1205500001305500000103MSG02010030102103500220102301096210104500002021
003035009703NNN9808PILINDBD"
    },
    "compliance": {
      "compliance_data_buffer":
"01082PH_02_S0201B0311147852369870607Algeria0708090719920812CIVILSERVANT09080
90220171008090220199901X3311Philippines3411Philippines4404GIFT6715PHILIPPINES
GOVT7007BROTHER7401Y"
    },
    "payment_details": {
      "originating_city": "METRO MANILA",
      "originating_state": "MA"
    },
    },
    "financials": {
      "taxes": {
        "municipal_tax": 0,
        "state_tax": 0,
        "county_tax": 0
      },
      "originators_principal_amount": 14500,
      "destination_principal_amount": 18163,
      "gross_total_amount": 64500,
      "plus_charges_amount": 0,
      "charges": 50000,
      "message_charge": 0
    },
    },
    "promotions": {
      "promo_code_description": "",
      "promo_message": "",
      "sender_promo_code": ""
    },
    },
    "new_details": {
      "mtcn": "6631123578",
      "new_mtcn": "1717386631123578",
      "filing_date": "06-22",
      "filing_time": "0221A EDT "
    }
  }
}
}
```

### 3.2.3.4. SendMoney : Direct to Bank Store

Use this API function to save and confirm Direct To Bank Transaction.

Module: **wuso**

Request: **SMstore**

REQUEST Parameters: (Basically the same with SendMoney Store)

Below are parameters to look out:

|                  |             |   |  |
|------------------|-------------|---|--|
| transaction_type | alpha-num:3 | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer |
|------------------|-------------|---|--|

# PERA HUB

|                |              |   |                                      |
|----------------|--------------|---|--------------------------------------|
| bank_name      | text:100     | C | Required when transaction type = D2B |
| account_number | num:50       | C | Required when transaction type = D2B |
| bank_code      | alpha-num:20 | C | Required when transaction type = D2B |
| bank_location  | alpha-num:20 | C | Required when transaction type = D2B |
| account_suffix | alpha-num:10 | C | Required when transaction type = D2B |

## Country Specific REQUIRED FIELDS:

US, INDIA

|                      |          |   |  |
|----------------------|----------|---|--|
| receiver_addr_line1  | text:200 | C | Required if Destination Country is US, INDIA |
| receiver_addr_line2  | text:200 | O |  |
| receiver_city        | text:50  | C | Required if Destination Country is US, INDIA |
| receiver_state       | text:100 | C | Required if Destination Country is US, INDIA |
| receiver_postal_code | num:10   |   | Required if Destination Country is US, INDIA |

CHINA, INDIA

|                 |         |   |           |
|-----------------|---------|---|-----------|
| reason_for_send | text:50 | M | of Sender |
|-----------------|---------|---|-----------|

NEW ZEALAND

|                |              |  |                                      |
|----------------|--------------|--|--------------------------------------|
| bank_location  | alpha-num:20 |  | Required when transaction type = D2B |
| account_suffix | alpha-num:10 |  | Required when transaction type = D2B |

## Sample JSON Data request:

```
{
  "uspuapi": {
    "header": {
      "coy": "yonder",
      "token": "2c50721f977156fa99cbaeddcf33edcf",
      "location_code": 6,
      "user_code": 1,
      "clientip": "120.28.158.206",
      "isweb": "1"
    },
    "body": {
      "module": "wuso",
      "request": "SMstore",
      "param": {
        "foreign_reference_no": "398e81a36e6418062337",
        "sender_name_type": "D",
        "sender_first_name": "JEEVITHA",
        "sender_middle_name": "",
        "sender_last_name": "RAJESH",
        "sender_addr_line1": "7TH AVENUE",

```

```
"sender_addr_line2": "",
"sender_city": "EKKATUTHANGAL",
"sender_state": "",
"sender_postal_code": "600032",
"sender_addr_country_code": "PH",
"sender_addr_currency_code": "PHP",
"sender_contact_phone": "9659215933",
"sender_mobile_country_code": "",
"sender_mobile_no": "",
"mywu_number": "",
"id_type": "B",
"id_country_of_issue": "Algeria",
"id_number": "14785236987",
"id_issue_date": "09022017",
"id_expiration_date": "09022019",
"date_of_birth": "09071992",
"occupation": "CIVILSERVANT",
"Country_of_Birth": "Philippines",
"nationality": "Philippines",
"Gender": "F",
"Source_of_Funds": "GIFT",
"Sender_Employeer": "PHILIPPINESGOVT",
"Relationship_to_Receiver": "BROTHER",
"reason_for_send": "P102",
"mywu_enroll_tag": "enroll",
"email": "",
"receiver_name_type": "D",
"receiver_first_name": "NARENDRA",
"receiver_middle_name": "",
"receiver_last_name": "MODI",
"receiver_addr_line1": "7th floor",
"receiver_addr_line2": "",
"receiver_city": "kolkata",
"receiver_state": "UTTARAKHAND",
"receiver_postal_code": "58746",
"receiver_addr_country_code": "IN",
"receiver_addr_currency_code": "INR",
"receiver_contact_phone": "919486877788",
"receiver_mobile_country_code": "91",
"receiver_mobile_no": "9486877788",
"destination_country_code": "IN",
"destination_currency_code": "INR",
"destination_state_code": "",
"destination_city_name": "",
"transaction_type": "D2B",
"principal_amount": 14500,
"fixed_amount_flag": "N",
"promo_code": "",
"message": [],
"bank_name": "ICIC",
"account_number": "023201513864",
"bank_code": "ICIC0000232",
"bank_location": "",
"account_suffix": "",
"terminal_id": "WBPT",
"operator_id": "001",
```

# PERA HUB

```

        "remote_terminal_id": "",
        "remote_operator_id": "",
        "addl_service_charges":
"1103FEE1205500001305500000103MSG02010030102103500220102301096210104500002021
003035009703NNN9808PILINDBD",
        "compliance_data_buffer":
"01082PH_02_S0201B0311147852369870607Algeria0708090719920812CIVILSERVANT09080
90220171008090220199901X3311Philippines3411Philippines4404GIFT6715PHILIPPINES
GOVT7007BROTHER7401Y",
        "originating_city": "METRO MANILA",
        "originating_state": "MA",
        "financials": {
            "taxes": {
                "municipal_tax": 0,
                "state_tax": 0,
                "county_tax": 0
            },
            "originators_principal_amount": 14500,
            "destination_principal_amount": 18163,
            "gross_total_amount": 64500,
            "plus_charges_amount": 0,
            "charges": 50000,
            "message_charge": 0
        },
        "promotions": {
            "promo_code_description": "",
            "promo_message": "",
            "sender_promo_code": ""
        },
        "mtcn": "6631123578",
        "new_mtcn": "1717386631123578",
        "exchange_rate": "1.2526294"
    },
    "signature": "anyvalues"
}
}

```

## REPONSE Parameters:

| Name               | Type         | Required | Description                                       |
|--------------------|--------------|----------|---|
| advisory_text      | alpha-num:50 | M        | Transaction Date and Time                         |
| mtcn               | num:10       | M        | Returned MTCN value                               |
| new_mtcn           | Num:16       | M        | Returned NEW MTCN value                           |
| filing_date        | text         | M        | Transaction Date                                  |
| filing_time        | text         | M        | Transaction Time                                  |
| pin_message        | text-array   | M        | Text array to be printed in Proof of Sendout Form |
| promo_text_message | text-array   | M        | Text array to be printed in Proof of Sendout Form |
| mywu_number        | alpha-num:20 | C        | With value if provided before submit              |
| new_points_earned  | num          | C        | With value if MyWU provided before submit         |
| other_message_1    | text-array   | O        | Text array to be printed in Proof of Sendout Form |

# PERA HUB

|                 |            |   |   |
|-----------------|------------|---|---|
|                 |            |   | Reserved field                                    |
| other_message_2 | text-array | O | Text array to be printed in Proof of Sendout Form |
|                 |            |   | Reserved field                                    |

Sample JSON Data response:

```
{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "confirmed_details": {
        "advisory_text": "06\22\17 02:22",
        "mtcn": "6631123578",
        "new_mtcn": "1717386631123578",
        "filing_date": "06-22",
        "filing_time": "0222A EDT ",
        "pin_message": ["Thank you for joining My WU
program.",
        "Watch out for exciting benefits & exclusive member
offers!",
        "Coming soon! Visit www.westernunion.com.ph for more
information."],
        "promo_text_message": ["Mahalaga sa amin ang iyong
opinyon!",
        "Pumunta sa westernunion.com\ nakikinig at ipaalam sa
amin ang iyong",
        "masasabi tungkol sa aming serbisyo.",
        "",
        "",
        ""],
        "mywu_number": "175457673",
        "new_points_earned": 30,
        "other_message_1": ["",
        "",
        ""],
        "other_message_2": ["",
        "",
        ""]
      }
    }
  }
}
```

### 3.2.3.5. SendMoney : Cash to Mobile Validate

Use this function to validate transaction Cash to Mobile/Mobile Money Transfer data.

Module: **wuso**

Request: **SMvalidate**

REQUEST Parameters: (Basically the same with SendMoney validate)

Below are parameters to look out:

|                              |             |   |   |
|------------------------------|-------------|---|---|
| transaction_type             | alpha-num:3 | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer  |
| sender_mobile_country_code   | num:3       | O | Mobile Country Code   |
| sender_mobile_no             | num:20      | O | Mobile Number   |
| receiver_mobile_country_code | num:3       | C | Required if transactions type is MMT<br><br>Required if Destination Country is CHINA, INDIA, NIGERIA, USA and transaction type is D2B |
| receiver_mobile_no           | num:20      | C | Required if transactions type is MMT<br><br>Required if Destination Country is CHINA, INDIA, NIGERIA, USA and transaction type is D2B |

### 3.2.3.6. SendMoney : Cash to Mobile Store

Use this API function to save and confirm Cash to Mobile/Mobile Money Transfer Transaction.

Module: **wuso**

Request: **SMstore**

REQUEST Parameters: (Basically the same with SendMoney Store)

Below are parameters to look out:

|                              |             |   |   |
|------------------------------|-------------|---|---|
| transaction_type             | alpha-num:3 | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer  |
| sender_mobile_country_code   | num:3       | O | Mobile Country Code   |
| sender_mobile_no             | num:20      | O | Mobile Number   |
| receiver_mobile_country_code | num:3       | C | Required if transactions type is MMT<br><br>Required if Destination Country is CHINA, INDIA, NIGERIA, USA and transaction type is D2B |
| receiver_mobile_no           | num:20      | C | Required if transactions type is MMT<br><br>Required if Destination Country is CHINA, INDIA, NIGERIA,                                 |



|  |  |  |                                 |
|--|--|--|---------------------------------|
|  |  |  | USA and transaction type is D2B |
|--|--|--|---------------------------------|

## 3.2.4. QuickPay

### 3.2.4.1. QuickPay Validate

Use this function to validate transaction Quick Pay data

Module: **wuqp**

Request: **QPvalidate**

REQUEST Parameters:

| Name                       | Type         | Required | Description   |
|----------------------------|--------------|----------|---|
| foreign_reference_no       | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value)   |
| sender_name_type           | alpha:1      | M        | D = Firstname/LastName<br>M = Paternal/Maternal (WU Advised to use option D in case customer or teller encountered this name type)  |
| sender_first_name          | alpha:100    | M        | First Name  |
| sender_middle_name         | alpha:100    | M        |   |
| sender_last_name           | text:200     | M        | Last Name   |
| sender_addr_line1          | text:200     | M        |   |
| sender_addr_line2          | text:200     | O        |   |
| sender_city                | text:50      | M        | City / Municipality   |
| sender_state               | text:100     | M        | State / Province / Region   |
| sender_postal_code         | num:10       | M        |   |
| sender_addr_country_code   | alpha:2      | M        | 2 letter ISO country code   |
| sender_addr_currency_code  | alpha:3      | M        | 3 letter ISO currency code  |
| sender_contact_phone       | num:30       | O        | Format should be Mobile Country Code + phone number   |
| sender_mobile_country_code | num:3        | O        | Mobile Country Code   |
| sender_mobile_no           | num:20       | O        | Mobile Number   |
| mywu_number                | num:20       | O        | MyWU number   |
| mywu_enroll_tag            | alpha:10     | M        | mywu = when customer has MyWU Number<br><br>enroll = when customer want to enroll in MyWU Program. This is another way to enroll customer into MyWU aside from stand-alone enrollment<br><br>none=when customer does not want to enroll to MyWU |
| id_type                    | text:20      | M        | Refer to IDTypeList   |
| id_country_of_issue        | text:100     | M        | of Sender   |
| id_number                  | text:50      | M        | of Sender   |

# PERA HUB

|                           |                   |   |   |
|---------------------------|-------------------|---|---|
| id_issue_date             | date:<br>ddmmyyyy | M | of Sender   |
| id_expiration_date        | date:<br>ddmmyyyy | C | of Sender (required depends on ID Type)   |
| date_of_birth             | date:<br>ddmmyyyy | M | of Sender   |
| occupation                | text:100          | M | of Sender   |
| Country_of_Birth          | text:100          | M | of Sender   |
| nationality               | text:100          | M | of Sender   |
| Gender                    | text:1            | M | of Sender   |
| Source_of_Funds           | text:50           | M | of Sender   |
| Sender_Employeer          | text:50           | M | of Sender   |
| Relationship_to_Receiver  | text:50           | M | of Sender   |
| reason_for_send           | text:50           | M | of Sender   |
| GEN_III_Indicator         | num:1             | M | Value should be "1" if compliance lookup is successful<br><br>Otherwise BLANK or NULL<br><br>Adjustment required by WU during PI certification                  |
| ack_flag                  | alpha:1           | M | Acknowledgement Flag that users has entered correct values, Required by WU<br><br>Value to pass is "X"<br><br>Adjustment required by WU during PI certification |
| email                     | email             | O | of Sender   |
| company_name              | alpha:100         | M | Company Name/Recipient of Money Transfer. Please Refer to Company List JSON Data provided   |
| company_code              | alpha:100         | M | Company Code/Recipient of Money Transfer. Please Refer to Company List JSON Data provided   |
| company_account_code      | alpha:100         | M | Company Account Code/Recipient of Money Transfer. Please Refer to Company List JSON Data provided   |
| reference_no              | text:100          | M | Reference Number from the customer  |
| destination_country_code  | alpha:2           | M | 2 letter ISO country code   |
| destination_currency_code | alpha:3           | M | 3 letter ISO currency code  |
| transaction_type          | alpha-num:3       | M | QP = QuickPay   |
| principal_amount          | num               | M | Amount to Send  |
| fixed_amount_flag         | alpha:1           | M | <b>F</b> if customer wants a fixed principal amount in the destination country and will not   |

# PERA HUB

|             |              |   |  |
|-------------|--------------|---|--|
|             |              |   | be subject to currency fluctuation. Otherwise <b>N</b>   |
| promo_code  | alpha-num:20 | O | Promo code   |
| message     | text:array   | O | Optional Message from SENDER to RECEIVER<br>Maximum Length per line is 79 characters<br>Maximum array length is 14 |
| operator_id | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user  |
| terminal_id | alpha-num:10 | M | Terminal ID will be provided by Petnet per partner location  |

## Sample JSON Data request:

```
{
  "uspuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "wuso",
      "request": "SMvalidate",
      "param": {
        "foreign_reference_no": "sample-0001",
        "sender_name_type": "D",
        "sender_first_name": "WINNIE",
        "sender_middle_name": "",
        "sender_last_name": "CONSTANTINO",
        "sender_addr_line1": "CALUMPIT",
        "sender_addr_line2": "BLANK IF NOT USED",
        "sender_city": "CALUMPIT",
        "sender_state": "REGION 3",
        "sender_postal_code": "3003",
        "sender_addr_country_code": "PH",
        "sender_addr_currency_code": "PHP",
        "sender_addr_country_name": "PHILIPPINES",
        "sender_contact_phone": "6329446115",
        "sender_mobile_country_code": "63",
        "sender_mobile_no": "9175337900",
        "mywu_number": "185015541",
        "id_type": "B",
        "id_country_of_issue": "PHILIPPINES",
        "id_number": "1234567890",
        "id_issue_date": "01122015",
        "id_expiration_date": "01122018",
        "date_of_birth": "01121996",
        "occupation": "Employee",
        "Country_of_Birth": "PHILIPPINES",
        "nationality": "FILIPINO",
        "Gender": "F",
```

# PERA HUB

```

        "Source_of_Funds": "Employment",
        "Sender_Employeer": "Vox Dei",
        "Relationship_to_Receiver": "Client",
        "reason_for_send": "228990",
        "GEN_III_Indicator": "",
        "ack_flag": "X",
        "email": "WINNIEANN.CONSTANTINO@VOXDEISYSTEMS.COM",
        "company_name": "TESTING ONLY",
        "company_code": "1A IA",
        "company_account_code": "123123123123",
        "reference_no": "123123123",
        "destination_country_code": "US",
        "destination_currency_code": "USD",
        "transaction_type": "QP",
        "principal_amount": "150000",
        "fixed_amount_flag": "F",
        "promo_code": "",
        "terminal_id": "WBPt",
        "operator_id": "001",
        "remote_terminal_id": "",
        "remote_operator_id": ""
    },
    "signature": "anyvaluesfornow"
}

```

## REPOSE Parameters:

| Name                   | Type          | Required | Description  |
|------------------------|---------------|----------|--|
| addl_service_charges   | text:200      | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| compliance_data_buffer | alpha-num:200 | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| originating_city       | alpha-num:50  | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| originating_state      | alpha-num:10  | M        | Must be preserve as is since this will be use as parameter in SendMoney Store                                  |
| financials             | array         | M        | The whole array should be preserved as is  |
| promotions             | array         | M        | The whole array should be preserved as is<br><br>Adjustment required by WU during PI certification             |
| mtcn                   | num:10        | M        | Money Transfer Control Number<br>Must be preserve as is since this will be use as parameter in SendMoney Store |
| new_mtcn               | num:16        | M        | Money Transfer Control Number<br>Must be preserve as is since this will be use as parameter in SendMoney Store |

# PERA HUB

## Sample JSON Data response:

```
{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "service_code": {
        "addl_service_charges":
"1103FEE1205375001305375000103MSG02010030109001096150101002010030109703NNN980
7PILQQCU",

        "addl_service_block": {
          "addl_service_length": 377,
          "addl_service_data_buffer": ""
        }
      },
      "compliance": {
        "compliance_flags_buffer": "",
        "compliance_data_buffer":
"01082PH_02_S0201S0308147896540611Philippines0708120419910810Programmer090802
0720151008120720179901X3311Philippines3408Filipino3501F4413Personal
Loan6706Abaris7006Friend7401YB4014"
      },
      "payment_details": {
        "originating_city": "METRO MANILA",
        "originating_state": "MA"
      },
      "financials": {
        "taxes": {
          "municipal_tax": 0,
          "state_tax": 0,
          "county_tax": 0
        },
        "originators_principal_amount": 30000,
        "destination_principal_amount": 585,
        "gross_total_amount": 67500,
        "plus_charges_amount": 0,
        "charges": 37500
      },
      "promotions": {
        "promo_code_description": "T3001 Valid promotion with
discount.",
        "promo_name": "A0027 50% OFF CHARGES",
        "promo_message": "A0027 Special 50% Off Charges Intro",
        "promo_discount_amount": 250,
        "sender_promo_code": "A0027"
      },
      "new_details": {
        "mtcn": "1671430550",
        "new_mtcn": "1711681671430550",
        "filing_date": "04-26",
        "filing_time": "1111P EDT"
      }
    }
  }
}
```

## 3.2.4.2. QuickPay Store



Use this API to store confirmed data for Quick Pay Transaction type.

Module: **wuqp**

Request: **QPstore**

REQUEST Parameters:

| Name                       | Type              | Required | Description  |
|----------------------------|-------------------|----------|--|
| foreign_reference_no       | alpha-num:50      | M        | This will be provided upon Sign-on (for the meantime, please use any value)  |
| sender_name_type           | alpha:1           | M        | D = Firstname/LastName<br>M = Paternal/Maternal (WU)<br>Advised to use option D in case customer or teller encountered this name type) |
| sender_first_name          | alpha:100         | M        | First Name   |
| sender_middle_name         | alpha:100         | M        |  |
| sender_last_name           | text:200          | M        | Last Name  |
| sender_addr_line1          | text:200          | M        |  |
| sender_addr_line2          | text:200          | O        |  |
| sender_city                | text:50           | M        | City / Municipality  |
| sender_state               | text:100          | M        | State / Province / Region  |
| sender_postal_code         | num:10            | M        |  |
| sender_addr_country_code   | alpha:2           | M        | 2 letter ISO country code  |
| sender_addr_currency_code  | alpha:3           | M        | 3 letter ISO currency code   |
| sender_contact_phone       | num:30            | O        | Format should be Mobile Country Code + phone number  |
| sender_mobile_country_code | num:3             | O        | Mobile Country Code  |
| sender_mobile_no           | num:20            | O        | Mobile Number  |
| mywu_number                | num:20            | O        | MyWU number  |
| id_type                    | text:20           | M        | Refer to IDTypeList  |
| id_country_of_issue        | text:100          | M        | of Sender  |
| id_number                  | text:50           | M        | of Sender  |
| id_issue_date              | date:<br>ddmmyyyy | M        | of Sender  |
| id_expiration_date         | date:<br>ddmmyyyy | C        | of Sender (required depends on ID Type)  |
| date_of_birth              | date:<br>ddmmyyyy | M        | of Sender  |
| occupation                 | text:100          | M        | of Sender  |
| Country_of_Birth           | text:100          | M        | of Sender  |
| nationality                | text:100          | M        | of Sender  |
| Gender                     | text:1            | M        | of Sender  |
| Source_of_Funds            | text:50           | M        | of Sender  |
| Sender_Employeer           | text:50           | M        | of Sender  |

# PERA HUB

|                           |              |   |  |
|---------------------------|--------------|---|--|
| Relationship_to_Receiver  | text:50      | M | of Sender  |
| reason_for_send           | text:50      | M | of Sender  |
| email                     | email        | O | of Sender  |
| company_name              | alpha:100    | M | Company Name/Recipient of Money Transfer. Please Refer to Company List JSON Data provided  |
| company_code              | alpha:100    | M | Company Code/Recipient of Money Transfer. Please Refer to Company List JSON Data provided  |
| company_account_code      | alpha:100    | M | Company Account Code/Recipient of Money Transfer. Please Refer to Company List JSON Data provided  |
| reference_no              | text:100     | M | Reference Number from the customer   |
| destination_country_code  | alpha:2      | M | 2 letter ISO country code  |
| destination_currency_code | alpha:3      | M | 3 letter ISO currency code   |
| destination_state_code    | alpha-num:20 | C | Required if Destination Country is USA and Mexico  |
| destination_city_name     | text:50      | C | Required if Destination Country is USA and Mexico  |
| transaction_type          | alpha-num:3  | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer   |
| principal_amount          | num          | M | Amount to Send   |
| fixed_amount_flag         | alpha:1      | M | <b>F</b> if customer wants a fixed principal amount in the destination country and will not be subject to currency fluctuation. Otherwise <b>N</b> |
| exchange_rate             | num          | M | Currency exchange rate of PHP vs Currency of destination country   |
| promo_code                | alpha-num:20 | O | Promo code   |
| message                   | text:array   | O | Optional Message from SENDER to RECEIVER<br>Maximum Length per line is 79 characters<br>Maximum array length is 14                                 |
| bank_name                 | text:100     | C | Required when transaction type = D2B   |
| account_number            | num:50       | C | Required when transaction type = D2B   |
| bank_code                 | alpha-num:20 | C | Required when transaction type = D2B   |
| bank_location             | alpha-num:20 | C | Required when transaction type = D2B   |
| account_suffix            | alpha-num:10 | C | Required when transaction type = D2B   |
| operator_id               | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user  |

# PERA HUB

|                        |               |   |   |
|------------------------|---------------|---|---|
| terminal_id            | alpha-num:10  | M | Terminal ID will be provided by Petnet per partner location   |
| addl_service_charges   | text:200      | M | Derive value from SendMoney validate  |
| compliance_data_buffer | alpha-num:200 | M | Derive value from SendMoney validate  |
| originating_city       | alpha-num:50  | M | Derive value from SendMoney validate  |
| originating_state      | alpha-num:10  | M | Derive value from SendMoney validate  |
| financials             | array         | M | Derive value from SendMoney validate  |
| promotions             | array         | M | The whole array should be preserved as is<br><br>Adjustment required by WU during PI certification  |
| mtcn                   | num:10        | M | Derive value from SendMoney validate  |
| new_mtcn               | num:16        | M | Derive value from SendMoney validate  |
| mywu_enroll_tag        | alpha:10      | M | mywu = when customer has MyWU Number<br><br>enroll = when customer want to enroll in MyWU Program. This is another way to enroll customer into MyWU aside from stand-alone enrollment<br><br>none=when customer does not want to enroll to MyWU |

## Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "wuqp",
      "request": "QPstore",
      "param": {
        "foreign_reference_no": "123123sadasd",
        "sender_name_type": "D",
        "sender_first_name": "WINNIE",
        "sender_middle_name": "",
        "sender_last_name": "CONSTANTINO",
        "sender_addr_line1": "CALUMPIT",
        "sender_addr_line2": "",
        "sender_city": "CALUMPIT",

```



# PERA HUB

```
"sender_state": "REGION 3",
"sender_postal_code": "3003",
"sender_addr_country_code": "PH",
"sender_addr_currency_code": "PHP",
"sender_addr_country_name": "Philippines",
"sender_contact_phone": "6329446115",
"sender_mobile_country_code": "",
"sender_mobile_no": "",
"mywu_number": "185015541",
"id_type": "S",
"id_country_of_issue": "Philippines",
"id_number": "14789654",
"id_issue_date": "02072015",
"id_expiration_date": "12072017",
"date_of_birth": "12041991",
"occupation": "Programmer",
"Country_of_Birth": "Philippines",
"nationality": "Filipino",
"Gender": "F",
"Source_of_Funds": "Personal Loan",
"Sender_Employeer": "Abaris",
"Relationship_to_Receiver": "Friend",
"reason_for_send": "Purchase of Real Estate",
"email": "WINNIEANN.CONSTANTINO@VOXDEISYSTEMS.COM",
"company_name": "TESTING ONLY",
"company_code": "1A IA",
"company_account_code": "123123123123",
"reference_no": "123123123",
"destination_country_code": "US",
"destination_currency_code": "USD",
"destination_state_code": "",
"destination_city_name": "",
"transaction_type": "QP",
"principal_amount": 30000,
"fixed_amount_flag": "N",
"promo_code": "",
"message": [],
"terminal_id": "WBPt",
"operator_id": "001",
"remote_terminal_id": "",
"remote_operator_id": "",
"addl_service_charges":
"1103FEE1205375001305375000103MSG02010030109001096150101002010030109703NNN980
7PILQQCU",
"compliance_data_buffer":
"01082PH_02_S0201S0308147896540611Philippines0708120419910810Programmer090802
0720151008120720179901X3311Philippines3408Filipino3501F4413Personal
Loan6706Abaris7006Friend7401YB4014",
"originating_city": "METRO MANILA",
"originating_state": "MA",
"financials": {
    "taxes": {
        "municipal_tax": 0,
        "state_tax": 0,
        "county_tax": 0
    },

```

# PERA HUB

```

        "originators_principal_amount": 30000,
        "destination_principal_amount": 585,
        "gross_total_amount": 67500,
        "plus_charges_amount": 0,
        "charges": 37500,
        "message_charge": 0
    },
    "promotions": {
        "promo_code_description": "T3001 Valid
promotion with discount.",
        "promo_name": "A0027 50% OFF CHARGES",
        "promo_message": "A0027 Special 50% Off
Charges Intro",
        "promo_discount_amount": 250,
        "sender_promo_code": "A0027"
    },
    "mtcn": "1671430550",
    "new_mtcn": "1711681671430550",
    "mywu_enroll_tag": "mywu"
},
"signature": "anyvaluefornow"
}
}

```

## REPONSE Parameters:

| Name               | Type         | Required | Description   |
|--------------------|--------------|----------|---|
| advisory_text      | alpha-num:50 | M        | Transaction Date and Time   |
| mtcn               | num:10       | M        | Returned MTCN value   |
| new_mtcn           | Num:16       | M        | Returned NEW MTCN value   |
| filing_date        | text         | M        | Transaction Date  |
| filing_time        | text         | M        | Transaction Time  |
| pin_message        | text-array   | M        | Text array to be printed in Proof of Sendout Form                   |
| promo_text_message | text-array   | M        | Text array to be printed in Proof of Sendout Form                   |
| mywu_number        | alpha-num:20 | C        | With value if provided before submit                                |
| new_points_earned  | num          | C        | With value if MyWU provided before submit                           |
| other_message_1    | text-array   | O        | Text array to be printed in Proof of Sendout Form<br>Reserved field |
| other_message_2    | text-array   | O        | Text array to be printed in Proof of Sendout Form<br>Reserved field |

## Sample JSON Data response:

```

{
    "uspuapi": {
        "header": {
            "errorcode": "1",

```

# PERA HUB

```
    "message": "good"
  },
  "body": {
    "confirmed_details": {
      "advisory_text": "04\26\17 23:11",
      "mtcn": "1671430550",
      "new_mtcn": "1711681671430550",
      "filing_date": "04-26",
      "filing_time": "1111P EDT",
      "pin_message": ["Thank you for joining My WU program.",
        "Watch out for exciting benefits & exclusive member offers!", "Coming soon!
        Visit www.westernunion.com.ph for more information."],
      "promo_text_message": ["", "", "", "", "", ""],
      "mywu_number": "185015541",
      "new_points_earned": 30,
      "other_message_1": "",
      "other_message_2": ""
    }
  }
}
```

## 3.2.5. ReceiveMoney

### 3.2.5.1. ReceiveMoney Search

Use this API to search Money Transfer available and waiting to be paid to the intended customer.

Module: **wupo**

Request: **search**

REQUEST Parameters:

| Name                  | Type         | Required | Description   |
|-----------------------|--------------|----------|---|
| foreign_reference_no  | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value)       |
| mtcn                  | num:10       | M        | Money Transfer Control Number   |
| pd_dest_currency_code | alpha:3      | M        | 3 letter ISO currency code,<br>Currency Option by Customer (Payout in PHP or USD) |
| operator_id           | alpha-num:10 | M        | Operator ID will be provided Petnet per partner teller/user                       |
| terminal_id           | alpha-num:10 | M        | Terminal ID will be provided by Petnet per partner location                       |

Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "1",
      "user_code": "1",

```

# PERA HUB

```

        "clientip": ":::1",
        "isweb": "1"
    },
    "body": {
        "module": "wupo",
        "request": "search",
        "param": {
            "foreign_reference_no": "LBCSAMPLE0001",
            "mtcn": "6980850750",
            "pd_dest_currency_code": "USD",
            "operator_id": "001",
            "terminal_id": "WBPt"
        }
    },
    "signature": "anyvaluesfornow"
}

```

## REPONSE Parameters:

| Name   | Type     | Required | Description  |
|--|----------|----------|--|
| payment_transaction                            | array    | M        | Array containing all details of money transfer to be paid.   |
| sender   | array    | M        | Sub-array of under payment transaction containing details pertaining to <b>sender</b> of money transfer                      |
| receiver                                       | array    |          | Sub-array of under payment transaction containing details pertaining to <b>recipient</b> of money transfer                   |
| financials                                     | array    | M        | Sub-array of under payment transaction containing details pertaining to breakdown of amount                                  |
| payment_details                                | array    | M        | Sub-array of under payment transaction containing details pertaining to ORIGIN and DESTINATION information of money transfer |
| payment_transaction:<br>pay_status_description | alpha:10 | M        | <b>W/C</b> = will call or available and can be paid<br><br>PAID = already paid<br>HOLD = if on hold                          |
| gross_payout                                   | num      | M        | Gross Amount to be paid to customer.<br><br>Equal to Net Payout if money transfer origination within Philippines             |
| dst  | num      | M        | Documentary Stamp Tax, for Philippines.<br><br>to be deducted from Gross Amount  |

# PERA HUB

|            |     |   |  |
|------------|-----|---|--|
|            |     |   | Normally have value when money transfer originated from outside Philippines. |
| net_payout | num | M | Net Amount to be paid to customer  |

Sample JSON Data response:

```
{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "payment_transaction": {
        "sender": {
          "name": {
            "name_type": "D",
            "first_name": "WILLIAM",
            "last_name": "CONSTANTINO"
          },
          "address": {
            "city": "CALUMPIT",
            "state": "BULACAN",
            "country_code": {
              "iso_code": {
                "country_code": "PH",
                "currency_code": "PHP"
              }
            },
            "state_zip": "3003",
            "street": "PUNGO"
          },
          "contact_phone": "639479976352",
          "mobile_phone": {
            "phone_number": []
          },
          "mobile_details": []
        },
        "receiver": {
          "name": {
            "name_type": "D",
            "first_name": "WINNIE",
            "last_name": "CONSTANTINO"
          },
          "address": {
            "country_code": {
              "iso_code": {
                "country_code": "PH",
                "currency_code": "PHP"
              }
            }
          },
          "preferred_customer": {
            "mywu_number": ""
          }
        }
      }
    }
  }
}
```

```

        "mobile_phone": {
            "phone_number": []
        },
        "mobile_details": []
    },
    "financials": {
        "taxes": {
            "tax_worksheet": ""
        },
        "gross_total_amount": 50500,
        "pay_amount": 50000,
        "principal_amount": 50000,
        "charges": 500,
        "tolls": 0
    },
    "payment_details": {
        "expected_payout_location": {
            "state_code": "",
            "city": ""
        },
        "destination_country_currency": {
            "iso_code": {
                "country_code": "PH",
                "currency_code": "PHP"
            }
        },
        "originating_country_currency": {
            "iso_code": {
                "country_code": "PH",
                "currency_code": "PHP"
            }
        },
        "originating_city": "METRO MANILAPI1",
        "transaction_type": "WMF",
        "exchange_rate": 1,
        "original_destination_country_currency": {
            "iso_code": {
                "country_code": "PH",
                "currency_code": "PHP"
            }
        }
    },
    "filing_date": "04-25-17 ",
    "filing_time": "0244A EDT",
    "money_transfer_key": "3623964162",
    "pay_status_description": "W\C",
    "mtcn": "6980850750",
    "new_mtcn": "1711586980850750",
    "fusion": {
        "fusion_status": "W\C",
        "account_number": ""
    },
    "wu_network_agent_indicator": ""
},
"gross_payout": 50000,
"dst": 0,

```

```

        "net_payout": 50000
    }
}
}

```

### 3.2.5.2. ReceiveMoney Pay

Use this API to confirm payout of money transfer.

Module: **wupo**

Request: **pay**

REQUEST Parameters:

| Name                   | Type         | Required | Description   |
|------------------------|--------------|----------|---|
| foreign_reference_no   | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value) |
| receiver_name_type     | alpha:1      | M        | Should be marked "D" in most cases  |
| receiver_first_name    | alpha:100    | M        | First Name  |
| receiver_last_name     | alpha:100    | M        | Last Name   |
| sender_first_name      | alpha:100    | M        | First Name  |
| sender_last_name       | alpha:100    | M        | Last Name   |
| receiver_city          | text:50      | M        | City / Municipality   |
| receiver_state         | text:100     | M        | State / Province / Region   |
| receiver_country_code  | alpha:2      | M        | 2 letter ISO country code   |
| receiver_currency_code | alpha:3      | M        | 3 letter ISO currency code  |
| receiver_state_zip     | email        | O        | Valid email format  |
| receiver_street        |              |          |   |
| id_type                | text:20      | M        | Refer to IDTypeList   |
| id_country_of_issue    | text:100     | M        | of Recipient  |
| id_number              | text:50      | M        | of Recipient  |
| id_issue_date          | date:ddmmyyy | M        | of Recipient  |
| id_expiration_date     | date:ddmmyyy | C        | of Recipient (required depends on ID Type)                                  |
| date_of_birth          | date:ddmmyyy | M        | of Recipient  |
| occupation             | text:100     | M        | of Recipient  |
| addr_line1             | text:200     | M        | of Recipient  |
| curr_city              | text:50      | M        | City / Municipality of Recipient  |
| curr_state_name        | text:100     | M        | State / Province / Region of Recipient                                      |
| postal_code            | num:10       | M        | of Recipient  |

# PERA HUB

|  |            |   |  |
|--|------------|---|--|
| country                                    |            |   | of Recipient   |
| contact_phone                              | num:30     | O | Format should be Mobile Country Code + phone number                              |
| Country_of_Birth                           | alpha:2    | M | 2 letter ISO country code  |
| nationality                                | text:100   | M | of Recipient   |
| Source_of_Funds                            | text:100   | M | of Recipient   |
| Name_of_Employer_Business                  | text:100   | M | of Recipient   |
| Relationship_to_Receiver_Sender            | text:100   | M | of Recipient   |
| Does_the_ID_have_an_expiration_date        | alpha:1    | M | Should be marked "Y" if ID provided by customer has expiration, otherwise "N"    |
| Does_receiver_have_a_phone_number          | alpha:1    | M | Should be marked "Y" if ID provided by have phone number provided, otherwise "N" |
| ack_flag                                   | alpha:1    | M | Marked as "X"  |
| GEN_III_Indicator                          | alpha:1    | M | Marked as "1"  |
| pd_state_code                              | text       | M | from search response payment_details > expected_payout_location                  |
| pd_city                                    | text       | M | from search response payment_details > expected_payout_location                  |
| pd_dest_country_code                       | alpha:2    | M | from search response payment_details > destination_country                       |
| pd_dest_currency_code                      | alpha:3    | M | from search response payment_details > destination_country                       |
| pd_orig_country_code                       | alpha:2    | M | from search response payment_details > originating_country                       |
| pd_orig_currency_code                      | alpha:3    | M | from search response payment_details > originating_country                       |
| pd_originating_city                        | text       | M | from search response payment_details > expected_payout_location                  |
| pd_transaction_type                        | alphanum:5 | M | from search response payment_details > transaction_type                          |
| pd_exchange_rate                           | num        | M | from search response payment_details > exchange_rate                             |
| pd_orig_dest_country_currency_country_code | alpha:2    | M | from search response payment_details > original_destination                      |
| pd_orig_dest_country_currency_currency_    | alpha:3    | M | from search response   |



# PERA HUB

|                             |              |   |  |
|-----------------------------|--------------|---|--|
| code                        |              |   | payment_details > original_destination                                       |
| gross_total_amount          | num          | M | Gross Amount details on country of origin                                    |
| pay_amount                  | num          | M | Principal Amount details on destination country                              |
| principal_amount            | num          | M | Principal Amount details on country of origin                                |
| charges                     | num          | M | Charges/ Fees details on country of origin                                   |
| tolls                       | num          | M | Toll Fees on country of origin   |
| money_transfer_key          | num:10       | M | 10 digit Money Transfer control key,<br><br>From search response parameters  |
| new_mtcn                    | num:16       | M | 16 digit Money Transfer Control Number                                       |
| mtcn                        | num:10       | M | 10 digit Money Transfer Control Number                                       |
| pay_or_do_not_pay_indicator | alpha:1      | M | Should be Marked "P"   |
| rec_mob_country_code        | num:3        | O | Mobile Country Code  |
| national_number             | num:20       | O | Mobile Number  |
| telephone_city_code         | num:3        | O | Mobile Country Code  |
| filing_time                 | text         | M | from search response   |
| filing_date                 | text         | M | from search response   |
| message                     | array        | O | from search response   |
| client_reference_no         | text         | M | Reference Number of Partner's System<br><br>Should be unique                 |
| real_principal_amount       | num          | M | Gross Principal Amount in destination country                                |
| dst_amount                  | num          | M | DST amount   |
| real_net_amount             | num          | M | NET Amount to release to recipient   |
| user_code                   |              |   | user code of user/teller from partner's system                               |
| customer_code               | alphnum:20   | O | Customer code to be provided if mobile customer<br><br>Otherwise leave blank |
| operator_id                 | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user                  |
| terminal_id                 | alpha-num:10 | M | Terminal ID will be provided by Petnet per partner location                  |
| remote_terminal_id          | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user                  |

# PERA HUB

|                    |              |   |  |
|--------------------|--------------|---|--|
|                    |              |   | Equal to Terminal ID   |
| remote_operator_id | alpha-num:10 | M | Terminal ID will be provided by Petnet per partner location        |
|                    |              |   | Equal to Terminal ID   |
| mywu_number        | num:20       | O | MyWU Number of the customer if customer is existing MyWU Customer. |
|                    |              |   | Otherwise leave blank  |

Sample JSON Data request:

```
{
  "uspuapi" : {
    "header" : {
      "coy" : "usp",
      "token" : "0dc1aac91226345d7fecbc08cf47f39",
      "location_code" : "8",
      "user_code" : "4",
      "clientip" : "127.0.0.1",
      "isweb" : "1"
    },
    "body" : {
      "module" : "wupo",
      "request" : "pay",
      "param" : {
        "foreign_reference_no" : "12121212547",
        "receiver_name_type" : "D",
        "receiver_first_name" : "JERICA",
        "receiver_last_name" : "NAPARATE",
        "sender_first_name" : "WINNIE",
        "sender_last_name" : "CONSTANTINO",
        "receiver_city" : "CALOOCAN CITY",
        "receiver_state" : "MANILA",
        "receiver_country_code" : "PH",
        "receiver_currency_code" : "PHP",
        "receiver_state_zip" : "1420",
        "receiver_street" : "",
        "id_type" : "A",
        "id_country_of_issue" : "Philippines",
        "id_number" : "0987654321",
        "id_issue_date" : "01122012",
        "id_expiration_date" : "01122017",
        "date_of_birth" : "10081996",
        "occupation" : "Programmer",
        "addr_line1" : "1953 Ph 3b Block 6 Lot 9 Camarin",
        "curr_city" : "CALOOCAN CITY",
        "curr_state_name" : "MANILA",
        "postal_code" : "1420",
        "country" : "PH",
        "contact_phone" : "9089488895",
        "Country_of_Birth" : "Philippines",
        "nationality" : "Filipino",

```

# PERA HUB

```
"Source_of_Funds" : "Medical Expenses",
"Name_of_Employer_Business" : "Abaris Technologies",
"Relationship_to_Receiver_Sender" : "Spouse",
"Does_the_ID_have_an_expiration_date" : "Y",
"Does_receiver_have_a_phone_number" : "N",
"ack_flag" : "X",
"GEN_III_Indicator" : "1",
"pd_state_code" : "",
"pd_city" : "",
"pd_dest_country_code" : "PH",
"pd_dest_currency_code" : "PHP",
"pd_orig_country_code" : "PH",
"pd_orig_currency_code" : "PHP",
"pd_originating_city" : "METRO MANILAPI1",
"pd_transaction_type" : "WMF",
"pd_exchange_rate" : "1",
"pd_orig_dest_country_currency_country_code" : "PH",
"pd_orig_dest_country_currency_currency_code" :
"PHP",

"gross_total_amount" : "6500",
"pay_amount" : "1000",
"principal_amount" : "1000",
"charges" : "500",
"tolls" : "5000",
"money_transfer_key" : "3623993857",
"new_mtcn" : "1712884940856864",
"mtcn" : "4940856864",
"pay_or_do_not_pay_indicator" : "P",
"rec_mob_country_code" : "63",
"national_number" : "9089488895",
"telephone_city_code" : "",
"filing_time" : "0719A EDT",
"filing_date" : "05-08-17 ",
"message" : {
    "message_details" : "Sample message here
"

    },
"client_reference_no" : "WBPt201705110001",
"real_principal_amount" : "10",
"dst_amount" : "0",
"real_net_amount" : "10",
"user_code" : "000003",
"customer_code" : "HOIFLGNNWR",
"terminal_id" : "WBPt",
"operator_id" : "001",
"remote_terminal_id" : "",
"remote_operator_id" : "",
"mywu_number" : "181595968"
    }
},
"signature" : ""
}
}
```

## REPONSE Parameters:

| Name              | Type  | Required | Description                       |
|-------------------|-------|----------|-----------------------------------|
| confirmed_details | array | M        | Array containing the reply if pay |

|                   |          |   |  |
|-------------------|----------|---|--|
|                   |          |   | was successful.  |
| advisory_text     | text     | O | Reserved field for other information regarding money transfer            |
| new_points_earned | num      | M | Points earned by MyWUNumber if provided on submit of pay request.        |
| paid_date_time    | datetime | M | Timestamp of actual date and time money transfer was paid in the system. |
| host_message_set1 | text     | O | Reserved field1 for other messages from WU.                              |
| host_message_set2 | text     | O | Reserved field2 for other messages from WU.                              |
| host_message_set3 | text     | O | Reserved field3 for other messages from WU.                              |

Sample JSON Data response:

```
{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": {
        "confirmed_details": {
          "advisory_text": "",
          "new_points_earned": 10,
          "paid_date_time": "04-26-2017 05:33",
          "host_message_set1": "",
          "host_message_set2": "Thank you for joining My
WU program. Watch out for exciting benefits & exclusive member offers!Coming
soon! Visit www.westernunion.com.ph for more information.",
          "host_message_set3": ""
        }
      }
    },
    "body": null
  }
}
```

## 3.2.6. Stage and Pay

### 3.2.6.1. Stage SendMoney

#### 3.2.6.1.1. SendMoney Stage Validate

Use this function to validate transaction Send Money data to be HOLD

Module: **wusostg**

Request: **SMSvalidate**

REQUEST Parameters:

| Name                 | Type         | Required | Description   |
|----------------------|--------------|----------|---|
| foreign_reference_no | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value) |

# PERA HUB

|                             |                   |   |   |
|-----------------------------|-------------------|---|---|
|                             |                   |   |   |
| sender_first_name           | alpha:100         | M | First Name  |
| sender_middle_name          | alpha:100         | M |   |
| sender_last_name            | text:200          | M | Last Name   |
| sender_addr_line1           | text:200          | M |   |
| sender_addr_line2           | text:200          | O |   |
| sender_city                 | text:50           | M | City / Municipality                                       |
| sender_state                | text:100          | M | State / Province / Region                                 |
| sender_postal_code          | num:10            | M |   |
| sender_addr_country_code    | alpha:2           | M | 2 letter ISO country code                                 |
| sender_addr_currency_code   | alpha:3           | M | 3 letter ISO currency code                                |
| sender_contact_phone        | num:30            | O | Format should be Mobile Country Code + phone number       |
| sender_mobile_country_code  | num:3             | O | Mobile Country Code                                       |
| sender_mobile_no            | num:20            | O | Mobile Number   |
| mywu_number                 | num:20            | O | MyWU number   |
| id_type                     | text:20           | M | Refer to IDTypeList                                       |
| id_country_of_issue         | text:100          | M | of Sender   |
| id_number                   | text:50           | M | of Sender   |
| id_issue_date               | date:<br>ddmmyyyy | M | of Sender   |
| id_expiration_date          | date:<br>ddmmyyyy | C | of Sender (required depends on ID Type)                   |
| date_of_birth               | date:<br>ddmmyyyy | M | of Sender   |
| occupation                  | text:100          | M | of Sender   |
| Country_of_Birth            | text:100          | M | of Sender   |
| nationality                 | text:100          | M | of Sender   |
| Gender                      | text:1            | M | of Sender   |
| Source_of_Funds             | text:50           | M | of Sender   |
| Sender_Employeer            | text:50           | M | of Sender   |
| Relationship_to_Receiver    | text:50           | M | of Sender   |
| reason_for_send             | text:50           | M | of Sender   |
| email                       | email             | O | of Sender   |
| receiver_first_name         | alpha:100         | M |   |
| receiver_middle_name        | alpha:100         | O |   |
| receiver_last_name          | alpha:100         | M |   |
| receiver_addr_line1         | text:200          | C | Required if Destination Country is US, INDIA              |
| receiver_addr_line2         | text:200          | O |   |
| receiver_city               | text:50           | C | Required if Destination Country is US, INDIA              |
| receiver_state              | text:100          | C | Required if Destination Country is US, INDIA              |
| receiver_postal_code        | num:10            |   | Required if Destination Country is US, INDIA              |
| receiver_addr_country_code  | alpha:2           | O | 2 letter ISO country code                                 |
| receiver_addr_currency_code | alpha:3           | O | 3 letter ISO currency code                                |
| receiver_contact_phone      | num:30            | C | Required if Destination Country is CHINA, INDIA, NIGERIA, |

# PERA HUB

|                              |              |   |  |
|------------------------------|--------------|---|--|
|                              |              |   | USA and transaction type is D2B  |
| receiver_mobile_country_code | num:3        | C | Required if transactions type is MMT   |
| receiver_mobile_no           | num:20       | C | Required if transactions type is MMT   |
| destination_country_code     | alpha:2      | M | 2 letter ISO country code  |
| destination_currency_code    | alpha:3      | M | 3 letter ISO currency code   |
| destination_state_code       | alpha-num:20 | C | Required if Destination Country is USA and Mexico  |
| destination_city_name        | text:50      | C | Required if Destination Country is USA and Mexico  |
| transaction_type             | alpha-num:3  | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer   |
| principal_amount             | num          | M | Amount to Send   |
| fixed_amount_flag            | alpha:1      | M | <b>F</b> if customer wants a fixed principal amount in the destination country and will not be subject to currency fluctuation. Otherwise <b>N</b> |
| promo_code                   | alpha-num:20 | O | Promo code   |
| message                      | text:array   | O | Optional Message from SENDER to RECEIVER<br>Maximum Length per line is 79 characters<br>Maximum array length is 14                                 |
| bank_name                    | text:100     |   | Required when transaction type = D2B   |
| account_number               | num:50       |   | Required when transaction type = D2B   |
| bank_code                    | alpha-num:20 |   | Required when transaction type = D2B   |
| bank_location                | alpha-num:20 |   | Required when transaction type = D2B   |
| account_suffix               | alpha-num:10 |   | Required when transaction type = D2B   |
| staging_buffer               | text         | M | Get Value from FeeSurvey API   |
| operator_id                  | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user  |
| terminal_id                  | alpha-num:10 | M | Terminal ID will be provided by Petnet per partner location  |

Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "yundu",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
  },
}
```

# PERA HUB

```
"body": {
  "module": "wuso",
  "request": "SMvalidate",
  "param": {
    "foreign_reference_no": "123123sadasd",
    "sender_first_name": "WINNIE",
    "sender_middle_name": "",
    "sender_last_name": "CONSTANTINO",
    "sender_addr_line1": "CALUMPIT",
    "sender_addr_line2": "",
    "sender_city": "CALUMPIT",
    "sender_state": "REGION 3",
    "sender_postal_code": "3003",
    "sender_addr_country_code": "PH",
    "sender_addr_currency_code": "PHP",
    "sender_contact_phone": "6329446115",
    "sender_mobile_country_code": "",
    "sender_mobile_no": "",
    "mywu_number": "185015541",
    "id_type": "S",
    "id_country_of_issue": "Philippines",
    "id_number": "14789654",
    "id_issue_date": "02072015",
    "id_expiration_date": "12072017",
    "date_of_birth": "06041992",
    "occupation": "Programmer",
    "Country_of_Birth": "Philippines",
    "nationality": "Filipino",
    "Gender": "F",
    "Source_of_Funds": "Personal Loan",
    "Sender_Employeer": "Abaris",
    "Relationship_to_Receiver": "Father",
    "reason_for_send": "228990",
    "email": "WINNIEANN.CONSTANTINO@VOXDEISYSTEMS.COM",
    "receiver_first_name": "William",
    "receiver_middle_name": "",
    "receiver_last_name": "Constantino",
    "receiver_addr_line1": "",
    "receiver_addr_line2": "",
    "receiver_city": "",
    "receiver_state": "",
    "receiver_postal_code": "",
    "receiver_addr_country_code": "PH",
    "receiver_addr_currency_code": "PHP",
    "receiver_contact_phone": "",
    "receiver_mobile_country_code": "",
    "receiver_mobile_no": "",
    "destination_country_code": "PH",
    "destination_currency_code": "PHP",
    "destination_state_code": "",
    "destination_city_name": "",
    "transaction_type": "SO",
    "principal_amount": 100000,
    "fixed_amount_flag": "N",
    "promo_code": "",
    "message": [""],
  }
}
```

# PERA HUB

```

        "bank_name": "",
        "account_number": "",
        "bank_code": "",
        "bank_location": "",
        "account_suffix": "",
        "staging_buffer": "getvalue from FeeSurvey",
        "terminal_id": "WBPT",
        "operator_id": "001"
    },
    },
    "signature": "anyvaluesfornow"
}
}

```

## REPONSE Parameters:

| Name                   | Type          | Required | Description  |
|------------------------|---------------|----------|--|
| addl_service_charges   | text:200      | M        | Must be preserve as is since this will be use as parameter in SendMoney Store HOLD                               |
| compliance_data_buffer | alpha-num:200 | M        | Must be preserve as is since this will be use as parameter in SendMoney Store HOLD                               |
| originating_city       | alpha-num:50  | M        | Must be preserve as is since this will be use as parameter in SendMoney Store HOLD                               |
| originating_state      | alpha-num:10  | M        | Must be preserve as is since this will be use as parameter in SendMoney Store HOLD                               |
| staging_buffer         | text          | M        | Must be preserve as is since this will be use as parameter in SendMoney Store HOLD                               |
| financials             | array         | M        | The whole array should be preserved as is  |
| mtcn                   | num:10        | M        | Money Transfer Control Number Must be preserve as is since this will be use as parameter in SendMoney Store HOLD |
| new_mtcn               | num:16        | M        | Money Transfer Control Number Must be preserve as is since this will be use as parameter in SendMoney Store HOLD |

## Sample JSON Data response:

```

{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "good"
    },
    "body": {
      "service_code": {
        "addl_service_charges":
"1103FEE12041500130415000103MSG0201003010210300022010230109001096210104500002
021003035009703NNN9806PILPIL"
      },
      "compliance": {

```



# PERA HUB

```
        "compliance_data_buffer":
"01082PH_02_S0201S0308147896540611Philippines0708060419920810Programmer090802
0720151008120720179901X3311Philippines3408Filipino3501F4413Personal
Loan6706Abaris7006Father7401Y"
    },
    "payment_details": {
        "originating_city": "METRO MANILA",
        "originating_state": "MA",
        "staging_buffer": "0101C0202MB0303PIL0820CCUANA00WU
CCMBAGCA"
    },
    },
    "financials": {
        "taxes": {
            "municipal_tax": 0,
            "state_tax": 0,
            "county_tax": 0
        },
        "originators_principal_amount": 100000,
        "destination_principal_amount": 100000,
        "gross_total_amount": 101500,
        "plus_charges_amount": 0,
        "charges": 1500,
        "message_charge": 0
    },
    "new_details": {
        "mtcn": "9231430092",
        "new_mtcn": "1711689231430092",
        "filing_date": "04-26",
        "filing_time": "1030P EDT "
    }
}
}
}
```

## 3.2.6.1.2. *SendMoney Stage Hold*

Use this API function to save and confirm Send Money Transaction to be HOLD

Module: **wusostg**

Request: **SMSstore**

REQUEST Parameters:

| Name                 | Type         | Required | Description   |
|----------------------|--------------|----------|---|
| foreign_reference_no | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value) |
| sender_first_name    | alpha:100    | M        | First Name  |
| sender_middle_name   | alpha:100    | M        |   |
| sender_last_name     | text:200     | M        | Last Name   |
| sender_addr_line1    | text:200     | M        |   |
| sender_addr_line2    | text:200     | O        |   |
| sender_city          | text:50      | M        | City / Municipality   |
| sender_state         | text:100     | M        | State / Province / Region   |

# PERA HUB

|                              |                   |   |   |
|------------------------------|-------------------|---|---|
| sender_postal_code           | num:10            | M |   |
| sender_addr_country_code     | alpha:2           | M | 2 letter ISO country code   |
| sender_addr_currency_code    | alpha:3           | M | 3 letter ISO currency code  |
| sender_contact_phone         | num:30            | O | Format should be Mobile Country Code + phone number                                       |
| sender_mobile_country_code   | num:3             | O | Mobile Country Code   |
| sender_mobile_no             | num:20            | O | Mobile Number   |
| mywu_number                  | num:20            | O | MyWU number   |
| id_type                      | text:20           | M | Refer to IDTypeList   |
| id_country_of_issue          | text:100          | M | of Sender   |
| id_number                    | text:50           | M | of Sender   |
| id_issue_date                | date:<br>ddmmyyyy | M | of Sender   |
| id_expiration_date           | date:<br>ddmmyyyy | C | of Sender (required depends on ID Type)   |
| date_of_birth                | date:<br>ddmmyyyy | M | of Sender   |
| occupation                   | text:100          | M | of Sender   |
| Country_of_Birth             | text:100          | M | of Sender   |
| nationality                  | text:100          | M | of Sender   |
| Gender                       | text:1            | M | of Sender   |
| Source_of_Funds              | text:50           | M | of Sender   |
| Sender_Employeer             | text:50           | M | of Sender   |
| Relationship_to_Receiver     | text:50           | M | of Sender   |
| reason_for_send              | text:50           | M | of Sender   |
| email                        | email             | O | of Sender   |
| receiver_first_name          | alpha:100         | M |   |
| receiver_middle_name         | alpha:100         | O |   |
| receiver_last_name           | alpha:100         | M |   |
| receiver_addr_line1          | text:200          | C | Required if Destination Country is US, INDIA  |
| receiver_addr_line2          | text:200          | O |   |
| receiver_city                | text:50           | C | Required if Destination Country is US, INDIA  |
| receiver_state               | text:100          | C | Required if Destination Country is US, INDIA  |
| receiver_postal_code         | num:10            |   | Required if Destination Country is US, INDIA  |
| receiver_addr_country_code   | alpha:2           | O | 2 letter ISO country code   |
| receiver_addr_currency_code  | alpha:3           | O | 3 letter ISO currency code  |
| receiver_contact_phone       | num:30            | C | Required if Destination Country is CHINA, INDIA, NIGERIA, USA and transaction type is D2B |
| receiver_mobile_country_code | num:3             | C | Required if transactions type is MMT  |
| receiver_mobile_no           | num:20            | C | Required if transactions type is MMT  |
| destination_country_code     | alpha:2           | M | 2 letter ISO country code   |
| destination_currency_code    | alpha:3           | M | 3 letter ISO currency code  |
| destination_state_code       | alpha-num:20      | C | Required if Destination Country   |

# PERA HUB

|                        |               |   |   |
|------------------------|---------------|---|---|
|                        |               |   | is USA and Mexico   |
| destination_city_name  | text:50       | C | Required if Destination Country is USA and Mexico   |
| transaction_type       | alpha-num:3   | M | SO = Send Money<br>D2B = Direct to Bank<br>MMT = Mobile Money Transfer  |
| principal_amount       | num           | M | Amount to Send  |
| fixed_amount_flag      | alpha:1       | M | F if customer wants a fixed principal amount in the destination country and will not be subject to currency fluctuation.<br>Otherwise N |
| exchange_rate          | num           | M | Currency exchange rate of PHP vs Currency of destination country  |
| promo_code             | alpha-num:20  | O | Promo code  |
| message                | text:array    | O | Optional Message from SENDER to RECEIVER<br>Maximum Length per line is 79 characters<br>Maximum array length is 14                      |
| bank_name              | text:100      | C | Required when transaction type = D2B  |
| account_number         | num:50        | C | Required when transaction type = D2B  |
| bank_code              | alpha-num:20  | C | Required when transaction type = D2B  |
| bank_location          | alpha-num:20  | C | Required when transaction type = D2B  |
| account_suffix         | alpha-num:10  | C | Required when transaction type = D2B  |
| operator_id            | alpha-num:10  | M | Operator ID will be provided Petnet per partner teller/user   |
| terminal_id            | alpha-num:10  | M | Terminal ID will be provided by Petnet per partner location   |
| addl_service_charges   | text:200      | M | Derive value from SendMoney validate Stage  |
| compliance_data_buffer | alpha-num:200 | M | Derive value from SendMoney validate  |
| staging_buffer         | text          | M | Derive value from SendMoney validate Stage  |
| originating_city       | alpha-num:50  | M | Derive value from SendMoney validate Stage  |
| originating_state      | alpha-num:10  | M | Derive value from SendMoney validate Stage  |
| financials             | array         | M | Derive value from SendMoney validate Stage  |
| mtcn                   | num:10        | M | Derive value from SendMoney validate Stage  |
| new_mtcn               | num:16        | M | Derive value from SendMoney validate Stage  |
| mywu_enroll_tag        | alpha:10      | M | mywu = when customer has MyWU Number<br><br>enroll = when customer want to  |

# PERA HUB

|  |  |  |  |
|--|--|--|--|
|  |  |  | <p>enroll in MyWU Program. This is another way to enroll customer into MyWU aside from stand-alone enrollment</p> <p><b>none</b>=when customer does not want to enroll to MyWU</p> |
|--|--|--|--|

## Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "wuso",
      "request": "SMstore",
      "param": {
        "foreign_reference_no": "123123sadasd",
        "sender_first_name": "WINNIE",
        "sender_middle_name": "",
        "sender_last_name": "CONSTANTINO",
        "sender_addr_line1": "CALUMPIT",
        "sender_addr_line2": "",
        "sender_city": "CALUMPIT",
        "sender_state": "REGION 3",
        "sender_postal_code": "3003",
        "sender_addr_country_code": "PH",
        "sender_addr_currency_code": "PHP",
        "sender_contact_phone": "6329446115",
        "sender_mobile_country_code": "",
        "sender_mobile_no": "",
        "mywu_number": "185015541",
        "id_type": "S",
        "id_country_of_issue": "Philippines",
        "id_number": "14789654",
        "id_issue_date": "02072015",
        "id_expiration_date": "12072017",
        "date_of_birth": "06041992",
        "occupation": "Programmer",
        "Country_of_Birth": "Philippines",
        "nationality": "Filipino",
        "Gender": "F",
        "Source_of_Funds": "Personal Loan",
        "Sender_Employeer": "Abaris",
        "Relationship_to_Receiver": "Father",
        "reason_for_send": "228990",
        "email": "WINNIEANN.CONSTANTINO@VOXDEISYSTEMS.COM",
        "receiver_first_name": "William",
        "receiver_middle_name": "",
        "receiver_last_name": "Constantino",

```

# PERA HUB

```
        "receiver_addr_line1": "",
        "receiver_addr_line2": "",
        "receiver_city": "",
        "receiver_state": "",
        "receiver_postal_code": "",
        "receiver_addr_country_code": "PH",
        "receiver_addr_currency_code": "PHP",
        "receiver_contact_phone": "",
        "receiver_mobile_country_code": "",
        "receiver_mobile_no": "",
        "destination_country_code": "PH",
        "destination_currency_code": "PHP",
        "destination_state_code": "",
        "destination_city_name": "",
        "transaction_type": "SO",
        "principal_amount": 100000,
        "fixed_amount_flag": "N",
        "promo_code": "",
        "message": [""],
        "bank_name": "",
        "account_number": "",
        "bank_code": "",
        "bank_location": "",
        "account_suffix": "",
        "terminal_id": "WBPt",
        "operator_id": "001",
        "addl_service_charges":
"1103FEE12041500130415000103MSG0201003010210300022010230109001096210104500002
021003035009703NNN9806PILPIL",
        "staging_buffer": "0101C0202MB0303PIL0820CCUANA00WU
CCMBAGCA",
        "originating_city": "METRO MANILA",
        "originating_state": "MA",
        "financials": {
            "taxes": {
                "municipal_tax": 0,
                "state_tax": 0,
                "county_tax": 0
            },
            "originators_principal_amount": 100000,
            "destination_principal_amount": 100000,
            "gross_total_amount": 101500,
            "plus_charges_amount": 0,
            "charges": 1500,
            "message_charge": 0
        },
        "mtcn": "9231430092",
        "new_mtcn": "1711689231430092",
        "mywu_enroll_tag": "mywu"
    },
    "signature": "anyvaluesfornow"
}
```

## 3.2.6.2. Fulfil SendMoney

### 3.2.6.2.1. SendMoney Staged Search

### 3.2.6.2.2. SendMoney Staged Release

## 3.2.6.3. Stage ReceiveMoney

### 3.2.6.3.1. ReceiveMoney Stage Search

Use this API to search Money Transfer available and waiting to be staged to the intended customer using mobile phone.

Module: **wupostg**

Request: **search**

REQUEST Parameters:

| Name                 | Type         | Required | Description   |
|----------------------|--------------|----------|---|
| foreign_reference_no | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value)                                 |
| mtcn                 | Num:10       | M        | Money Transfer Control Number Must be preserve as is since this will be use as parameter in SendMoney Store |

Sample JSON Data request:

```
{
  "uspuapi": {
    "header": {
      "coy": "yonder",
      "token": "0dc1aac91226345d7fecbc08cf47f39",
      "location_code": "8",
      "user_code": "4",
      "clientip": "127.0.0.1",
      "isweb": "1"
    },
    "body": {
      "module": "wupostg",
      "request": "search",
      "param": {
        "mtcn": "8350742730",
        "foreign_reference_no": "201705120002"
      }
    },
    "signature": ""
  }
}
```

REPNSE Parameters:

| Name                | Type  | Required | Description   |
|---------------------|-------|----------|---|
| payment_transaction | array | M        | Array containing all details of money transfer to be paid.  |
| sender              | array | M        | Sub-array of under payment transaction containing details pertaining to <b>sender</b> of money transfer |

# PERA HUB

|  |          |   |   |
|--|----------|---|---|
| receiver                                       | array    |   | Sub-array of under payment transaction containing details pertaining to <b>recipient</b> of money transfer  |
| financials                                     | array    | M | Sub-array of under payment transaction containing details pertaining to breakdown of amount   |
| payment_details                                | array    | M | Sub-array of under payment transaction containing details pertaining to ORIGIN and DESTINATION information of money transfer  |
| payment_transaction:<br>pay_status_description | alpha:10 | M | W/C = will call or available and can be paid<br><br>PAID = already paid<br>HOLD = if on hold  |
| gross_payout                                   | num      | M | Gross Amount to be paid to customer.<br><br>Equal to Net Payout if money transfer origination within Philippines  |
| dst  | num      | M | Documentary Stamp Tax, for Philippines.<br><br>to be deducted from Gross Amount<br><br>Normally have value when money transfer originated from outside Philippines. |
| net_payout                                     | num      | M | Net Amount to be paid to customer   |

Response: Sample JSON Data response:

```
{
  "instant_notification" : {
    "addl_service_charges" : ""
  },
  "payment_transactions" : {
    "payment_transaction" : {
      "sender" : {
        "name" : {
          "name_type" : "D",
          "first_name" : "SELVARAJ",
          "last_name" : "NATESAN"
        },
        "address" : {
          "city" : "Moskva",
          "country_code" : {
            "iso_code" : {
              "country_code" : "EC",
              "currency_code" : "USD"
            }
          }
        },
        "state_zip" : "676575657",
        "street" : "epre"
      }
    }
  }
}
```

```
    },
    "phone_country_code" : "89",
    "contact_phone" : "070987897",
    "mobile_phone" : {
        "phone_number" : {
            "country_code" : "7",
            "national_number" : "9070987897"
        }
    },
    "mobile_details" : {
        "city_code" : "7",
        "number" : "9070987897"
    }
},
"receiver" : {
    "name" : {
        "name_type" : "D",
        "first_name" : "NAVYA",
        "last_name" : "NAIR"
    },
    "address" : {
        "country_code" : {
            "iso_code" : {
                "country_code" : "PH",
                "currency_code" : "USD"
            }
        }
    },
    "preferred_customer" : {
        "mywu_number" : ""
    },
    "mobile_phone" : {
        "phone_number" : []
    },
    "mobile_details" : []
},
"financials" : {
    "taxes" : {
        "tax_worksheet" : ""
    },
    "gross_total_amount" : 9300,
    "pay_amount" : 344457,
    "principal_amount" : 7000,
    "charges" : 2000,
    "tolls" : 300
},
"payment_details" : {
    "expected_payout_location" : {
        "state_code" : "",
        "city" : ""
    },
    "destination_country_currency" : {
        "iso_code" : {
            "country_code" : "PH",
            "currency_code" : "PHP"
        }
    },
    "originating_country_currency" : {
        "iso_code" : {
            "country_code" : "CH",
            "currency_code" : "CHF"
        }
    },
    "originating_city" : "GENEVE",
```



# PERA HUB

```
{
  "originating_state" : "SW",
  "transaction_type" : "WMN",
  "exchange_rate" : 49.2080713,
  "original_destination_country_currency" : {
    "iso_code" : {
      "country_code" : "PH",
      "currency_code" : "USD"
    }
  },
  "stage_pay_fields" : {
    "snp_indicator" : "C"
  }
},
"filing_date" : "05-12-17 ",
"filing_time" : "0250A EDT",
"money_transfer_key" : "3623949569",
"pay_status_description" : "W\C",
"mtcn" : "8350742730",
"new_mtcn" : "1713288350742730",
"fusion" : {
  "fusion_status" : "W\C",
  "account_number" : ""
},
"wu_network_agent_indicator" : ""
},
"delivery_services" : [],
"misc_buffer" : "",
"foreign_remote_system" : {
  "identifier" : "WGSSPH2590T",
  "reference_no" : "201705120002",
  "counter_id" : "PH259SSP001A"
},
"gross_payout" : 3444.57,
"dst" : 5.17,
"net_payout" : 3439.4
}
```

### 3.2.6.3.2. *ReceiveMoney Stage Hold*

Use this API to confirm payout to hold.

Module: **wupostg**

Request: **hold**

REQUEST Parameters:

| Name                 | Type         | Required | Description   |
|----------------------|--------------|----------|---|
| foreign_reference_no | alpha-num:50 | M        | This will be provided upon Sign-on (for the meantime, please use any value) |
| receiver_name_type   | alpha:1      | M        | Should be marked "D" in most cases  |
| receiver_first_name  | alpha:100    | M        | First Name  |
| receiver_last_name   | alpha:100    | M        | Last Name   |
| sender_first_name    | alpha:100    | M        | First Name  |
| sender_last_name     | alpha:100    | M        | Last Name   |

# PERA HUB

|                                     |                       |   |  |
|-------------------------------------|-----------------------|---|--|
| receiver_city                       | text:50               | M | City / Municipality  |
| receiver_state                      | text:100              | M | State / Province / Region  |
| receiver_country_code               | alpha:2               | M | 2 letter ISO country code  |
| receiver_currency_code              | alpha:3               | M | 3 letter ISO currency code   |
| receiver_state_zip                  | email                 | O | Valid email format   |
| receiver_street                     |                       |   |  |
| id_type                             | text:20               | M | Refer to IDTypeList  |
| id_country_of_issue                 | text:100              | M | of Recipient   |
| id_number                           | text:50               | M | of Recipient   |
| id_issue_date                       | date:<br>ddmmyyy<br>y | M | of Recipient   |
| id_expiration_date                  | date:<br>ddmmyyy<br>y | C | of Recipient (required depends on ID Type)                                       |
| date_of_birth                       | date:<br>ddmmyyy<br>y | M | of Recipient   |
| occupation                          | text:100              | M | of Recipient   |
| addr_line1                          | text:200              | M | of Recipient   |
| curr_city                           | text:50               | M | City / Municipality of Recipient   |
| curr_state_name                     | text:100              | M | State / Province / Region of Recipient   |
| postal_code                         | num:10                | M | of Recipient   |
| country                             |                       |   | of Recipient   |
| contact_phone                       | num:30                | O | Format should be Mobile Country Code + phone number                              |
| Country_of_Birth                    | alpha:2               | M | 2 letter ISO country code  |
| nationality                         | text:100              | M | of Recipient   |
| Source_of_Funds                     | text:100              | M | of Recipient   |
| Name_of_Employer_Business           | text:100              | M | of Recipient   |
| Relationship_to_Receiver_Sender     | text:100              | M | of Recipient   |
| Does_the_ID_have_an_expiration_date | alpha:1               | M | Should be marked "Y" if ID provided by customer has expiration, otherwise "N"    |
| Does_receiver_have_a_phone_number   | alpha:1               | M | Should be marked "Y" if ID provided by have phone number provided, otherwise "N" |
| ack_flag                            | alpha:1               | M | Marked as "X"  |
| GEN_III_Indicator                   | alpha:1               | M | Marked as "1"  |
| pd_state_code                       | text                  | M | from search response payment_details > expected_payout_location                  |

# PERA HUB

|   |            |   |   |
|---|------------|---|---|
| pd_city                                     | text       | M | from search response<br>payment_details ><br>expected_payout_location             |
| pd_dest_country_code                        | alpha:2    | M | from search response<br>payment_details ><br>destination_country                  |
| pd_dest_currency_code                       | alpha:3    | M | from search response<br>payment_details ><br>destination_country                  |
| pd_orig_country_code                        | alpha:2    | M | from search response<br>payment_details ><br>originating_country                  |
| pd_orig_currency_code                       | alpha:3    | M | from search response<br>payment_details ><br>originating_country                  |
| pd_originating_city                         | text       | M | from search response<br>payment_details ><br>expected_payout_location             |
| pd_transaction_type                         | alphanum:5 | M | from search response<br>payment_details ><br>transaction_type                     |
| pd_exchange_rate                            | num        | M | from search response<br>payment_details ><br>exchange_rate                        |
| pd_orig_dest_country_currency_country_code  | alpha:2    | M | from search response<br>payment_details ><br>original_destination                 |
| pd_orig_dest_country_currency_currency_code | alpha:3    | M | from search response<br>payment_details ><br>original_destination                 |
| gross_total_amount                          | num        | M | Gross Amount details<br>on country of origin                                      |
| pay_amount                                  | num        | M | Principal Amount<br>details on destination<br>country                             |
| principal_amount                            | num        | M | Principal Amount<br>details on country of<br>origin                               |
| charges                                     | num        | M | Charges/ Fees details<br>on country of origin                                     |
| tolls                                       | num        | M | Toll Fees on country of<br>origin   |
| money_transfer_key                          | num:10     | M | 10 digit Money Transfer<br>control key,<br><br>From search response<br>parameters |
| new_mtcn                                    | num:16     | M | 16 digit Money Transfer<br>Control Number   |
| mtcn  | num:10     | M | 10 digit Money Transfer<br>Control Number   |
| pay_or_do_not_pay_indicator                 | alpha:1    | M | Should be Marked "P"  |
| rec_mob_country_code                        | num:3      | O | Mobile Country Code   |
| national_number                             | num:20     | O | Mobile Number   |

# PERA HUB

|                       |              |   |   |
|-----------------------|--------------|---|---|
| telephone_city_code   | num:3        | O | Mobile Country Code   |
| filing_time           | text         | M | from search response  |
| filing_date           | text         | M | from search response  |
| message               | array        | O | from search response  |
| client_reference_no   | text         | M | Reference Number of Partner's System<br><br>Should be unique                                    |
| real_principal_amount | num          | M | Gross Principal Amount in destination country   |
| dst_amount            | num          | M | DST amount  |
| real_net_amount       | num          | M | NET Amount to release to recipient  |
| user_code             |              |   | user code of user/teller from partner's system  |
| customer_code         | alphnum:20   | O | Customer code to be provided if mobile customer<br><br>Otherwise leave blank                    |
| operator_id           | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user                                     |
| terminal_id           | alpha-num:10 | M | Terminal ID will be provided by Petnet per partner location                                     |
| remote_terminal_id    | alpha-num:10 | M | Operator ID will be provided Petnet per partner teller/user<br><br>Equal to Terminal ID         |
| remote_operator_id    | alpha-num:10 | M | Terminal ID will be provided by Petnet per partner location<br><br>Equal to Terminal ID         |
| mywu_number           | num:20       | O | MyWU Number of the customer if customer is existing MyWU Customer.<br><br>Otherwise leave blank |

Sample JSON Data request:

```
{
  "uspuapi" : {
    "header" : {
      "coy" : "yundu",
      "token" : "0dc1aac91226345d7fecbc08cf47f39",
      "location_code" : "8",
      "user_code" : "4",
      "clientip" : "127.0.0.1",
      "isweb" : "1"
    },
    "body" : {
      "module" : "wupostg",
      "request" : "hold",
      "param" : {
```

# PERA HUB

```
"foreign_reference_no" : "312dsefse",
"mywu_number" : "",
"sender_first_name" : "WINNIE",
"sender_last_name" : "CONSTANTINO",
"receiver_name_type" : "D",
"receiver_first_name" : "JERICA",
"receiver_last_name" : "NAPARATE",
"receiver_city" : "CALOOCAN CITY",
"receiver_state" : "MANILA",
"receiver_country_code" : "PH",
"receiver_currency_code" : "PHP",
"receiver_state_zip" : "1420",
"receiver_street" : "",
"id_type" : "J",
"id_country_of_issue" : "Philippines",
"id_number" : "12346567892",
"id_issue_date" : "10052017",
"id_expiration_date" : "",
"date_of_birth" : "10081996",
"occupation" : "Programmer",
"addr_line1" : "1953 Ph 3b Block 6 Lot 9 Camarin",
"curr_city" : "CALOOCAN CITY",
"curr_state_name" : "MANILA",
"postal_code" : "1420",
"country" : "PH",
"contact_phone" : "9089488895",
"Country_of_Birth" : "Philippines",
"nationality" : "Filipino",
"Source_of_Funds" : "Medical Expenses",
"Name_of_Employer_Business" : "Abaris Technologies",
"Relationship_to_Receiver_Sender" : "Spouse",
"Does_the_ID_have_an_expiration_date" : "N",
"Does_receiver_have_a_phone_number" : "Y",
"ack_flag" : "X",
"GEN_III_Indicator" : "1",
"rec_mob_country_code" : "63",
"national_number" : "9089488895",
"telephone_city_code" : "",
"pd_state_code" : "",
"pd_city" : "",
"pd_dest_country_code" : "PH",
"pd_dest_currency_code" : "PHP",
"pd_orig_country_code" : "PH",
"pd_orig_currency_code" : "PHP",
"pd_originating_city" : "METRO MANILA",
"pd_transaction_type" : "WMF",
"pd_exchange_rate" : "1",
"pd_orig_dest_country_currency_country_code" : "PH",
"pd_orig_dest_country_currency_currency_code" :
"PHP",

"gross_total_amount" : "8300",
"pay_amount" : "295248",
"principal_amount" : "1000",
"charges" : "500",
"tolls" : "5000",
"money_transfer_key" : "3624017665",
"new_mtcn" : "1713285971093319",
"mtcn" : "5971093319",
"pay_or_do_not_pay_indicator" : "P",
"message" : [],
"filing_date" : "05-05-17",
"filing_time" : "0205A EDT",
"client_reference_no" : "201705120002",
"real_principal_amount" : "10",
```

# PERA HUB

```

        "dst_amount" : "0",
        "real_net_amount" : "10",
        "user_code" : "4",
        "customer_code" : "HOIFLGNNWR",
        "terminal_id" : "WBpt",
        "operator_id" : "001",
        "hold_contact_phone" : "639175101664"
    },
    "signature" : ""
}

```

## RESPONSE Parameters:

| Name   | Type     | Required | Description   |
|--|----------|----------|---|
| payment_transaction                            | array    | M        | Array containing all details of money transfer to be paid.  |
| sender   | array    | M        | Sub-array of under payment transaction containing details pertaining to <b>sender</b> of money transfer   |
| receiver                                       | array    |          | Sub-array of under payment transaction containing details pertaining to <b>recipient</b> of money transfer  |
| financials                                     | array    | M        | Sub-array of under payment transaction containing details pertaining to breakdown of amount   |
| payment_details                                | array    | M        | Sub-array of under payment transaction containing details pertaining to ORIGIN and DESTINATION information of money transfer  |
| payment_transaction:<br>pay_status_description | alpha:10 | M        | <b>W/C</b> = will call or available and can be paid<br><br>PAID = already paid<br>HOLD = if on hold   |
| gross_payout                                   | num      | M        | Gross Amount to be paid to customer.<br><br>Equal to Net Payout if money transfer origination within Philippines  |
| dst  | num      | M        | Documentary Stamp Tax, for Philippines.<br><br>to be deducted from Gross Amount<br><br>Normally have value when money transfer originated from outside Philippines. |
| net_payout                                     | num      | M        | Net Amount to be paid to customer   |

Response: Sample JSON Data response:

# PERA HUB

```
{
  "uspwuapi" : {
    "header" : {
      "errorcode" : "1",
      "message" : {
        "confirmed_details" : {
          "instant_notification" : {
            "addl_service_charges" : ""
          },
          "advisory_text" : "",
          "receiver" : {
            "compliance_details" : {
              "compliance_data_buffer" :
"01082PH_02_P0201J0311123465678920611Philippines0708100819960810Programmer0908100520172002PH2
9321953 Ph 3b Block 6 Lot 9 Camarin3013CALOOCAN
CITY31041420321091751016643311Philippines3408Filipino4416Medical Expenses6719Abaris
Technologies7006Spouse7401N7601Y8606MANILA9901XB4011"
            }
          },
          "payment_details" : {
            "mt_requested_status" : "HOLD"
          },
          "mtcn" : "5971093319",
          "new_mtcn" : "1713285971093319",
          "paid_date_time" : "05-15-2017 03:14",
          "foreign_remote_system" : {
            "identifier" : "WGSSPH2590T",
            "reference_no" : "312dsefse",
            "counter_id" : "PH259SSP001A"
          }
        }
      },
      "body" : null
    }
  }
}
```

## 3.2.6.4. Fulfil ReceiveMoney

### 3.2.6.4.1. ReceiveMoney Staged Search

### 3.2.6.4.2. ReceiveMoney Staged Release

## 3.3.E-Wallet

### 3.3.1. Common Functions

#### 3.3.1.1. Customer Registration

Use this API function to get the details of customers. Provides several search options for MyWU customers.

Module: **Registration**

Request: **Register**

REQUEST Parameters:

| Name     | Type        | Required | Description         |
|----------|-------------|----------|---------------------|
| username | Alpha-num15 | M        | Unique code for OTP |

# PERA HUB

|                     |                  |   |                        |
|---------------------|------------------|---|------------------------|
| mobile              | Numeric 10       | M | In 09 prefix           |
| phone               | Numeric 9        | 0 | Numeric or blank       |
| surname             | Alpha:30         | M | mandatory              |
| givenname           | alpha:30         | M | mandatory              |
| middlename          | alpha:30         | M | mandatory              |
| password            | SHA512           | M | mandatory              |
| Birthdate           | Date(mm/dd/yyyy) | M | mm/dd/yyyy format      |
| Nationality         | alpha:30         | M |                        |
| PresentAddress      | Alpha 255        | M |                        |
| PermanentAddress    | Alpha 255        | M |                        |
| Occupation          | Alpha 30         | M |                        |
| NameOfEmployer      | Alpha 50         | M |                        |
| SecurityQuestion    | Alpha 255        | M |                        |
| Answer              | Md5              | M |                        |
| ValidIdentification | Alpha 20         | M |                        |
| Photo               | Binary           | M | Binary Image format    |
| WuCardNo            | Alpha-num        | C | Alpha numeric or blank |
| DebitCardNo         | Alpha-num        | C | Alpha numeric or blank |
| LoyaltyCardNo       | Alpha-num        | C | Alpha numeric or blank |

## Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "Registration",
      "request": "Register",
      "param": {
        "username": "ricoll111",
        "mobile": "09171234567",
        "email": "ricojayv@gmail.com",
        "phone": "02417111",
        "surname": "villanueva",
        "givenname": "rico jay",
        "middlename": "santos",

        "password": "3627909A29C31381A071EC27F7C9CA97726182AED29A7DDD2E54353322CFB30ABB9E3A6DF2AC2C20FE23436311D678564D0C8D305930575F60E2D3D048184D79",
        "Birthdate": "10/15/1977",
        "Nationality": "fil",
        "PresentAddress": "manila",
        "PermanentAddress": "qc",
        "Occupation": "developer",
        "NameOfEmployer": "voc dei",
        "SecurityQuestion1": "number 1?",
        "Answer1": "1",
        "SecurityQuestion2": "number 2?",

```



```

        "Answer2": "2",
        "SecurityQuestion3": "number 3?",
        "Answer3": "3",
        "ValidIdentification": "drivers license",
        "photo": "",
        "WuCardNo": "123",
        "DebitCardNo": "123",
        "LoyaltyCardNo": "123"
    },
    "signature": "asda"
}

```

### 3.3.1.2. *Get Secret Question*

Use this function to get the secret question for password reset

Module: **SPassword**

REQUEST: **get\_question**

REQUEST Parameters:

| Name     | Type        | Required | Description        |
|----------|-------------|----------|--------------------|
| username | Alpha-num15 | M        | Username for login |

Sample Json Request:

```

{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "Password",
      "request": "get_question",
      "param": {
        "username": "REYNOVFAD05241980RNF"
      }
    },
    "signature": "anyvalue"
  }
}

```

Sample response:

```

{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "Good"
    },
    "body": {
      "question": "pets name",
      "username": "REYNOVFAD05241980RNF"
    }
  }
}

```

```
}
}
```

### 3.3.1.3. *Reset Password*

Use this function to trigger reset password

Module: **SPassword**

Request: **reset\_password**

REQUEST Parameters:

| Name            | Type        | Required | Description                      |
|-----------------|-------------|----------|----------------------------------|
| username        | Alpha-num15 | M        | Username for login               |
| Password        | SHA512      | M        | SHA512 format of password        |
| secret_question | Alpha num   | M        | Retrieved text from get_question |
| Answer          | SHA512      | M        | SHA512format of secret question  |

Sample Json Request:

```
{
  "uspuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "SPassword",
      "request": "reset_password",
      "param": {
        "username": "REYNOVFAD05241980RNF",
        "password": "3627909A29C31381A071EC27F7C9CA97726182AED29A7DDD2E54353322CFB30ABB9E3A6DF2AC2C20FE23436311D678564D0C8D305930575F60E2D3D048184D79",
        "secret_question": "number 1?",
        "answer": "4DFF4EA340F0A823F15D3F4F01AB62EAE0E5DA579CCB851F8DB9DFE84C58B2B37B89903A740E1EE172DA793A6E79D560E5F7F9BD058A12A280433ED6FA46510A"
      }
    },
    "signature": ""
  }
}
```

Sample response:

```
{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "Good"
    },
    "body": {
      "username": "REYNOVFAD05241980RNF"
    }
  }
}
```

### 3.3.1.4. *Acrivate Card*

Use this function to transfer card information from USP to mobile.

# PERA HUB

Module: **ActivateCard**  
Request: **activate\_card**

REQUEST Parameters:

| Name     | Type        | Required | Description        |
|----------|-------------|----------|--------------------|
| usercode | Alpha-num15 | M        | Username for login |

Sample Json Request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "ActivateCard",
      "request": "activate_card",
      "param": {
        "usercode": "REYNOVFAD05241980RNF"
      }
    }
  },
  "signature": "asda"
}
```

Sample response:

```
{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "Good"
    },
    "body": {
      "username": "REYNOVFAD05241980RNF"
    }
  }
}
```

### 3.3.1.5. *Update information*

Use this API to update customer information.

Module: **Registration**  
Request: **Register**

REQUEST Parameters:

| Name       | Type        | Required | Description     |
|------------|-------------|----------|-----------------|
| Usercode   | Alpha-num15 | M        | mandatory       |
| surname    | Alpha:30    | M        | mandatory       |
| givenname  | alpha:30    | M        | mandatory       |
| Middlename | alpha:30    | M        | mandatory       |
| Mobile     | Numeric     | M        | In 09 prefix    |
| Email      | Alphanum    | M        | In email format |

# PERA HUB

|                  |               |   |           |
|------------------|---------------|---|-----------|
| presentaddress   | Alpha num 255 | M | mandatory |
| permanentaddress | Alpha num 255 | M | mandatory |
| secretquestion1  | Alpha num 255 | M | mandatory |
| answer1          | SHA512        | M | mandatory |
| secretquestion2  | Alpha num 255 | M | mandatory |
| answer2          | SHA512        | M | mandatory |
| secretquestion3  | Alpha num 255 | M | mandatory |
| answer3          | SHA512        | M | mandatory |

Sample JSON Data request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "Registration",
      "request": "update_info",
      "param": {
        "usercode": "REYNOVFAD05241980RNF",
        "surname": "dela cruz",
        "givenname": "juan",
        "middlename": "santos",
        "mobile": "0923123456",
        "email": "juan@gmail.com",
        "presentaddress": "pedro st manila",
        "permanentaddress": "pedro st qc",
        "secretquestion1": "Kung kelan pinatay, saka humaba ang buhay.",
        "answer1": "
ABE323C22654CAEDC55F2B0DD829A84B6F172FE32A45CF59FA9B8118EAFBD1BADE544FA564A
CC282EB0DDFC70FF59BD6E0695166B75F81A2F40B902EB58EBB34 ",
        "secretquestion2": "Baboy ko sa pulo, balahiboy pako",
        "answer2": "
BF2C22A1E25F16B3296E485FCBF558BF800EDCAC4D76586187BB0F03EC3477EE720CDDE33B42
1735D2733C4048318AD776C0118C3E4993FC90B16E77C5A857C9 ",
        "secretquestion3": "Nang sumipot sa maliwanag, kulubot na ang balat.",
        "answer3": "
A3BEFF6300C4770EE90805EB3CBE773CF98129EE91BBF3C61E947F6853F28DA370DD3B84E7EF
BFE9B8F20E64F1F6BEBB20191600400D0F29FB62F5F98CD70FB0 "
      }
    },
    "signature": "asda"
  }
}
```

## 3.3.2. Transactional

### 3.3.2.1. Balance Inquiry

Use this function to get amount cash card of a certain customer.

Module: **UBClass**

Request: **get\_balance**

REQUEST Parameters:

| Name          | Type      | Required | Description                               |
|---------------|-----------|----------|---|
| usercode      | Alpha-num | M        | Usercode for validation                   |
| operator_code | Alpha-num | M        | User for usp use send ""(blank) for yondu |
| session_id    | Alpha-num | M        | Sessionid from signin                     |

Sample JSON request:

```
{
  "uspuapi": {
    "header": {
      "coy": "yondu",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "UBClass",
      "request": "get_balance",
      "param": {
        "usercode": "RV101577JSCT",
        "operator_code": "ABC12345",
        "session_id": "123145"
      }
    }
  },
  "signature": "asda"
}
```

Sample JSON Output:

```
{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "Good"
    },
    "body": {
      "available_balance": "315.00",
      "current_balance": "315.00"
    }
  }
}
```

### 3.3.2.2. Debit Account

Use function to debit amount from customer.

# PERA HUB

Module: **UBClass**

Request: **debit\_amount**

REQUEST Parameters:

| Name          | Type      | Required | Description   |
|---------------|-----------|----------|---|
| usercode      | Alpha-num | M        | Usercode for validation   |
| amount        | integer   | M        | Amount to be debited with no decimal point , decimal values should be padded to the right, ex:100.68 the amount should be 10068 |
| password      | Sha512    | M        | Sha512 of password uppercased of the user   |
| Operator_code | Alpha num | M        | For usp use only  |
| Session_id    | Alpha_num | M        | Session from signin   |

Sample JSON request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "yonder",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "UBClass",
      "request": "debit_amount",
      "param": {
        "usercode": "RV101577JSCT",
        "amount": "10068",
        "password":
"3627909A29C31381A071EC27F7C9CA97726182AED29A7DDD2E54353322CFB30ABB9E3A6DF2AC
2C20FE23436311D678564D0C8D305930575F60E2D3D048184D79",
        "operator_code": "2221111",
        "session_id": "111"
      }
    },
    "signature": "asda"
  }
}
```

Sample JSON response:

```
{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "Good"
    },
    "body": {
      "code": "1",
      "amount_deducted": 10068
    }
  }
}
```

### 3.3.2.3. Credit Account

Use this function to credit amount to customer.

Module: **UBClass**

Request: **credit\_amount**

REQUEST Parameters:

| Name          | Type      | Required | Description   |
|---------------|-----------|----------|---|
| usercode      | Alpha-num | M        | Usercode for validation   |
| amount        | integer   | M        | Amount to be debited with no decimal point , decimal values should be padded to the right, ex:100.68 the amount should be 10068 |
| password      | Sha512    | M        | Sha512 of password uppercase of the user  |
| otp_code      | Integer   | M        | Otp from sms  |
| otp_pin       | Integer   | M        | For usp use only, send blank  |
| Operator_code | Alpha num | M        | For usp use only  |
| Session_id    | Alpha—num | M        | Session from signin   |

Sample JSON request:

```
{
  "uspwuapi": {
    "header": {
      "coy": "yundu",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "UBClass",
      "request": "credit_amount",
      "param": {
        "usercode": "RV101577JSCT",
        "amount": "10059",
        "password": "3627909A29C31381A071EC27F7C9CA97726182AED29A7DDD2E54353322CFB30ABB9E3A6DF2AC2C20FE23436311D678564D0C8D305930575F60E2D3D048184D79",
        "otp_code": "778541",
        "otp_pin": "",
        "operator_code": "2221111",
        "session_id": "111"
      }
    }
  },
  "signature": "asda"
}
```

Sample JSON output:

```
{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "Good"
    },
  },
}
```

```

    "body": {
      "code": "1",
      "amount_credited": 10059
    }
  }
}

```

### 3.3.2.4. Transaction History

User this function to get transaction records valid for 60 days difference from and to dates

Module: **Transaction**

Request: **get\_transaction**

REQUEST Parameters:

| Name       | Type                   | Required | Description             |
|------------|------------------------|----------|-------------------------|
| usercode   | Alpha-num              | M        | Usercode for validation |
| date_start | yyyy-mm-dd<br>hh:mm:ss | M        | From date               |
| date_end   | yyyy-mm-dd<br>hh:mm:ss | M        | To date                 |
| Session_id | Alpha-num              | M        | Session from signin     |

Sample JSON request:

```

{
  "uspwuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    },
    "body": {
      "module": "UBClass",
      "request": "get_transaction",
      "param": {
        "usercode": "RV101577JSCT",
        "date_start": "2017-07-16 01:01:01",
        "date_end": "2017-07-19 11:01:01",
        "session_id": "asdf"
      }
    }
  },
  "signature": "asda"
}

```

Sample JSON Output:

```

{
  "uspwuapi": {
    "header": {
      "errorcode": "1",
      "message": "Good"
    },
    "body": [{
      "return": {
        "trxnList": {

```



# PERA HUB

```

        "txn": [{
            "id": "95466",
            "tranDate": "2017-07-19 15:33:59",
            "amount": "-100.00",
            "branch": "NA",
            "tranDesc": "Fund Transfer Internal

[from]",

            "balance": "113682.64",
            "txnCurrency": "608",
            "pplcode": ""
        },
        {
            "id": "94698",
            "tranDate": "2017-07-18 15:05:12",
            "amount": "-5.00",
            "branch": "NA",
            "tranDesc": "Fund Transfer Internal

[from]",

            "balance": "113782.64",
            "txnCurrency": "608",
            "pplcode": ""
        },
        {
            "id": "94807",
            "tranDate": "2017-07-18 15:02:45",
            "amount": "-10.00",

            "branch": "NA",
            "tranDesc": "Fund Transfer Internal

[from]",

            "balance": "113787.64",
            "txnCurrency": "608",
            "pplcode": ""
        }
    ]
}
}
}
```

### 3.3.2.5. *Send SMS*

### Use this function to send SMS for OTP

Module: **UBClass**

Request: **send sms user**

REQUEST Parameters:

| Name       | Type      | Required | Description             |
|------------|-----------|----------|-------------------------|
| usercode   | Alpha-num | M        | Usercode for validation |
| Session id | Alpha-num | M        | Session from signin     |

Sample JSON request:

```
{
  "uspuapi": {
    "header": {
      "coy": "usp",
      "token": "b0dd9378fb63749c462a66d209b06454",
      "location_code": "6",
      "user_code": "1",
      "clientip": "::1",
      "isweb": "1"
    }
  }
}
```

# PERA HUB

```
    },
    "body": {
      "module": "UBClass",
      "request": "send_sms_user",
      "param": {
        "usercode": "RV101577JSCT",
        "session_id": "778"
      }
    },
    "signature": "asda"
  }
}

Sample JSON output:
{
  "uspuapi": {
    "header": {
      "errorcode": "1",
      "message": "Good"
    },
    "body": {
      "mobile": "09175101497"
    }
  }
}
```