

bite-sized.sql

SQL: NULL-safe comparisons

Setup

```
DROP TABLE IF EXISTS null_comparisons;
```

```
CREATE TABLE null_comparisons  
(  
    a int,  
    b int  
);
```

```
INSERT INTO null_comparisons  
    (a,b)  
VALUES  
    (1, 1),  
    (1, 2),  
    (1, null),  
    (null, null),  
    (null, 2);
```





	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2


Select rows where a = b

	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2

This row is not
returned



```
SELECT *  
FROM null_comparisons  
WHERE a = b;
```



	a	b
1	1	1

bite-sized.sql

**Let's find
where a is not
equal to b**

Select rows where a <> b

	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2


Both of these rows
are not returned

```
SELECT *  
FROM null_comparisons  
WHERE a <> b;
```


	a	b
1	1	2

The vendor-independent long-winded way

	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2



```
SELECT *  
FROM null_comparisons  
WHERE (a <> b)  
OR (a IS NULL AND b IS NOT NULL)  
OR (a IS NOT NULL AND b IS NULL);
```



	a	b
1	1	2
2	1	NULL
3	NULL	2

SQL Server versions < 2022

	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2



The value you select for the second parameter of IFNULL or COALESCE must not be a legitimate value and it must be type-compatible with the other side of the comparison

```
SELECT *  
FROM null_comparisons  
WHERE ISNULL(a,0) <> ISNULL(b,0);
```

ISNULL returns the first argument if it's not NULL and the second argument if the first argument is NULL

	a	b
1	1	2
2	1	NULL
3	NULL	2

We can also use **COALESCE** in the same way

e.g. **COALESCE(a,0)**

SQL Server 2022+ and PostgreSQL

	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2



```
SELECT *  
FROM null_comparisons  
WHERE a IS DISTINCT FROM b;
```



IS DISTINCT FROM is a NULL-safe inequality predicate. We can also use **IS NOT DISTINCT FROM** for a NULL-safe equality predicate.

	a	b
1	1	2
2	1	NULL
3	NULL	2

bite-sized.sql

MySQL

	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2



In MySQL, we can also use `IFNULL(a,0) <> IFNULL(b,0)` in a similar way to SQL Server, but **NOT** with `<=>` is more safe as we don't need to specify a default value for NULLs

`SELECT *`
`FROM null_comparisons`
`WHERE NOT a <=> b;`


While the `<=>` operator looks like a null-safe “not equals”, it is actually a null-safe “equals”, so we precede it with **NOT** here to get “not equals”.

	a	b
1	1	2
2	1	NULL
3	NULL	2


bite-sized.sql

Oracle - 1

	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2



```
SELECT *  
FROM null_comparisons  
WHERE NVL(a,0) <> NVL(b,0);
```




Similarly to T-SQL's ISNULL and MySQL's IFNULL, we must be careful when choosing a default value.

	a	b
1	1	2
2	1	NULL
3	NULL	2


bite-sized.sql

Oracle - 2


	a	b
1	1	1
2	1	2
3	1	NULL
4	NULL	NULL
5	NULL	2



```
SELECT *  
FROM null_comparisons  
WHERE DECODE(a,b,'equal','unequal') = 'unequal';
```



DECODE compares the first and second arguments. If they're equal, it returns the third argument, if they're unequal, it returns the fourth argument if supplied, or NULL if there's no fourth argument. The third and fourth arguments can be any value.



	a	b
1	1	2
2	1	NULL
3	NULL	2

