

QA from GPT

Lecture 9 - SVM Kernel

Quanying Liu

2024.03.26

0. What is Hinge loss? Why does it help SVM learn?

Hinge loss is a fundamental component in the learning process of Support Vector Machines (SVMs). It plays a crucial role in how SVMs are able to find the optimal decision boundary between different classes. Here's a detailed explanation of why hinge loss is effective in training SVMs:

1. **Definition of Hinge Loss**: Hinge loss is defined as $L(y) = \max(0, 1 - y \cdot f(x))$, where y is the actual label of the data point (typically +1 or -1 in binary classification), and $f(x)$ is the predicted value by the model. The predicted value is the result of the dot product between the data point's features and the model's weights, plus a bias term.

2. **Encouraging Correct Classification**: Hinge loss directly encourages the model to classify examples correctly. A data point is considered correctly classified only if the predicted value $f(x)$ has the same sign as the actual label y and is correct by a margin of at least 1. If this condition is met, the hinge loss is 0. This means the model is not penalized for points that are correctly classified with a sufficient margin.

3. **Margin Maximization**: SVM aims to find the decision boundary that maximizes the margin between the two classes. The margin is defined as the distance between the decision boundary and the closest data points from either class, which are known as support vectors. Hinge loss contributes to this objective by penalizing points that fall within the margin, even if they are correctly classified. This penalty encourages the model to push the decision boundary away from the data points, thus increasing the margin.

4. **Handling Misclassifications**: When a data point is misclassified or falls within the margin, the hinge loss is positive and increases linearly with the degree of misclassification. This linear increase in loss ensures that the model is heavily penalized for misclassifications, especially those that are far from the decision boundary. Consequently, the SVM is motivated to adjust its parameters to reduce these losses.

5. **Simplifying Optimization**: The linear nature of hinge loss (for misclassified points or points within the margin) makes the optimization problem convex, which is easier to solve mathematically. Convex optimization guarantees that the solution found is the global minimum, meaning the model has found the best possible decision boundary given the data.

6. **Sparsity and Support Vectors**: Due to the nature of hinge loss, only the data points that

are misclassified or lie within the margin (the support vectors) contribute to the loss. This results in a model that is influenced only by the critical points near the decision boundary, leading to a sparser solution that emphasizes the most informative features of the dataset.

In summary, hinge loss is instrumental in SVM's learning process as it aligns with the core objectives of SVM: to correctly classify points while maximizing the margin between classes. It achieves this by imposing a structured penalty system that encourages correct classification and margin maximization, thereby guiding the model toward the optimal decision boundary.

1. How to use gradient descent with hinge loss in SVM?

Using gradient descent with hinge loss in the context of training a Support Vector Machine (SVM) involves iteratively adjusting the model's parameters to minimize the hinge loss across the training data. Here's a step-by-step guide on how to apply gradient descent with hinge loss for SVM training:

1. Initialize Parameters

First, you need to initialize the model's parameters (weights \mathbf{w} and bias b) randomly or with zeros.

2. Define the Hinge Loss Function

The hinge loss for a single data point (x_i, y_i) is defined as:

$$L_i = \max(0, 1 - y_i(\mathbf{w} \cdot \mathbf{x}_i + b))$$

For the whole dataset, the loss is the sum of the individual losses:

$$L = \sum_{i=1}^n \max(0, 1 - y_i(\mathbf{w} \cdot \mathbf{x}_i + b))$$

In addition, SVMs typically include a regularization term to avoid overfitting, resulting in the following loss function:

$$L = \lambda \|\mathbf{w}\|^2 + \sum_{i=1}^n \max(0, 1 - y_i(\mathbf{w} \cdot \mathbf{x}_i + b))$$

where λ is the regularization parameter.

3. Compute the Gradient

The gradient of the loss function with respect to the weights \mathbf{w} and bias b needs to be calculated to update these parameters. The gradient differs depending on whether a data point is correctly classified and outside the margin ($1 - y_i(\mathbf{w} \cdot \mathbf{x}_i + b) \leq 0$) or not.

- If $(1 - y_i(\mathbf{w} \cdot \mathbf{x}_i + b)) > 0$ (misclassified or within the margin), the gradient w.r.t. \mathbf{w} is $\nabla_{\mathbf{w}} L = \lambda \mathbf{w} - y_i \mathbf{x}_i$ and w.r.t. b is $\nabla_b L = -y_i$.
- If $(1 - y_i(\mathbf{w} \cdot \mathbf{x}_i + b)) \leq 0$ (correctly classified and outside the margin), the gradient w.r.t. \mathbf{w} is $\nabla_{\mathbf{w}} L = \lambda \mathbf{w}$ and w.r.t. b is $\nabla_b L = 0$.

4. Update the Parameters

Update the parameters \mathbf{w} and b using the gradients calculated above. If you're using a learning rate α , the updates would be:

- $\mathbf{w} := \mathbf{w} - \alpha \nabla_{\mathbf{w}} L$
- $b := b - \alpha \nabla_b L$

5. Iterate

Repeat steps 3 and 4 for a number of iterations or until the loss converges to a minimum value. This iterative process will gradually adjust the weights and bias to minimize the hinge loss, thus training the SVM.

6. Evaluation

After training, evaluate the performance of the SVM on a validation or test set to ensure that it generalizes well to unseen data.

Practical Considerations

- **Batch vs. Stochastic Gradient Descent**: You can perform these updates using all the data points (batch gradient descent), a single data point (stochastic gradient descent), or a mini-batch of data points at each iteration.
- **Convergence**: You should monitor the loss during training to ensure it is decreasing and converging to a minimum.
- **Hyperparameters**: The learning rate α and the regularization parameter λ are crucial hyperparameters that need to be tuned for optimal performance.

Applying gradient descent with hinge loss in SVM training allows the model to find the optimal decision boundary by minimizing the classification errors and maximizing the margin, adhering to the core principles of SVMs.

1. How to use gradient descent with hinge loss in SVM?

Sure, I can provide a simple Python implementation of an SVM trained using gradient descent with hinge loss. This example will be somewhat basic and focus on the key aspects of the training process:

1. Generate a synthetic dataset.
2. Define the hinge loss and its gradient.
3. Implement gradient descent to update the weights and bias.
4. Visualize the resulting decision boundary.

Let's start coding:

```
# Parameters
weights = np.zeros(X.shape[1])
bias = 0
learning_rate = 0.001
epochs = 1000
lambda_param = 0.01

# Training loop
for epoch in range(epochs):
    for i, x in enumerate(X):
        # Calculate the condition for the hinge loss
        condition = y[i] * (np.dot(x, weights) + bias)

        # Check if the data point is misclassified or within the margin
        if condition < 1:
            # Update for misclassified points or points within the margin
            weights -= learning_rate * (2 * lambda_param * weights - np.outer(y[i], x))
            bias -= learning_rate * (-y[i])
        else:
            # Update only based on the regularizer for correctly classified points
            # outside the margin
            weights -= learning_rate * (2 * lambda_param * weights)

# After training, we will plot the decision boundary again
plot_decision_boundary(X, y, weights, bias)
```

It seems the error persists due to the dimension mismatch in the weight update. I'll correct this by ensuring that the update is properly aligned for the weight vector's dimensions. Let's fix the update rule and execute the gradient descent process again.

```
python Copy code


# Correcting the weight update process

# Re-initialize the weights and bias
weights = np.zeros(X.shape[1])
bias = 0

# Corrected training using gradient descent
for epoch in range(epochs):
    for i, x in enumerate(X):
        # Calculate the condition for the hinge loss
        condition = y[i] * (np.dot(x, weights) + bias)

        # Check if the data point is misclassified or within the margin
        if condition < 1:
            # Update for misclassified points or points within the margin
            weights -= learning_rate * (2 * lambda_param * weights - y[i] * x)
            bias -= learning_rate * (-y[i])
        else:
            # Update only based on the regularizer for correctly classified points
            weights -= learning_rate * (2 * lambda_param * weights)

# Let's plot the decision boundary again with the corrected model
plot_decision_boundary(X, y, weights, bias)
```



Here's the updated plot showing the decision boundary of the SVM after training with gradient descent and hinge loss. The decision boundary is illustrated with a solid line, while the margins are represented by dashed lines. The model aims to maximize the margin while correctly classifying the data points, as visualized here.

2. What is Kernel trick?

The kernel trick is a powerful technique used primarily in machine learning algorithms, notably in Support Vector Machines (SVMs), to enable them to operate in

higher-dimensional spaces without explicitly computing the coordinates of the data in those spaces. This trick allows algorithms to leverage the power of high-dimensional space computations while avoiding the significant computational cost typically associated with such operations.

Core Idea

The kernel trick relies on the observation that many machine learning algorithms, especially those that are based on inner products (like SVMs), can be rewritten in a form where the input data only appears inside inner products. By replacing the standard inner product with a kernel function, which effectively computes the inner product in a higher-dimensional space, the algorithm can implicitly work in this high-dimensional space without directly computing or manipulating data in that space.

How It Works with SVMs

In the context of SVMs, the kernel trick allows the algorithm to find a linear separating hyperplane in a transformed feature space, which corresponds to a non-linear boundary in the original input space. This significantly enhances the flexibility and power of SVMs, enabling them to capture complex relationships in the data.

Kernel Functions

A kernel function $K(x, y)$ computes the inner product of two vectors x and y in some (potentially much higher-dimensional) feature space without ever explicitly computing their coordinates in that space. Common examples include:

- **Linear Kernel:** $K(x, y) = x \cdot y$
- **Polynomial Kernel:** $K(x, y) = (1 + x \cdot y)^d$, where d is the degree of the polynomial.
- **Radial Basis Function (RBF) or Gaussian Kernel:** $K(x, y) = \exp(-\gamma \|x - y\|^2)$, where γ is a parameter that determines the spread of the kernel.

Benefits

- **Complexity**: It allows algorithms to harness the computational simplicity of linear methods while achieving the complexity of non-linear methods.
- **Feature Mapping**: It implicitly maps input data to high-dimensional feature spaces, enabling linear separation in that space.
- **Flexibility**: Different kernel functions can be chosen to suit the problem at hand, providing a versatile approach to handling various data distributions.

Conclusion

The kernel trick is a cornerstone in the realm of machine learning, particularly for

algorithms like SVMs, where it provides a potent mechanism to extend linear models to handle non-linear relationships without incurring prohibitive computational costs.

3. How to design a Kernel? What is the requirement of a kernel?

Designing a kernel function for machine learning algorithms, especially for support vector machines (SVMs) or any kernelized method, requires understanding the properties that the function must satisfy to be a valid kernel. The main requirement for a function to be considered a kernel is that **it must correspond to an inner product in some feature space**. This is formally captured by Mercer's theorem, which provides conditions under which a function can be considered a valid kernel.

Requirements for a Kernel Function

1. **Symmetry**: A kernel function $K(x, y)$ must be symmetric, which means $K(x, y) = K(y, x)$ for all x and y . This symmetry implies that the kernel matrix (or Gram matrix) is also symmetric.

2. **Positive Semidefiniteness**: For any finite set of points, the kernel matrix K generated by applying the kernel function to all pairs of points must be positive semidefinite. This means that for any non-zero vector a , it holds that $a^T K a \geq 0$. This requirement ensures that the optimization problems in algorithms like SVMs remain convex, allowing them to find global minima.

Designing a Kernel

1. **Direct Construction**: You can design a kernel by defining a feature mapping $\phi(x)$ and then setting $K(x, y) = \phi(x) \cdot \phi(y)$. However, the challenge is to ensure that the feature mapping leads to a valid kernel without explicitly computing high-dimensional feature vectors.

2. **Combining Existing Kernels**: Existing kernels can be combined to form new kernels. For example, if K_1 and K_2 are valid kernels, then $K(x, y) = aK_1(x, y) + bK_2(x, y)$ is also a valid kernel for any $a, b \geq 0$. Similarly, $K(x, y) = K_1(x, y) \times K_2(x, y)$ is a valid kernel.

3. **Kernel Transformations**: Functions of a kernel can also be kernels under certain conditions. For example, if K is a valid kernel, then $f(K)$ is a valid kernel for certain functions f , like exponential functions.

4. **Kernel from a Distance Function**: If you have a distance function $d(x, y)$ that satisfies the properties of a metric, you can sometimes construct a kernel from it. For example, the Gaussian kernel is derived from the Euclidean distance.

5. **Empirical Design**: In some cases, you might design a kernel empirically by considering the specific characteristics of your data and task. However, you'll need to ensure that the kernel satisfies the positive semidefiniteness condition.

6. **Validation**: After designing a kernel, it's important to validate it, typically by checking the positive semidefiniteness of the kernel matrix on sample data points. For complex kernels, theoretical proofs or empirical checks might be necessary to confirm that they meet the required conditions.

In summary, designing a kernel requires a careful balance between leveraging theoretical properties and considering practical aspects related to the data and problem at hand. Understanding the underlying feature space and ensuring that the kernel is valid and effective for the task are crucial steps in this process.

4. How to know whether a matrix is Positive definiteness?

Determining whether a matrix is positive definite is crucial in various areas, including optimization and machine learning. Here are several methods to check the positive definiteness of a matrix:

1. Eigenvalue Method

A matrix is positive definite if all its eigenvalues are positive. You can compute the eigenvalues of the matrix and check their signs. This method is straightforward but computationally intensive for large matrices.

- **Procedure**: Calculate the eigenvalues of the matrix A . If all eigenvalues are greater than zero, then A is positive definite.

2. Cholesky Decomposition

A matrix is positive definite if and only if it has a Cholesky decomposition. If an algorithm can decompose the matrix A into $A = LL^T$, where L is a lower triangular matrix with positive diagonal elements, then A is positive definite.

- **Procedure**: Attempt to perform a Cholesky decomposition on A . If the decomposition succeeds without encountering negative or zero pivots, then A is positive definite.

3. Sylvester's Criterion (Principal Minor Criterion)

For a Hermitian matrix (in the real case, symmetric), you can use Sylvester's Criterion: the matrix is positive definite if and only if all leading principal minors (determinants of the leading principal submatrices) are positive.

- **Procedure**: Compute all leading principal minors of the matrix. If each one is positive, then the matrix is positive definite.

4. Checking the Definition

Directly use the definition of positive definiteness: a symmetric matrix A is positive definite if, for any non-zero vector x , $x^T A x > 0$.

- **Procedure**: This is more of a theoretical check and less practical for numerical verification, but if you can show that $x^T A x > 0$ for all non-zero vectors x , then A is positive definite.

Practical Implementation

In practice, especially in programming and data analysis, the Cholesky decomposition and eigenvalue methods are commonly used. Libraries in programming languages like Python (e.g., NumPy, SciPy) provide built-in functions to perform these checks.

Here's an example in Python using NumPy to check if a matrix is positive definite using the eigenvalue method:

```
python
import numpy as np

def is_positive_definite(A):
    eigenvalues = np.linalg.eigvals(A)
    return np.all(eigenvalues > 0)

# Example matrix
A = np.array([[2, 1], [1, 2]])

print(is_positive_definite(A)) # Output: True if A is positive definite
```

Note that the matrix should be symmetric (or Hermitian in the complex case) to apply these methods meaningfully, as the definition of positive definiteness inherently assumes symmetry.

5. What is Radial Basis Function (RBF) kernel? Why the feature of RBF is infinite dimension?

The Radial Basis Function (RBF) kernel, often associated with the Gaussian kernel in the context of machine learning, is a popular kernel function used in various kernelized learning algorithms, including Support Vector Machines (SVMs) and kernel principal component analysis. The RBF kernel is defined as:

$$K(x, y) = \exp\left(-\frac{\|x - y\|^2}{2\sigma^2}\right)$$

where:

- $\|x\|$ and $\|y\|$ are two feature vectors in the input space,
- $\|x - y\|^2$ denotes the squared Euclidean distance between $\|x\|$ and $\|y\|$,
- σ is a parameter that determines the spread of the kernel. In machine learning, particularly in SVMs, this parameter is often denoted by $\frac{1}{2\gamma}$ where $\gamma > 0$.

Infinite Dimensional Feature Space

The RBF kernel corresponds to an inner product in an infinite-dimensional feature space. This is one of its most remarkable properties, allowing algorithms like SVMs to construct non-linear decision boundaries in the original input space.

The infinite-dimensional nature of the RBF kernel can be understood through its expansion into a series of basis functions. Specifically, when the RBF kernel is applied, it effectively maps the input data into an infinite-dimensional space where each dimension corresponds to a feature mapped by the Gaussian function centered at a different point in the input space. This mapping allows linear separation in this high-dimensional space, which corresponds to a non-linear separation in the original input space.

Why is the Feature Space Infinite?

The RBF kernel can be seen as an infinite sum of basis functions, each representing a dimension in the feature space. This is conceptually akin to the Fourier series, where a function is represented by an infinite sum of sines and cosines, each corresponding to a dimension in the function's frequency space.

The essence of why the RBF kernel maps to an infinite-dimensional space lies in its functional form. The Gaussian function, which constitutes the RBF kernel, does not limit the degree of features it can represent. Unlike polynomial kernels, where the degree of the polynomial determines the dimensionality of the feature space, the Gaussian function's smooth and continuous nature across all scales allows it to encapsulate an infinite number of dimensions.

Implications in Machine Learning

1. **Flexibility**: The RBF kernel provides a powerful way to capture complex patterns in the data, enabling learning algorithms to model non-linear relationships effectively.
2. **Kernel Trick**: Thanks to the kernel trick, algorithms can leverage this infinite-dimensional space without the need to explicitly compute the high-dimensional

mappings, making computations tractable even though they operate in an infinite-dimensional feature space.

3. **Tuning**: The parameter σ (or γ) plays a critical role in the performance of the kernel, influencing the decision boundary's smoothness and complexity. It needs to be carefully tuned, often using techniques like cross-validation.

The RBF kernel's ability to map data to an infinite-dimensional space is a key feature that underpins its utility and effectiveness in various machine learning tasks, enabling complex, non-linear decision-making based on linear methods in transformed space.

6. Can you explain it with Taylor expansion?

The explanation of why the Radial Basis Function (RBF) kernel corresponds to an infinite-dimensional feature space can be illustrated using a Taylor expansion, though typically, this explanation is more directly applied to kernels like the polynomial kernel. For the RBF kernel, the connection to an infinite-dimensional space is more intuitively understood through its series expansion, but let's delve into how a Taylor expansion relates to this concept.

Taylor Expansion of the Exponential Function

The RBF kernel uses the exponential function $\exp\left(-\frac{\|x-y\|^2}{2\sigma^2}\right)$. The exponential function e^z can be expanded using Taylor series around $z = 0$ as follows:

$$e^z = 1 + z + \frac{z^2}{2!} + \frac{z^3}{3!} + \dots$$

Now, applying this to the RBF kernel, where $z = -\frac{\|x-y\|^2}{2\sigma^2}$, we get an infinite series:

$$\exp\left(-\frac{\|x-y\|^2}{2\sigma^2}\right) = 1 - \frac{\|x-y\|^2}{2\sigma^2} + \frac{(\|x-y\|^2)^2}{2!(2\sigma^2)^2} - \frac{(\|x-y\|^2)^3}{3!(2\sigma^2)^3} + \dots$$

Interpretation in Feature Space

While this series itself does not directly demonstrate the feature space mapping like a polynomial expansion would (where each term corresponds to a feature in the polynomial kernel), it hints at the complexity and the multi-dimensional nature of the feature space induced by the RBF kernel. Each term in the series can be seen as contributing to a dimension in the feature space. However, unlike polynomial kernels, these aren't dimensions in the traditional sense where you have a clear x_1 , x_2 , etc., but rather more abstract dimensions related to the distance between points in the input space.

The infinite series implies that the RBF kernel is capturing interactions at all levels of complexity, from linear to infinitely complex, allowing the kernel to support learning in an

infinite-dimensional space. Each additional term in the Taylor series adds another dimension or feature, contributing to the ability of the RBF kernel to model complex, non-linear phenomena.

Conclusion

While the Taylor series expansion helps illustrate why the RBF kernel is so expressive, capturing the kernel's mapping to an infinite-dimensional space is more abstract than with polynomial kernels. The key takeaway is that the RBF kernel, through its infinite series expansion, can model complex, high-dimensional relationships in data, providing a powerful tool for kernel-based machine learning methods.

7. How many hyperparameters in RBF kernel based SVM? how to choose hyperparameters?

In a Support Vector Machine (SVM) using the Radial Basis Function (RBF) kernel, there are typically two main hyperparameters:

1. **C (Regularization Parameter)**: This hyperparameter trades off correct classification of training examples against maximization of the decision function's margin. For larger values of C , a smaller margin will be accepted if the decision function classifies all training points correctly. A lower C will encourage a larger margin, therefore a simpler decision function, at the cost of training accuracy. In other words, C behaves as a regularization parameter in the SVM.

2. **γ (Gamma) in the RBF Kernel**: The RBF kernel has a parameter γ which can be understood as the inverse of the radius of influence of samples selected by the model as support vectors. When γ is too large, the radius of the area of influence of the support vectors only includes the support vector itself and no amount of regularization with C will be able to prevent overfitting. When γ is very small, the model is too constrained and cannot capture the complexity or "shape" of the data. The mathematics behind this involves the Gaussian function, where γ is the inverse of the variance.

Choosing Hyperparameters:

1. **Grid Search with Cross-Validation**: A common approach for choosing C and γ is to perform a grid search. The idea is to try a range of values for C and γ , and evaluate the SVM's performance using cross-validation. The combination of C and γ that gives the best performance is chosen. This method is exhaustive and can be computationally expensive, but it is effective in finding good values for the hyperparameters.

2. **Random Search**: As an alternative to grid search, random search allows you to sample a given number of C and γ values from predefined distributions. This approach can be more efficient than grid search, especially when only a few hyperparameters affect the performance of the SVM.

3. **Domain Knowledge**: If you have some understanding of the data or the problem, this can sometimes guide the selection of hyperparameters. For example, if you know that the data is very noisy, you might choose a smaller γ to prevent the model from fitting to the noise.

4. **Heuristic Methods**: Some heuristic methods can be applied to choose an initial set of hyperparameters, such as using the median distance between points as a starting value for γ .

5. **Automated Hyperparameter Tuning Tools**: Tools like Bayesian optimization, genetic algorithms, or gradient-based optimization can be used to automate the search for the best hyperparameters.

Choosing the right hyperparameters is crucial as they significantly influence the performance of the SVM. The optimal hyperparameters can vary widely between different data sets and the specific task at hand, so there is generally no one-size-fits-all solution.

8. How to choose the kernel function in SVM?

Choosing the right kernel function in SVM is crucial because it can significantly influence the model's performance. The choice of kernel depends on the data distribution and the problem at hand. Here's a general guide to selecting a kernel function for SVM:

1. Linear Kernel

- **When to use**: If the data is linearly separable, you can use the linear kernel. It's simpler and computationally less intensive than other kernels.
- **Advantages**: Less prone to overfitting, easier to interpret, and faster to compute.
- **Use case**: High-dimensional spaces where the number of features is greater than the number of samples.

2. Polynomial Kernel

- **When to use**: If the data is not linearly separable and you suspect a certain degree of polynomial relationship between the features.
- **Parameters**: Degree of the polynomial and a coefficient term.
- **Advantages**: Can model more complex relationships than the linear kernel.
- **Use case**: When you have prior knowledge that data has polynomial features.

3. Radial Basis Function (RBF) Kernel

- **When to use**: When you have no prior knowledge about the data or when the data is not linearly separable. RBF can handle non-linear relationships well.
- **Parameters**: Gamma (γ), which defines how far the influence of a single training example reaches.
- **Advantages**: Very flexible, can model complex relationships.
- **Use case**: Most common choice, works well in many scenarios without prior domain knowledge.

4. Sigmoid Kernel

- **When to use**: Less common, can be used to model neural networks.
- **Advantages**: Mimics the behavior of neural network activation functions.
- **Use case**: Rarely used, but can be an option when trying to replicate neural network-like decision boundaries.

Choosing the Kernel: Steps and Tips

1. **Start with the Linear Kernel**: It's often recommended to start with the simplest model, which is the linear kernel. If the model performs well, there might be no need to move to more complex kernels.
2. **Cross-Validation**: Use cross-validation to compare the performance of different kernels. Keep an eye on overfitting, especially with more complex kernels like the RBF.
3. **Grid Search**: Perform a grid search to find the best combination of kernel parameters. For the RBF kernel, this would mean searching over different values of C and γ .
4. **Visualize the Data (if possible)**: If the dataset is not high-dimensional, try to visualize it to get an intuition about the separability of the classes.
5. **Consider Computational Resources**: More complex kernels like the RBF or polynomial kernel require more computational resources. If you're working with a very large dataset, the computational cost might be a limiting factor.
6. **Domain Knowledge**: If you have specific knowledge about the data or the problem, it might guide you in choosing a kernel. For example, if you know that the data has a certain type of non-linear relationship, you might choose a kernel that can model that relationship.

In practice, selecting the right kernel often involves a combination of these strategies, alongside empirical testing to find the kernel that offers the best performance for your specific dataset and problem.