## Introduction to Software Verification 236342, Homework 1

## Yosef Goren

## November 9, 2022

## 1

- A. Correct. Since the precondition is false, the postcondition is 'always' satisfied (since it is never tested).
- B. Incorrect. Counterexample x = -100, y = -99:
  - $l_0, -100, -99$
  - $l_1, -100, -99$
  - $l_2, -100, -99$
  - $l_3, -1, -99$
  - $l_*, -1, -99$

As can be seen, precondition is satisfied and postcondition is not.

- C. Correct. The postcondition is true, so regardless of anything else, for every input selection it will be evaluated as true (the program does not even have to terminate either).
- D. Incorrect. Counterexample x = 1, y = 9:
  - $l_0, 1, 9$
  - $l_1, 1, 9$
  - $l_2, -8, 9$
  - $l_3, -8, 9$
  - $l_*, -8, 9$

Postcondition is false, so it is not satisfied.

- E. Incorrect. Counterexample x = 1, y = 3:
  - $l_0, 1, 3$
  - $l_1, 1, 3$

- $l_2, 1, 3$
- $l_3, -2, 3$
- $l_4, -2, 3$
- $l_1, -2, -3$
- $l_2, -2, -3$
- $l_3, -2, -3$
- $l_4, -2, -3$
- $l_1, -2, 3$
- $l_2, -2, 3$
- $l_3, -5, 3$
- $l_4, -5, 3$
- F. Incorrect. Counterexample x=1,y=2, By running this example we see that the program gets stuck in a loop at labels  $l_1,l_2,l_3,l_4$ . And each 4 iterations result with the state being the same as the initial state at  $l_1$ . Since this is a total correcness condition on the specification, the correctness is contredicted by the program failing to terminate.