

# LISTS & DICTIONARIES

---

## LECTURE 05-2

JIM FIX, REED COLLEGE CSCI 121

## MORE ON PROJECT 1: GRID

- ▶ **REMINDER:** A checkpoint for **Project 1** is due **Thursday**.
  - ➡ Added a Gradescope problem to submit `rules.py` and `demo.py`
  - ➡ Just want to see that you've completed *three rules*.
- ▶ **NOTE:** I just updated the **Project 1** page.
  - ➡ There is an enhanced `Grid.py` available under "Set Up"..
    - Linked as `project1-with-save.zip`.
  - ➡ These enhancements are described under "Update"..
    - Can help you build a richer demo next week.
- ▶ **[[[DEMO of my SOLUTION and also some COOL RULES]]]**

# READING FOR PYTHON LISTS

- ▶ **Reading:**

- ➡ TP Ch 8-10

- ➡ CP Ch 2.1-2.4

# LIST "ARITHMETIC"

- ▶ We can build new lists from other list's contents using **+** and **\***:

```
>>> [1,2,17] + [111,8]
[1, 2, 17, 111, 8]
>>> [1,2,17] * 4
[1, 2, 17, 1, 2, 17, 1, 2, 17, 1, 2, 17]
>>> [1,2,17] + []
[1, 2, 17]
>>> [] + [1,2,17]
[1, 2, 17]
>>> [1,2,17] * 1
[1, 2, 17]
>>> [1,2,17] * 0
[]
>>> [] * 4
[]
>>> [] + []
[]
```

# LIST "SLICING"

- We can build new lists by copying portions of other lists:

```
>>> xs = [45,1,8,17,100,6]
>>> xs
[45, 1, 8, 17, 100, 6]
>>> xs[2:5]           # Build a new list from the 2,3,4 slice.
[8, 17, 100]
>>> xs[2:4]           # Build a new list from the 2,3 slice.
[8, 17]
>>> xs[:4]            # Build a new list from the 0,1,2,3 slice.
[45, 1, 8, 17]
>>> xs[4:]            # Build a new list from the 4,5 slice.
[100, 6]
>>> ys = xs[:]         # Build a new list as a full copy.
>>> xs[1] = 121
>>> xs
[45, 121, 8, 17, 100, 6]
>>> ys
[45, 1, 8, 17, 100, 6]
```

**SLICING** [start:stop:step]

- default values are [0, len, 1]
- or [-1, -(len+1), -1]

# LISTS OF LISTS

- Lists can be stored within other lists.

```
>>> lls = [[45,19],[8],[17,100,6],[]]
>>> lls[2]
[17, 100, 6]
>>> lls[2][0]
17
>>> lls[2][0] = 7777
>>> lls
[[45, 19], [8], [7777, 100, 6], []]
>>> lls[0].pop()
19
>>> lls[0].extend([0,0,0])
>>> lls
[[45,19,0,0,0],[8],[7777,100,6],[]]
>>> lls.append([5,4,3,2])
>>> lls
[[45, 19, 0, 0, 0], [8], [7777, 100, 6], [], [5, 4, 3, 2]]
```

## TWO PRINTING PROCEDURES

- ▶ This procedure outputs the contents of a list.

```
def output_using_while(xs):  
    i = 0  
    while i < len(xs):  
        print(xs[i])  
        i = i + 1
```

- ▶ This procedure also outputs the contents of a list.

```
def output_using_for(xs):  
    for x in xs:  
        print(x)
```

## WHILE VS. FOR LOOPS IN GENERAL

- ▶ This code snippet prints 0, 1, 2, 3, 4 (one number per line)

```
i = 0
while i < 5:
    print(i)
    i = i + 1
```

- ▶ This code snippet also prints 0, 1, 2, 3, 4 (one number per line)

```
for i in range(5)
    print(i)
```

`range(start, stop, step)`

- default values are `start = 0` and `step = 1` and optional
- loop until value is `stop - 1`



---

# WHILE VS. FOR LOOPS

## WHILE loops

- ▶ **unbounded** number of iterations
- ▶ can end early via **break**
- ▶ can use a **counter** but must **initialize** before loop and increment it inside loop
- ▶ may not be able to **rewrite** a while loop using a FOR loop

## FOR loops

- ▶ **know** number of iterations
- ▶ can end early via **break**
- ▶ uses a **counter** or **list** or **dict**
- ▶ can **rewrite** a for loop using a while loop

# PYTHON LIST SUMMARY ENHANCED WITH FOR

- ▶ List creation via enumeration, concatenation, repetition, slicing:

```
[3,1,7]    []    [1,2]+[3,4,5]    [1,2]*4    xs[3:5]    xs[3:]    xs[:]
```

- ▶ Accessing contents by index; list length:

```
xs[3]    xs[-1]    len(xs)
```

- ▶ Updating contents by indexed assignment:

```
xs[3] = 5
```

- ▶ Modifying/mutating a list object:

```
xs.append(5)    xs.extend([8,9,10])    xs.insert(2,357)  
xs.pop()        del xs[6]
```

- ▶ Checking membership, content equality, object identity:

```
3 in xs    xs == [1,2,3]    xs is ys
```

- ▶ Scan according to index using a **while** loop.

- ▶ Loop through the contents using a **for** loop.

# OUR SECOND DATA STRUCTURE: DICTIONARIES

- ▶ Python lets you store a collection of *associations*

```
>>> d = {"bob":35, "mel":24, "betty":29}
>>> d
{'bob': 35, 'mel': 24, 'betty': 29}
>>> d['bob']
35
>>> d['mel']
24
```

← CREATE

← READ

- ▶ This is a built-in data structure called a Python *dictionary*.
  - ➡ A dictionary contains a collection of *entries*.
  - ➡ The left part of each entry is called its *key*.
  - ➡ The right part is that key's *associated value*.
  - ➡ There is *at most one entry* for a key.
- A Python dictionary is our 2nd explicit example of a Python (data) *object*

# DICTIONARIES

- ▶ Python lets you store a collection of *associations*

```
>>> d = {"bob":35, "mel":24, "betty":29}
>>> d
{'bob': 35, 'mel': 24, 'betty': 29}
>>> d['bob']
35
>>> d['mel']
24
```

- ▶ This is a built-in data structure called a Python **dictionary**.
  - ➡ It's also called a "**key-value mapping**", or sometimes just a "map".
  - ➡ Sometimes it's called a "**hash table**" or just "**hashmap**".
- In some languages, you mimic a dictionary with an "association list":

```
d = [{"bob", 35}, {"mel", 24}, {"betty", 29}]
```

# MODIFYING A DICTIONARY'S CONTENTS

- ▶ A Python dictionary is also a *mutable* data structure.
  - ➡ You can add new key-value pairs, or modify the associated value to a key.
  - ➡ The syntax for **adding a new entry** and **updating an existing entry** is the same

```
>>> d = {"bob":35, "mel":24, "betty":29}
>>> d
{'bob': 35, 'mel': 24, 'betty': 29}
>>> d['mel']
24
>>> d['mel'] = 25
>>> d['mel']
25
>>> d
{'bob': 35, 'mel': 25, 'betty': 29}
>>> d['lou'] = 87
>>> d
{'bob': 35, 'mel': 24, 'betty': 29, 'lou': 87}
```



UPDATE

# DICTIONARY CONTENT CHECKS

```
>>> d = {"bob":35, "mel":24, "betty":29, "lou": 87}
>>> 'mel' in d          # Does the dictionary contain a key?
True
>>> 'jim' in d
False
>>> 35 in d
False
>>> e = {"lou": 87, "mel":24, "betty":29, "bob":35}
>>> e == d              # Are the dictionary's contents the same?
True
>>> e is d              # Are they the same object?
False
>>> len(d)              # Get the number of entries.
4
```

# BUILDING AND MODIFYING A DICTIONARY

```
>>> d = {}  
>>> d['bob'] = 35  
>>> d['betty'] = 29  
>>> d['mel'] = 24  
>>> d  
{'bob': 35, 'mel': 24, 'betty': 29}  
>>> del d['betty']  
>>> d  
{'bob': 35, 'mel': 24}
```



DELETE

# LOOPING

```
>>> d = {}
>>> d = {"bob":35, "betty":29, "mel":24}
>>> for k in d:
...     print(k + " -> " + str(d[k]))
...
bob -> 35
betty -> 29
mel -> 24
>>>
```

- ▶ A **for** loop runs through the **keys** of the dictionary.
  - ➡ You can then look up the associated value.



# PYTHON DICTIONARY SUMMARY

- ▶ List **creation** via enumeration of some associations:

```
{ 'a':89, 'b':4 }      {}
```

- ▶ **Accessing** contents by key; dictionary **size**:

```
d['a']                len(d)
```

- ▶ **Updating** an entry's associated value with key re-assignment:

```
d['a'] = 88
```

- ▶ Modifying/**mutating** a dictionary to add/remove entries:

```
d['c'] = 111
```

```
del d['b']
```

- ▶ Checking **key inclusion**, content **equality**, object **identity**:

```
'a' in d              d == {'e':78}          d1 is d2
```

- ▶ **Loop through the keys** using a **for** loop.

---

# LIST VS. DICTIONARY

## LIST

- ▶ **ordered** sequence of elements
- ▶ look up an element by an **integer index**
- ▶ indices have an **order**
- ▶ index is an **integer**

## DICTIONARY

- ▶ **matches** “keys” to “values
- ▶ look up an item by another **item**
- ▶ **no order** is guaranteed
- ▶ key can be any **immutable** type