

ITERATION

LECTURE 03-1

JIM FIX, REED COLLEGE CSCI 121

ITERATION WITH LOOPS

- ▶ We look at code that uses *iteration* or *loop* statements.
 - ➡ In Python, these are the **while** and **for** statements.
 - ➡ These statements allow us to repeat actions several times.
 - ✦ *Definite* loops: perform an action several times.
 - ✦ *Indefinite* loops: perform an action until a condition is met.
- ▶ **Reading** for this week's material:
 - ✦ TP Ch 5
 - ✦ CP Ch 1.5

UNROLLING LOOPS

AN INFINITE LOOP

- ▶ Python lets you execute the same statement repeatedly with a **while** loop statement. For example:

```
print("This line runs once, first.")  
while True:  
    print("This line keeps getting run.")  
print("This line never runs.")
```

- ▶ Output of the script above:

```
This line runs once, first.  
This line keeps getting run.  
This line keeps getting run.  
This line keeps getting run.  
This line keeps getting run.  
...
```

- ▶ **NOTE:** hit [CTRL-c] to terminate the Python script's execution.

MORE LOOPING FOREVER

- ▶ The prior example loops forever. And so does this one:

```
print("This line runs once, first.")
while True:
    print("This line keeps getting run.")
    print("And so does this one.")
print("This line never runs.")
```

- ▶ Output of the script above:

```
This line runs once, first.
This line keeps getting run.
And so does this one.
This line keeps getting run.
And so does this one.
This line keeps getting run.
And so does this one.
```

...

LOOPING, UNROLLED

- The behavior of that script is like this infinite script:

```
print("This line runs once, first.")
print("This line keeps getting run.")
print("And so does this one.")
print("This line keeps getting run.")
print("And so does this one.")
print("This line keeps getting run.")
print("And so does this one.")
print("This line keeps getting run.")
print("And so does this one.")
...
```

LOOPING, UNROLLED

- ▶ Well, technically, it's more like this infinite script:

```
print("This line runs once, first.")
if True:
    print("This line keeps getting run.")
    print("And so does this one.")
    if True:
        print("This line keeps getting run.")
        print("And so does this one.")
        if True:
            print("This line keeps getting run.")
            print("And so does this one.")
            if True:
                ...

print("This line never runs.")
```

COUNTING FOREVER

- ▶ The prior example loops forever. And so does this one:

```
hellos_said = 0
while True:
    print("Hello!!!")
    hellos_said = hellos_said + 1
    print("That was 'hello' #" + str(hellos_said) + ".")
print("This line never runs.")
```

- ▶ Output of the script above:

```
Hello!!!
That was 'hello' #1.
Hello!!!
That was 'hello' #2.
Hello!!!
That was 'hello' #3.
Hello!!!
That was 'hello' #4.
...
```


COUNTING FOREVER, UNROLLED

- ▶ Well, technically, it's more like this infinite script:

```
hellos_said = 0                                # sets to 0
if True:
    print("Hello!!!")
    hellos_said = hellos_said + 1                # sets to 1
    print("That was 'hello' #" + str(hellos_said) + ".")
    if True:
        print("Hello!!!")
        hellos_said = hellos_said + 1            # sets to 2
        print("That was 'hello' #" + str(hellos_said) + ".")
        if True:
            print("Hello!!!")
            hellos_said = hellos_said + 1        # sets to 3
            print("That was 'hello' #" + str(hellos_said) + ".")
            if True:
                ...
```

COUNTING ONLY SO FAR

- ▶ This outputs a count from 0 up to 5:

```
print("I'm going to count for you.")
count = 0
while count < 6:
    print(count)
    count = count + 1
print("I'm done counting now.")
```

- ▶ Output of the script above:

```
I'm going to count for you.
0
1
2
3
4
5
I'm done counting now.
```

COUNTING ONLY SO FAR

- ▶ This outputs a count from 0 up to **2**:

```
print("I'm going to count for you.")  
count = 0  
while count < 3:  
    print(count)  
    count = count + 1  
print("I'm done counting now.")
```

- ▶ Output of the script above:

```
I'm going to count for you.  
0  
1  
2  
I'm done counting now.
```

UNROLLED

- Here is an unrolling of that loop's code:

```
print("I'm going to count for you.")
count = 0                                # sets to 0
if count < 3:
    print(count)
    count = count + 1                    # sets to 1
    if count < 3:
        print(count)
        count = count + 1                # sets to 2
        if count < 3:
            print(count)                  # never happens
            count = count + 1              # sets to 4; never happens
            if count < 3:
                ...
print("I'm done counting now.")
```

COUNTING ACCORDING TO AN INPUT

- ▶ This outputs a count from 0 up to some input value:

```
print("I'm going to count for you.")
max = int(input("Enter how far you'd like me to count: "))
count = 0
while count <= max:
    print(count)
    count = count + 1
print("I'm done counting now.")
```

- ▶ Output of the script above:

```
I'm going to count for you.
Enter how far you'd like me to count: 4
0
1
2
3
4
I'm done counting now.
```

ANATOMY OF A WHILE LOOP

- ▶ The template below gives the syntax of a while loop statement:

lines of statements to execute first

while *condition-expression*:

 *lines of statements to execute if the condition holds*

...

lines of statements to executed when the condition no longer holds

EXECUTION OF A WHILE LOOP

- ▶ The template below gives the syntax of a while loop statement:

lines of "set up" statements to execute first

while *condition-expression* :

lines of "loop body" statements to execute if the condition holds

...

lines of "follow up" to execute when the condition no longer holds

- ▶ Here is how Python executes this code:

1. Executes the **set up** code.
2. It evaluates the **condition**. If **False** it *skips* to **Step 5**.
3. Otherwise, if **True**, it evaluates the **loop body**'s code.
4. It goes back to **Step 2**.
5. It executes the **follow up**, and subsequent, code.

ANATOMY OF A COUNTING LOOP

- ▶ Here is the standard structure of a "counting loop":

*initialize the **count** to the **start-value***

while **count** < **one-too-far**:

*actions to perform with that particular **count** value*

*increment the **count** by 1*

*at this point can now use the fact that **count** == **one-too-far***

- ▶ This is an extremely common coding pattern...

➡ **PLEASE TAKE THIS TEMPLATE TO HEART!!!!**

DEFINITE VS. INDEFINITE LOOPS

► Some terminology:


- "*Count up to 6.*" and "*Count up to the input value.*" are examples of *definite* loops.
- "*Get an input until they've entered something valid.*" is an example of an *indefinite* loop. The number of repetitions isn't known.

► An example of the second kind of coding:

```
def get_float(prompt):  
    return float(input(prompt))
```

Note that the loop body might not run at all!

```
def get_area():  
    a = get_float("Circle area? ")  
    while a < 0.0:  
        a = get_float("Not an area. Try again:")  
    return a
```



NESTING CONTROL STATEMENTS WITHIN A LOOP

- Of course you can put a conditional statement within a loop's body.

```
count = 0
while count < 6:
    if count % 2 == 0:
        print(str(count) + " is even.")
    else:
        print(str(count) + " is odd.")
    count = count + 1
print("Done.")
```

- Output of the script above:

```
0 is even.
1 is odd.
2 is even.
3 is odd.
4 is even.
5 is odd.
Done.
```

NESTED LOOPS

NESTING A LOOP WITHIN A LOOP

- ▶ Nested loops are a common programming pattern:

```
a = 0
while a < 6:
    b = 0
    while b < 8:
        print(str(a)+str(b),end=" ")
        b = b + 1
    print()
    a = a + 1
print("Done.")
```

- ▶ *What does this do???*

NESTING A LOOP WITHIN A LOOP

- ▶ Nested loops are a common programming pattern:

```
a = 0
while a < 6:
    b = 0
    while b < 8:
        print(str(a)+str(b),end=" ")
        b = b + 1
    print()
    a = a + 1
print("Done.")
```

- ▶ *It outputs a sequence of digit pairs, separated by spaces:*

```
00 01 02 03 04 05 06 07
10 11 12 13 14 15 16 17
20 21 22 23 24 25 26 27
30 31 32 33 34 35 36 37
40 41 42 43 44 45 46 47
50 51 52 53 54 55 56 57
Done.
```

NESTING A LOOP WITHIN A LOOP

- ▶ Nested loops are a common programming pattern:

```
a = 0
while a < 6:
    b = 0
    while b < 8:
        print(str(a)+str(b), end=" ")
        b = b + 1
    print()
    a = a + 1
print("Done.")
```

Inner loop, along with set-up/follow-up

- ▶ *It outputs a sequence of digit pairs, separated by spaces:*

```
00 01 02 03 04 05 06 07
10 11 12 13 14 15 16 17
20 21 22 23 24 25 26 27
30 31 32 33 34 35 36 37
40 41 42 43 44 45 46 47
50 51 52 53 54 55 56 57
Done.
```

Outer loop, along with set-up/follow-up

NESTING A LOOP WITHIN A LOOP

- ▶ Nested loops are a common programming pattern:

```
a = 0
while a < 6:
    b = 0
    while b < 8:
        print(str(a)+str(b), end=" ")
        b = b + 1
    print()
    a = a + 1
print("Done.")
```

Executed once for each value of a.

Inner loop, along with set-up/follow-up

- ▶ *It outputs a sequence of digit pairs, separated by spaces:*

```
00 01 02 03 04 05 06 07
10 11 12 13 14 15 16 17
20 21 22 23 24 25 26 27
30 31 32 33 34 35 36 37
40 41 42 43 44 45 46 47
50 51 52 53 54 55 56 57
Done.
```

Outer loop, along with set-up/follow-up

BREAKING OUT OF A LOOP

BREAKING OUT OF A LOOP

- ▶ Here is another way of writing the counting loop.

```
print("Counting from 0 to 5:")
count = 0
while True:
    if count >= 6:
        break
    print(count)
    count = count + 1
print("Done.")
```

- ▶ The code uses a **break** statement to jump down to the follow-up code.
- ▶ If within several loops, it jumps to just after the innermost one.
- ▶ This is an artificial example

USING CONDITION VARIABLES TO GOVERN LOOPING

- ▶ Using **break** to express other break-out conditions:

```
while count < 6:
    if somethingElseMakesMeStop(...):
        break
    ...
    count = count + 1
print("Done.")
```

- ▶ I worry that **break** can sometimes be missed by other coders.
- ▶ I usually prefer using explicit break-out conditions instead, like so:

```
done = False
while !done and count < 6:
    if somethingElseMakesMeStop(...):
        done = True
    if not done:
        ...
        count = count + 1
print("Done.")
```

USING CONDITION VARIABLES TO GOVERN LOOPING

- ▶ Using **break** to express other break-out conditions:

```
while count < 6:  
    if somethingElseMakesMeStop(...)  
        break
```

PLEASE use break sparingly, and with taste.

```
    count = count + 1  
print("Done.")
```

- ▶ I worry that **break** can sometimes be missed by other coders.
- ▶ I usually prefer using explicit break-out conditions instead, like so:

```
done = False  
while !done and count < 6:  
    if somethingElseMakesMeStop(...)  
        done = True  
    if not done:  
        ...  
        count = count + 1  
print("Done.")
```

USING RETURN WITHIN A LOOP

- ▶ This procedure uses **return** to exit its loop and the procedure:

```
def countUpTo(n)
    count = 1
    while True:
        if count > n:
            return
        print(count)
        count = count + 1
```

- ▶ The **return** statement breaks out of the loop and returns back to the place where **countUpTo** was called.

SUMMARY

- ▶ The while loop statement expresses **iterative** code.
 - ➡ Allows you to perform a series of actions *until* a condition holds.
 - ➡ The negation of this *terminating condition* is the loop's condition.
- ▶ It's possible for the code to loop forever. This is an **infinite** loop.
- ▶ Counting loops are common examples of **definite** loops.
- ▶ Loops that iterate an undetermined number of times are **indefinite**.

SUMMARY (CONT'D)

- ▶ Loop bodies can contain other control statements:
 - For example, you can have **if** statements or other **while** statements.
 - If another loop statement is inside, then it is a **nested loop**.
 - If a **break** statement, we can jump out of the loop mid-body.
 - If a **return** statement, we exit the loop *and* the function/procedure.