## 1. Identification of The Substance or Mixture and The Supplier

| | |
|---|---|
| **Product**<br>Substance or Trade Name | <br>BCP 80/100 |
| **Recommended Use** | De-aromatized Hydrocarbon |
| **Details of the Supplier of the Safety Data Sheet**<br>Company Name<br>Address<br><br>Telephone<br>Fax | <br>Bangchak Corporation Public Company Limited<br>2098 M Tower Building, 8th floor, Sukhumvit Road,<br>Phra Khanong Tai, Phra Khanong, Bangkok 10260 Thailand<br>+66 2335 4999<br>+66 2016 3991 |
| **Emergency Number** | +66 2335 8888 |

## 2. Hazards Identification

**Classification of the Mixture according to Globally Harmonized System (GHS) Standards.**

| | |
|---|---|
| Flammable Liquid | Category 2 |
| Skin Corrosion/Irritation | Category 2 |
| Central Nervous System Toxicity | Category 3 |
| Aspiration Hazard | Category 1 |
| Acute Aquatic Toxicity | Category 2 |
| Chronic Aquatic Toxicity | Category 2 |

**GHS Label Elements**

**Signal Word**: Danger

**Hazard Statements:**

H225 – Highly flammable liquid and vapor.

H304 – May be fatal if swallowed and enters airways.

H315 – Causes skin irritation.

H336 – May cause drowsiness or dizziness.

H411 – Toxic to aquatic life with long lasting effects.

**Precautionary Statements:**

P210 – Keep away from heat/sparks/open flames/hot surfaces. -- No smoking.

P233 – Keep container tightly closed.

P240 – Ground/bond container and receiving equipment.

P241 – Use explosion-proof electrical, ventilating and lighting equipment.

P242 – Use only non-sparking tools.

P243 – Take precautionary measures against static discharge.

P264 – Wash skin thoroughly after handling.

P271 – Use only outdoors or in a well- ventilated area.

P273 – Avoid release to the environment.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352 – IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353 – IF ON SKIN (or hair):Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 – Call a POISON CENTER or doctor/physician if you feel unwell.

P331 – Do NOT induce vomiting.

P332 + P313 – If skin irritation occurs: Get medical advice/attention.

P362 + P364 – Take off contaminated clothing and wash it before reuse.

P370 + P378 – In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.

P391 – Collect spillage.

P403 + P235 – Store in a well-ventilated place. Keep cool.

P405 – Store locked up.

P501 – Dispose of contents and container in accordance with local regulations.

**Other Hazards:**

| | |
|---|---|
| Physical/Chemical: | Material can accumulate static charges which may cause an ignition. Material can release vapors that readily form flammable mixtures. Vapor accumulation could flash and/or explode if ignited. |
| Health: | Excessive exposure to normal hexane may affect peripheral nerves, causing weakness or numbness in the legs. It may also irritate the eyes, nose, throat, and lungs, and could lead to decreased central nervous system function. |
| Environmental: | No additional hazards. |

## 3. Composition/Information on Ingredients

This material is defined as a mixture.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure**

| No. | Component | CAS No. | Content (%) |
|---|---|---|---|
| 1 | Naphtha (Petroleum), Hydrotreated Light | 64742-49-0 | 100 |

**Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure**

| No. | Component | CAS No. | Content (%) |
|---|---|---|---|
| 1 | Cyclohexane | 110-82-7 | 15 - 35 |
| 2 | Heptane and Isomers | Isomer Mixtures | 25 - 40 |
| 3 | Methylcyclohexane | 108-87-2 | 1 - 25 |
| 4 | n-Hexane | 110-54-3 | < 15 |

## 4. First Aid Measures

| | |
|---|---|
| **Inhalation** | Avoid further contact. For those providing assistance, avoid touching both yourself and others. Wear appropriate respiratory protection. If airway irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical attention. If breathing stops, perform artificial respiration using a ventilator or mouth-to-mouth resuscitation. |
| **Skin Contact** | Wash the affected area with soap and water. Remove contaminated clothing. Wash the contaminated clothing before reusing it. |
| **Eye Contact** | Rinse thoroughly with clean water. If irritation occurs, seek medical attention immediately. |
| **Ingestion** | Seek immediate medical attention. Do not induce vomiting. |
| **Note to Physician** | If ingested, the substance may be absorbed into the lungs and cause chemical pneumonia, requiring appropriate treatment. This substance or components of it may be associated with cardiac stimulation if exposed to very high doses (above the allowable workplace exposure limit) or when combined with stimulants such as epinephrine. Use of such substances should be avoided. |
| **Pre-existing Medical Conditions** | This product contains hexane. Individuals with pre-existing neurological conditions should avoid contact. |

## 5. Fire Fighting Measures

| | |
|---|---|
| **Suitable Extinguishing Media:** | Foam, dry chemical, or carbon dioxide ($CO_2$) |
| **Unsuitable Extinguishing Media:** | Straight streams of water. |
| **Required Special Protective Equipment for Fire-fighters:** | Risk of violent reaction or explosion. Vapors may form an explosive mixture with air. Vapors may drift to ignition sources and ignite. Most vapors are heavier than air, spreading along surfaces and accumulating in low-lying or enclosed areas. Explosive hazard of vapors indoors, outdoors, or in sewers. Containers may explode when heated. |
| **Special Protective Equipment and Precautions for Firefighters:** | Standard protective equipment should be used, and self-contained breathing apparatus (SCBA) should be used in enclosed areas. Water can be used to reduce the temperature of surfaces exposed to the fire and to protect personnel. |

## 6. Accidental Release Measure

| | |
|---|---|
| **Personal Precautions:** | Avoid contact with the spilled substance. Warning or evacuating those in the surrounding area and downwind areas, if necessary, as the substance is toxic or highly flammable. Additional precautions may be required depending on the specific situation and/or at the discretion of emergency rescue experts. |
| **Environmental Precautions:** | Large Spills: Construct a barrier far from the point of spillage for easier cleanup and disposal later. Prevent the liquid from flowing into water sources, sewers, basements, or enclosed areas. |
| **Methods for Cleaning:** | Absorb or cover with dry soil, sand, or other non-combustible material. Use clean, non-sparking tools to collect absorbed material and transfer it to a disposal container. Close drains. Collect, bundle, and pump out spilled liquid. |

## 7. Handling and Storage

| | |
|---|---|
| **Handling:** | Avoid inhaling aerosols or vapors. Avoid skin contact. Prevent contact with ignition sources, such as using non-sparking tools and explosion-proof equipment. Potentially toxic/irritating fumes/vapors may be generated from heated or mixed materials. Use only in well-ventilated areas. Prevent minor spills and leaks to avoid slip hazards. The material may accumulate static electricity, which may cause sparks (ignition source). Use proper |

| | |
|---|---|
| | grounding and/or earthing connections. However, grounding and earthing connections may not completely eliminate the hazard of static electricity buildup.<br><br>Please consult relevant local standards for guidance. Additional references include the American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents), National Fire Protection Agency 77 (Recommended Practice on Static Electricity), or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity). |
| **Storage:** | No data available. |
| **Storage Temperature:** | Ambient temperature |
| **Other Information:** | No data available. |

## 8. Exposure Controls/Personal Protection

| | |
|---|---|
| **Engineering Measures:** | The level of protection and type of controls required will vary depending on the potential exposure conditions.<br><br>Control measures to consider: Adequate ventilation should be provided to avoid exceeding exposure limits. Use explosion-proof ventilation; provide localized air extraction. |
| **Personal Protection** | |
| **Respiratory Protection:** | If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: No protection is ordinarily required under normal conditions of use and with adequate ventilation. Half-face filter respirator Type A filter material.<br><br>For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded. |
| **Eye Protection:** | Safety glasses with side shields. |

| | |
|---|---|
| **Hand Protection:** | Chemical/oil resistant clothing. |
| **Hygiene Measures:** | Always practice good personal hygiene, such as washing hands after touching materials and before eating, drinking, and/or smoking. Work clothes and protective equipment should be washed regularly to remove contaminants. Discard contaminated clothing and shoes that cannot be cleaned. Maintain cleanliness within the building. |

## 9. Physical and Chemical Properties

| | |
|---|---|
| **Physical:** | Liquid |
| **Color:** | Colorless |
| **Odor:** | Slightly |
| **Density:** | 0.730 kg/L at 15 ºC |
| **Relative Density:** | 0.73 with respect to water at 15 ºC |
| **Pour Point:** | No data available. |
| **Freezing Point:** | No data available. |
| **Flash Point:** | -18 ºC |
| **Boiling Point:** | 79 - 96 ºC |
| **Melting Point:** | No data available. |
| **Auto-ignition Temperature:** | 258 ºC |
| **Decomposition Temperature:** | No data available. |
| **Vapor Pressure:** | 10 kPa at 20 ºC |
| **Flammable Limits:** | Min (LFL) % : 1.1 % v/v<br>Max (UFL) % : 8.0 % v/v |
| **Flammability:** | No data available. |
| **Evaporation Rate:** | No data available. |
| **pH:** | No data available. |
| **Solubility:** | No data available. |
| **Viscosity:** | 0.7 cSt at 20 ºC<br>0.6 cSt at 40 ºC |
| **Molecular Weight:** | No data available. |
| **Coefficient of Thermal Expansion:** | No data available. |
| **Octanol-water Partition Coefficient (Log $P_{ow}$):** | No data available. |

## 10. Stability and Reactivity

| | |
|---|---|
| **Stability:** | Material is stable under normal conditions, but needs to avoid heat, sparks, flames, and other sources of ignition. |
| **Materials to Avoid:** | Strong oxidizing agents. |
| **Hazardous Decomposition Products:** | Material does not decompose at room temperature. |

## 11. Toxicological Information

| **Acute Toxicity** | |
|---|---|
| **Oral** | No data available. |
| **Dermal** | No data available. |
| **Inhalation** | No data available. |
| **Skin Corrosion/Irritation** | It can cause skin irritation. |
| **Eye Damage/Irritation** | It may cause slight eye discomfort and is only temporary. |
| **Germ Cell Mutagenicity** | It is not expected to be a mutagen in germ cells. |
| **Carcinogenicity** | It is not expected to cause cancer. |
| **Reproductive Toxicity** | It is not expected to be toxic to the reproductive system. |
| **Specific Target Organ Toxicity - Single Exposure** | It may cause drowsiness or dizziness. |
| **Specific Target Organ Toxicity - Repeated Exposure** | Prolonged or repeated exposure is not expected to cause organ damage. |
| **Aspiration hazard** | It can be fatal if it is swallowed and enters the airway. |

## 12. Ecological Information

| | |
|---|---|
| **Ecotoxicity** | Expected to be toxic to aquatic life and may cause long-term harm to the aquatic environment. |
| **Persistence and Degradability** | Expected to be easily biodegradable in nature and decompose rapidly in the air. |
| **Bio-accumulative Potential** | No data available. |
| **Mobility** | It is highly volatile and disperses rapidly in the air; it is not expected to disperse in the sediment and solids in wastewater. |
| **Other Adverse Effects** | No data available. |

## 13. Disposal Considerations

| | |
|---|---|
| **Waste Disposal** | Suitable for incineration in controlled, enclosed furnaces for use as fuel or for disposal by supervised incineration at very high temperatures to prevent the formation of undesirable combustion products. |
| **Container Disposal** | Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractors and in accordance with government regulations.<br><br>Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. they may explode and cause injury or death. |

## 14. Transport Information

Dangerous for Conveyance unless the Flash Point is known to be greater than 61 ºC.

| **Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)** | |
|---|---|
| UN Number | UN 3295 |
| Proper Shipping Name | HYDROCARBONS, LIQUID, N.O.S. |
| Hazard Class | 3 |
| Packing Group | II |
| Hazchem Code | 3YE |
| Labels | 3, EHS |
| **International Maritime Dangerous Goods (IMDG)** | |
| UN Number | UN 3295 |
| Proper Shipping Name | HYDROCARBONS, LIQUID, N.O.S. (heptane & Isomers) |
| Hazard Class | 3 |
| Packing Group | II |
| Labels | 3 |
| EmS Number | F-E, S-D |
| Marine Pollutant | Yes |
| Document Name used for Transportation | UN3295, HYDROCARBONS, LIQUID, N.O.S.<br>(heptane & Isomers), 3, PG II, (-18°C c.c.), MARINE POLLUTANT |

| International Air Transport Association (IATA) | |
|---|---|
| UN Number | UN 3295 |
| Proper Shipping Name | HYDROCARBONS, LIQUID, N.O.S. |
| Hazard Class | 3 |
| Packing Group | II |
| Labels | 3 |
| Document Name used for Transportation | UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, PG II |

## 15. Regulatory Information

This material is considered hazardous according to the classification criteria of the Hazard Classification and Communication System for Hazardous Materials BE 2555 but not regulated by Hazardous Substance Act BE 2535.

## 16. Other Information

Issue Date: 27 May 2009

Revision Date: 2 February 2026

**Reference**

1. National Institute of Technology and Evaluation (SAFE NITE)

http://www.safe.nite.go.jp/english/ghs/ghs_index.html

2. Globally Harmonized System of Classification and Labelling of Chemical (GHS), United Nation, 2011

The information contained herein is to the best of our knowledge accurate, but since the circumstances and conditions in which it may be used are beyond our control, we do not accept liability for any loss or damage, however arising, which results directly or indirectly from the use of such information, nor do we offer any warranty of immunity against patent infringement.