## 1. Identification of The Substance or Mixture and The Supplier

| | |
|---|---|
| **Product**<br>Substance or Trade Name | D80 (Dearomatized Hydrocarbon) |
| **Recommended Use** | Solvent |
| **Details of the Supplier of the Safety Data Sheet** | |
| Company Name | Bangchak Corporation Public Company Limited |
| Address | 2098 M Tower Building, 8th floor, Sukhumvit Road,<br>Phra Khanong Tai, Phra Khanong, Bangkok 10260 Thailand |
| Telephone | +66 2335 4999 |
| Fax | +66 2016 3991 |
| **Emergency Number** | +66 2335 8888 |

## 2. Hazards Identification

**Classification of the Mixture according to Globally Harmonized System (GHS) Standards.**

| | |
|---|---|
| Flammable Liquid | Category 4 |
| Aspiration Toxicant | Category 1 |

**GHS Label Elements**

**Signal Word**: Danger

**Hazard Statements:**

H227 – Combustible liquid.

H304 – May be fatal if swallowed and enters airways.

**Precautionary Statements:**

P210 – Keep away from flames and hot surfaces. No smoking.

P280 – Wear protective gloves and eye / face protection.

P301 + P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 – Do NOT induce vomiting.

P370 + P378 – In case of fire: Use water fog, foam, dry chemical or carbon dioxide ($CO_2$) to extinguish.

P403 + P235 – Store in a well-ventilated place. Keep cool.

P405 – Store locked up.

P501 – Dispose of contents and container in accordance with local regulations.

**Other hazards**

Material can accumulate static charges which may cause an ignition.

Material can release vapors that readily form flammable mixtures.

Vapor accumulation could flash and/or explode if ignite.

Mildly irritating skin, eyes, nose, throat and lungs.

May cause central nervous system depression.

## 3. Composition/Information on Ingredients

This material is defined as a mixture.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure**

| No. | Component | CAS No. | Content (%) |
|---|---|---|---|
| 1 | Distillates (Petroleum), Hydrotreated Light | 64742-47-8 | 100 |

## 4. First Aid Measures

| | |
|---|---|
| **Inhalation** | Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation. |
| **Skin Contact** | Wash contacts areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. |
| **Eye Contact** | Flush thoroughly with water. If irritation occurs, get medical assistance. |
| **Ingestion** | Seek immediate medical attention. Do not induce vomiting. |
| **Note to Physician** | If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. |

## 5. Fire Fighting Measures

| | |
|---|---|
| **Suitable Extinguishing Media:** | Water fog, foam, dry chemicals or carbon dioxide ($CO_2$) to extinguish flames. |
| **Unsuitable Extinguishing Media:** | Straight streams of water. |
| **Required Special Protective Equipment for Fire-fighters:** | Evacuate area. Prevent running-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel. |

## 6. Accidental Release Measure

| | |
|---|---|
| **Personal Precautions:** | Avoid contact with spilled material. Keep unnecessary and unprotected personnel away. Keep upwind, evacuate downwind. Warn personnel of toxicity and flammability of the substance. Evacuate personnel to safe areas. See Section 5 for firefighting information. See Section 3 for the Hazard Identification. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expected judgment of the emergency responders. |
| **Environmental Precautions:** | <u>Large Spills</u>: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas. |
| **Methods for Cleaning:** | <u>Land Spill</u>: Eliminate all ignition sources. Stop leak if you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements or confined areas. A vapor-suppressing foam may be used to reduce vapor. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapor but may not prevent ignition in enclosed spaces. Recover by pumping or with suitable absorbent.<br><u>Water Spill</u>: Stop leak if you can do so without risk. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. |

## 7. Handling and Storage

| | |
|---|---|
| **Handling:** | Avoid contact with skin. Small metal particles from machining may cause abrasion of the skin and may predispose dermatitis. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity). |
| **Storage:** | The type of container used to store the material may affect static accumulation and dissipation. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Storage containers should be grounded and bonded. Fixed storage containers, transfer containers and associated equipment should be grounded and bonded to prevent accumulation of static charge. |
| **Storage Temperature:** | Ambient temperature |
| **Other Information:** | No data available. |

## 8. Exposure Controls/Personal Protection

| | |
|---|---|
| **Engineering Measures:** | The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider: Adequate ventilation should be provided so that exposure limits are not exceeded. Use explosion- proof ventilation equipment. |
| **Personal Protection** | |
| **Respiratory Protection:** | If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: |

| | |
|---|---|
| | No protection is ordinarily required under normal conditions of use and with adequate ventilation. Half-face filter respirator Type A filter material.<br><br>For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded. |
| **Eye Protection:** | If contact is likely, safety glasses with side shields are recommended. |
| **Hand Protection:** | Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: If prolonged or repeated contact is likely, chemical-resistant gloves are recommended. If contact with forearms is likely, wear gauntlet-style gloves: Nitrile. |
| **Hygiene Measures:** | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. |

## 9. Physical and Chemical Properties

| | |
|---|---|
| **Physical:** | Liquid |
| **Color:** | Colorless |
| **Odor:** | Slight |
| **Flammability:** | No data available. |
| **Density:** | 0.794 kg/L |
| **Relative Density:** | 0.79 with respect to water at 15.6 ºC |
| **Pour Point:** | -48 ºC |
| **Freezing Point:** | No data available. |
| **Flash Point:** | 81 ºC |
| **Boiling Point:** | 200 - 250 ºC |
| **Melting Point:** | No data available. |
| **Auto-ignition Temperature:** | 227 ºC (Extrapolation) |

| | |
|---|---|
| **Decomposition Temperature:** | No data available. |
| **Vapor Pressure:** | 0.01 kPa at 20 ºC |
| **Flammable Limits:** | Min (LEL) % : 0.6 % v/v<br>Max (UEL) % : 6.0 % v/v |
| **Evaporation Rate:** | 0.01 (n-butyl acetate = 1) |
| **pH:** | No data available. |
| **Solubility:** | Negligible in water |
| **Viscosity:** | 1.6 cSt at 40 ºC |
| **Molecular Weight:** | 178 g/mol (Calculation) |
| **Coefficient of Thermal Expansion:** | 0.00092 per ºC (Calculation) |
| **Octanol-water Partition Coefficient (Log $P_{ow}$):** | > 4 (Estimation) |

## 10. Stability and Reactivity

| | |
|---|---|
| **Stability:** | Material is stable under normal conditions. |
| **Materials to Avoid:** | Strong oxidizers. |
| **Hazardous Decomposition Products:** | Material does not decompose at ambient temperatures. |

## 11. Toxicological Information

| | |
|---|---|
| **Acute Toxicity** | |
| **Oral** | LD50 (Rat): > 5,000 mg/kg |
| **Dermal** | No data available. |
| **Inhalation** | LC50 (Rat): > 5,000 mg/$m^3$ |
| **Skin Corrosion/Irritation** | LD50 (Rat): > 5,000 mg/kg |
| **Eye Damage/Irritation** | May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. |
| **Germ Cell Mutagenicity** | No data available. |
| **Carcinogenicity** | No data available. |
| **Reproductive Toxicity** | No data available. |
| **Specific Target Organ Toxicity - Single Exposure** | No data available. |
| **Specific Target Organ Toxicity - Repeated Exposure** | No data available. |
| **Aspiration hazard** | No data available. |

## 12. Ecological Information

| | |
|---|---|
| **Ecotoxicity** | Not expected to be harmful to aquatic organisms.<br>Not expected to demonstrate chronic toxicity to aquatic organisms. |
| **Persistence and Degradability** | No data available. |
| **Bio-accumulative Potential** | Not expected to demonstrate chronic toxicity and be harmful to aquatic organisms. Expected to degrade rapidly in air. |
| **Mobility** | No data available. |
| **Other Adverse Effects** | No data available. |

## 13. Disposal Considerations

| | |
|---|---|
| **Waste Disposal** | Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. |
| **Container Disposal** | Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractors and in accordance with government regulations. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. |

## 14. Transport Information

Dangerous for Conveyance unless the Flash Point is known to be greater than 61 ºC.

| **Department of Transportation (DOT)** | |
|---|---|
| UN Number | UN 1268 |
| Proper Shipping Name | Petroleum Distillates, N.O.S |
| Hazard Class | Combustible Liquid |
| Packing Group | III |
| Emergency Response Guidebook (ERG) | 128 |

## 15. Regulatory Information

This material is considered hazardous according to the classification criteria of the Hazard Classification and Communication System for Hazardous Materials BE 2555 but not regulated by Hazardous Substance Act BE 2535.

## 16. Other Information

Issue Date: 27 May 2009

Revision Date: 2 February 2026

**Reference**


1. National Institute of Technology and Evaluation (SAFE NITE)
http://www.safe.nite.go.jp/english/ghs/ghs_index.html
2. Globally Harmonized System of Classification and Labelling of Chemical (GHS), United Nation, 2011