

1. Identification of The Substance or Mixture and The Supplier

Product	
Substance or Trade Name	White Spirit 3040 (Aliphatic Hydrocarbon)
Recommended Use	Solvent
Details of the Supplier of the Safety Data Sheet	
Company Name	Bangchak Corporation Public Company Limited
Address	2098 M Tower Building, 8th floor, Sukhumvit Road, Phra Khanong Tai, Phra Khanong, Bangkok 10260 Thailand
Telephone	+66 2335 4999
Fax	+66 2016 3991
Emergency Number	+66 2335 8888

2. Hazards Identification
Classification of the Mixture according to Globally Harmonized System (GHS) Standards.

Flammable Liquid	Category 3
Aspiration Hazard	Category 1
Serious Eye Damage/Eye Irritation	Category 2B
Skin Corrosion/Irritation	Category 3
Acute Aquatic Toxicity	Category 2
Chronic Aquatic Toxicity	Category 2
Specific Target Organ Toxicity, Single Exposure	Category 3
Specific Target Organ Toxicity, Repeated Exposure	Category 1

GHS Label Elements

Signal Word: Danger

Hazard Statements:

H226 – Flammable liquid and vapor.
H304 – May be fatal if swallowed and enters airways.
H315 – Causes skin irritation.
H316 – Causes mild skin irritation.
H320 – Causes eyes irritation.
H335 – May cause respiratory irritation.
H336 – May cause drowsiness or dizziness.
H340 – May cause genetic defects.
H350 – May cause cancer.
H372 – Causes damage to organs through prolonged or repeated exposure (central nervous system).
H411 – Toxic to aquatic life with long lasting effects.

Precautionary Statements:

P201 – Obtain special instructions before use.
P202 – Do not handle until all safety precautions have been read and understood.
P210 – Keep away from heat/sparks/open flames/hot surfaces. -- No smoking.
P233 – Keep container tightly closed.
P240 – Ground/bond container and receiving equipment.
P241 – Use explosion-proof electrical, ventilating and lighting equipment.
P242 – Use only non-sparking tools.
P243 – Take precautionary measures against static discharge.
P261 – Avoid breathing mist / vapors.
P271 – Use only outdoors or in a well- ventilated area.
P273 – Avoid release to the environment.
P280 – Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313 – IF exposed or concerned: Get medical advice/attention.
P312 – Call a POISON CENTER or doctor/physician if you feel unwell.
P331 – Do NOT induce vomiting.
P332 + P313 – If skin irritation occurs: Get medical advice/attention.
P370 + P378 – In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.
P391 – Collect spillage.
P403 + P235 – Store in a well-ventilated place. Keep cool.
P405 – Store locked up.
P501 – Dispose of contents and container in accordance with local regulations.

Other Hazards:

Physical/Chemical: Material can accumulate static charges which may cause an ignition. Material can release vapors that readily form flammable mixtures. Vapor accumulation could flash and/or explode if ignited.

Health: Mildly irritating skin. May be irritating to the eyes, nose, throat, and lungs. May cause central nervous system depression.

Environmental: No additional hazards.

3. Composition/Information on Ingredients

This material is defined as a mixture.

Hazardous Substance(s) or Complex Substance(s) required for disclosure

No.	Component	CAS No.	Content (%)
1	Naphtha (Petroleum), Hydrodesulfurization Heavy	64742-82-1	100

Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure

No.	Component	CAS No.	Content (%)
1	Naphthalene	91-20-3	0.1 - < 1
2	Pseudocumene (1, 2, 4-trimethylbenzene)	95-63-6	1 - < 5
3	Xylenes	1330-20-7	1 - < 5

4. First Aid Measures

Inhalation	Remove to fresh air. If the victim has difficulty breathing or tightness of the chest, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.
Skin Contact	Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes and follow by washing with soap and water if available.
Eye Contact	Immediately flush eyes with large amounts of water for at least 10 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.
Ingestion	Seek immediate medical attention. Do not induce vomiting.
Note to Physician	If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

5. Fire Fighting Measures

Suitable Extinguishing Media:	Water fog, foam, dry chemicals or carbon dioxide (CO ₂) to extinguish flames.
Unsuitable Extinguishing Media:	Straight streams of water.
Required Special Protective Equipment for Fire-fighters:	Fire-fighters should wear appropriate personal protective equipment including clothing flame protection, Safety helmet, Neoprene or nitrile gloves to prevent skin contact, and boot. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA).

6. Accidental Release Measure

Personal Precautions:	Avoid contact with spilled or released material. Immediately remove all contaminated clothing.
Environmental Precautions:	<u>Large Spills</u> : Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.
Methods for Cleaning:	<u>Land Spill</u> : Eliminate all ignition sources. Stop leak if you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements or confined areas. A vapor-suppressing foam may be used to reduce vapor. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. <u>Large Spills</u> : Water spray may reduce vapor but may not prevent ignition in enclosed spaces. Recover by pumping or with suitable absorbent. <u>Water Spill</u> : Stop leak if you can do so without risk. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. <u>Water and Land Spill</u> : Recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

7. Handling and Storage

Handling:	Avoid contact with skin, eyes, and clothing. Do not breathe vapor. Extinguish any naked flame. Remove ignition sources. Avoid sparks. Do not smoke. The vapor is heavier than air spreads along the ground and distant ignition is possible. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not use compressed air for filling, discharging, or handling operations. Handle and open containers with care in well-ventilated area. Do not empty the drains.
Storage:	Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Bulk storage tanks should be diked (bunded). Keep away from aerosols, flammables, oxidizing agents, and corrosives.
Storage Temperature:	Ambient temperature
Other Information:	Containers even those that have been emptied can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

8. Exposure Controls/Personal Protection

Engineering Measures:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Controlled measures to consider: Use explosion-proof ventilation equipment to stay below exposure limits.
Personal Protection	
Respiratory Protection:	If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: No protection is ordinarily required under normal conditions of use and with adequate ventilation. Half-face filter respirator Type A filter material. For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Eye Protection:	If contact is likely, safety glasses with side shields are recommended.
Hand Protection:	Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: If prolonged or repeated contact is likely, chemical-resistant gloves are recommended. If contact with forearms is likely, wear gauntlet-style gloves: Nitrile.
Hygiene Measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

9. Physical and Chemical Properties

Physical:	Liquid
Color:	Colorless
Odor:	Petroleum/Solvent
Density:	0.790 kg/L at 15 °C
Relative Density:	0.79 with respect to water at 15 °C
Pour Point:	-69 °C
Freezing Point:	No data available.
Flash Point:	38 °C
Boiling Point:	143 - 198 °C
Melting Point:	No data available.
Auto-ignition Temperature:	237 °C
Decomposition Temperature:	No data available.
Vapor Pressure:	0.2 kPa at 20 °C
Flammable Limits:	Min (LFL) % : 0.7 % v/v Max (UFL) % : 6.0 % v/v
Flammability:	No data available.
Evaporation Rate:	0.3 (n-Butyl acetate = 1)
pH:	No data available.
Solubility:	Negligible
Viscosity:	1.6 cSt at 40 °C

Molecular Weight:	145 g/mol (Calculation)
Coefficient of Thermal Expansion:	0.00097 per °C (Calculation)
Octanol-water Partition Coefficient (Log P_{ow}):	> 4 (Estimation)

10. Stability and Reactivity

Stability:	Material is stable under normal conditions.
Materials to Avoid:	Strong oxidizing agents.
Hazardous Decomposition Products:	Thermal decomposition is highly dependent on conditions. Carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation. May form explosive peroxides.

11. Toxicological Information

Acute Toxicity	
Oral	LD50 (Rat): > 15,000 mg/kg
Dermal	LD50 (Rabbit): > 3,400 mg/kg
Inhalation	LC50 (Rat): > 13.1 mg/L
Skin Corrosion/Irritation	Irritating skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.
Eye Damage/Irritation	Irritating to eyes.
Germ Cell Mutagenicity	No data available.
Carcinogenicity	No data available.
Reproductive Toxicity	Not expected to impair fertility. Not a developmental toxicant.
Specific Target Organ Toxicity - Single Exposure	No data available.
Specific Target Organ Toxicity - Repeated Exposure	No data available.
Aspiration hazard	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

12. Ecological Information

Ecotoxicity	Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
--------------------	--

Persistence and Degradability	Biodegradation: Expected to be inherently biodegradable. Hydrolysis: Transformation due to hydrolysis is not expected to be significant. Photolysis: Transformation due to photolysis is not expected to be significant. Atmospheric Oxidation: Expected to degrade rapidly in air.
Bio-accumulative Potential	Has the potential to bioaccumulate.
Mobility	Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.
Other Adverse Effects	No data available.

13. Disposal Considerations

Waste Disposal	Recover or recycle if possible. It is responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulation. Do not dispose into the environment, in drains or in water courses. Waste products should not be allowed to contaminate soil or water.
Container Disposal	Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut, or weld uncleaned drums. Send to drum recovery or metal reclaimer.

14. Transport Information

Dangerous for Conveyance unless the Flash Point is known to be greater than 61 °C.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)	
UN Number	UN 1300
Proper Shipping Name	Turpentine Substitute
Hazard Symbol	Flammable Liquid
Hazard Class	3
Packing Group	III
International Maritime Organization (IMO)	
UN Number	UN 1300
Proper Shipping Name	Turpentine Substitute
Hazard Symbol	Flammable Liquid
Hazard Class	3.3
Packing Group	III
Marine Pollutant	Yes, Marine Pollutant Marks Required

International Maritime Dangerous Goods (IMDG)	
UN Number	UN1300
Proper Shipping Name	Turpentine Substitute
Hazard Symbol	Flammable Liquid
Hazard Class	3
Packing Group	III

15. Regulatory Information

This material is considered hazardous according to the classification criteria of the Hazard Classification and Communication System for Hazardous Materials BE 2555 but not regulated by Hazardous Substance Act BE 2535.

16. Other Information

Issue Date: 27 May 2009
Revision Date: 2 February 2026

Reference

1. National Institute of Technology and Evaluation (SAFE NITE)
http://www.safe.nite.go.jp/english/ghs/ghs_index.html
2. Globally Harmonized System of Classification and Labelling of Chemical (GHS), United Nation, 2011

The information contained herein is to the best of our knowledge accurate, but since the circumstances and conditions in which it may be used are beyond our control, we do not accept liability for any loss or damage, however arising, which results directly or indirectly from the use of such information, nor do we offer any warranty of immunity against patent infringement.