nonprobsvy – An R package for modern methods for non-probability surveys

Łukasz Chrostowski ⓘ
Adam Mickiewicz University

Maciej Beręsewicz ⓘ
Poznań University of Economics and Business

Piotr Chlebicki ⓘ
Stockholm University

Abstract

The abstract of the article.

Keywords: keywords, not capitalized, R.

1. Introduction

This template demonstrates some of the basic LaTeX that you need to know to create a JSS article.

1.1. Code formatting

In general, don't use Markdown, but use the more precise LaTeX commands instead:

- Java

- **plyr**

One exception is inline code, which can be written inside a pair of backticks (i.e., using the Markdown syntax).

If you want to use LaTeX commands in headers, you need to provide a `short-title` attribute. You can also provide a custom identifier if necessary. See the header of Section 2 for example.

2. R code

Can be inserted in regular R markdown blocks.

```
R> x <- 1:10
R> x
```

```
 [1]  1  2  3  4  5  6  7  8  9 10
```

2.1. Features specific to rticles

- Adding short titles to section headers is a feature specific to **rticles** (implemented via a Pandoc Lua filter). This feature is currently not supported by Pandoc and we will update this template if it is officially supported in the future.
- Using the \AND syntax in the `author` field to add authors on a new line. This is a specific to the `rticles::jss_article` format.

Affiliation:

Łukasz Chrostowski
Pearson
First line
Second line
E-mail: name@company.com
URL: https://posit.co

Maciej Beręsewicz
Statistical Office in Poznań
Department of Statistics,
Institute of Informatics and Electronic Economy,
Poznań University of Economics and Business

Piotr Chlebicki
Stockholm University
Department of Statistics and Mathematics,
Faculty of Biosciences,
Universitat Autònoma de Barcelona