

# The HTTP Module

## Introduction

This blurb is about using QDL's HTTP module. This module allows you to do basic operations to a website using the HTTP protocol.

## Loading the module

This is a Java module and is included in the standard distribution, but is not loaded, so to use it load it by issuing

```
http := j_load('http')
```

## Supported functions

Name	Description	Comment
close()	close the connection	All requests will fail until open() is called
delete()	DELETE	Use current host
delete(parameters.)	DELETE	Use current host, add parameters
delete(uri_path, parameters.)	DELETE	Append uri_path to host, add parameters
get()	GET	Use current host
get(uri_path)	GET	Add add uri path to host, no parameters.
get(parameters.)	GET	Use host, parameters. is a stem of query parameters to be encoded and added to the path
get(uri_path, parameters.)	GET	Append path_uri to host, use parameters
headers()	list the current default headers	
headers(arg.)	set the default headers	
host()	get the current host	
host(host_name)	set the current host	Returns previous host
is_open()	is the connection open?	
is_json(response.)	Is the response content of type JSON?	This and is_text accept either the response or just the headers.

is_text(response.)	Is the response content of type text?	This does not include JSON since there is a separate method for that.
open()	open a new connection	
open(insecure)	open a new, insecure connection	insecure is a boolean, which if <b>true</b> will turn off security for SSL. Default is <b>false</b> .
post(arg   arg.)	POST	Payload may be a string or a stem.
post(uri_path, arg   arg.)	POST	Append uri_path to host, send payload
put(arg   arg.)	PUT	Payload may be a string or stem
put(uri_path, arg   arg.)	PUT	Append uri_path to host, send payload

Get returns a stem with entries for status, content and any returned headers.

## Typical examples

Assuming you have loaded the above, open up a connection and get

```

http:= j_load('http')
http#host('https://didact-patto.dev.umccr.org/api/visa') ;
http#open();
true
z. := http#get({'sub':'https://nagim.dev/p/wjaha-ppqrg-10000'});
z.
{
  headers: {
    Connection:keep-alive,
    etag:W/"e6-suhkGbMm3fkbNhOR6bOIwIgh8A",
    Apigw-Requestid:Gv9mdhv4SwMEMHw=,
    Content-Length:230,
    Date:Tue, 05 Oct 2021 19:37:04 GMT,
    Content-Type:application/json; charset=utf-8,
    X-Powered-By:Express
  },
  content: [
    {
s:XnKFk14RTXtB2DD0f5f4yLtfcTaCGyqMxIV8Q42zX_XR1p9Cnxeqq2KI_4UCzcJZ2XGv_h1qVGOW5_3FE
9ZHCQ,
      v:c:8XZF4195109CIERC35P577HAM et:1633549022 iu:https://nagim.dev/p/wjaha-ppqrg-
10000 iv:2f69e2650aed4f0e,
      k:rfc8032-7.1-test1
    }
  ],
  status: {
    code:200,
    message:OK
  }
}
is_json(z.)

```

true

So we see the various components of the response, z.:

- `headers`. - A stem of the headers, where the key is the name of the header and the value is its value (as a string, so `Content-Length` is not a number).
- `content`. - The exact content. Here, it is an array with a single element and note that `headers.Content-Type` contains `application/json` and hence was in JSON format. If the content type is anything else, it will be returned as a stem of lines. The `is_json` function tell you if the content type was JSON. In this example, it was a JSON blob with 3 entries.
- `status`. - The http status, which includes the [status code](#) and the message from the server. Anything other than something in the 200 range is an error.

Note that there are other options for `content`. but it will always be an array. For instance, from other servers it may be the lines in the body of the response if the `Content-Type` is `form_encoding`. In that case, you will have to loop through the lines and process each of them in turn.

## A GET example

In this case, we have several pages to be fetched

```
http := j_load('http');
http#open();
true
http#host('https://cilogon.org/.well-known/openid-configuration');

pages. := ['', 'fermilab', 'ligo'];
while[vi E pages.][say(http#get(vi).content.'issuer');];
https://cilogon.org
https://cilogon.org/fermilab
https://cilogon.org/ligo
http#close();
true
```

In this case, it goes to the Cilogon server and grabs some well known pages in turn, constructing the paths for various VIs (virtual issuers), showing the issuer entry for each page. This is quite basic. Normally you might enclose the call in a try – catch block, check return codes, etc. but this is to show how `get()` works, naught else.

To amplify this, had we issued

```
http#host('https://some_service.com');
http#get('logon', {'id' : 'Knútr.Forkbeard', 'password' : '123 foo'})
```

The resulting request constructed would be

[https://some\\_service.com/logon?id=Kn%C3%BAttr.Forkbeard&password=123%20foo](https://some_service.com/logon?id=Kn%C3%BAttr.Forkbeard&password=123%20foo)

Contrast this with a call like

```
http#post('logon', {'id' : 'Knútr.Forkbeard', 'password' : '123 foo'})
```

which would send the request to [https://some\\_service.com/logon](https://some_service.com/logon) but with the body of the post as [id=Kn%C3%Batr.Forkbeard&password=123%20foo](#)