

7 Ways to Improve Your Virtual Experience - Exploring the Obstacles of Mainstream VR

Andrey Krekhov

October 4, 2015
Version: My First Draft

Clean Thesis Style University

CleanThesis

Department of Clean Thesis Style

Institute for Clean Thesis Dev

Clean Thesis Group (CTG)

Documentation

7 Ways to Improve Your Virtual Experience - Exploring the Obstacles of Mainstream VR

Andrey Krekhov

- | | |
|--------------------|--|
| <i>1. Reviewer</i> | Jane Doe
Department of Clean Thesis Style
Clean Thesis Style University |
| <i>2. Reviewer</i> | John Doe
Department of Clean Thesis Style
Clean Thesis Style University |
| <i>Supervisors</i> | Jane Doe and John Smith |

October 4, 2015

Andrey Krekhov

7 Ways to Improve Your Virtual Experience - Exploring the Obstacles of Mainstream VR

Documentation, October 4, 2015

Reviewers: Jane Doe and John Doe

Supervisors: Jane Doe and John Smith

Clean Thesis Style University

Clean Thesis Group (CTG)

Institute for Clean Thesis Dev

Department of Clean Thesis Style

Street address

Postal Code and City

Abstract

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

Abstract (different language)

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

Acknowledgement

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language. Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

This is the second paragraph. Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language. Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.

Contents

1	Introduction	1
2	Locomotion in VR	3
2.1	Presence and Cybersickness	3
2.2	VR Locomotion Landscape	5
2.2.1	Stationary Approaches	5
2.3	Design Implications	8
	Bibliography	11
	Listings	19
	Declaration	21

Introduction

Annti tweeted: VR bad. is it true? Fin: VR isnt good, but research makes it better. Does it fix it? No. BUT: curiosity is human nature, and everyone in the studies loved trying vr. So, even if it is only an intermediate solution, we should keep it, because we are humans, after all.

Locomotion in VR

Curiosity and the thirst for exploration are an important part of human nature. It is not surprising how easy we tend to lose ourselves in large, open game worlds, spending countless hours on roaming around unknown terrain. Hence, locomotion ever since had an important role in game design. And while this challenge is solved to a large extent in common digital games, locomotion techniques in virtual reality (VR) remain a large obstacle to this day.

This chapter discusses the challenges of VR locomotion and outlines a number of available solutions that allow the exploration of fictional worlds. We begin by looking at two important components of VR that one might also call the curse and blessing of such immersive setups: cybersickness and presence. In particular, we explain why common locomotion approaches, such as mouse and keyboard, are not viable in VR, and how the high degree of immersion allows the players to experience a feeling of being in the virtual world.

The main part of the chapter focuses on classifying the past and ongoing research on VR locomotion. We discuss a broad spectrum of possibilities to move in VR, ranging from stationary approaches relying on gamepads to advanced redirected walking techniques that trick our perception to enable unrestricted natural walking in a limited space. Finally, we propose a set of design guidelines to simplify the implementation of player locomotion in future VR games.

2.1 Presence and Cybersickness

At present, VR technology is considered mainstream, and more and more manufacturers are putting effort into creating head-mounted displays (HMDs) at affordable prices. Such HMDs are capable of rendering stereoscopic images at HD resolutions for each eye while maintaining a high refresh rate (90 Hz or above). The hardware also tracks the head orientation, which allows players to look around in VR like in real world and gather close-up experiences during gaming.

Players usually describe such impressions as a feeling of “being there” [Hee92; LD97]. Other popular wordings often include the two terms *presence* and *immersion* — sometimes in an interchangeable manner. Throughout the chapter, we utilize immersion [CCN14] when focusing on the technical quality of VR hardware [BD95; SC02]. In contrast, we use presence to describe how immersive setups affect our perception to make us believe that we are indeed in the virtual environment [Sla03].

Hence, (game) researchers and developers often target the increase of presence when coming up with novel VR approaches, and VR locomotion is a prominent advocate for such presence-enhancing research [SUS95]. To measure presence, the most common methods include the Presence Questionnaire (PQ) [WJS05] and the Igroup Presence Questionnaire (IPQ) [Sch03; SRF18]. In addition, the Immersive Tendencies Questionnaire (ITQ) [WS98] can be administered before the actual survey to check participants' individual tendencies to get immersed in an activity or fiction.

Unfortunately, the increase in players' perceived presence is not the only thing that an immersive setup entail. The produced realism imposes high demands on VR software and hardware regarding the human perception. Minor faults or technical issues, such as slightly offset locomotion or a sudden frame rate drop, can have severe consequences regarding the players' well-being and result in *cybersickness* [SKD97; LaV00]. Other prominent terms often used in this context are *simulator sickness* [Kol95] and *motion sickness* [Mon70; HR92; Ohy+07]. In contrast to the manifold reasons of cybersickness, the main cause of simulator sickness is an incorrectly adjusted simulator [Ken+89] and can be regarded as a rather technical problem.

Cybersickness involves symptoms such as nausea, eye strain, and headaches. Roughly spoken, the main reason behind that negative phenomenon is a mismatch in our vestibulo-ocular system. Our vestibular system senses acceleration that ideally matches the visual input. When these signals do not match, the aforementioned symptoms are likely to occur [RB75]. There exist three popular explanations [LaV00] for such an unwanted body reaction: poison theory, postural instability theory, and—the most prominent—conflict theory.

Hettinger et al. [Het+90] also mentionedvection as a possible reason behind cybersickness. Vection describes the feeling of movement that relies only on our visual system and can be experienced when, e.g., we sit in a standing train and observe another train that is currently accelerating. Vection is influenced by several factors, including the field of view (FOV), the alignment and proximity of moving objects, and the optical flow rate. For instance, the combination of a large FOV and fast objects that account for a large proportion of players' view amplify the perceivedvection and smooth the way to cybersickness. Hence, limiting the FOV is one of the possible approaches to reduce cybersickness [FF16; Lin+02].

To conclude, we suggest keeping cybersickness in mind and to avoid cognitive mismatches where possible — however, not at all costs, as “sickness-save”, stationary scenes without any locomotion would potentially miss out on a wide range of benefits that VR has to offer. And sometimes, as shown by von Mammen et al. [VKE16], games might even benefit from an artificially induced cybersickness.

2.2 VR Locomotion Landscape

We have seen that locomotion in VR is not just a way of transporting the player from A to B. Rather, locomotion strives to provide realistic, immersive experiences that increase the player's presence while working around cybersickness. In recent years, research [Bol17] and the game industry [Hab+17] created a plethora of varying locomotion approaches. As often the case, there is no “right” answer which one to pick for your upcoming VR game. Hence, the main purpose of the following sections is to provide a rough overview and classification of available approaches and to serve as a starting ground for further research and development. In particular, we start by considering locomotion approaches that do not involve a physical movement of the player, before moving on to techniques that evolve around the idea of natural walking in VR.

2.2.1 Stationary Approaches

Although HMDs can track head movements, only a subset of them is capable of tracking the global position of a player in the room. One also says that such setups support *room-scale tracking*. One common approach is to utilize a set of base stations that emit infrared pulses, which are captured by the HMD to estimate the global position. Conversely, there is a considerable amount of HMDs that comes without room-scale support. Main reasons to omit such tracking are the lower costs and the increased portability. As such devices do not support the physical movement of the player, stationary locomotion techniques are required to allow the exploration of game worlds. Another reason for stationary approaches is the reduced fatigue, as players might even remain seated during a gaming session.

Traditional I/O Approaches

Existing games are sometimes ported to VR, be it to promote the title or to build on the success of the original game. In such cases, developers tend to take over the controls including locomotion to reduce the turnaround time and keep the familiar game UI. Hence, VR players are pushed towards desktop I/O, be it a keyboard [AM16], a joystick [Boz+16a], or a gamepad [FF16]. The advantage of the method is, without doubt, its simplicity regarding implementation and the familiarity to experienced players.

However, as we pointed out before, a cognitive mismatch between our vision system, i.e., seeing the motion via the HMD, and our vestibular system, i.e., remain stationary or even seated, can easily lead to cybersickness when using such approaches. Hence, we recommend to pay close attention to this issue when relying on traditional methods. As a partial remedy, developers might want to reduce the FOV, as, e.g., was

done in Skyrim VR [Bet17]. Another way would be to limit or disable continuous in-game player motion in favor of quick or discrete player movements [Hab+17] to reduce vection. The work of Medeiros et al. [Med+16] and Yao et al. [Yao+14] also confirmed the benefits of short, fast movements with no acceleration as one measure to combat cybersickness in such cases.

Teleportation

If we take the idea of fast and short movements to the extreme, we will end up with a technique called the point and teleport locomotion approach [Boz+16b]. Players select a destination using a pointing device, e.g., a controller [XMS17], and are instantly teleported to that place, thus entirely removing the vection issues. Regarding cybersickness, this technique is more robust than traditional gamepad locomotion [FSW17] and is being strongly encouraged by the majority of established VR systems such as the HTC Vive.

The targeting is often visualized by an arc that starts at the controller or the virtual hand representation and ends at the planned destination. On the one hand, the targeting is considered intuitive and robust. On the other hand, however, such implementation limits the travel distance to visible places that are not far away, and certain virtual environments might further limit the travel distance by exposing obstacles, such as trees or walls, that prevent players from targeting more distant locations. In addition, the displayed teleportation arc itself is a rather obstructive interface element that covers parts of the game world and might decrease players' perceived presence, if it does not blend in well with the setting. Another issue to be considered is the limited precision when teleporting to very close areas, as the displayed arc gets too compressed and is not very helpful for predicting the outcome. This uncertainty often results in numerous relocation attempts until the desired position is finally achieved.

The last drawback of teleportation is the reduced spatial orientation of players, which might also impact their experienced presence. Players need to reorient themselves after a relocation, which imposes an additional cognitive load. To overcome this obstacle, researchers propose to render previews of the destination area, or, as proposed by Bruder et al. [BSH09], utilize such previews as virtual portals where players have to pass through to reach their target.

The described arc-based teleportation, although being recommended by hardware manufacturers, is still relatively uncommon in VR games. A more widespread variation of the technique is known as node-based teleportation [Hab+17]. This technique is based on predefined points of interest that could be represented by, e.g., an icon. In contrast to the arc-based method, players cannot pick their destination

freely and can only travel between such nodes. The node selection is usually implemented by looking at a node and pressing a button. The subsequent teleportation process is often accompanied by a fading animation. This feature, in combination with a clever choice of node locations, allows to reduce player disorientation, but obviously limits the perceived freedom of exploration.

Redirected Walking

In contrast to walking in place techniques, which address the room-scale limitation by completely avoiding that the player moves through the real room, other approaches enable natural walking by applying redirection or reorientation. The idea of redirected walking is to manipulate the player's movement in the virtual world by creating a mismatch between the real world locomotion and the translation in the game world. As a result, the perceived movement in the virtual world is more extensive than the player actually moves in the real world space [RKW01; Raz05; Ste+10]. While players do not notice the manipulation, they unconsciously compensate the offset by slightly repositioning and reorienting themselves. Hence, by manipulating translation, path curvature, and rotation, reorientation techniques can be used to keep players inside the boundaries of the tracked space without making them aware of the fact that they are actually walking in circles. Nescher et al. [NYK14] and Paris et al. [Par+17] discuss different redirection methods and algorithms, providing further information how such techniques can be applied to VR games.

Redirection and reorientation techniques maintain the advantages of natural walking regarding high perceived presence, intuitiveness, and a low risk of cybersickness. However, though current approaches tackle the issue of space limitation to some extent, they still require a much larger space than is given in common living rooms and, thus, require further adaptations in that regard [Gre+16; Eng+08; LBS16; BSH09]. The demands of such techniques in terms of the VR setup and the implementation are considerably high.

Multiscale Navigation

Until now, the approaches we considered usually perform on a 1:1 ratio between the physical and the real world. In other words, the travelled distance in the physical room roughly corresponds our virtual footprint. An alternative way to deal with the room-scale limitation is rescaling of players and/or their motion [BTF17]. Note that world rescaling is equivalent to player rescaling. However, we strongly discourage altering the world size, i.e., the size of all objects, due to obvious performance reasons and, in worst case, floating point precision issues.

In research, the dynamic scaling of virtual environments is mostly used within multiscale virtual environments (MSVEs) [ZF02]. For instance, such approaches can be utilized to explore the inner organs of virtual human representations [Kop+06]. Hereby, the current scale can be set either manually by the player or computed automatically based on current task or location. As shown by Argelaguet et al. [AM16], automatic scaling is often more predictable for developers and allows to optimize rendering parameters to reduce diplopia or cybersickness.

In games research, a recent example of player rescaling is a locomotion technique called *GulliVR* [Kre+18]. The approach allows players to turn into giants on demand and cover large distances in just a few steps. At first glance, the idea is similar to a common flying approach, as both variants share the same camera position and velocity. However, flying is known for its severe cybersickness due to the cognitive mismatch of physical and virtual movement speeds. In contrast, *GulliVR* increases the interpupillary distance as part of the whole-body rescaling process, which has two effects. First and foremost, the cybersickness is removed as players feel like they are walking as giants (no mismatch) and not like they are artificially floating or flying. Second, players perceive the environment from above as a miniature world, which opens up novel design possibilities [CKK19].

2.3 Design Implications

Locomotion in VR has a huge impact on the failure or success of a game. A well-chosen technique is able to enhance the player experience and help players to immerse even more in the fictional worlds. On the downside, technical issues or cognitive mismatches can easily render a game unplayable due to a significant amount of introduced cybersickness. Not surprisingly, our high-level recommendation is to design locomotion in a way that minimizes the risks of cybersickness and maximizes the perceived presence. Ideally, we would choose natural walking for most cases, but, unfortunately, the room-scale limitation forces us to consider alternatives and handle respective trade-offs.

For that reason, we recommend enforcing a decision regarding locomotion quite early in the development process, as certain approaches have a considerable interplay with other game mechanics, such as object interaction, quest locations, world size, etc. As a starting point for such decision making, we summarized the mentioned locomotion methods in Figure 2.1. Please note that such overviews rely on certain over-generalizations, e.g., not all gamepad-based techniques are causing cybersickness. However, we feel that a condensed summary might be helpful, especially when designing a VR game for the first time. Furthermore, we propose the following questions to be asked during the VR game design process with respect to locomotion:

	natural motion	cybersickness	intuitiveness	hardware reqs	short distances	long distances	fatigue
traditional I/O	-	-	○	+	+	○	+
teleport/node	-	+	-	+	○	+	+
gestures	-	○	○	○	+	○	○
natural walking	+	+	+	○	+	-	-
walking in place	○	○	+	○	+	○	-
treadmills	+	+	+	-	+	○	-
redirected walking	+	+	+	-	+	○	-
multiscale nav	+	+	○	○	-	+	-

Fig. 2.1: An overview of VR locomotion techniques including their benefits and drawbacks. Green color (+) means that this attribute is a known advantage of the technique, yellow (○) stands for limited value, and red (-) is rather a disadvantage.

What is my target audience? The canonical question for almost any kind of decision making. We emphasize three aspects of this question. First, how exhausting is the locomotion allowed to be? This depends on age and the overall target group, as well as the type of the game, i.e., it might be an exergame or something meant for relaxation/recovery. Second, how long are the players meant to play the game at a time? This aspect also determines how physically straining the locomotion is allowed to be. Third, what hardware setups do our players have? In other words, are we designing for Google Cardboard that only tracks head orientation or can we assume room-scale tracking? In particular, we are limited to stationary approaches if we do not have access to the player position.

How important is exploration? In general, games with a heavy focus on exploration and player movement benefit a lot from realistic, well-constructed locomotion approaches that allow a free and natural journey through the virtual world. Conversely, if the main emphasis of the game is on aiming and shooting, a node-based teleportation technique with carefully predefined locations might be more efficient. Furthermore, the overall size of the virtual world should be considered, as some of the techniques excel at short distances, whereas other approaches are designed to cover large distances in a short amount of time. Taken to the extreme, certain game genres, such as escape rooms, might even consider to rely only on natural walking by fitting the virtual environment completely into the living room.

What else happens during locomotion? This question is also related to the main focus of the game. Certain techniques, such as gaze-based locomotion, limit the amount of concurrent activities and are less suited for games in which players need to perform additional interactions while walking. The overall effort required for locomotion—be it mental or physical—also impacts the general pace of the game. In other words, fast-paced games might rather benefit from an instant, node-based teleportation rather than forcing players to physically run through their living rooms or spending precious seconds while aiming with the arc-based teleportation approach.

Again, these questions are meant as a starting point. In combination with the overview in Figure 2.1, this kind of reasoning might be helpful to establish a well-suited locomotion technique early on and to take full advantage of virtual reality gaming.

Bibliography

- [AM16] Ferran Argelaguet and Morgant Maignant. „GiAnt: stereoscopic-compliant multi-scale navigation in VEs“. In: *Proceedings of the 22nd ACM Conference on Virtual Reality Software and Technology*. ACM. 2016, pp. 269–277 (cit. on pp. 5, 8).
- [BD95] Frank Biocca and Ben Delaney. „Communication in the Age of Virtual Reality“. In: ed. by Frank Biocca and Mark R. Levy. Hillsdale, NJ, USA: L. Erlbaum Associates Inc., 1995. Chap. Immersive Virtual Reality Technology, pp. 57–124 (cit. on p. 3).
- [Bet17] Bethesda Softworks LLC. Skyrim VR. Game [SteamVR]. Bethesda Softworks LLC, Rockville, Maryland, U.S. Rockville, Maryland, U.S., Dec. 2017 (cit. on p. 6).
- [Bol17] Costas Boletsis. „The new era of virtual reality locomotion: a systematic literature review of techniques and a proposed typology“. In: *Multimodal Technologies and Interaction* 1.4 (2017), p. 24 (cit. on p. 5).
- [Boz+16a] Evren Bozgeyikli, Andrew Raij, Srinivas Katkoori, and Rajiv Dubey. „Locomotion in Virtual reality for individuals with autism spectrum disorder“. In: *Proceedings of the 2016 Symposium on Spatial User Interaction*. ACM. 2016, pp. 33–42 (cit. on p. 5).
- [Boz+16b] Evren Bozgeyikli, Andrew Raij, Srinivas Katkoori, and Rajiv Dubey. „Point & teleport locomotion technique for virtual reality“. In: *Proceedings of the 2016 Annual Symposium on Computer-Human Interaction in Play*. ACM. 2016, pp. 205–216 (cit. on p. 6).
- [BSH09] Gerd Bruder, Frank Steinicke, and Klaus H Hinrichs. „Arch-explore: A natural user interface for immersive architectural walkthroughs“. In: (2009) (cit. on pp. 6, 7).
- [BTF17] Jiwan Bhandari, Sam Tregillus, and Eelke Folmer. „Legomotion: Scalable Walking-based Virtual Locomotion“. In: *Proceedings of the 23rd ACM Symposium on Virtual Reality Software and Technology*. VRST '17. Gothenburg, Sweden: ACM, 2017, 18:1–18:8 (cit. on p. 7).
- [CCN14] Paul Cairns, Anna Cox, and A Imran Nordin. „Immersion in digital games: review of gaming experience research“. In: *Handbook of digital games* (2014), pp. 337–361 (cit. on p. 3).

- [CKK19] Sebastian Cmentowski, Andrey Krekhov, and Jens Krueger. „Outstanding: A Perspective-Switching Technique for Covering Large Distances in VR Games“. In: *Extended Abstracts of the 2019 CHI Conference on Human Factors in Computing Systems*. ACM. 2019, LBW1612 (cit. on p. 8).
- [Eng+08] David Engel, Cristóbal Curio, Lili Tcheang, Betty Mohler, and Heinrich H Bülthoff. „A psychophysically calibrated controller for navigating through large environments in a limited free-walking space“. In: *Proceedings of the 2008 ACM symposium on Virtual reality software and technology*. ACM. 2008, pp. 157–164 (cit. on p. 7).
- [FF16] Ajoy S Fernandes and Steven K Feiner. „Combating VR sickness through subtle dynamic field-of-view modification“. In: *3D User Interfaces (3DUI), 2016 IEEE Symposium on*. IEEE. 2016, pp. 201–210 (cit. on pp. 4, 5).
- [FSW17] Julian Frommel, Sven Sonntag, and Michael Weber. „Effects of controller-based locomotion on player experience in a virtual reality exploration game“. In: *Proceedings of the 12th International Conference on the Foundations of Digital Games*. 2017 (cit. on p. 6).
- [Gre+16] Timofey Grechkin, Jerald Thomas, Mahdi Azmandian, Mark Bolas, and Evan Suma. „Revisiting Detection Thresholds for Redirected Walking: Combining Translation and Curvature Gains“. In: *Proceedings of the ACM Symposium on Applied Perception*. SAP ’16. Anaheim, California: ACM, 2016, pp. 113–120 (cit. on p. 7).
- [Hab+17] M.P. Jacob Habgood, David Wilson, David Moore, and Sergio Alapont. „HCI Lessons From PlayStation VR“. In: *Extended Abstracts Publication of the Annual Symposium on Computer-Human Interaction in Play*. CHI PLAY ’17 Extended Abstracts. Amsterdam, The Netherlands: ACM, 2017, pp. 125–135 (cit. on pp. 5, 6).
- [Hee92] Carrie Heeter. „Being there: The subjective experience of presence“. In: *Presence: Teleoperators & Virtual Environments* 1.2 (1992), pp. 262–271 (cit. on p. 3).
- [Het+90] Lawrence J. Hettinger, Kevin S. Berbaum, Robert S. Kennedy, William P. Dunlap, and Margaret D. Nolan. „Vection and simulator sickness“. In: 2 (Feb. 1990), pp. 171–81 (cit. on p. 4).
- [HR92] Lawrence J Hettinger and Gary E Riccio. „Visually induced motion sickness in virtual environments“. In: *Presence: Teleoperators & Virtual Environments* 1.3 (1992), pp. 306–310 (cit. on p. 4).
- [Ken+89] Robert S Kennedy, Michael G Lilienthal, Kevin S Berbaum, DR Baltzley, and ME McCauley. „Simulator sickness in US Navy flight simulators.“ In: *Aviation, Space, and Environmental Medicine* 60.1 (1989), pp. 10–16 (cit. on p. 4).
- [Kol95] Eugenia M Kolasinski. *Simulator Sickness in Virtual Environments*. Tech. rep. Army Research Inst. for the Behavioral and Social Sciences, Alexandria, VA, 1995 (cit. on p. 4).
- [Kop+06] Regis Kopper, Tao Ni, Doug A Bowman, and Marcio Pinho. „Design and evaluation of navigation techniques for multiscale virtual environments“. In: *Virtual Reality Conference, 2006*. Ieee. 2006, pp. 175–182 (cit. on p. 8).

- [Kre+18] Andrey Krekhov, Sebastian Cmentowski, Katharina Emmerich, Maic Masuch, and Jens Krüger. „GulliVR: A Walking-Oriented Technique for Navigation in Virtual Reality Games Based on Virtual Body Resizing“. In: *Proceedings of the 2018 Annual Symposium on Computer-Human Interaction in Play*. CHI PLAY '18. Melbourne, VIC, Australia: ACM, 2018, pp. 243–256 (cit. on p. 8).
- [LaV00] Joseph J LaViola Jr. „A discussion of cybersickness in virtual environments“. In: *ACM SIGCHI Bulletin* 32.1 (2000), pp. 47–56 (cit. on p. 4).
- [LBS16] Eike Langbehn, Gerd Bruder, and Frank Steinicke. „Subliminal reorientation and repositioning in virtual reality during eye blinks“. In: *Proceedings of the 2016 Symposium on Spatial User Interaction*. ACM. 2016, pp. 213–213 (cit. on p. 7).
- [LD97] Matthew Lombard and Theresa Ditton. „At the heart of it all: The concept of presence“. In: *Journal of Computer-Mediated Communication* 3.2 (1997), pp. 0–0 (cit. on p. 3).
- [Lin+02] JJ-W Lin, Henry Been-Lirn Duh, Donald E Parker, Habib Abi-Rached, and Thomas A Furness. „Effects of field of view on presence, enjoyment, memory, and simulator sickness in a virtual environment“. In: *Virtual Reality, 2002. Proceedings. IEEE*. IEEE. 2002, pp. 164–171 (cit. on p. 4).
- [Med+16] Daniel Medeiros, Eduardo Cordeiro, Daniel Mendes, et al. „Effects of speed and transitions on target-based travel techniques“. In: *Proceedings of the 22nd ACM Conference on Virtual Reality Software and Technology*. ACM. 2016, pp. 327–328 (cit. on p. 6).
- [Mon70] K E Money. „Motion sickness.“ In: *Physiological Reviews* 50.1 (1970), pp. 1–39 (cit. on p. 4).
- [NYK14] T. Nescher, Ying-Yin Huang, and A. Kunz. „Planning redirection techniques for optimal free walking experience using model predictive control“. In: *2014 IEEE Symposium on 3D User Interfaces (3DUI)*. Mar. 2014, pp. 111–118 (cit. on p. 7).
- [Ohy+07] Seizo Ohyama, Suetaka Nishiike, Hiroshi Watanabe, et al. „Autonomic responses during motion sickness induced by virtual reality“. In: *Auris Nasus Larynx* 34.3 (2007), pp. 303–306 (cit. on p. 4).
- [Par+17] R. A. Paris, T. P. McNamara, J. J. Rieser, and B. Bodenheimer. „A comparison of methods for navigation and wayfinding in large virtual environments using walking“. In: *2017 IEEE Virtual Reality (VR)*. Mar. 2017, pp. 261–262 (cit. on p. 7).
- [Raz05] Sharif Razzaque. *Redirected walking*. University of North Carolina at Chapel Hill, 2005 (cit. on p. 7).
- [RB75] James T Reason and Joseph John Brand. *Motion sickness*. Academic press, 1975 (cit. on p. 4).
- [RKW01] Sharif Razzaque, Zachariah Kohn, and Mary C Whitton. „Redirected walking“. In: *Proceedings of EUROGRAPHICS*. Vol. 9. Citeseer. 2001, pp. 105–106 (cit. on p. 7).
- [SC02] William R Sherman and Alan B Craig. *Understanding virtual reality: Interface, application, and design*. Elsevier, 2002 (cit. on p. 3).

- [Sch03] Thomas W. Schubert. „The sense of presence in virtual environments: A three-component scale measuring spatial presence, involvement, and realness“. In: *Zeitschrift für Medienpsychologie* 15.2 (2003), pp. 69–71 (cit. on p. 4).
- [SKD97] Kay M Stanney, Robert S Kennedy, and Julie M Drexler. „Cybersickness is not simulator sickness“. In: *Proceedings of the Human Factors and Ergonomics Society annual meeting*. Vol. 41. 2. SAGE Publications Sage CA: Los Angeles, CA. 1997, pp. 1138–1142 (cit. on p. 4).
- [Sla03] Mel Slater. „A note on presence terminology“. In: *Presence connect* 3.3 (2003), pp. 1–5 (cit. on p. 3).
- [SRF18] Thomas Schubert, Holger Regenbrecht, and Frank Friedmann. *Igroup Presence Questionnaire (IPQ)*. 2018 (cit. on p. 4).
- [Ste+10] F. Steinicke, G. Bruder, J. Jerald, H. Frenz, and M. Lappe. „Estimation of Detection Thresholds for Redirected Walking Techniques“. In: *IEEE Transactions on Visualization and Computer Graphics* 16.1 (Jan. 2010), pp. 17–27 (cit. on p. 7).
- [SUS95] Mel Slater, Martin Usoh, and Anthony Steed. „Taking steps: the influence of a walking technique on presence in virtual reality“. In: *ACM Transactions on Computer-Human Interaction (TOCHI)* 2.3 (1995), pp. 201–219 (cit. on p. 4).
- [VKE16] Sebastian Von Mammen, Andreas Knotte, and Sarah Edenhofer. „Cyber sick but still having fun“. In: *Proceedings of the 22nd ACM Conference on Virtual Reality Software and Technology*. ACM. 2016, pp. 325–326 (cit. on p. 4).
- [WJS05] Bob G. Witmer, Christian J. Jerome, and Michael J. Singer. „The Factor Structure of the Presence Questionnaire“. In: *Presence: Teleoperators and Virtual Environments* 14.3 (2005), pp. 298–312 (cit. on p. 4).
- [WS98] Bob G Witmer and Michael J Singer. „Measuring presence in virtual environments: A presence questionnaire“. In: *Presence* 7.3 (1998), pp. 225–240 (cit. on p. 4).
- [XMS17] M. Xu, M. Murcia-López, and A. Steed. „Object location memory error in virtual and real environments“. In: *2017 IEEE Virtual Reality (VR)*. Mar. 2017, pp. 315–316 (cit. on p. 6).
- [Yao+14] Richard Yao, Tom Heath, Aaron Davies, et al. „Oculus vr best practices guide“. In: *Oculus VR* (2014), pp. 27–39 (cit. on p. 6).
- [ZF02] Xiaolong Zhang and George W. Furnas. „Social Interactions in Multiscale CVEs“. In: *Proceedings of the 4th International Conference on Collaborative Virtual Environments*. CVE '02. ACM, 2002, pp. 31–38 (cit. on p. 8).

List of Figures

- 2.1 An overview of VR locomotion techniques including their benefits and drawbacks. Green color (+) means that this attribute is a known advantage of the technique, yellow (○) stands for limited value, and red (-) is rather a disadvantage. 9

List of Tables

Listings

Declaration

You can put your declaration here, to declare that you have completed your work solely and only with the help of the references you mentioned.

City, October 4, 2015

Andrey Krekhov

