

Programming with C and C++

CSC-101 (Lecture 28)

Dr. R. Balasubramanian
Professor

Department of Computer Science and Engineering
Mehta Family School of Data Science and Artificial Intelligence
Indian Institute of Technology Roorkee
Roorkee 247 667

bala@cs.iitr.ac.in
<https://faculty.iitr.ac.in/cs/bala/>



Sample CPP code



<https://ideone.com/5hi8xD>

```
1  #include <iostream>
2
3  using namespace std;
4
5  int main() {
6      int num1, num2;
7      cout << "Enter the first number: " << endl;
8      cin >> num1;
9      cout << "Enter the second number: " << endl;
10     cin >> num2;
11
12     int sum = num1 + num2;
13     cout << "Sum of " << num1 << " and " << num2 << " is: " << sum << endl;
14
15     return 0;
16 }
17
```

Success #stdin #stdout 0.01s 5424KB

Enter the first number:

Enter the second number:

Sum of 10 and 5 is: 15

Rating Ranges in Codeforces



Elo-MMR	Title	Division	Number	Percentile
3000+	Legendary Grandmaster	1	8	99.99
2700-2999	International Grandmaster	1	37	99.95
2400-2699	Grandmaster	1	255	99.7
2200-2399	International Master	1	560	99.1
2000-2199	Master	1	2089	97
1800-1999	Candidate Master	2	3968	93
1600-1799	Expert	2	7103	86
1400-1599	Specialist	3	11003	75
1200-1399	Apprentice	3	16909	58
1000-1199	Pupil	4	23977	34
Up to 999	Newbie	4	33923	0

Ratings in Codeforces



HOME TOP CATALOG CONTESTS GYM PROBLEMSET GROUPS RATING EDU

AMNESIAC_DUSK BLOG TEAMS SUBMISSIONS GROUPS CONTESTS

Grandmaster
amnesiac_dusk

Rahul Dugar, India
From IIT Roorkee



Contest rating: **2532** (max. **international grandmaster, 2820**)



Contribution: **+10**



Friend of: 4,655 users

- ▶ Some operators used only in C++ and not in C?
 - **this, new, ::, throw, ...**
- ▶ switch-case and loops are same
- ▶ All the concepts till previous lecture (Arrays, functions, pointers and pass by value) are similar
- ▶ Till procedural oriented concepts both are similar
- ▶ Of course, the syntax is different
- ▶ Reference variable concept is found in C++ but not in C (will be covered in this lecture)

Sample cpp code



```
1  #include <iostream>
2  #include <cmath>
3
4  using namespace std;
5
6  bool isPrime(int num) {
7      if (num <= 1)
8          return false;
9      if (num == 2)
10         return true;
11
12     if (num % 2 == 0)
13         return false;
14 }
```

<https://ideone.com/mPHqxf>



Sample cpp code



```
15     int sqrtNum = sqrt(num);
16     for (int i = 2; i <= sqrtNum; i++) {
17         if (num % i == 0)
18             return false;
19     }
20
21     return true;
22 }
23
```

Sample cpp code



```
23
24 int main() {
25     int num;
26     cout << "Enter a number: ";
27     cin >> num;
28
29     if (isPrime(num))
30         cout << num << " is a prime number." << endl;
31     else
32         cout << num << " is not a prime number." << endl;
33
34     return 0;
35 }
36
37
```

stdin

43

stdout

Enter a number: 43 is a prime number.

Arrays



- ▶ Write a C++ program to generate the following series using Arrays

1,7,2,9,8,9,11,17,17,20, ...



Arrays



<https://ideone.com/xBW0Ur>

```
1  #include <iostream>
2
3  using namespace std;
4
5  void generateSeries(int n) {
6      int series[n];
7      series[0] = 1;
8      series[1] = 7;
9      series[2] = 2;
10     series[3] = 9;
11
12     for (int i = 4; i < n; i++) {
13         series[i] = series[i - 4] + series[i - 3];
14     }
15 }
16
17
```

Arrays



```
18      // Print the generated series
19      for (int i = 0; i < n; i++) {
20          cout << series[i] << " ";
21      }
22  }
23
24  int main() {
25      int n;
26
27      cout << "Enter the number of terms in the series: ";
28      cin >> n;
29
30      generateSeries(n);
31
32      return 0;
33  }
34
```

Arrays



 stdin

 copy

20

 stdout

 copy

Enter the number of terms in the series: 1 7 2 9 8 9 11 17 17 20 28 34 37 48 62 71 85
110 133 156



Reference Operator (&) in C++



<https://ideone.com/vTUskQ>

```
1  #include <iostream>
2  using namespace std;
3
4  int main() {
5      int num1, num2;
6      cout << "Enter the first number: " << endl;
7      cin >> num1;
8      cout << "Enter the second number: " << endl;
9      cin >> num2;
10     int sum = num1 + num2;
11     cout << "Sum of " << num1 << " and " << num2 << " is: " << sum << endl;
12     cout << "Address of num1 is " << &num1 << endl;
13     cout << "Address of num2 is " << &num2 << endl;
14     cout << "Address of sum is " << &sum << endl;
15
16     return 0;
17 }
18
```

Reference Operator (&) in C++



Success #stdin #stdout 0.01s 5448KB

Enter the first number:

Enter the second number:

Sum of 50 and 100 is: 150

Address of num1 is 0x7fff95f4cebc

Address of num2 is 0x7fff95f4cec0

Address of sum is 0x7fff95f4cec4

Reference Operator in C++



```
1  #include <iostream>
2  using namespace std;
```

<https://ideone.com/RV4ud1>

```
3
4  int main() {
5      // your code goes here
6      int n=44;
7      int rn;
8      rn=n;
9      cout<<"n="<<n<<" "<<"rn="<<rn<<endl;
10     n--;
11     cout<<"n="<<n<<" "<<"rn="<<rn<<endl;
12     rn*=2;
13     cout<<"n="<<n<<" "<<"rn="<<rn<<endl;
14
15     return 0;
16 }
17
```

n=44 rn=44

n=43 rn=44

n=43 rn=88

Reference Operator in C++



```
1  #include <iostream>
2  using namespace std;
3
4  int main() {
5      // your code goes here
6      int n=44;
7      int& rn=n;
8      cout<<"n="<<n<<" "<<"rn="<<rn<<endl;
9      n--;
10     cout<<"n="<<n<<" "<<"rn="<<rn<<endl;
11     rn*=2;
12     cout<<"n="<<n<<" "<<"rn="<<rn<<endl;
13
14     return 0;
15 }
16
17
```

<https://ideone.com/6zc2ds>

n=44 rn=44

n=43 rn=43

n=86 rn=86


```
1  #include <stdio.h>
2
3  int main(void) {
4      // your code goes here
5      int n=44;
6      int& rn=n;
7      printf("%d",n);
8      return 0;
9  }
10
11
```

<https://ideone.com/Kgc3qM>

Compilation error #stdin compilation error #stdout 0s 0KB

 stdin

Standard input is empty

compilation info

prog.c: In function 'main':

prog.c:6:5: error: expected identifier or '(' before '&' token

```
int& rn=n;
```


```
    ^
```

Dereference Operator (*) in C++



A pointer is a variable that points to an address of an another variable.

```
void main()
{
int u=30;
int v;
int *pu, *pv;
pu=&u;
v=*pu;
pv=&v;
cout<<u<<&u<<pu<<*pu;
cout<<v<<&v<<pv<<*pv;
}
```

A faint, light gray illustration of a lion statue, likely the IIT Roorkee mascot, positioned behind the code block.

Dereference Operator (*) in C++




```
1  #include <iostream>
2  using namespace std;
3
4  int main() {
5      // your code goes here
6      int u=30;
7      int v;
8      int *pu, *pv;
9      pu=&u;
10     v=*pu;
11     pv=&v;
12     cout<<"u="<<u<<" &u="<<&u<<" pu="<<pu<<" *pu="<<*pu<<endl;
13     cout<<"v="<<v<<" &v="<<&v<<" pv="<<pv<<" *pv="<<*pv<<endl;
14
15     return 0;
16 }
```

<https://ideone.com/hrfFzp>

Success #stdin #stdout 0.01s 5544KB

u=30 &u=0x7ffcd1dcd3e0 pu=0x7ffcd1dcd3e0 *pu=30
v=30 &v=0x7ffcd1dcd3e4 pv=0x7ffcd1dcd3e4 *pv=30

- ▶ All pointer concepts are similar to C
- ▶ Null pointer, Dangling pointer, Arrays and pointers, functions and pointers are similar to C



Pointers in C++



<https://ideone.com/qxbaM2>

```
1  #include <iostream>
2  using namespace std;
3
4  int main() {
5      // your code goes here
6      int u=50;
7      int v;
8      int *pu, *pv;
9      pu=&u; //stores the address of number variable
10     v=*pu;
11     pv=&v;
12     cout<<"u="<<u<<" &u="<<&u<<" pu="<<pu<<" *pu="<<*pu<<endl;
13     cout<<"v="<<v<<" &v="<<&v<<" pv="<<pv<<" *pv="<<*pv<<endl;
14
15     return 0;
16 }
17
```

Success #stdin #stdout 0.01s 5536KB

u=50 &u=0x7ffc2765a7f0 pu=0x7ffc2765a7f0 *pu=50
v=50 &v=0x7ffc2765a7f4 pv=0x7ffc2765a7f4 *pv=50

Pointers in C++



```
1  #include <iostream>
2  using namespace std;
3
4  int main() {
5      int v=5;
6      int *pv;
7      pv=&v; //stores the address of number variable
8      cout<<*pv<<" "<<v<<endl;
9      *pv=500;
10     cout<<*pv<<" "<<v<<endl;
11     return 0;
12 }
13
```

<https://ideone.com/49j43G>

 stdout

5	5
500	500

Null Pointer



```
1  #include <iostream>
2  using namespace std;
3
4  int main() {
5      // your code goes here
6      int u=50;
7      int* pu;
8      pu=NULL; //stores the address of number variable
9      cout<<*pu;
10
11     return 0;
12 }
13
```

<https://ideone.com/P9rHcO>

Runtime error #stdin #stdout 0.01s 5476KB

Dangling Pointer



```
1  #include <iostream>
2  using namespace std;
3
4  int main() {
5      int u1,u2;
6      int v=20;
7      int *pv;
8      u1=2*(v+5);
9      u2=2*(*pv+5);
10     cout<<u1<<" "<<u2<<endl;
11     return 0;
12 }
13
```

<https://ideone.com/ZThZ2p>

Runtime error

Arrays and Pointers



```
1  #include <iostream>
2  using namespace std;
3
4  int main()
5  { int a[3];
6    for (int i=0; i<3; i++)
7      {cin>>a[i];
8       cout<<a[i]<<endl;
9       cout<<a+i<<endl;
10      cout<<*(a+i)<<endl;
11      cout<<i[a]<<endl<<endl;
12    }
13    return 0;
14  }
15
```

<https://ideone.com/arqZ4m>

10

0x7ffe1893683c

10

10

30

0x7ffe18936844

30


30

20

0x7ffe18936840

20

20



Call by Value



<https://ideone.com/SCvrCx>

```
1  #include <iostream>
2  using namespace std;
3
4  void swapVariables(float var1, float var2)
5  {
6      float temp;
7      temp = var1;
8      var1 = var2;
9      var2 = temp;
10     cout<<var1<<" "<<var2<<endl;
11 }
12
13 int main( )
14 {
15     float float1 = 3.5, float2 = 5.6;
16     swapVariables(float1, float2);
17     cout<<float1<<" "<<float2<<endl;
18     return 0;
19 }
```

 stdout

5.6 3.5

3.5 5.6

Call by Reference



<https://ideone.com/h9gXrt>

```
1  #include <iostream>
2  using namespace std;
3
4  void swapVariables(float& var1, float& var2)
5  { float temp;
6      temp = var1;
7      var1 = var2;
8      var2 = temp;
9      cout<<var1<<" "<<var2<<endl;
10 }
11
12 int main( )
13 { float float1 = 3.5, float2 = 5.6;
14     swapVariables(float1, float2);
15     cout<<float1<<" "<<float2<<endl;
16     return 0;
17 }
18
```

 stdout

5.6 3.5

5.6 3.5

