

Programming with C and C++

CSC-101 (Lecture 08)


Dr. R. Balasubramanian
Professor

Department of Computer Science and Engineering
Mehta Family School of Data Science and Artificial Intelligence
Indian Institute of Technology Roorkee
Roorkee 247 667

bala@cs.iitr.ac.in
<https://faculty.iitr.ac.in/cs/bala/>



Type casing



Implicit casting



</> source code

```
1  #include<stdio.h>
2  main(){
3      int i=40;
4      float a;
5      //Implicit conversion
6      a=i;
7      printf("implicit value:%f",a);
8  }
9
```

<https://ideone.com/vljn86>

Explicit casting



</> source code

```
1  #include<stdio.h>
2  main(){
3      int i=40;
4      short a;
5      //Explicit conversion
6      a=(short)i;
7      printf("explicit value:%d",a);
8  }
9  |
```

<https://ideone.com/rWWOUI>



</> source code

```
1  #include <stdio.h>
2
3  main() {
4
5      int sum = 470, count = 5;
6      double mean;
7
8      mean = (double) sum / count;
9      printf("Value of mean : %f\n", mean );
10 }
11
```

<https://ideone.com/zxeMS4>

</> source code


```
1  #include <stdio.h>
2
3  main() {
4
5      int sum = 471, count = 5;
6      double mean;
7      long int mean1;
8      int mean2;
9
10     mean = (double) sum / count;
11     mean1= (long) mean;
12     mean2= (int) mean1;
13     printf("Value of mean : %f\n", mean);
14     printf("Value of mean : %ld\n", mean1);
15     printf("Value of mean : %d\n", mean2);
16 }
17
```

<https://ideone.com/F34xod>

Operators in C



- ▶ Arithmetic Operators
- ▶ Relational Operators
- ▶ Shift Operators
- ▶ Logical Operators
- ▶ Bitwise Operators
- ▶ Ternary or Conditional Operators
- ▶ Assignment Operator
- ▶ Misc Operator



Arithmetic Operators



Operator	Use of Operator
+	Use to Add Two Numbers and Also used to Concatenate two strings
-	Used for Subtraction
*	Used to multiply numbers
/	Used for Division
%	Used for Finding Mod (Remainder Operator)



Arithmetic Operators



- ▶ Write a C Program to reverse 4 digit number using arithmetic operator

</> source code

```
1  #include <stdio.h>
2
3  int main() {
4      int number, reversedNumber;
5
6      printf("Enter a 4-digit number: ");
7      scanf("%d", &number);
8
9      if (number < 1000 || number > 9999)
10         printf("Please enter a valid 4-digit number.\n");
11
12     int thousands = number / 1000;
13     int hundreds = (number % 1000) / 100;
14     int tens = (number % 100) / 10;
15     int ones = number % 10;
```

```
16  
17     reversedNumber = ones * 1000 + tens * 100 + hundreds * 10 + thousands;  
18  
19     printf("Reversed number: %d\n", reversedNumber);  
20  
21     return 0;  
22 }
```

<https://ideone.com/N2F860>

 stdin

6789

 stdout

Enter a 4-digit number: Reversed number: 9876

Relational Operator



Operator	Result
==	Equal to
!=	Not equal to
>	Greater than
<	Less than
>=	Greater than or equal to
<=	Less than or equal to

Relational Operator



</> source code

```
1  #include <stdio.h>
2
3  main() {
4
5      int a = 21;
6      int b = 10;
7      int c ;
8
9      if( a == b ) {
10         printf("Line 1 - a is equal to b\n" );
11     } else {
12         printf("Line 1 - a is not equal to b\n" );
13     }
14
```

Relational Operator



```
14
15 ▼  if ( a < b ) {
16     printf("Line 2 - a is less than b\n" );
17 ▼  } else {
18     printf("Line 2 - a is not less than b\n" );
19     }
20
21 ▼  if ( a > b ) {
22     printf("Line 3 - a is greater than b\n" );
23 ▼  } else {
24     printf("Line 3 - a is not greater than b\n" );
25     }
```

Relational Operator



```
26
27  /* Lets change value of a and b */
28  a = 5;
29  b = 20;
30
31  if ( a <= b ) {
32      printf("Line 4 - a is either less than or equal to b\n" );
33  }
34
35  if ( b >= a ) {
36      printf("Line 5 - b is either greater than or equal to b\n" );
37  }
38  }
```

Success #stdin #stdout 0.01s 5516KB

Line 1 - a is not equal to b

Line 2 - a is not less than b

Line 3 - a is greater than b

Line 4 - a is either less than or equal to b

Line 5 - b is either greater than or equal to b

<https://ideone.com/HAZzof>

Bitwise operators



</> source code

```
1  #include <stdio.h>
2
3  int main(void) {
4      // your code goes here
5      int a=10;
6      int b=5;
7      int c=a&b;
8      int d=a|b;
9      printf("AND %d\n", c);
10     printf("OR %d\n", d);
11     return 0;
12 }
13
```



<https://ideone.com/r7SMJF>

Powers of 2



- ▶ Write a C program to find the maximum of three numbers



Logical (Conditional) Operators



Operator	Use of Operator
&&	Logical-AND
	Logical-OR
!	Logical- NOT

Logical (Conditional) Operators



</> source code

```
1  #include <stdio.h>
2
3  main() {
4
5      int a = 5;
6      int b = 20;
7      int c ;
8
9      if ( a && b ) {
10         printf("Line 1 - Condition is true\n" );
11     }
12
13     if ( a || b ) {
14         printf("Line 2 - Condition is true\n" );
15     }
16
```

```
17      /* lets change the value of  a and b */
18      a = 0;
19      b = 10;
20
21      if ( a && b ) {
22          printf("Line 3 - Condition is true\n" );
23      } else {
24          printf("Line 3 - Condition is not true\n" );
25      }
26
27      if ( !(a && b) ) {
28          printf("Line 4 - Condition is true\n" );
29      }
30
31  }
```

⚙️ stdout

Line 1 - Condition is true

Line 2 - Condition is true

Line 3 - Condition is not true

Line 4 - Condition is true

<https://ideone.com/9o5zrV>

Truth Table



P	Q	$P \& Q$	$P \parallel Q$	$\neg P$
T	T	T	T	F
T	F	F	T	F
F	T	F	T	T
F	F	F	F	T



Assignment Operators



Sum=a+b;

Shorthand Operators

Operator	Example	Equivalent
+=	i += 8	i = i + 8
-=	i -= 8.0	i = i - 8.0
*=	i *= 8	i = i * 8
/=	i /= 8	i = i / 8
%=	i %= 8	i = i % 8

Increment and Decrement Operators



Operator	Name	Example expression	Meaning
++	Postfix increment	x++	add 1 to x and return the old value
++	Prefix increment	++x	add 1 to x and return the new value
--	Postfix decrement	x--	take 1 from x and return the old value
--	Prefix decrement	--x	take 1 from x and return the new value



Increment and Decrement Operators



</> source code

```
1  #include <stdio.h>
2  int main ()
3  {
4  int x=1, y=1;
5
6  ++x;
7  ++y;
8
9  printf (" \n The updated value of the X: %d ", x);
10 printf (" \n The updated value of the Y: %d ", y);
11
12 x--;
13 y--;
14
15 printf (" \n The updated value of the X: %d ", x);
16 printf (" \n The updated value of the Y: %d ", y);
17
18 return 0;
19 }
```

The updated value of the X: 2

The updated value of the Y: 2

The updated value of the X: 1

The updated value of the Y: 1

<https://ideone.com/N3eJ6d>

Increment Operator



</> source code

```
1  #include <stdio.h>
2  int main ()
3  {
4  int a=44, b=45;
5  int c,d;
6
7  c=++b;
8  d=a++;
9
10 printf (" \n The updated value of the a: %d ", a);
11 printf (" \n The updated value of the b: %d ", b);
12 printf (" \n The updated value of the c: %d ", c);
13 printf (" \n The updated value of the d: %d ", d);
14
15 return 0;
16 }
```

The updated value of the X: 45

The updated value of the Y: 46

The updated value of the X: 46

The updated value of the Y: 44

Decrement Operator



</> source code

```
1  #include <stdio.h>
2  int main ()
3  {
4  int a=44, b=45;
5  int c,d;
6
7  c=--b;
8  d=a--;
9
10 printf (" \n The updated value of the a: %d ", a);
11 printf (" \n The updated value of the b: %d ", b);
12 printf (" \n The updated value of the c: %d ", c);
13 printf (" \n The updated value of the d: %d ", d);
14
15 return 0;
16 }
```

The updated value of the a: 43

The updated value of the b: 44

The updated value of the c: 44

The updated value of the d: 44

