

Programming with C and C++

CSC-101 (Lecture 10)

Dr. R. Balasubramanian
Professor

Department of Computer Science and Engineering
Mehta Family School of Data Science and Artificial Intelligence
Indian Institute of Technology Roorkee
Roorkee 247 667

bala@cs.iitr.ac.in
<https://faculty.iitr.ac.in/cs/bala/>



Shift Operator



</> source code

input Output

Success #stdin #stdout 0s 5544KB
240

```
1  #include <stdio.h>
2
3  int main(void) {
4      // your code goes here
5      int a=60;
6      int b=2;
7      int c=a<<b;
8      printf("%d",c);
9      return 0;
10 }
```

<https://ideone.com/rv4fP2>

Shift Operator



$a \ll 2$

$a = 60$

\rightarrow 0011 1100
 \leftarrow

$a \ll 2$ 11 11 00 00
 $\rightarrow 240$

$$\begin{aligned} a \ll b' &= \left\lceil a * 2^{b'} \right\rceil \\ &= \left\lceil 60 * 2^2 \right\rceil \\ &= 240 \end{aligned}$$

$b' = 2$

$a \ll 4$

\rightarrow 1111 0000 0000
 \leftarrow

$$\begin{aligned} &\left\lceil a * 2^4 \right\rceil \\ &= 60 * 16 \\ &= 960 \end{aligned}$$

Shift Operator



</> source code

 stdout

```
1  #include <stdio.h>
2
3  int main(void) {
4      // your code goes here
5      int a=60;
6      int b=2;
7      int c=a>>b;
8      printf("%d",c);
9      return 0;
10 }
```

15

<https://ideone.com/ieiOFK>

Shift Operator



$a \gg 2$

$a \rightarrow 0011 \ 1100$
 \rightarrow

$$\checkmark a \gg b' = \left\lfloor \frac{a}{2^b} \right\rfloor$$

$$= \left\lfloor \frac{60}{2^2} \right\rfloor$$

$$= \left\lfloor \frac{60}{4} \right\rfloor = 15$$

$a \gg 2 \rightarrow$

00	11	11	
			1
			2
			4
			8
<hr/>			
15			
<hr/>			

Shift Operator



$a \ll b$

(or) $a \gg b$

$b > 0$ ✓

$a \ll (-2)$

0011100

XX

$[a \times 2^b] \rightarrow [60 \times 2^{-2}]$

$\rightarrow (15)$ X

May not get

SizeOfEx.c

```
1 ▾ #include <stdio.h>
2 ▾ int main() {
3   int a = 600;
4   printf("Size of variable a : %d\n", sizeof(a));
5   printf("Size of int data type : %d\n", sizeof(int));
6   printf("Size of char data type : %d\n", sizeof(char));
7   printf("Size of float data type : %d\n", sizeof(float));
8   printf("Size of double data type : %d", sizeof(double));
9   return 0;
10 }
```

~\$./a.out

Size of variable a : 4

Size of int data type : 4

Size of char data type : 1

Size of float data type : 4

Size of double data type : 8

~\$ █



<https://ideone.com/T6hsYB>

The precedence and associativity of operators



Category	Operator	Associativity
Postfix	() [] -> . ++ --	Left to right
Unary	+ - ! ~ ++ -- (type)* & sizeof	Right to left
Multiplicative	* / %	Left to right
Additive	+ -	Left to right
Shift	<< >>	Left to right
Relational	< <= > >=	Left to right
Equality	== !=	Left to right
Bitwise AND	&	Left to right
Bitwise XOR	^	Left to right

The precedence and associativity of operators



Category	Operator	Associativity
Bitwise OR		Left to right
Logical AND	&&	Left to right
Logical OR		Left to right
Conditional	?:	Right to left
Assignment	= += -= *= /= %>>= <<= &= ^= =	Right to left
Comma	,	Left to right



Right to Left



</> source code

stdout

-56

```
1  #include <stdio.h>
2
3  int main(void) {
4      // your code goes here
5      int a=60;
6      int b=2;
7      int c=~a+b-~b;
8      printf("%d",c);
9      return 0;
10 }
11
```

<https://ideone.com/6CTCp0>

Right to Left



</> source code

Success #stdin #stdout 0s 5432KB

4

```
1  #include <stdio.h>
2
3  int main(void) {
4      // your code goes here
5      int a=3;
6      int b=2;
7      int c=1;
8      int d=~a/b*~c;
9      printf("%d",d);
10     return 0;
11 }
```

<https://ideone.com/g4sMPE>

Right to Left



Right2Left.c

```
1 ▾ #include <stdio.h>
2
3 ▾ int main(void) {
4   → // your code goes here
5   → int a=5;
6   → int b=6;
7   → a*=b*=5;
8   → printf("%d,%d\n", a,b);
9   → return 0;
10 }
```

```
~$ gcc Right2Left.c
```

```
~$ ./a.out
```

```
150,30
```


```
~$ █
```

<https://ideone.com/COmvxh>

C switch Statement



```
switch (expression) {  
  case value1:  
    //code to be executed;  
    break; //optional  
  case value2:  
    //code to be executed;  
    break; //optional  
  .....  
  default:  
    code to be executed if all cases are not match  
ed;  
}
```

A large, faint watermark of a lion statue is visible in the background of the slide, positioned behind the code text.

C switch Statement



</> source code

```
1  #include <stdio.h>
2  int main()
3  {
4      int x = 10, y = 5;
5      switch(x>y && x+y>0)
6      {
7          case 1:
8              printf("IITR");
9              break;
10         case 0:
11             printf("IITM");
12             break;
13         default:
14             printf("IITK");
15     }
16
17 }
18
```

Success #stdin #stdout 0.01s 5516KB

IITR



<https://ideone.com/MZKPsU>

C switch Statement



```
1  #include <stdio.h>
2
3  int main () {
4
5      /* local variable definition */
6      char grade = 'B';
7
8      switch(grade) {
9          case 'A' :
10             printf("Excellent!\n" );
11             break;
12         case 'B' :
13         case 'C' :
14             printf("Well done\n" );
15             break;
16         case 'D' :
17             printf("You passed\n" );
18             break;
```


C switch Statement



```
19     case 'F' :
20         printf("Better try again\n" );
21         break;
22     default :
23         printf("Invalid grade\n" );
24 }
25
26 printf("Your grade is  %c\n", grade );
27
28 return 0;
29 }
30
```

⚙️ stdout

Well done

Your grade is B

<https://ideone.com/eYrZ7L>

C switch Statement



```
1  #include <stdio.h>
2
3  int main () {
4
5      /* local variable definition */
6      char grade = 'B';
7
8      switch(grade) {
9          case 'A' :
10             printf("Excellent!\n" );
11             break;
12          case 'B' :
13          case 'C' :
14             printf("Well done\n" );
15          case 'D' :
16             printf("You passed\n" );
17          case 'F' :
18             printf("Better try again\n" );
19             break:|
```

C switch Statement



```
20         default :
21             printf("Invalid grade\n" );
22     }
23
24     printf("Your grade is  %c\n", grade );
25
26     return 0;
27 }
28
```

⚙️ stdout

Well done

You passed

Better try again

Your grade is B

<https://ideone.com/3QEeqn>


- ▶ The variable used in a switch statement can only be a short, int, or char.
- ▶ You can have any number of case statements within a switch. Each case is followed by the value to be compared to and a colon.
- ▶ The value for a case must be the same data type as the variable in the switch and it must be a constant or a literal.
- ▶ When the variable being switched on is equal to a case, the statements following that case will execute until a *break* statement is reached.

- ▶ When a *break* statement is reached, the switch terminates, and the flow of control jumps to the next line following the switch statement.
- ▶ Not every case needs to contain a break. If no break appears, the flow of control will *fall through* to subsequent cases until a break is reached.
- ▶ A *switch* statement can have an optional default case, which must appear at the end of the switch. The default case can be used for performing a task when none of the cases is true. No break is needed in the default case.

Decision Making and Looping



- ▶ The process of repeatedly executing a block of statements is known as looping
- ▶ The C language provides for three constructs for performing loop operations
 - while construct
 - do construct
 - for construct




The while Loop



- ▶ A while loop is a control structure that allows you to repeat a task a certain number of times.
- ▶ **Syntax**

```
while(Boolean_expression)
{
    //Statements
}
```



The while Loop



whileex1.c

```
1 ▾ #include <stdio.h>
2
3 ▾ int main () {
4
5 ▾     /* local variable definition */
6     int a = 10;
7
8 ▾     /* while loop execution */
9 ▾     while( a < 20 ) {
10         printf("value of a: %d\n", a);
11         a++;
12     }
13
14     return 0;
15 }
```

```
~$ gcc whileex1.c
~$ ./a.out
value of a: 10
value of a: 11
value of a: 12
value of a: 13
value of a: 14
value of a: 15
value of a: 16
value of a: 17
value of a: 18
value of a: 19
~$ █
```

<https://ideone.com/QosfjB>

The while Loop



whileex2.c

```
1 ▾ #include<stdio.h>
2  int main()
3  ▾ {
4      int i=1,fact=1,number;
5      printf("Enter a number: ");
6      scanf("%d",&number);
7  ▾      while (i<=number){
8          fact=fact*i;
9          i++;
10     }
11     printf("Factorial of %d is: %d\n",number,fact);
12     return 0;
13 }
14
```

```
~$ gcc whileex2.c
~$ ./a.out
Enter a number: 6
Factorial of 6 is: 720
~$ █
```

