

# LLM-Based Intelligent Notification Composition: From Static Personalization to Context-Aware Persuasive Messaging

Nilesh Agrawal   nilesh.d.agrawal@gmail.com

Independent Researcher, Seattle, WA, USA

March 2026

## Abstract

Push notifications remain among the most direct and time-sensitive channels through which digital platforms engage users, yet conventional approaches to notification copywriting—manual authoring and rule-based templating—do not scale to the billions of user interactions generated by modern platforms. This paper presents a systematic survey and architectural framework for LLM-based intelligent notification composition. Modern notification systems are highly effective at deciding *who* to notify, *when* to notify, and *what* to recommend, but they remain weak at deciding *how* to communicate. Most systems still rely on rigid, slot-filled templates that produce relevance without intelligence. We argue that the next evolution of notifications is not simply better personalization, but intelligent composition: using LLMs to transform static alerts into context-aware, persuasive, and adaptive messages. We examine how LLMs are being integrated into production notification pipelines across social media, food delivery, and e-commerce, focusing on the technical mechanisms that enable scalable and context-aware generation, including Retrieval-Augmented Generation (RAG), Parameter-Efficient Fine-Tuning (PEFT), pairwise reward modeling, and contextual bandits for send-time optimization.

A central contribution of this work is the explicit disentanglement of message generation from adjacent recommender system components such as audience targeting, content ranking, and delivery timing. We argue that observed gains in engagement are often incorrectly attributed to text generation alone, when in practice they arise from interaction effects across the full pipeline. Rather than proposing a novel algorithmic primitive, this paper contributes an integration-level architectural synthesis: a unified notification framework that incorporates budget-aware routing, grounded generation, candidate ranking, diversity controls, frequency capping, and online learning. We also critically assess current evaluation practice, highlighting the mismatch between short-term click metrics and long-term user health, the fragility of causal inference assumptions in networked platforms, and the ethical boundary between personalization and manipulation. Our analysis suggests that LLMs can deliver meaningful value in high-context, high-variance notification settings, but only when deployed with rigorous safeguards, careful experimental design, and explicit recognition that language generation is not always the primary bottleneck.

**Keywords:** Large Language Models, Push Notifications, Personalization, Natural Language Generation, Recommender Systems, Causal Inference, Retrieval-Augmented Generation, Reward Modeling

# 1 Introduction

In the contemporary digital economy, user attention is scarce, interruptible, and intensely contested. Consumer platforms invest heavily in acquisition, but long-term value depends just as much on retention, reactivation, and repeated high-value engagement. Push notifications have therefore become a central operational mechanism for re-engaging users outside the application surface. On large consumer platforms, daily notification volumes range from millions to billions, and small changes in notification quality can materially affect click-through rates (CTR), conversion outcomes, and the broader health of the platform ecosystem (Bie et al., 2026). Poorly targeted or repetitive notifications do not merely underperform; they actively erode trust, accelerate opt-outs, and contribute to long-term channel degradation (Ohly et al., 2023).

Historically, platforms have relied on two broad strategies for notification composition: manual copywriting and template-based generation. Most production notification systems today remain template-driven. Even when personalization is present, it is often limited to slot filling, such as inserting a user’s preferred category, recent item, or location into a fixed message pattern. This makes notifications relevant in a narrow sense, but rarely intelligent in how they communicate. The central tension is that modern systems are effective at deciding *who* to notify, *when* to notify, and *what* to recommend, but they are still weak at deciding *how* to communicate the recommendation in an adaptive, context-rich, and persuasive way.

Large Language Models (LLMs) create a new opportunity: not merely to personalize notifications, but to make them context-aware, adaptive, and semantically persuasive (Vaswani et al., 2017). Consider a user with a historical preference for pizza receiving a dinner-time notification at 6 PM. A conventional system may send a static message such as “Order your favorite pizza now.” An LLM-enabled system, by contrast, can incorporate temporal context, prior taste signals, and controlled novelty to generate a richer message such as: “It’s the perfect time for dinner—your usual pizza spot is nearby, and their sweet-and-savory pineapple special might be worth trying tonight.” In this setting, the value of the LLM is not in identifying the user or the category alone, but in producing a more intelligent, context-sensitive, and action-inducing framing of the recommendation.

Yet enthusiasm for LLM-based messaging has also created analytical confusion. In many production pipelines, the notification message is only one stage in a larger decision stack that includes audience selection, content ranking, delivery timing, budget allocation, and post-hoc candidate filtering. Reported gains in engagement are often attributed broadly to “AI notifications” or “LLM personalization,” even when the observed uplift may be driven primarily by upstream improvements in targeting or timing. This conflation obscures both scientific understanding and engineering decision-making.

This paper addresses that gap by providing both a systematic survey and an architectural framework for LLM-based intelligent notification composition. We argue that the next evolution of notifications is not simply better personalization, but intelligent composition: using LLMs to transform static or slot-filled alerts into context-aware, persuasive, and adaptive messages that better align recommendations with user intent, real-time context, and controlled novelty.

## 1.1 Contributions and Novelty Statement

This paper makes four contributions:

1. **Systematic Synthesis:** A structured systematic survey of academic and industrial work on LLM-based notification systems, using a PRISMA-guided review process and an evidence-

tiering scheme to distinguish between peer-reviewed results, industrial deployment reports, and contextual sources.

2. **Architectural Disentanglement:** An architectural attribution perspective that explicitly separates the contribution of message generation from adjacent components such as targeting, ranking, and send-time optimization.
3. **Unified Framework:** A unified end-to-end framework for notification composition that integrates grounded generation, style adaptation, reward-based candidate ranking, diversity and frequency controls, budget-aware routing, and online learning. The novelty lies in *integration novelty*—the logic and operational sequencing across known components—rather than the invention of any single component.
4. **Critical Evaluation Framework:** A critical evaluation and governance perspective highlighting shortcomings in current measurement practice, especially around causal inference, heterogeneous treatment effects, long-term user health, and the ethical boundary between personalization and manipulation.

## 2 Review Methodology

To support a structured and transparent synthesis, this survey followed a systematic review methodology designed for a fast-moving applied field in which relevant evidence is distributed across both academic publication channels and industrial documentation.

### 2.1 Search Strategy and PRISMA Flow

We conducted targeted searches across arXiv, ACM Digital Library, IEEE Xplore, and ScienceDirect, along with engineering publications and official technical blogs from major technology companies. The review covered the period from **January 2018 through March 2026**, chosen to capture the transition from pre-LLM notification optimization methods to contemporary generative systems. Search terms combined model-oriented concepts (“LLM”, “RAG”, “PEFT”, “LoRA”, “reward modeling”) with application-oriented phrases (“push notification”, “message composition”, “send-time optimization”, “CTR optimization”, “contextual bandit”).

The screening process followed a formal PRISMA (Preferred Reporting Items for Systematic Reviews and Meta-Analyses) flow, as illustrated in Figure 1.

### 2.2 Evidence Tiering and Source Limitations

Because industrial notification systems often evolve more quickly than formal academic publication cycles, excluding non-academic sources would omit some of the most operationally relevant systems. At the same time, engineering blogs and deployment writeups frequently lack the methodological transparency needed for strong causal claims. To address this, sources were organized into three evidence tiers, which are marked inline throughout the text:

- **[T1] Tier 1 (High Rigor):** Peer-reviewed papers and formally published preprints (e.g., WSDM, CHI, RecSys) with clear methodology, baseline comparisons, and meaningful technical depth.

Table 1: Key Primary Sources and Systems Reviewed

| System / Paper                                    | Domain            | Primary Technology                 | Technol- | Evaluation           | Key Finding                    | Tier |
|---------------------------------------------------|-------------------|------------------------------------|----------|----------------------|--------------------------------|------|
| <b>PushGen</b> (Bie et al., 2026)                 | Social Media      | LLM (SFT) + Pair-wise Reward Model |          | Online A/B + Offline | +14.08% CTR                    | [T1] |
| <b>Instagram Diversity</b> (Sun et al., 2025)     | Social Media      | Similarity Layer                   | Penalty  | Online A/B           | Reduced volume, improved CTR   | [T2] |
| <b>DoorDash GNN</b> (Sinha, 2024)                 | Food Delivery     | ID-GNN + Contextual Copy           |          | Online A/B           | +1.8% engagement lift          | [T2] |
| <b>E-Commerce LLM</b> (ACM Digital Library, 2025) | E-Commerce        | LLM Content Optimization           | Opti-    | Online A/B           | +12.5% CTR, +8.3% CVR          | [T1] |
| <b>Tu et al.</b> (Tu et al., 2021)                | Professional Net. | Heterogeneous Treatment Effects    | Treat-   | A/B + Causal Sim.    | Personalized caps reduce churn | [T1] |
| <b>Yancey et al.</b> (Yancey et al., 2020)        | EdTech            | Contextual (Thompson)              | Bandit   | Online A/B           | Send-time opt. increases DAU   | [T1] |
| <b>Luo et al.</b> (Luo et al., 2024)              | General RS        | Causal Inference Survey            | Survey   | Literature Review    | Identifies SUTVA violations    | [T1] |

- **[T2] Tier 2 (Moderate Rigor):** Official engineering blogs and deployment reports from major technology companies describing production systems and online results. **Limitation:** These often omit experimental controls or statistical detail.
- **[T3] Tier 3 (Contextual):** Vendor documentation and secondary summaries used only for framing broader trends rather than establishing performance claims.

### 2.3 Corpus Summary and Quantitative Synthesis

Table 1 summarizes the key primary sources anchoring our architectural synthesis, classified by domain and evaluation method.

**Quantitative Synthesis:** Across the corpus, reported engagement lifts from LLM integration vary significantly by domain and baseline quality. Studies replacing manual or poorly optimized static

templates report large CTR gains ranging from +8.0% to +14.5% (Bie et al., 2026; ACM Digital Library, 2025). However, in highly mature systems where LLMs are competing against heavily optimized contextual slot-filling, the marginal relative lifts are typically much smaller, clustering in the +1.0% to +2.5% range (Sinha, 2024). This variance underscores that “LLM uplift” is not an absolute constant, but a function of the baseline system’s prior sophistication.

### 3 Disentangling LLM Contributions from Adjacent Systems

A recurring analytical error in both industrial discourse and academic reporting is to treat notification performance as if it were primarily a function of the copy itself. In real systems, however, the notification message is the output of a multi-stage decision process. The system must choose whom to notify, what to notify them about, when to deliver the message, how to phrase it, and, if multiple candidates are generated, which candidate to send. LLMs affect only a subset of that stack.

Table 2: Architectural Attribution Matrix

| Component                        | Contribution to Engagement                                                                      |
|----------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Audience Selection</b>        | Ensures budget is spent on users with highest marginal return; prevents spamming dormant users. |
| <b>Content Ranking</b>           | Ensures the underlying item is highly relevant to the user’s interests.                         |
| <b>Send-Time Optimization</b>    | Capitalizes on user’s daily routines; minimizes disruption.                                     |
| <b>Message Generation (LLMs)</b> | Adapts tone, length, and specific hooks to user persona; increases semantic diversity.          |
| <b>Candidate Ranking</b>         | Aligns stylistic generation with historical CTR data; filters out poor LLM outputs.             |

This decomposition (Table 2) clarifies both the promise and the limits of LLMs. LLMs are strongest when the system already knows the relevant content and approximate delivery conditions, but still needs to decide how best to frame the notification. Their marginal value lies in semantic diversity, contextual nuance, and stylistic adaptation. They do not solve the targeting problem, the relevance problem, or the temporal decision problem.

## 4 Core Architectural Frameworks and Technical Tradeoffs

Across the literature, several technical patterns recur in the generation and ranking stages of notification systems. Table 3 categorizes these dominant architectural patterns by their strengths, weaknesses, and primary failure modes.

### 4.1 Retrieval-Augmented Generation and Grounding

Retrieval-Augmented Generation (RAG) is one of the most natural fits for notification systems because notifications are highly contextual and often fact-sensitive (Lewis et al., 2020). Rather than

Table 3: Comparative Synthesis of Architectural Patterns

| Pattern                         |   | Main Strength                                       | Main Weakness                         | Key Failure Mode           |
|---------------------------------|---|-----------------------------------------------------|---------------------------------------|----------------------------|
| <b>Template Slot Filling</b>    | / | Low latency, high control, easy compliance          | Low diversity, weak personalization   | Message fatigue            |
| <b>RAG-Grounded LLM</b>         |   | Context-aware personalization, factual grounding    | Retrieval latency, grounding failures | Faithfulness hallucination |
| <b>PEFT / LoRA</b>              |   | Cheap specialization, hot-swappable voice control   | Requires curation of style objectives | Overfitting to narrow tone |
| <b>Pairwise Reward Modeling</b> |   | Better relative ranking than pointwise CTR          | Exposure bias, delayed reward issues  | Reward hacking             |
| <b>Diversity Penalty</b>        |   | Reduces novelty fatigue, improves long-term quality | Can suppress short-term CTR           | Under-delivery             |
| <b>Contextual Bandit STO</b>    |   | Adapts to user routines, improves timing            | Exploration cost, sparse feedback     | Wrong-time cold-start      |
| <b>Budget-Aware Routing</b>     |   | Aligns compute with expected value                  | Depends on accurate CLV estimation    | Over-serving active users  |
| <b>Counterfactual Logging</b>   |   | Supports off-policy evaluation                      | Operationally costly and complex      | Biased logs                |

depending solely on the model’s internal parameters, RAG injects external information into the prompt at inference time, typically including user profile attributes, item metadata, recent behavioral context, and campaign constraints.

However, RAG introduces nontrivial system design challenges. Retrieval granularity affects both relevance and latency. Small chunks may improve precision but omit necessary surrounding context, while larger chunks improve recall at the expense of noise and prompt length (COLING, 2025). Furthermore, retrieval success does not guarantee faithful generation. Even when the correct context is retrieved, the model may ignore it, blend it with parametric memory, or produce an output that is only loosely supported by the evidence—a phenomenon known as “faithfulness hallucination” (EMNLP, 2025). The implication is that RAG should be treated as a grounding mechanism, not a complete factuality solution.

## 4.2 Parameter-Efficient Fine-Tuning and Style Control

Notification systems often require control over tone, brevity, urgency, and brand voice. While prompting alone can induce some stylistic variation, stable control at scale often requires model adaptation. Full fine-tuning is expensive and operationally inflexible. Parameter-Efficient Fine-Tuning (PEFT) methods, especially Low-Rank Adaptation (LoRA) (Hu et al., 2022), provide a more practical alternative by freezing the pre-trained model weights and injecting trainable rank decomposition matrices ( $W = W_0 + BA$ , where  $B$  and  $A$  are low-rank) into the Transformer layers.

This is particularly useful in notification systems because different campaigns, user segments, or

brands may demand different stylistic priors. The appeal of LoRA is not only training efficiency but deployment flexibility: adapters can be swapped or merged with the base model weights during deployment, resulting in zero inference latency overhead (Han et al., 2024). Still, style adaptation creates its own risks. Over-optimization toward a narrow tone may increase short-term reward while pushing the system toward formulaic or manipulative language.

### 4.3 Pairwise Reward Modeling and Candidate Ranking

A central challenge in notification generation is not merely producing candidate messages, but identifying which candidate is most likely to produce the desired downstream action. Pointwise prediction of click probability from a single candidate is often unstable because observed outcomes are confounded by item quality, creator popularity, time of day, and historical policy bias. Pairwise reward modeling offers a more robust alternative: instead of predicting an absolute score, the model learns to prefer one candidate over another (Bie et al., 2026).

Yet reward modeling is also vulnerable to exposure bias. Historical logs contain feedback only for messages that were actually shown, meaning the reward model inherits the distributional blind spots of the previous system. Delayed rewards make the problem worse: the user may click immediately but convert much later, or not at all (University of Milano-Bicocca, 2024). Addressing this requires *counterfactual logging*—deploying exploratory logging policies (like  $\epsilon$ -greedy) to gather unbiased data for off-policy evaluation (Joachims et al., 2018).

### 4.4 Send-Time Optimization Through Contextual Bandits

Although notification copy is often the most visible element of the system, timing can be equally or more important than wording. Send-time optimization (STO) determines whether a message is delivered when the user is receptive, distracted, asleep, or oversaturated.

Contextual multi-armed bandits provide a strong formalism for this task. By conditioning on user state and continuously trading off exploration and exploitation, bandit-based timing policies can discover individualized temporal windows for engagement. The Duolingo system models STO as a “sleeping recovering bandit” using Thompson Sampling for exploration (Yancey et al., 2020). The key lesson is architectural: timing should not be treated as a minor delivery detail after generation. In many systems it is one of the dominant determinants of performance (Ho et al., 2018).

## 5 Domain-Specific Applications and Limits of Generalization

Although the underlying technical components recur across domains, the meaning of a “good” notification varies substantially by industry. Differences in user intent, action latency, business objective, and tolerance for persuasion shape both architecture and evaluation. Figure 2 provides a conceptual mapping of these differences.

### 5.1 Social Media

In social media platforms, notifications often drive content discovery, return sessions, or creator engagement. High-value users may be defined in terms of DAU, content production, or network centrality rather than direct revenue. This makes diversity especially important: repetitive or overly formulaic notifications may produce short-term clicks but harm long-term engagement through



novelty fatigue. The PushGen system (Bie et al., 2026) and Instagram’s diversity penalty layer (Sun et al., 2025) are highly representative of this domain’s need to balance relevance with semantic variety.

## 5.2 Food Delivery and Local Commerce

Food delivery notifications are strongly shaped by spatiotemporal context. Weather, time of day, delivery radius, restaurant availability, and recent ordering behavior all interact in ways that can make language framing materially important. A lunch offer framed around convenience during rain may outperform a generic discount message even when the underlying restaurant recommendation is the same (Sinha, 2024). This domain illustrates the critical importance of grounding: unlike pure content discovery, food delivery notifications encode strict operational claims about availability and ETA.

## 5.3 E-Commerce

E-commerce notifications are typically closer to direct-response marketing. Here the primary objective is not always the click itself, but conversion, order value, or recovery of partially completed user intent. Abandoned-cart flows, price-drop alerts, and browse-retargeting campaigns all provide natural contexts in which multiple framings can be plausible and economically meaningful. The reported +12.5% CTR and +8.3% CVR gains from LLM content optimization (ACM Digital Library, 2025) are consistent with the hypothesis that e-commerce users are particularly responsive to urgency and scarcity framing.

# 6 When LLM Text Generation Is Not the Binding Constraint

A recurring risk in the current discourse on LLM-driven notification systems is the assumption that better text generation necessarily yields the largest marginal gain in engagement. In mature notification stacks, this is often false. The dominant constraint may instead lie upstream in audience selection, content ranking, or send-time optimization. If the system selects the wrong user, promotes the wrong item, or delivers at the wrong time, even highly persuasive text will not recover performance.

This observation implies that LLM generation should be treated as a conditional optimization layer rather than a universal default. Its value is highest when the notification task has three properties: first, the promoted content admits multiple plausible framings; second, user response is sensitive to linguistic nuance rather than only item relevance; and third, the system has sufficient user context to support grounded personalization. These conditions are often satisfied in re-engagement campaigns, discovery surfaces, abandoned-cart recovery, and recommendation explanations. They are less likely to hold in low-variance transactional alerts such as password resets, delivery confirmations, payment receipts, or fraud warnings.

A mature architecture should therefore support dynamic routing between generation strategies. The budget allocator in our proposed pipeline can be interpreted not merely as a compute-control mechanism, but as a policy layer for deciding whether an LLM should be invoked at all. This reframes LLMs as one component in a portfolio of messaging strategies rather than the default endpoint for all notification composition tasks.



## 7 Evaluation Frameworks Beyond Short-Term CTR

A major weakness in the current literature is that evaluation strategies lag behind architectural complexity. Most published results still report short-term click or conversion gains, yet LLM-based notification systems operate in environments where treatment effects are delayed, interference is common, and user welfare is multi-dimensional. Figure 3 outlines a proposed multi-layer evaluation framework.

### 7.1 The Identification Problem: Why Simple A/B Testing Is Not Enough

Randomized A/B testing remains the operational gold standard, but its interpretation in notification systems is more fragile than commonly assumed. In networked and recommender-driven environments, the Stable Unit Treatment Value Assumption (SUTVA) is frequently violated (Luo et al., 2024). Notifying one user can alter content popularity, inventory exposure, or social activity in ways that indirectly affect untreated users. This creates spillover effects that contaminate causal attribution.

In addition, standard message-level tests often fail to isolate which part of the pipeline caused the uplift. A measured gain may be driven by better ranking, better timing, or better targeting rather than by language generation itself. A rigorous experimental program should therefore distinguish at least three treatment layers: item selection, send-time decision, and message realization.

### 7.2 Offline Evaluation Is Structurally Biased

Offline evaluation remains useful for rapid iteration, but it is subject to severe bias. Historical logs only contain feedback for actions that were actually taken, meaning that novel prompts or candidate framings have no unbiased counterfactual labels. This problem is especially acute for reward models trained on logged notification outcomes, because these models inherit the exposure policy that generated the data.

Selection bias also appears at the population level. Users who permit notifications are typically more engaged and more tolerant of outreach than the marginal users whose behavior platforms most want to influence. Evaluating generation quality only on this observed subpopulation leads to optimistic results that may not transfer to churn-risk or dormant users.

### 7.3 Heterogeneous Treatment Effects Must Be First-Class

Average Treatment Effects (ATEs) are often too coarse for notification systems. Different users respond differently not only to content categories but also to persuasion intensity, timing frequency, and stylistic framing. A gain that is positive on average may conceal harm to important subgroups, including low-engagement users, new users, or users already close to opt-out thresholds. Tu et al. (2021) demonstrated that the causal effect of notifications varies drastically across user cohorts. Evaluation should therefore estimate Heterogeneous Treatment Effects (HTEs) across user segments defined by lifecycle stage, baseline engagement, CLV, and prior notification saturation.

### 7.4 Multi-Objective Evaluation Is Required

Notification quality cannot be reduced to CTR. A system optimized only for click propensity will often converge toward clickbait-like phrasing, over-alerting, or manipulative urgency cues (Jannach

et al., 2023). These behaviors may improve short-term metrics while degrading long-term trust, retention, and channel health. We recommend structuring metrics into three layers:

1. **Primary outcome metrics:** CTR, CVR, order value, session return.
2. **Guardrail metrics:** Notification opt-out rate, mute actions, dismissals without open, complaint rate, and uninstall risk.
3. **Long-horizon health metrics:** 7-day and 30-day retention, notification fatigue trajectories, cohort survival, and reactivation durability.

## 8 Ethical Frameworks and Governance

The ethical risks of LLM-based notification systems cannot be reduced to hallucination alone. Because notifications are interruptive, personalized, and often optimized for behavior change, they sit close to the boundary between helpful communication and covert manipulation.

### 8.1 Persuasive Asymmetry and the Manipulation Boundary

Digital platforms possess profound informational advantages over users. [Susser et al. \(2019\)](#) define online manipulation as the use of information technology to covertly influence decision-making by exploiting cognitive biases, bypassing rational agency. When LLMs generate personalized text utilizing scarcity heuristics (“Only 1 left!”) or false urgency, they cross the boundary from persuasion into manipulation. Ethical systems must prohibit prompt instructions that encourage deceptive framing, classifying them as “dark patterns” ([Mathur et al., 2021](#)).

### 8.2 Fairness and Differential Susceptibility

Fairness in recommender systems is often discussed in terms of exposure or ranking parity ([Wang et al., 2023](#)), but notification generation adds a different concern: differential susceptibility. Some user groups (e.g., older adults, low-literacy users) may be more influenced by certain tones, urgency cues, or authoritative language patterns than others. Fairness requires auditing reward models to ensure they do not systematically exploit the vulnerabilities of specific demographic groups to artificially inflate CTR.

### 8.3 Accountability and Regulatory Compliance

Under the EU’s Digital Services Act (DSA) Article 40 and GDPR Article 22, platforms face increasing obligations regarding algorithmic transparency and the right of users not to be subject to decisions based solely on automated processing ([Fabbri, 2023](#)). Platforms must ensure data minimization in RAG contexts and provide researchers with access to audit the fairness of the notification pipeline. Frequency caps, forbidden content policies, factuality checks, and audit logs are not optional accessories; they are part of the core production design.

## 9 Proposed Unified Architectural Framework

Based on the surveyed literature and the preceding analysis, we propose a unified operational framework for LLM-based notification composition (Figure 4). The novelty of this framework is integrative rather than algorithmic. It specifies how known components should be sequenced and coordinated to support scalable, grounded, and policy-compliant notification delivery.

### 9.1 Architectural Flow and Failure Modes

The pipeline begins with three inputs: user profile/value estimates, content inventory, and contextual signals. These flow into a content-selection layer. Crucially, a **Budget-Aware Router** then decides whether the user-item-context tuple justifies invocation of the LLM pathway or whether a simpler templated strategy should be used.

If the LLM pathway is selected, **RAG** retrieves relevant context. The generator produces multiple candidates, conditioned through **PEFT/LoRA** adapters. A **Factuality and Policy Guard** stage filters candidates containing unsupported claims or prohibited phrases. The remaining candidates are scored by a **Pairwise Reward Model**. After ranking, a **Diversity and Frequency Control Layer** ensures the chosen message does not contribute to alert fatigue. Finally, a **Send-Time Optimization Module (Bandit)** determines whether the message should be delivered immediately or deferred. Outcomes then flow back into an **Online Learning Layer**.

**Failure Modes and Tradeoffs:** This pipeline trades increased inference latency and compute cost for semantic diversity. If the Factuality Guardrail is too strict, it throttles throughput; if too loose, it risks brand damage. If the Reward Model suffers from exposure bias, it will continually select the same “safe” candidates, defeating the purpose of the LLM generator entirely.

## 10 Threats to Validity

Several threats to the validity of this survey must be acknowledged:

1. **Publication Bias:** Industry labs are highly incentivized to publish successful A/B tests and suppress negative results, potentially skewing the reported efficacy of LLM notifications.
2. **Temporal Degradation:** The rapid evolution of LLM capabilities means that technical constraints (e.g., inference latency) reported in 2024–2025 papers may be resolved by hardware advances in 2026.
3. **Domain Representation:** Our corpus heavily favors Social Media and E-Commerce; findings may not generalize to high-stakes domains like healthcare or financial alerts.
4. **Reproducibility:** Many of the most important industrial systems depend on proprietary data and internal experimentation frameworks, lacking widely accepted open benchmarks.

## 11 Conclusion

This paper surveyed the emerging field of LLM-based notification message composition and argued that its real significance lies not in language generation alone, but in the interaction between generation and the surrounding notification architecture. The literature shows that grounded

generation, efficient style adaptation, relative candidate ranking, diversity control, and contextual timing can together improve the quality and relevance of notifications.

A central conclusion of this survey is that LLM text generation is not universally the binding constraint in notification systems. For transactional, factual, or low-variance alerts, high-quality templates remain the superior design. The strongest case for LLM deployment arises when user response is sensitive to framing, when multiple context signals can be synthesized into useful copy, and when the expected business value justifies the additional inference, evaluation, and governance burden.

Future research must move beyond binary claims that LLMs do or do not improve notifications. Progress will depend on stronger experimental design, component-isolated evaluation, better off-policy learning infrastructure, more rigorous fairness auditing, and open benchmarks that allow researchers to disentangle the contribution of generation from the broader recommender stack.

## Acknowledgments

The author thanks the broader research community working at the intersection of recommender systems, natural language generation, and causal inference for the foundational work that made this synthesis possible.

## References

- ACM Digital Library. Llm-driven e-commerce marketing content optimization: Balancing creativity and conversion. In *Proceedings of the ACM Web Conference 2025*, 2025. URL <https://dl.acm.org/doi/10.1145/3757749.3757850>.
- S. Bie, J. Cao, Z. Luo, et al. Pushgen: Push notifications generation with llm. In *Proceedings of the Nineteenth ACM International Conference on Web Search and Data Mining (WSDM '26)*, 2026. URL <https://arxiv.org/abs/2512.14490>.
- COLING. Mix-of-granularity: Optimize the chunking granularity for retrieval-augmented generation. In *Proceedings of COLING 2025*, 2025. URL <https://aclanthology.org/2025.coling-main.384/>.
- EMNLP. Benchmarking llm faithfulness in rag with evolving leaderboards. In *Proceedings of EMNLP 2025*, 2025. URL <https://aclanthology.org/2025.emnlp-industry.54/>.
- M. Fabbri. An ethical perspective on the implementation of the transparency requirements for recommender systems set by the digital services act of the european union. In *Proceedings of the 2023 AAAI/ACM Conference on AI, Ethics, and Society*, 2023. URL <https://dl.acm.org/doi/abs/10.1145/3600211.3604717>.
- Z. Han et al. Parameter-efficient fine-tuning for large models: A comprehensive survey. *arXiv preprint arXiv:2403.14608*, 2024. URL <https://arxiv.org/abs/2403.14608>.
- B. J. Ho et al. Notifying users at the right time using reinforcement learning. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, 2018. URL <https://dl.acm.org/doi/pdf/10.1145/3267305.3274107>.

- E. J. Hu et al. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022. URL <https://arxiv.org/abs/2106.09685>.
- D. Jannach et al. A survey on multi-objective recommender systems. *National Center for Biotechnology Information (PMC)*, 2023. URL <https://pmc.ncbi.nlm.nih.gov/articles/PMC10073543/>.
- T. Joachims, A. Swaminathan, and M. de Rijke. Deep learning with logged bandit feedback. In *International Conference on Learning Representations (ICLR)*, 2018.
- P. Lewis et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. In *Advances in Neural Information Processing Systems (NeurIPS 2020)*, 2020. URL <https://arxiv.org/abs/2005.11401>.
- H. Luo et al. A survey on causal inference for recommendation. *arXiv preprint arXiv:2303.11666v2*, 2024. URL <https://arxiv.org/html/2303.11666v2>.
- A. Mathur, M. Kshirsagar, and J. Mayer. What makes a dark pattern... dark? design attributes, normative considerations, and measurement methods. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, 2021. URL <https://dl.acm.org/doi/abs/10.1145/3411764.3445610>.
- S. Ohly et al. Effects of task interruptions caused by notifications from smartphones. *National Center for Biotechnology Information (PMC)*, 2023. URL <https://pmc.ncbi.nlm.nih.gov/articles/PMC10244611/>.
- N. Sinha. Beyond the click: Elevating doordash’s personalized notification experience with gnn recommendation. DoorDash Engineering Blog, 2024. URL <https://careersatdoordash.com/blog/doordash-customize-notifications-how-gnn-work/>.
- X. Sun et al. A new ranking framework for better notification quality on instagram. Engineering at Meta, 2025. URL <https://engineering.fb.com/2025/09/02/ml-applications/a-new-ranking-framework-for-better-notification-quality-on-instagram/>.
- D. Susser et al. Technology, autonomy, and manipulation. *Internet Policy Review*, 2019. URL <https://policyreview.info/articles/analysis/technology-autonomy-and-manipulation>.
- Y. Tu, K. Basu, C. DiCiccio, et al. Personalized treatment selection using causal heterogeneity. In *Proceedings of the Web Conference 2021 (WWW ’21)*, 2021. URL <https://dl.acm.org/doi/abs/10.1145/3442381.3450075>.
- University of Milano-Bicocca. Thompson sampling for performance marketing and delayed conversions. 2024. URL <https://boa.unimib.it/handle/10281/460458>.
- A. Vaswani et al. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS 2017)*, 2017. URL <https://arxiv.org/abs/1706.03762>.
- Y. Wang et al. A survey on the fairness of recommender systems. *ACM Transactions on Information Systems*, 2023. URL <https://dl.acm.org/doi/10.1145/3547333>.
- K. P. Yancey et al. A sleeping, recovering bandit algorithm for optimizing notifications. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2020. URL <https://research.duolingo.com/papers/yancey.kdd20.pdf>.




Figure 1: PRISMA flow diagram detailing the literature search, screening, and inclusion process.

| Domain Generalizability Matrix |                                                                     |                                                                             |                                                                           |
|--------------------------------|---------------------------------------------------------------------|-----------------------------------------------------------------------------|---------------------------------------------------------------------------|
| Dimension                      | 📱 Social Media                                                      | 🍽️ Food Delivery                                                            | 🛒 E-Commerce                                                              |
| "High-Value" User Definition   | High-DAU user with strong social graph; influencer or power user    | Repeat orderer with high AOV; lapsed user with reactivation potential       | High-CLV customer; abandoned-cart user with purchase intent               |
| Primary Success Metric         | Engagement Rate (likes, shares, comments)<br>Session re-entry       | Order Conversion Rate<br>GMV per notification<br>Reactivation rate          | Click-to-Purchase CVR<br>Revenue per notification<br>Cart recovery rate   |
| Key Contextual Signals         | Social activity feed<br>Friend/follower events<br>Content freshness | Time of day (meal windows)<br>Order history & recency<br>Location & weather | Browse & cart history<br>Price drop / stock alerts<br>Seasonal promotions |
| LLM Role in Pipeline           | Personalise social recap & trending content summaries               | Generate contextual urgency copy (e.g., lunch offers)                       | Produce persuasive product descriptions & recovery messages               |
| Persuasion Tolerance           | Moderate — users expect social updates, not hard selling            | High during meal windows; low outside peak hours                            | High for deal/discount frames; low for generic promotions                 |
| Dominant Failure Mode          | Notification fatigue from over-frequency; tone mismatch             | False urgency (dark pattern risk); stale context                            | Hallucinated prices or stock levels; reward hacking                       |
| Cross-Domain Transferability   | GNN audience selection transfers; LLM copy style does not           | STO bandit transfers; urgency framing is domain-specific                    | RAG grounding transfers; CLV segmentation transfers broadly               |

Shaded left bars indicate row dimension category. Green cells = transferable across domains. White cells = domain-specific.

Figure 2: Domain Generalizability Matrix comparing high-value user definitions, primary metrics, key contextual signals, LLM roles, and key risks across Social Media, Food Delivery, and E-Commerce.




Figure 3: A multi-layer evaluation framework for intelligent notification composition, spanning from immediate predictive accuracy to long-term ecosystem health and governance constraints.






Figure 4: The proposed unified notification pipeline, demonstrating the integration novelty of separating generation from adjacent systems and the inclusion of explicit safety guardrails, contextual bandits, and counterfactual feedback loops.